

Sunday, July 12, 2026 6:58 PM

Codecademy:

Manage data stored in relational databases. → data stored in rows & columns.

SQLite Relational Database Management System.

- SELECT * FROM celebs ;

- Clause

Statement is text that the database recognizes as a valid command.
Statements end with ;

CREATE TABLE <table_name> (<column_1><datatype>, <column_2><data-type>, <column_3><data-type>);

↓
column name

- To create a new table in the database.

celebs		
id	name	age

```

CREATE TABLE
name TEXT,
age INTEGER
);

```



OneNote

2) INSERT

- Add a row to the table.

Eg: Adding a celebrity info:

```

INSERT INTO celebs (id, name, age)
VALUES (1, 'Justin Bieber', 29);

```

```

INSERT INTO celebs (id, name, age)
VALUES (2, 'Beyonce Knowles', 42);

```

```

INSERT INTO celebs (id, name, age)
VALUES (3, 'Jeremy Lin', 35);

```

```

INSERT INTO celebs (id, name, age)
VALUES (4, 'Taylor Swift', 33);

```



id	
1	Justin
2	Beyonce
3	Jeremy
4	Taylor

3) SELECT

- Fetch data from a database.

Eg: Getting all the data from a column:

```

SELECT name FROM celebs; → return all data / all celeb names

```

Eg: Get data from all columns

```

→ SELECT * FROM celebs; → return whole table

```

A **result set** is a table that contains the values returned by the SELECT statement.

4) ALTER

- Adds a new column to the table.

Eg: Adding a column with their username:

```
ALTER TABLE celebs  
ADD COLUMN twitter_handle TEXT;
```

$NULL(\emptyset) \Rightarrow$ missing / unknown data

—

5) UPDATE

- Edit a row in the table.

Eg: Updating Taylor Swift's info to include her twitter handle:

```
UPDATE celebs  
SET twitter_handle = '@taylorswift13'  
WHERE id = 4;
```

—

6) DELETE

- deletes one or more rows.

Eg: to delete rows where celebs don't have a twitter handle:

```
DELETE FROM celebs  
WHERE twitter_handle IS NULL;
```

—

Constraints:

- Constraints are rules applied to values.

Eg: Setting constraints to Celebs table.

```
CREATE TABLE celebs (
```

```
  id INTEGER PRIMARY KEY,
```

```
  name TEXT UNIQUE,
```

```
  dob TEXT NOT NULL,
```

```
  dod TEXT DEFAULT 'Not Applicable'
```

```
);
```

→ used to uniquely identify the row

→ columns have a different value for each row
→ can never be 0

→ sets a default value