## **Exercises Week 5**

## **Information Theory**

- 1. For the following channels, compute the channel capacity and the input probabilities required to reach it:
  - a. Noiseless binary channel
  - b. Noisy binary non-overlapping channel
  - c. "Noisy typewriter"
  - d. Binary symmetric channel
  - e. Binary erasure channel
  - f. Symmetric channel of order n
- 2. Consider a discrete transmission channel with the following channel matrix:

$$P(Y|X) = \begin{bmatrix} \frac{1}{2} & 0 & \frac{1}{2} & 0 & 0 & 0\\ 0 & 0 & 0 & \frac{1}{3} & 0 & \frac{2}{3}\\ 0 & \frac{1}{6} & 0 & 0 & \frac{5}{6} & 0 \end{bmatrix}$$

- a. Draw the graph of the channel, and compute the equivocation H(X|Y);
- b. If  $p(x_1) = \frac{1}{2}$ ,  $p(x_2) = \frac{1}{4}$  and  $p(x_3) = \frac{1}{4}$ , compute the average information transmitted on the channel I(X,Y);
- c. Compute the redundancy and the efficiency of the channel.
- 3. Two binary channels are connected in series, as in the picture below:

[see on whiteboard]

- a. Find q such that the equivalent channel is a binary symmetric channel;
- b. Not done: Find the channel capacity of the equivalent channel from a).
- 4. Not done: A logical AND gate with two inputs can be considered a transmission channel, with four input symbols  $x_1 = 00$ ,  $x_2 = 01$ ,  $x_3 = 10$ ,  $x_4 = 11$ , and two output symbols  $y_1 = 0$ ,  $y_2 = 1$ .
  - a. If  $p(x_1) = p(x_2) = p(x_3) = p(x_4) = \frac{1}{4}$ , find the average information transmitted on this channel;
  - b. Find the channel capacity and the probabilities of the inputs required to reach it.

1