

# Implementing digital IIR filters in the lattice form

## Lab 6, SDP

### Objective

The students should become familiar with *lattice*-type realization structure used for implementing IIR filters.

### Theoretical notions

### Exercises

1. Consider the causal IIR system with poles and zeros, with the system function:

$$H(z) = \frac{1 + 2z^{-1} + 3z^{-2} + 2z^{-3}}{1 + \frac{2}{5}z^{-1} + \frac{7}{20}z^{-2} + \frac{1}{2}z^{-3}}$$

Find and draw the equivalent *lattice* structure for the IIR filter.

2. Consider the causal IIR system, with no zeros, with the following system function:

$$H(z) = \frac{1}{1 + \frac{2}{5}z^{-1} + \frac{7}{20}z^{-2} + \frac{1}{2}z^{-3}}$$

Find and draw the equivalent *lattice* structure for the IIR filter.

3. In the Matlab environment, use the `fdatool` tool to design one of the following filters:
  - a. A low-pass IIR filter of order 4, elliptic type, with cutoff frequency of 6kHz at a sampling frequency of 44.1kHz;

- b. A high-pass IIR filter of order 4, elliptic type, with cutoff frequency of 2.5kHz at a sampling frequency of 44.1kHz;
  - c. A band-pass IIR filter of order 4, elliptic type, with passband between 0.5kHz and 5.5kHz at a sampling frequency of 44.1kHz.
4. In the Simulink environment, implement the above filters in *lattice* form. Apply at the input an audio signal and play the output signal, as well as the original, for comparison. How does the filtered signal sound like, compared to the original?

## Notes:

- Set the following parameters for the Simulink model, to enable a discrete simulation with fixed (auto) step:
  - Type: *Fixed-step*
  - Solver: *discrete (no continuous states)*





Figure 1: Model settings for discrete models

- You will need the blocks *Unit Delay*, *Sum* and *Gain*
- At the input put a *From Multimedia File* block, and at the output put a *To Audio Device* block
- At the output, before the *To Audio Device* block, put a *Manual Switch* block in order to be able to switch easily between the original signal and the filtered one
- For the *From Multimedia File* block, select an audio file (de ex. Kalimba.mp3 from My Documents) and update the following settings\$
  - choose *Sample-based*
  - *Samples per audio channel* = 1
  - “DataTypes/Audio output data type” = *double*



## Final questions

1. TBD