State-space implementations of digital IIR filters

Lab 9, SDP

Table of contents

1 Objective

The students should become familiar with *state-space* type realization structure used for implementing IIR filters.

2 Theoretical notions

2.1 State-Space Type I implementation

The equations defining the state-space type I filter realization are given in Figure 1, for a IIR system of order 3.

$$\begin{bmatrix} \upsilon_1[n+1] \\ \upsilon_2[n+1] \\ \upsilon_3[n+1] \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 \\ 0 & 0 & 1 \\ -a_3 & -a_2 & -a_1 \end{bmatrix} \begin{bmatrix} \upsilon_1[n] \\ \upsilon_2[n] \\ \upsilon_3[n] \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} x[n]$$

$$y[n] = \left[(b_3 - b_0 a_3)(b_2 - b_0 a_2)(b_1 - b_0 a_1) \right] \begin{bmatrix} \upsilon_1[n] \\ \upsilon_2[n] \\ \upsilon_3[n] \end{bmatrix} + b_0 x[n]$$

Figure 1: State-Space Type I equations, for an IIR system of order 3



Figure 2: Schematic according to the equations (type I, order 3)

The schematic according to these equation is in Figure 2.

2.2 State-Space Type II implementation

$$\begin{bmatrix} \upsilon_1[n+1] \\ \upsilon_2[n+1] \\ \upsilon_3[n+1] \end{bmatrix} = \begin{bmatrix} 0 & 0 & -a_3 \\ 1 & 0 & -a_2 \\ 0 & 1 & -a_1 \end{bmatrix} \begin{bmatrix} \upsilon_1[n] \\ \upsilon_2[n] \\ \upsilon_3[n] \end{bmatrix} + \begin{bmatrix} (b_3 - b_0 a_3) \\ (b_2 - b_0 a_2) \\ (b_1 - b_0 a_1) \end{bmatrix} x[n]$$

$$y[n] = \begin{bmatrix} 0 & 0 & 1 \end{bmatrix} \cdot \begin{bmatrix} \upsilon_1[n] \\ \upsilon_2[n] \\ \upsilon_3[n] \end{bmatrix} + b_0 x[n]$$

Figure 3: State-Space Type II equations, for an IIR system of order 3



Figure 4: Schematic according to the equations (type II, order 3)

The equations defining the state-space type II filter realization are given in Figure 3, for a IIR system of order 3.

The schematic according to these equation is in Figure 4.

2.3 General equations

$$\mathbf{v}[n+1] = \mathbf{F}\mathbf{v}[n] + \mathbf{q}x[n]$$
$$y[n] = \mathbf{g}^{\mathbf{t}}\,\mathbf{v}[n] + dx[n]$$

Figure 5: General state-space equations

In the general case, there are always the two equations in Figure 5:

$$\mathbf{F}=\begin{bmatrix} 0 & 1 & 0 & \cdot & \cdot & \cdot & 0 \\ 0 & 0 & 1 & 0 & \cdot & \cdot & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & \cdot & \cdot & \cdot & 0 & 1 \\ -a_N & -a_{N-1} & \cdot & \cdot & \cdot & -a_2 & -a_1 \end{bmatrix} \quad \mathbf{q}=\begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \\ 1 \end{bmatrix} \quad \mathbf{g}=\begin{bmatrix} b_N - b_0 a_N \\ b_{N-1} - b_0 a_{N-1} \\ \vdots \\ b_1 - b_0 a_1 \end{bmatrix} \quad d = b_0$$

Figure 6: Definition of the terms for type I

$$\mathbf{F}=\begin{bmatrix} 0 & 0 & \cdots & & & 0 & -a_N \\ 1 & 0 & \cdots & & & 0 & -a_{N-1} \\ \vdots & \vdots & & & & & \vdots \\ 0 & 0 & \cdots & 0 & 1 & 0 & -a_2 \\ 0 & 0 & \cdots & \cdot & 0 & 1 & -a_1 \end{bmatrix} \quad \mathbf{q}=\begin{bmatrix} b_N - b_0 a_N \\ b_{N-1} - b_0 a_{N-1} \\ \vdots \\ b_2 - b_0 a_2 \\ b_1 - b_0 a_1 \end{bmatrix} \quad \mathbf{g}=\begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \\ 1 \end{bmatrix} \quad d = b_0$$

Figure 7: Definition of the terms for type II

- the **state equation**: produces the next state $\mathbf{v}[n+1]$ depending on the current state $\mathbf{v}[n]$ and current input $x[n]$;
- the **output equation**: produces the current output $\mathbf{y}[n]$ depending on the current state $\mathbf{v}[n]$ and current input $x[n]$.

The definition of the general terms, according to type I or type II, is given in Figure 6 și Figure 7.

3 Theoretical exercises

1. Consider the IIR system with the system function

$$H(z) = \frac{1 + 2z^{-1} + 3z^{-2} + 2z^{-3}}{1 + 0.9z^{-1} + 0.8z^{-2} + 0.5z^{-3}}$$

   a. Write the equations and draw the type I and type II state-space implementations of this system
   b. Compute the first 5 values of the step response, considering the initial conditions $v[0] = \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix}$

2. Consider the system with the following state-space equations:

$$v[n+1] = \begin{bmatrix} 0 & 1 \\ -0.81 & 1 \end{bmatrix} v[n] + \begin{bmatrix} 0 \\ 1 \end{bmatrix} x[n]$$

$$y[n] = \begin{bmatrix} -1.81 & 1 \end{bmatrix} + x[n]$$

a. Find the system function of this system
b. Compute the first 5 values of the step response, considering the initial conditions $v[0] = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$
c. Draw the the type I and type II state-space implementations of this system, as well as the direct form II implementation

4 Practical exercises

1. In the Matlab environment, use the `fdatool` tool to design a stopband filter of order 4, elliptic type, with stop band between 1kHz and 3kHz, at a sampling frequency of 44.1kHz. Export the coefficients in the Matlab workspace as the vectors `a` and `b`.

2. In the Matlab environment, implement a function `filter_spst(b, a, x)` which filters a signal `x` with the filter defined by the coefficients `b` and `a`. Implementation shall follow the type I state-space equations.

3. Test the function written above with the coefficients designed at step 3, by filtering a sample audio signal.

4. Modify the function to perform temporal filtering of a video sequence, only for a filter of order 3. Test the function on the video sequence `veh_small.mp4`.

   To read frames from a video sequence in Matlab, you can use the following snippet:

```
v = VideoReader('videofile.mp4');

% Read all the frames from the video, one frame at a time.

while hasFrame(v)
 frame = readFrame(v);

 % Do the processing here

end
```

5 Final questions

1. TBD