

leetcode.com/problems/longest-common-prefix/

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

14. Longest Common Prefix

EasyTopicsCompanies

Write a function to find the longest common prefix string amongst an array of strings.

If there is no common prefix, return an empty string "".

Example 1:

Input: strs = ["flower","flow","flight"]
Output: "fl"

Example 2:

Input: strs = ["dog","racecar","car"]
Output: ""
Explanation: There is no common prefix among the input strings.

Constraints:

1 <= strs.length <= 200
0 <= strs[i].length <= 200

22K814227 Online

Code

C Auto

```
14         return strs[0];
15     }
16     }
17     i++;
18 }
19
20 return strs[0];
21 }
```

SavedLn 21, Col 2

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

strs =
["flower","flow","flight"]

Output

"fl"

leetcode.com/problems/reverse-string/

Problem List

Submit

Premium

DescriptionEditorialSolutionsSubmissions

344. Reverse String

EasyTopicsCompaniesHint

Write a function that reverses a string. The input string is given as an array of characters.

You must do this by modifying the input array **in-place** with **O(1)** extra memory.

Example 1:

Input: s = ["h","e","l","l","o"]
Output: ["o","l","l","e","h"]

Example 2:

Input: s = ["H","a","n","n","a","h"]
Output: ["h","a","n","n","a","H"]

Constraints:

- 1 <= s.length <= 10⁵

9.8K34148 Online

Code

CAuto

```
6 char temp = s[start];
7 s[start] = s[end];
8 s[end] = temp;
9
10 start++;
11 end--;
12 }
13 }
```

SavedLn 13, Col 2

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

s = ["h","e","l","l","o"]

Output

["o","l","l","e","h"]

Proble...

<

>

✕

👤

▶

📁 Submit

📄

⚡

🔧

⚙️

🔔

🔥 0

🔄

👤

🌐

Premium

Description

Editorial

Solutions

Submissions

242. Valid Anagram

Easy

Topics

Companies

Given two strings `s` and `t`, return `true` if `t` is an **anagram** of `s`, and `false` otherwise.

Example 1:

Input: `s = "anagram", t = "nagaram"`

Output: `true`

Example 2:

Input: `s = "rat", t = "car"`

Output: `false`

Constraints:

- `1 <= s.length, t.length <= 5 * 104`

14.8K

357

☆

🔖

🕒

190 Online

</> Code

C ▾ 🔒 Auto

☰

🔖

⌕

↶

↷

↺

```
11
12     for (int i = 0; i < 26; i++) {
13         if (count[i] != 0)
14             return false;
15     }
16
17     return true;
18 }
```

Saved

Ln 18, Col 2

✅ Testcase

> Test Result

Accepted

Runtime: 0 ms

✅ Case 1

✅ Case 2

Input

s =
"anagram"

t =
"nagaram"



leetcode.com/problems/move-zeroes/

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

283. Move Zeroes

Easy

Topics

Companies

Hint

Given an integer array `nums`, move all `0`'s to the end of it while maintaining the relative order of the non-zero elements.

Note that you must do this in-place without making a copy of the array.

Example 1:

Input: `nums = [0,1,0,3,12]`
Output: `[1,3,12,0,0]`

Example 2:

Input: `nums = [0]`
Output: `[0]`

Constraints:

20K 465 136 Online

Code

C Auto

```
8     }
9     }
10
11     while (position < numsSize) {
12         nums[position] = 0;
13         position++;
14     }
15 }
```

Saved Ln 15, Col 2

Testcase

Test Result

Accepted Runtime: 0 ms

Case 1

Case 2

Input

nums =
[0,1,0,3,12]

Output

[1,3,12,0,0]

704. Binary Search

Easy Topics Companies

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`. If `target` exists, then return its index. Otherwise, return `-1`.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [-1,0,3,5,9,12]`, `target = 9`

Output: `4`

Explanation: 9 exists in `nums` and its index is 4

Example 2:

Input: `nums = [-1,0,3,5,9,12]`, `target = 2`

Output: `-1`

Explanation: 2 does not exist in `nums` so return `-1`

Code

C Auto

```
10     else if (nums[mid] < target)
11     |     left = mid + 1;
12     else
13     |     right = mid - 1;
14     }
15
16     return -1;
17 }
```

Saved

Ln 17, Col 2

Testcase Test Result

Accepted Runtime: 0 ms

Case 1

Case 2

Input

`nums =`

`[-1,0,3,5,9,12]`

`target =`

`9`

121. Best Time to Buy and Sell Stock

Easy Topics Companies

You are given an array `prices` where `prices[i]` is the price of a given stock on the `ith` day.

You want to maximize your profit by choosing a **single day** to buy one stock and choosing a **different day in the future** to sell that stock.

Return the *maximum profit* you can achieve from this transaction. If you cannot achieve any profit, return `0`.

Example 1:

Input: `prices = [7,1,5,3,6,4]`

Output: `5`

Explanation: Buy on day 2 (price = 1) and sell on day 5 (price = 6), profit = 6-1 = 5.

Note that buying on day 2 and selling on day 1 is not allowed because you must buy before you sell.

Example 2:

36.5K 879 | ☆ 222 Online

Code

C v Auto

```
11     int profit = prices[i] - minPrice;
12
13     if (profit > maxProfit)
14         maxProfit = profit;
15     }
16
17     return maxProfit;
18 }
```

Saved

Ln 18, Col 2

Testcase | Test Result

Accepted Runtime: 0 ms

Case 1

Case 2

Input

`prices =`
`[7,1,5,3,6,4]`

Output

`5`

leetcode.com/problems/valid-parentheses/

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

20. Valid Parentheses

Easy

Topics

Companies

Hint

Given a string `s` containing just the characters `'('`, `'>`, `'{'`, `'>`, `'['` and `']'`, determine if the input string is valid.

An input string is valid if:

1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

Example 1:

Input: `s = "()"`

Output: `true`

Example 2:

Input: `s = "()[]{}"`

28.6K

721

266 Online

Code

C Auto

```
20         (c == ')' && open != '{')) {
21             return false;
22         }
23     }
24 }
25
26 return top == -1;
27 }
```

Saved

Ln 27, Col 2

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Case 3

Case 4

Case 5

Input

`s =`
`"()"`

Output

`true`

Scanned with OKEN Scanner

leetcode.com/problems/two-sum/

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

1. Two Sum

EasyTopicsCompaniesHint

You are given an array of integers `nums` and an integer `target`, return *indices of the two numbers such that they add up to* `target`.

You may assume that each input would have **exactly one solution**, and you may not use the *same* element twice.

You can return the answer in any order.

Example 1:

Input: `nums = [2,7,11,15], target = 9`
Output: `[0,1]`
Explanation: Because `nums[0] + nums[1] == 9`, we return `[0, 1]`.

Example 2:

Input: `nums = [3,2,4], target = 6`
Output: `[1,2]`

Code

C Auto

```
1 #include <stdlib.h>
2
3 int* twoSum(int* nums, int numsSize, int target, int* returnSize) {
4     int* result = (int*)malloc(2 * sizeof(int));
5
6     for (int i = 0; i < numsSize; i++) {
7         for (int j = i + 1; j < numsSize; j++) {
8             if (nums[i] + nums[j] == target) {
9                 result[0] = i;
10                result[1] = j;
11                *returnSize = 2;
12                return result;
13            }
14        }
15    }
16    return result;
17 }
```

SavedLn 1, Col 1

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1Case 2Case 3

Input

nums =

[2, 7, 11, 15]

target =

9

70.4K2.1K1401 Online

