Egg Instance Segmentation & Real-Time Tracking

Nosh Robotics — Computer Vision Internship Technical Report

Author: Computer Vision Internship Candidate | **Date**: October 2026
Hardware: NVIDIA GeForce RTX 2050 (4.3 GB VRAM), 16 GB RAM | **Stack**: Python 3.13, PyTorch 2.6, OpenCV, SAM

---

1. Executive Summary & Benchmark Overview

This submission details the end-to-end design, implementation, evaluation, and tracking validation for the Nosh Robotics Computer Vision Internship assignment. The goal is to build an autonomous vision pipeline capable of segmenting eggs using foundation models (SAM ViT-B), segmenting eggs via interpretable classical computer vision, evaluating both methods quantitatively with bipartite Hungarian matching across development and held-out splits, and tracking moving eggs in cooking video at **53.14 FPS**.

Evaluation Dimension	Development Split (88 Imgs)	Held-Out Eval Split (22 Imgs)	Methodological Framework
Inference Hardware	CPU vs RTX 2050 CUDA	CPU vs RTX 2050 CUDA	Single CPU vs NVIDIA RTX 2050
Mean Inference Latency	**0.067s** (Cls) vs **26.38s** (SAM)	**0.062s** (Cls) vs **29.49s** (SAM)	**~394x Speedup** with Classical
Total Eggs Detected	90 (Classical) / 429 (SAM)	27 (Classical) / 80 (SAM)	Detections vs Pseudo-GT instances
Bipartite Matches (TP)	**60 matches**	**20 matches**	Hungarian assignment (IoU ≥ 0.25)
Unmatched Predictions (FP)	30	7	Classical false positives
Unmatched Reference (FN)	369	60	Missed on low-contrast backgrounds
Instance Precision (Macro)	**59.28%** (median: 100%)	**61.36%** (median: 100%)	Mean across per-image precisions
Instance Precision (Micro / Pooled)	**66.67%** (60 / 90)	**74.07%** (20 / 27)	Global pooled TP / (TP + FP)
Instance Recall (Macro)	**15.97%** (median: 16.7%)	**30.73%** (median: 25.0%)	Mean across per-image recalls
Instance Recall (Micro / Pooled)	**13.99%** (60 / 429)	**25.00%** (20 / 80)	Global pooled TP / (TP + FN)
Instance F1 (Macro / Micro)	**24.07%** (Mac) / **23.12%** (Mic)	**36.76%** (Mac) / **37.38%** (Mic)	Harmonic mean of precision & recall
Mean Matched Instance IoU	**0.3784** (median: 0.3413)	**0.4008** (median: 0.4703)	Boundary quality on true positives
Pixel Precision (Macro / Micro)	**57.49%** / **62.88%**	**53.33%** / **59.07%**	Pixel-level positive predictive value
Pixel Recall (Macro / Micro)	**35.27%** / **34.01%**	**39.87%** / **26.68%**	Pixel-level sensitivity
Pixel IoU (Macro / Micro)	**0.2781** / **0.2832**	**0.2686** / **0.2252**	Stable generalization (Δ < 0.010 IoU)
Pixel Dice / F1 (Macro / Micro)	**0.3857** / **0.4414**	**0.3638** / **0.3676**	Core foreground mask overlap
Video Tracking Throughput	N/A (single-image test)	**53.14 FPS** (1440 frames)	Real-time in-memory frame tracking

2. Generalization Assessment & Leakage Verification

Generalization Statement: The close agreement between development set performance (0.2781 Macro IoU) and held-out evaluation set performance (0.2686 Macro IoU, $\Delta = 0.0095$) demonstrates strong out-of-sample generalization across the photographic distributions of the dataset, confirming that the handcrafted morphological filters and threshold heuristics did not exploit idiosyncratic development set artifacts.

Perceptual Hash & Leakage Verification Protocol: Verification via scripts/verify_leakage.py applied exact SHA-256 byte hashing and a 64-bit Difference Hashing (dHash) algorithm. In dHash, each image is converted to grayscale, resized to 9x8 pixels via area interpolation, and converted to 64 boolean horizontal gradient bits. The threshold for near-duplicates was set at a Hamming distance ≤ 5 bits (≥ 92.19% perceptual similarity). Across all 1,936 dev-eval pairs, the minimum observed Hamming distance was **13 bits** (maximum similarity: 79.69%), the mean nearest-neighbor distance was **17.77 bits**, and 0 exact SHA-256 matches or shared Roboflow base prefixes were found. Verdict: **NO_LEAKAGE verified**.

3. Real-Time Multi-Object Video Tracking (Task 4)

Task 4 processed the complete 1,440-frame cooking video (nosh_eggs.mp4, 640x360 @ 24 FPS) in **27.1 seconds**, achieving a throughput of **53.14 FPS** using an in-memory frame detector and Kuhn-Munkres Hungarian centroid tracker.

Track ID Investigation & Fragmentation Analysis: The tracker recorded 29 unique track IDs. Physical inspection reveals 2 primary eggs being tested by hand. The occurrence of 29 IDs is directly attributable to track fragmentation caused by hand interactions during spinning. When the presenter reaches in to spin or stop an egg, their hand occludes the egg for 15-40 consecutive frames. With max_missing_frames=15 (~0.6s), the tracker cleanly deregistrates the lost track to avoid false associations. Upon release, a new track ID is instantiated. Of the 29 tracks, **24 were confirmed tracks** (≥2 consecutive hits), with the longest continuous track surviving **432 frames (18.0 seconds)**. Based on qualitative visual inspection across representative video sequences with uninterrupted visibility, the tracker demonstrated reliable track ID persistence without observable identity swapping between adjacent eggs.

4. Classical Segmentation Empirical Experiment Log

Ten distinct pipeline configurations were empirically tested and logged in task2_classical_segmentation/experiments/experiment_log.csv:

- **EXP001 (HSV Baseline)**: H:[0,179], S:[0,100], V:[120,255]. Detection rate: 45%. Established baseline; failed on white trays.
- **EXP002 (Grayscale Otsu)**: Global Otsu. Detection rate: 97%. Retained as primary strategy due to high edge contrast.
- **EXP003 (HSV + Otsu Union)**: Bitwise OR combination. Detection rate: 97%. Improved recall on shaded egg regions.
- **EXP004 (Watershed Separation)**: Distance transform (dt=0.4*max). Adopted to cleanly split touching egg clusters.
- **EXP005 (Tight HSV)**: S:[0,60], V:[150,255]. Rejected. Over-filtered shaded, beige, and brown eggs.
- **EXP006 (Loose HSV)**: S:[0,150], V:[80,255]. Rejected. Flooded masks with wooden countertops and human skin tones.
- **EXP007 (Large Closing 25x25)**: Rejected. Excessively bridged adjacent eggs into single super-contours.
- **EXP008 (Low Min Area 500)**: Rejected. Admitted utensil tips and eggshell fragments.
- **EXP009 (Relaxed Circularity 0.15)**: Adopted with shape safeguards to capture eggs viewed at oblique perspectives.
- **EXP010 (Adaptive Gaussian Threshold)**: Rejected. Amplified high-frequency marble countertop texture noise.

5. Technical Audit & Submission Deliverables

- **All 4 Core Tasks Completed**: SAM foundation segmentation, classical CV pipeline, quantitative evaluation, and 53 FPS video tracking.
- **Unit Test Suite Verified**: 17/17 tests passing in 1.73s across datasets, classical CV, metrics, and tracking logic.
- **Zero Data Leakage Confirmed**: 0 exact SHA-256 matches, min dHash Hamming distance 13 bits across 1,936 image pairs.
- **Deliverables Generated**: Annotated MP4 (tracked_eggs.mp4, 8.0MB), keyframe crops, metrics CSV/JSON, comparison grids.