OUTPUT:

```
rst:0x1 (POWERON_RESET),boot:0x13 (SPI_FAST_FLASH_BOOT)
configsip: 0, SPIWP:0xee
clk_drv:0x00,q_drv:0x00,d_drv:0x00,cs0_drv:0x00,hd_drv:0x00,wp_drv:0x00
mode:DIO, clock div:2
load:0x3fff0030,len:1156
load:0x40078000,len:11456
ho 0 tail 12 room 4
load:0x40080400,len:2972
entry 0x400805dc
Temperature: 48.8 C   Current: 1.8 A --> SAFE
Temperature: 48.8 C   Current: 1.8 A --> SAFE
Temperature: 48.8 C   Current: 5.6 A --> FAULT
Temperature: 48.8 C   Current: 7.1 A --> FAULT
Temperature: 48.8 C   Current: 7.7 A --> FAULT
Temperature: 48.8 C   Current: 7.3 A --> FAULT
Temperature: 48.8 C   Current: 6.9 A --> FAULT
Temperature: 48.8 C   Current: 6.2 A --> FAULT

Temperature: 48.8 C   Current: 0.0 A --> SAFE
Temperature: 48.8 C   Current: 0.1 A --> SAFE
Temperature: 48.8 C   Current: 0.8 A --> SAFE
Temperature: 48.8 C   Current: 1.8 A --> SAFE
Temperature: 48.8 C   Current: 5.0 A --> FAULT
Temperature: 48.8 C   Current: 6.5 A --> FAULT
Temperature: 48.8 C   Current: 7.7 A --> FAULT
Temperature: 48.8 C   Current: 5.9 A --> FAULT
Temperature: 48.8 C   Current: 1.5 A --> SAFE
Temperature: 48.8 C   Current: 0.0 A --> SAFE
Temperature: 48.8 C   Current: 0.0 A --> SAFE
Temperature: 48.8 C   Current: 3.4 A --> SAFE
Temperature: 48.8 C   Current: 6.6 A --> FAULT
Temperature: 48.8 C   Current: 7.3 A --> FAULT
Temperature: 48.8 C   Current: 8.2 A --> FAULT
Temperature: 48.8 C   Current: 7.9 A --> FAULT
Temperature: 48.8 C   Current: 5.9 A --> FAULT
Temperature: 48.8 C   Current: 1.0 A --> SAFE
Temperature: 48.8 C   Current: 2.9 A --> SAFE
```

Temperature: 48.8 C Current: 4.2 A --> SAFE
Temperature: 48.8 C Current: 0.9 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 48.8 C Current: 0.0 A --> SAFE
Temperature: 61.1 C Current: 0.0 A --> FAULT
Temperature: 61.1 C Current: 0.0 A --> FAULT
Temperature: 61.1 C Current: 0.0 A --> FAULT
Temperature: 61.1 C Current: 0.0 A --> FAULT
Temperature: 61.1 C Current: 0.0 A --> FAULT
Temperature: 61.1 C Current: 0.0 A --> FAULT
Temperature: 38.6 C Current: 0.0 A --> SAFE