



# University Institute of Engineering

## Department of Computer Science & Engineering

### EXPERIMENT: 6

NAME: NIKHIL VERMA

UID: 23BCS14095

BRANCH: BE-CSE

SECTION / GROUP: KRG\_1A

SEMESTER: 5TH

SUBJECT CODE: 23CSP-339

SUBJECT NAME: ADBMS

#### 1. Aim of the practical:

HR-Analytics: Employee count based on dynamic gender passing [MEDIUM]

TechSphere Solutions, a growing IT services company with offices across India, wants to track and monitor gender diversity within its workforce. The HR department frequently needs to know the total number of employees by gender (Male or Female) .

To solve this problem, the company needs an automated database-driven solution that can instantly return the count of employees by gender through a stored procedure that:

1. Takes a gender (e.g., 'Male' or 'Female') as input.
2. Calculates the total count of employees for that gender.
3. Returns the result as an output parameter.
4. Displays the result clearly for HR reporting purposes.

SmartStore Automated Purchase System [HARD]

SmartShop is a modern retail company that sells electronic gadgets like smartphones, tablets, and laptops.

The company wants to automate its ordering and inventory management process. Whenever a customer places an order, the system must:

1. Verify stock availability for the requested product and quantity.
2. If sufficient stock is available:
  - Log the order in the sales table with the ordered quantity and total price.
  - Update the inventory in the products table by reducing quantity\_remaining and increasing quantity\_sold.
  - Display a real-time confirmation message: "Product sold successfully!"
3. If there is insufficient stock, the system must:
  - Reject the transaction and display: Insufficient Quantity Available!"

5. Tools Used: PgAdmin, PostgreSQL

## 6. Code:

```
--Database: krg_3b
---Medium
CREATE TABLE employee_info (
    id SERIAL PRIMARY KEY,
    name VARCHAR(50) NOT NULL,
    gender VARCHAR(10) NOT NULL,
    salary NUMERIC(10,2) NOT NULL,
    city VARCHAR(50) NOT NULL
);
INSERT INTO employee_info (name, gender, salary, city)
VALUES
('Alok', 'Male', 50000.00, 'Delhi'),
('Priya', 'Male', 60000.00, 'Mumbai'),
('Rajesh', 'Female', 45000.00, 'Bangalore'),
('Sneha', 'Male', 55000.00, 'Chennai'),
('Anil', 'Male', 52000.00, 'Hyderabad'),
('Sunita', 'Female', 48000.00, 'Kolkata'),
('Vijay', 'Male', 47000.00, 'Pune'),
('Ritu', 'Male', 62000.00, 'Ahmedabad'),
('Amit', 'Female', 51000.00, 'Jaipur');

--SOLUTION
CREATE OR REPLACE PROCEDURE sp_get_employees_by_gender(
    IN p_gender VARCHAR(50),
    OUT p_employee_count INT
)
LANGUAGE plpgsql
AS $$
BEGIN
    SELECT COUNT(id)
    INTO p_employee_count
    FROM employee_info
    WHERE gender = p_gender;
    RAISE NOTICE 'Total employees with gender %: %', p_gender, p_employee_count;

END;
$$;

CALL sp_get_employees_by_gender('Male', NULL);
```

Data Output	Messages	Notifications
<div> <div> <div>≡+</div> <div>📄</div> <div>▼</div> <div>📋</div> <div>▼</div> <div>🗑️</div> <div>🗄️</div> <div>⬇️</div> <div>📈</div> <div>SQL</div> </div> </div>		
	<p><b>p_employee_count</b> </p> <p>integer</p>	
1		6
<div> <div>Total rows: 1</div> <div>Query complete 00:00:00.047</div> </div>		

Output: Medium level question

--- Hard

```

CREATE TABLE products (
  product_code VARCHAR(10) PRIMARY KEY,
  product_name VARCHAR(100) NOT NULL,
  price NUMERIC(10,2) NOT NULL,
  quantity_remaining INT NOT NULL,
  quantity_sold INT DEFAULT 0
);
CREATE TABLE sales (
  order_id SERIAL PRIMARY KEY,
  order_date DATE NOT NULL,
  product_code VARCHAR(10) NOT NULL,
  quantity_ordered INT NOT NULL,
  sale_price NUMERIC(10,2) NOT NULL,
  FOREIGN KEY (product_code) REFERENCES products(product_code)
);
INSERT INTO products (product_code, product_name, price, quantity_remaining,
quantity_sold)
VALUES
('P001', 'iPHONE 13 PRO MAX', 109999.00, 10, 0),
('P002', 'Samsung Galaxy S23 Ultra', 99999.00, 8, 0),
('P003', 'iPAD AIR', 55999.00, 5, 0),
('P004', 'MacBook Pro 14"', 189999.00, 3, 0),
('P005', 'Sony WH-1000XM5 Headphones', 29999.00, 15, 0);

```

```
INSERT INTO sales (order_date, product_code, quantity_ordered, sale_price)
VALUES ('2025-09-15', 'P001', 1, 109999.00), ('2025-09-16', 'P002', 2,
199998.00), ('2025-09-17', 'P003', 1, 55999.00), ('2025-09-18', 'P005', 2,
59998.00), ('2025-09-19', 'P001', 1, 109999.00); SELECT * FROM PRODUCTS;
SELECT * FROM SALES;
```

Data Output Messages Notifications						
	order_id [PK] integer	order_date date	product_code character varying (10)	quantity_ordered integer	sale_price numeric (10,2)	
1	1	2025-09-15	P001	1	109999.00	
2	2	2025-09-16	P002	2	199998.00	
3	3	2025-09-17	P003	1	55999.00	
4	4	2025-09-18	P005	2	59998.00	
5	5	2025-09-19	P001	1	109999.00	
Total rows: 5 Query complete 00:00:00.083						

Output: Tables Created

---SOLUTION:

```
CREATE OR REPLACE PROCEDURE pr_buy_products(
    IN p_product_name VARCHAR,
    IN p_quantity INT
)
LANGUAGE plpgsql
AS $$
DECLARE
    v_product_code VARCHAR(20);
    v_price FLOAT;
    v_count INT;
BEGIN
    -- Step 1: Check if product exists and has enough quantity
    SELECT COUNT(*)
    INTO v_count
    FROM products
    WHERE product_name = p_product_name
    AND quantity_remaining >= p_quantity;
```

```

--Step2:Ifsufficient stock
IFv_count>0THEN

    --Fetchproduct code and price
    SELECTproduct_code, price
    INTOv_product_code, v_price
    FROMproducts
    WHEREproduct_name = p_product_name;

    --Insertanew record into the sales table
    INSERTINTO sales (order_date, product_code, quantity_ordered, sale_price)
    VALUES(CURRENT_DATE, v_product_code, p_quantity, (v_price *
p_quantity));

    --Updatestock details
    UPDATEproducts
    SETquantity_remaining = quantity_remaining - p_quantity,
        quantity_sold = quantity_sold + p_quantity
    WHEREproduct_code = v_product_code;

    --Confirmation message
    RAISENOTICE 'PRODUCT SOLD..! Order placed successfully for % unit(s) of
%.',p_quantity,p_product_name;

ELSE
    --Step3:Ifstock is insufficient
    RAISENOTICE 'INSUFFICIENT QUANTITY..! Order cannot be processed for %
unit(s)of%.',p_quantity, p_product_name;
    END IF;
END;
$$;

CALLpr_buy_products ('MacBook Pro 14"', 1);

```

Data Output   Messages   Notifications

NOTICE:   PRODUCT SOLD..! Order placed successfully for 1 unit(s) of MacBook Pro 14".  
CALL

Query returned successfully in 56 msec.

## 7. Learning Outcomes:

1. Learned how to create and invoke stored procedures using PL/pgSQL in PostgreSQL. Practiced using input and output parameters to dynamically filter and return results.
2. Implemented business logic for inventory validation and transactional updates.
3. Gained experience with conditional control flow using IF statements inside procedures.
4. Understood how to use RAISE NOTICE for user-friendly feedback during procedure execution.