

How to read a character using IO class :

---

String class which is available in java.lang package (library) has provided a non static method called charAt(int indexPosition) to retrieve a character from the given string.

```
public char charAt(int indexPosition);
```

WAP to extract a character from the given String :

---

```
void main()
{
    String str = "JAVA";
    char ch = str.charAt(0);
    IO.println(ch);
}
```

The same program we can re-write in a single line :

---

```
void main()
{
    char gender = IO.readLine("Enter a Character [M/F] : ").charAt(0);
    IO.println("Your Gender is :"+gender);

    if(gender == 'M' || gender == 'm')
    {
        IO.println("You are a Male");
    }
}
```

---

How to read a boolean value using IO class :

---

1) String to float :

```
String val = "12.7";
```

```
float x = Float.parseFloat(val);
```

2) String to boolean

```
-----
```

```
String str = "true";
```

```
boolean y = Boolean.parseBoolean(str);
```

WAP to read boolean value :

```
-----
```

```
void main()
```

```
{
```

```
    String val = IO.readLine("Enter a boolean value [true/false] ");
```

```
    boolean isValid = Boolean.parseBoolean(val);
```

```
    IO.println(isValid);
```

```
}
```

```
=====
```

```
===
```

Static Import :

```
-----
```

This facility is available from JDK 1.5V.

We can import static members.

```
import static java.lang.IO.*;
```

```
import static java.lang.Integer.*;
```

```
void main()
```

```
{
```

```
println("Hello");
```

```
String name = readln("Enter your Name :");
```

```
println("Your Name is :"+name);
```

```
int age = parseInt(readln("Enter your Age :"));
```

```
println(age);
```

```
}
```