



Crimping Information for Copper Compression Connectors

Compact, Concentric Connectors Class B, C, Flex Class G, H, I, K, M & DLO Copper Wire Only

OEC USA INC.

COPPER

Rev: 01. Date: 8/25/25



1. Select the proper lug or splice connector for the size of cable being installed, ensuring that the size matches the description in the table.
2. Strip the insulation from the cable to a length so that the stripped area of the cable can be completely inserted into and fill the barrel of the lug or splice. Carefully strip the insulation from the cable without nicking the strands.
3. Wire brush the stripped portion of the cable to remove oxide films.
4. The stripped portion of the cable must be clean and inserted completely into the connector barrel.
5. Using the tool and die combination specified for that connector in the table below, install crimps, leaving a space of 1/8 inch minimum between successive crimps.
For Short Barrel Connectors, apply 1 crimp,
For Long Barrel Connectors, apply 2 crimps on the color coded bands



Tooling Selection Chart With Die-less Crimping Tools (Range Taking)

Lug Size	Approved Cu Wire Classes										Range Taking (Applicable Wire Range)	Color	Burndy PAT444S & PAT4PC834LI.	Ilscos - IDT-6, IDT-6H, IDTB-6, IDTB- 6-LIO, TB-6DF1000-P, IDT-12-N, IVTB-6	Greenlee HK12ID, EK12IDL, N12ID	NSI M-500 & M-250	DeWalt DCE350	Milwaukee 2877-22
	B		C		G	H	I	K	M	DLO								
	AWG	STR	AWG	STR	AWG						AWG							
8	8	-	8	-	8	8	8	8	8	8	8-10	Red	-	-	-	-	-	-
6	6	7	6	19	6	6	6	6	-	6	6 - 8	Blue	Die-less	Die-less	Die-less	Die-less	Die-less	Die-less
4	4	7	4	19	-	-	-	-	-	-	4 - 6	Gray						
3	3	7	3	19	4	4	4	4	4	4	3 - 6	White						
2	2	7	2	19	4	4	4	4	4	4	2 - 6	Brown						
1	1	19	1	37	2	2	2	2	2	2	1 - 6	Green						
1/0	1/0	19	1/0	37	1	1	1	1	1	1	1/0 - 6	Pink						
2/0	2/0	19	2/0	37	1/0	1/0	1/0	1/0	1/0	1/0	2/0 - 4	Black						
3/0	3/0	19	3/0	37	2/0	2/0	2/0	2/0	2/0	2/0	3/0 - 2	Orange						
4/0	4/0	19	4/0	37	3/0	3/0	3/0	3/0	3/0	3/0	4/0 - 1	Purple						
250	250	37	250	61	4/0	4/0	4/0	4/0	4/0	4/0	250 - 1/0	Yellow						
300	300	37	300	61	250	250	-	-	-	-	300 - 2/0	White						
350	350	37	350	61	250	250	250	250	250	262	350 - 3/0	Red						
400	400	37	400	61	300	300	300	300	300	313	400 - 4/0	Blue						
500	500	37	500	61	350	350	350	350	350	373	500 - 250	Brown						
600	600	61	600	91	400	400	400	400	400	444	600 - 250	Green				-		
700	700	61	700	91	500	500	500	500	500	535	700 - 250	Pink				-		
750	750	61	750	91	600	600	600	-	600	646	750 - 500	Black				-		
1000	1000	61	1000	91	750	750	750	-	-	777	1000 - 750	White				-	-	

Tooling Selection Chart With Die Set Crimping Tools

Lug Size	Class B,C Cu. Cable		Class G,H,I,K Cu. Flex Cable	Class M Cu. Flex Cable	DLO Locomotive	Color	Burndy Y35, Y39, Y750, PAT750, PAT750LI	Ilscos ILC-12-N, ILC-12-H-N, ILCB-12	T&B TBM-15 & TBM14M	Huskie EP-510C	Greenlee HK1240 & EK1240LI	Hilti NUN-54-22	Milwaukee 2779-22	Panduit CT2931 & CT2940
	AWG	AWG	AWG	AWG	AWG									
8	8	8	8	8	8	Red	U8CRT	ILD - 21	15520	-	KC12 - 8	NCR SU CU 8	49-16-U008C	CD-920-8
6	6	6	6	6	-	Blue	U5CRT	ILD - 24-1	15522	HT41AT / HT41GL	KC12 - 6	NCR SU CU 6	49-16-U006C	CD-920-6
4	4	4	-	-	-	Gray	U4CRT	ILD - 29	15527-CK	HT41AU / HT41GE	KC12 - 4	NCR SU CU 4	49-16-U004C	CD-920-4
3	3	3	4	4	4	White	U3CRT	ILD - 29	-	HT41AV	-	NCR SU CU 2	-	-
2	2	2	4	4	4	Brown	U2CRT	ILD - 33	15528	HT41AW	KC12 - 2	NCR SU CU 2	49-16-U002C	CD-920-2
1	1	1	2	2	2	Green	U1CRT-1	ILD - 37	15512-CK	HT41AX	KC12 - 1	NCR SU CU 1	49-16-U001C	CD-920-1
1/0	1/0	1/0	1	1	1	Pink	U25RT	ILD - 42	15508	HT41AY	KC12 - 1/0	NCR SU CU 1/0	49-16-U01AC	CD-920-1/0
2/0	2/0	2/0	1/0	1/0	1/0	Black	U26RT	ILD - 45	15526	HT41AZ	KC12 - 2/0	NCR SU CU 2/0	49-16-U02AC	CD-920-2/0
3/0	3/0	3/0	2/0	2/0	2/0	Orange	U27RT	ILD - 50	15530	HT41BA	KC12 - 3/0	NCR SU CU 3/0	49-16-U03AC	CD-920-3/0
4/0	4/0	4/0	3/0	3/0	3/0	Purple	U28RT	ILD - 54	15511	HT41BC	KC12 - 4/0	NCR SU CU 4/0	49-16-U04AC	CD-920-4/0
250	250	250	4/0	4/0	4/0	Yellow	U29RT	ILD - 62	15510-CK	HT41BE	KC12 - 250	NCR SU CU 250	49-16-U250C	CD-920-250
300	300	300	250	-	-	White	U30RT	ILD - 66	15534	HT41BF	KC12 - 300	NCR SU CU 300	49-16-U300C	CD-920-300
350	350	350	250	250	262	Red	U31RT	ILD - 71	1551/4-CK	HT41BJ	KC12 - 350	NCR SU CU 350	49-16-U350C	CD-920-350
400	400	400	300	300	313	Blue	U32RT	ILD - 76	15512	HT41BK	KC12 - 400	NCR SU CU 400	49-16-U400C	CD-920-400
500	500	500	350	350	373	Brown	U34RT	ILD - 87	15506	HT41BL	KC12 - 500	NCR SU CU 500	49-16-U500C	CD-920-500
600	600	600	400	400	444	Green	U36RT	ILD - 94	15611	HT41BM /HT41HH	KC12 - 600	NCR SU CU 600	49-16-U600C	CD-920-600
700	700	700	500	500	535	Pink	U38RT/U38XRT	ILD - 99	15505	-	-	-	-	-
750	750	750	600	500	646	Black	U39RT	ILD - 106	15515-CK	HT41BP	KC12 - 750	-	49-16-U750C	CD-920-750
1000	1000	1000	750	-	777	White	U44XRT	ILD - 125	-	-	-	-	-	CD-940-1000