Aerrand API — Request & response shapes

Data shapes only: what you send, and what you get back.

```
Authorization: Bearer ak_live_...
Content-Type: application/json
Idempotency-Key: 5b0e2c3a-1d4f-4a9e-9f31-6c2b8a0d7e11
```

Base URL `https://api.aerrand.com/v1`

	Endpoint
Quote a price	`POST /quotes`
Create a delivery	`POST /errands`
Get a delivery	`GET /errands/{id}`
Track a delivery	`GET /errands/{id}/tracking`
Public tracking page data	`GET /errands/{id}/public`
Update drop-off instructions	`PUT /errands/{id}/dropoff`
Update pickup instructions	`PUT /errands/{id}/pickup`
Generate an item checklist (AI)	`POST /checklists/generate`
Attach a checklist	`POST /errands/{id}/checklist`
Attach tags	`POST /errands/{id}/tags`
Cancel	`POST /errands/{id}/cancel`
Service coverage	`GET /service-areas`

Features

Six capabilities behind one API key. Every one of them maps to something Aerrand runs today — this table says which endpoint serves it and where the full shape lives further down.

Feature	What you get	Endpoint	Full shape
Delivery tracking	live state of an errand: status, Aerrander, position, timeline, proof	`GET /errands/{id}/tracking`	§7
Aerrand stacking	one pickup → up to 5 drop-offs as a single Aerrander job	`POST /errands` with `dropoffs[]`	§3
Request pickup and delivery	turn a quote into a real, paid, dispatched errand	`POST /errands`	§2
Pricing	a binding quote before you commit	`POST /quotes`	§1
Drop-off instructions	who receives it and how it's handed over, editable mid-route	`PUT /errands/{id}/dropoff`	§5
Customer tracking	a tokenless link your own customer can open	`GET /errands/{id}/public`	§7d

Delivery tracking

What it is. The authoritative state of one errand, from the moment it's created to the proof-of-delivery photo — current status, the assigned Aerrander, their live position, a timestamped stage timeline, and the handover evidence.

In the stack. The Order record is the billing and lifecycle source of truth. The live fields — assigned Aerrander, GPS position, workflow phase, pickup/drop-off photos — live on the shared `deliveries` document that the Aerrander app writes to, and are merged onto the response at read time. Driver GPS reaches that document from the driver app's tracking loop (distance and time filtered, with a heartbeat) and is mirrored into Firebase Realtime Database, which is what makes a map move without polling.

Request. None — `GET /v1/errands/{id}/tracking`.

Response `200` (trimmed — full payload in §7a)


```
{
  "status": true,
  "data": {
    "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
    "status": "in_transit",
    "workflow_phase": "in_transit",
    "is_accepted": true,
    "driver": { "name": "Sam O.", "phone": "+15195550101", "rating": 4.9, "vehicle_type": "car" },
    "driver_location": { "lat": 42.3110, "lng": -83.0250, "heading": 118.4, "updated_at": "2026-09-23T09:31:02Z" },
    "timeline": [
      { "at": "2026-09-23T09:05:12Z", "state": "AERRANDER_ASSIGNED" },
      { "at": "2026-09-23T09:19:44Z", "state": "ROUTE_IN_PROGRESS" }
    ],
    "proof_of_delivery": null,
    "batch": { "id": "1f0a8c6e-4b21-4f90-9e77-3d2a5b6c8d10", "index": 0, "size": 2 }
  }
}
```


Poll every 5–10 s while an Aerrander is engaged, every 60 s before that — or take the webhooks in §7e and stop polling. `driver` is `null` until someone accepts.

Aerrand stacking — one pickup, many drop-offs

What it is. A single Aerrander collects one load and clears up to five drop-offs in sequence. One route, one price, one payment, one job on the Aerrander's phone.

In the stack. A stacked aerrand is **N delivery records, not one**: the API writes one Order per stop, linked by `batch_id` / `batch_index` / `batch_size`, mirrors them to the delivery documents as `batch: { id, index, size }`, and the driver backend groups them back into one job with ordered stops. Each stop keeps its own `errand_id`, handover code, status and share of the route price — so a stop can be delivered, or fail, on its own.

Request (`POST /v1/errands` — `dropoffs[]` instead of `dropoff`; full shape in §3)


```
{
  "reference": "RUN-2026-09-22-AM",
  "quote_id": "qt_01J8S3M4K9YV7B2R",
  "vehicle_type": "van",
  "pickup": {
    "label": "Warehouse A, 3040 Deziel Dr, Windsor, ON",
    "lat": "42.3149", "lng": "-83.0364",
    "contact": { "name": "Warehouse A", "phone_number": "+15195550137", "preference": "pickup" }
  },
  "dropoffs": [
```

```
    {
      "reference": "SHOP-10432",
      "label": "1823 Wyandotte St E, Windsor, ON",
      "lat": "42.3201", "lng": "-83.0187",
      "parcels": { "small": 2, "medium": 1 },
      "contact": { "name": "Jordan Alvarez", "phone_number": "+15195550188", "preference": "leave_at_door" }
    },
    {
      "reference": "SHOP-10433",
      "label": "3100 Howard Ave, Windsor, ON",
      "lat": "42.2789", "lng": "-82.9912",
      "parcels": { "small": 4 },
      "contact": { "name": "Priya Raman", "phone_number": "+15195550190", "preference": "meet_at_door" }
    }
  ]
}
```

Response `201` (trimmed)

```
{
  "batch_id": "1f0a8c6e-4b21-4f90-9e77-3d2a5b6c8d10",
  "status": "pending_payment",
  "stop_count": 2,
  "pricing": { "currency": "CAD", "route_price": 22.05, "hst": 2.87, "charge_total": 24.92 },
  "stops": [
    { "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44", "index": 0, "reference": "SHOP-10432", "status": "draft",
"price": "12.46", "delivery_code": "4F7K2Q" },
    { "errand_id": "a2d4f1b0-77c3-4e18-9a52-0b6d3e8c4411", "index": 1, "reference": "SHOP-10433", "status": "draft",
"price": "12.46", "delivery_code": "9T1M8C" }
  ]
}
```

Track each `errand_id` on its own; they share the `batch_id`. Five stops is the cap, and a load that exceeds van volume comes back from the quote as `overVanCapacity: true` — split it into two routes.

Request pickup and delivery

What it is. The create call: an address to collect from, one or more addresses to deliver to, what the parcel is, and how it's paid for.

In the stack. Create is two beats, not one. The errand is written as a draft in `pending_payment` and is **invisible to Aerranders until payment is verified** — verification is what promotes it to `broadcasted` and starts the Aerrander search. A `201` means accepted, not dispatched. Both a service-area check (is this address inside an activated city?) and your account's approval state are enforced at create time, before any money moves.

Request (minimal — everything else in §2 is optional)

```
{
  "reference": "SHOP-10432",
  "quote_id": "qt_01J8S3M4K9YV7B2R",
  "vehicle_type": "car",
  "parcel": { "size": "medium", "quantity": 3, "description": "3 x 18in pizza boxes" },
  "pickup": {
    "label": "Aerrand HQ, 500 Ouellette Ave, Windsor, ON N9A 1B3",
    "lat": "42.3149", "lng": "-83.0364",
    "contact": { "name": "Store 14 - back door", "phone_number": "+15195550137", "instructions": "Ring the loading-
bay bell.", "preference": "pickup" }
  },
```

```
  "dropoff": {
    "label": "1823 Wyandotte St E, Windsor, ON N9A 3K5",
    "lat": "42.3201", "lng": "-83.0187",
    "contact": { "name": "Jordan Alvarez", "phone_number": "+15195550188", "instructions": "Buzzer 4B.",
"preference": "leave_at_door" }
  },
  "payment": { "method": "invoice" },
  "metadata": { "shopify_order_id": "6712341" }
}
```

Response `201` (trimmed)

```
{
  "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
  "delivery_id": "66f2a1c4e9b7d3a50c118f22",
  "status": "pending_payment",
  "reference": "SHOP-10432",
  "delivery_code": "4F7K2Q",
  "pricing": { "currency": "CAD", "route_price": 12.05, "hst": 1.57, "charge_total": 13.62 },
  "payment": { "status": "unpaid", "method": "invoice", "checkout_url": null },
  "tracking": {
    "self": "https://api.aerrand.com/v1/errands/8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44/tracking",
    "public_url": "https://business.aerrand.com/track/8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44"
  }
}
```

`delivery_code` is the handover code the receiver gives the Aerrander. Keep it off any page your customer can reach — that's the whole reason the public payload in §7d omits it.

Pricing

What it is. A priced, time-limited quote you can show a customer before they commit, and book against afterwards.

In the stack. Two engines, and which one answers depends on what you ask for. **Route pricing** (the business engine) is deterministic and distance-driven: a trip base, a base per stop, distance charged beyond a free allowance, size add-ons per parcel, a handling fee past the included parcel count, a flat surcharge when the load needs a van on volume alone, then HST. No time-of-day component. **Parcel pricing** (the customer engine) adds rush and night surcharges and, when a declared value is present, Aerrand Guard — the item's value held in escrow on top of the fee.

The quote returns a `quote_id`. `POST /errands` takes **that id, never a price** — the server prices the errand itself and will not accept a client-supplied amount.

Request (route quote; parcel quote in §1b)

```
{
  "pickup": { "lat": 42.3149, "lng": -83.0364 },
  "stops": [
    { "lat": 42.3201, "lng": -83.0187, "parcels": { "small": 2, "medium": 1 } },
    { "lat": 42.2789, "lng": -82.9912, "parcels": { "small": 4 } }
  ]
}
```

Response `200` (trimmed)

```
{
  "quote_id": "qt_01J8S3M4K9YV7B2R",
```

```
  "expires_at": "2026-09-22T14:18:11Z",
  "currency": "CAD",
  "stopCount": 2,
  "totalParcels": 7,
  "routeKm": 9.84,
  "dropBaseTotal": 11.50,
  "distanceCharge": 8.55,
  "sizeAddOnTotal": 2.00,
  "handlingTotal": 0.00,
  "volumeSurcharge": 0.00,
  "routePrice": 22.05,
  "hst": 2.87,
  "chargeTotal": 24.92,
  "recommendedVehicle": "motorcycle",
  "requiresCargoVehicle": false,
  "overVanCapacity": false
}
```


Quoting is free and unmetered — quote on every cart change if you want. `chargeTotal` is what you pay, tax in.

Drop-off instructions

What it is. The receiving half of a delivery: who's expecting it, how to reach them, what the Aerrander should do at the door, and whether it can be left there at all.

In the stack. The instruction is its own record attached to the errand and mirrored onto the delivery document, which is why an edit reaches the Aerrander's phone immediately — including mid-route, after they've already left the pickup. `preference` is the one field that changes the Aerrander's behaviour rather than just informing it: `leave_at_door` permits an unattended drop with a photo, the other two require a person. Oversized parcels are forced to `meet_at_curb`.

Request (`PUT /v1/errands/{id}/dropoff` — partial updates are fine)

```
{
  "name": "Jordan Alvarez",
  "phone_number": "+15195550188",
  "instructions": "Changed: leave with the concierge in the lobby, buzzer is broken.",
  "preference": "leave_at_door"
}
```

Response `200`


```
{
  "status": true,
  "message": "Dropoff instruction updated",
  "data": {
    "id": "b7a1f0c2-4e39-4d51-a8c2-5f6d9e0b1234",
    "name": "Jordan Alvarez",
    "phone_number": "+15195550188",
    "instructions": "Changed: leave with the concierge in the lobby, buzzer is broken.",
    "preference": "leave_at_door"
  }
}
```


There's an edit window: once the Aerrander is within 1 km of the stop only `instructions` can still change, and after the stop completes nothing can. Full table in §5. Pickup instructions are the same shape at `PUT /v1/errands/{id}/pickup`.

Customer tracking

What it is. The page *your* customer opens — the one who ordered from you and has never heard of Aerrand. No account, no API key, no login.

In the stack. Same underlying tracking record, filtered. The errand id is the bearer token, so the payload is deliberately a safe subset: status, the two addresses, the Aerrander's first name, vehicle and plate, their live position, and the timeline. It carries **no** `delivery_code` — that's the handover OTP — and no account, pricing or contact data. Aerrand hosts a ready-made page at `business.aerrand.com/track/{errand_id}`; the JSON endpoint is there so you can render the same thing inside your own brand instead.

Request. None — `GET /v1/errands/{id}/public`, unauthenticated.

Response `200`


```
{
  "success": true,
  "data": {
    "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
    "status": "in_transit",
    "pickup": { "label": "500 Ouellette Ave, Windsor, ON", "lat": "42.3149", "lng": "-83.0364" },
    "dropoff": { "label": "1823 Wyandotte St E, Windsor, ON", "lat": "42.3201", "lng": "-83.0187" },
    "driver": {
      "name": "Sam O.", "image": null,
      "vehicle_model": "Toyota Corolla", "vehicle_type": "car", "plate_number": "CXYZ 123"
    },
    "driver_lat": "42.3110",
    "driver_lng": "-83.0250",
    "timeline": [ { "at": "2026-09-23T09:05:12Z", "state": "AERRANDER_ASSIGNED" } ],
    "created_at": "2026-09-22T14:03:11Z"
  }
}
```


Because the id is the token, treat the link the way you'd treat an order-confirmation link: fine in an email or SMS to the buyer, not fine on a public page.

Live today vs. built for the key

The six features above all exist inside Aerrand already — the dashboard and both apps use them every day. What the developer key adds is a public surface in front of them.

Feature	Already running	Needed for the key
Pricing	both engines, both endpoints	issue and bind `quote_id`; stop accepting a client-supplied price
Request pickup and delivery	create → pay → dispatch, service-area and approval gates	API-key auth, `Idempotency-Key`, `reference` / `metadata` passthrough
Aerrand stacking	N-order batch, single Aerrander job, one payment	nothing new — same create path, keyed
Delivery tracking	status, Aerrander, stage timeline	surface `driver_location` and `proof_of_delivery` on the endpoint; webhook delivery + signing
Drop-off instructions	edit endpoint, 1 km edit window	expose the field as `preference` (the stored column is misspelled `pick_up_prefrence`)
Customer tracking	tokenless public payload	a stable public URL and optional white-labelling

1. Pricing

`POST /v1/quotes`

Returns a `quote_id` you pass to `POST /v1/errands`. The price is locked to that quote until it expires.

1a. Route quote — one pickup, 1–5 stops

Request

```
{
  "pickup": { "lat": 42.3149, "lng": -83.0364 },
  "stops": [
    { "lat": 42.3201, "lng": -83.0187, "parcels": { "small": 2, "medium": 1 } },
    { "lat": 42.2789, "lng": -82.9912, "parcels": { "small": 4 } }
  ]
}
```

Response `200`

```
{
  "quote_id": "qt_01J8S3M4K9YV7B2R",
  "expires_at": "2026-09-22T14:18:11Z",
  "currency": "CAD",

  "stopCount": 2,
  "totalParcels": 7,
  "routeKm": 9.84,

  "dropBaseTotal": 11.50,
  "distanceCharge": 8.55,
  "sizeAddOnTotal": 2.00,
  "handlingTotal": 0.00,
  "volumeSurcharge": 0.00,
  "routePrice": 22.05,
  "hstRate": 0.13,
  "hst": 2.87,
  "chargeTotal": 24.92,
  "amount_cents": 2492,

  "recommendedVehicle": "motorcycle",
  "requiresCargoVehicle": false,
  "totalCargoUnits": 4.0,
  "overVanCapacity": false
}
```

Field	Meaning
`dropBaseTotal`	first stop + each additional stop
`distanceCharge`	driven km beyond the free allowance
`sizeAddOnTotal`	per-parcel size add-ons
`handlingTotal`	parcels beyond the included count, per stop
`volumeSurcharge`	flat, only when the load needs a van on volume alone
`routePrice`	pre-tax total
`chargeTotal`	what you're charged, tax in
`overVanCapacity`	`true` → the route can't be booked; split it

1b. Parcel quote — single pickup → drop-off

Request

```
{
  "pickup": { "lat": 42.3149, "lng": -83.0364 },
  "dropoff": { "lat": 42.2789, "lng": -82.9912 },
  "size": "medium",
  "priority": false,
  "declared_value": 400.00,
  "scheduled_at": "2026-09-23T15:00:00Z"
}
```

`size` accepts a tier (`small` · `medium` · `large` · `xl`) or a weight in pounds. `declared_value` turns on Aerrand Guard — the value is held in escrow and added to the total.

Response `200`

```
{
  "quote_id": "qt_01J8S3P7T2XM4C9D",
  "expires_at": "2026-09-22T14:18:11Z",
  "currency": "CAD",

  "size_category": "medium",
  "distanceKm": 6.4,
  "estimatedTimeMinutes": 13.2,

  "deliveryFee": 14.28,
  "guardFee": 12.00,
  "itemValueHeld": 400.00,
  "hstRate": 0.13,
  "hst": 3.42,
  "totalDueAtBooking": 429.71,
  "amount_cents": 42971,

  "breakdown": {
    "base": 6.00,
    "distanceAddOn": 5.28,
    "sizeAddOn": 2.00,
    "surchargeLabel": "rush",
```

```
    "rushHourSurcharge": 1.00,
    "nightSurcharge": 0.00,
    "timeAddOn": 0.00,
    "priorityMultiplierApplied": false,
    "guardActive": true,
    "guardValueBand": "mid"
  }
}
```

Tax applies to the delivery fee and the Guard fee. `itemValueHeld` is escrow, not a sale — it's in the total but not taxed. `surchargeLabel` is `null`, `"rush"` or `"night"`.

2. Create a delivery — single drop-off

`POST /v1/errands`

Request

```
{
  "reference": "SHOP-10432",
  "quote_id": "qt_01J8S3M4K9YV7B2R",
  "vehicle_type": "car",
  "scheduled_at": "2026-09-23T15:00:00Z",

  "parcel": {
    "size": "medium",
    "quantity": 3,
    "description": "3 x 18in pizza boxes",
    "declared_value": null
  },

  "pickup": {
    "label": "Aerrand HQ, 500 Ouellette Ave, Windsor, ON N9A 1B3",
    "lat": "42.3149",
    "lng": "-83.0364",
    "contact": {
      "name": "Store 14 - back door",
      "phone_number": "+15195550137",
      "email": "store14@example.com",
      "instructions": "Ring the loading-bay bell, ask for the shift lead.",
      "preference": "pickup"
    }
  },

  "dropoff": {
    "label": "1823 Wyandotte St E, Windsor, ON N9A 3K5",
    "lat": "42.3201",
    "lng": "-83.0187",
    "contact": {
      "name": "Jordan Alvarez",
      "phone_number": "+15195550188",
      "instructions": "Buzzer 4B. Leave with concierge if no answer.",
      "preference": "leave_at_door"
    }
  },

  "delivery_note": "Keep flat - do not stack.",
  "payment": { "method": "invoice" },
  "metadata": { "shopify_order_id": "6712341", "channel": "web" }
}
```

Response `201`

```
{
  "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
  "delivery_id": "66f2a1c4e9b7d3a50c118f22",
  "status": "pending_payment",
  "reference": "SHOP-10432",
```

```
  "created_at": "2026-09-22T14:03:11Z",
  "scheduled_at": "2026-09-23T15:00:00Z",
  "delivery_code": "4F7K2Q",

  "pricing": {
    "currency": "CAD",
    "route_price": 12.05,
    "hst": 1.57,
    "charge_total": 13.62,
    "amount_cents": 1362
  },

  "payment": {
    "status": "unpaid",
    "method": "invoice",
    "checkout_url": null,
    "reference": null
  },

  "pickup": {
    "label": "Aerrand HQ, 500 Ouellette Ave, Windsor, ON N9A 1B3",
    "lat": "42.3149",
    "lng": "-83.0364",
    "contact": {
      "name": "Store 14 - back door",
      "phone_number": "+15195550137",
      "email": "store14@example.com",
      "instructions": "Ring the loading-bay bell, ask for the shift lead.",
      "preference": "pickup"
    }
  },

  "dropoff": {
    "label": "1823 Wyandotte St E, Windsor, ON N9A 3K5",
    "lat": "42.3201",
    "lng": "-83.0187",
    "contact": {
      "name": "Jordan Alvarez",
      "phone_number": "+15195550188",
      "instructions": "Buzzer 4B. Leave with concierge if no answer.",
      "preference": "leave_at_door"
    }
  },

  "tracking": {
    "self": "https://api.aerrand.com/v1/errands/8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44/tracking",
    "public_url": "https://business.aerrand.com/track/8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44"
  },

  "metadata": { "shopify_order_id": "6712341", "channel": "web" }
}
```

3. Create a delivery — multi-stop route

Same envelope, one shared `pickup` and a `dropoffs` array (1–5 stops).

Request

```
{
  "reference": "RUN-2026-09-22-AM",
  "quote_id": "qt_01J8S3M4K9YV7B2R",
  "vehicle_type": "van",
  "scheduled_at": "2026-09-23T09:00:00Z",

  "pickup": {
    "label": "Warehouse A, 3040 Deziel Dr, Windsor, ON",
    "lat": "42.3149",
    "lng": "-83.0364",
    "contact": {
      "name": "Warehouse A",
      "phone_number": "+15195550137",
      "instructions": "Dock 3",
      "preference": "pickup"
    }
  },

  "dropoffs": [
    {
      "reference": "SHOP-10432",
      "label": "1823 Wyandotte St E, Windsor, ON",
      "lat": "42.3201",
      "lng": "-83.0187",
      "parcels": { "small": 2, "medium": 1 },
      "contact": {
        "name": "Jordan Alvarez",
        "phone_number": "+15195550188",
        "instructions": "Buzzer 4B",
        "preference": "leave_at_door"
      }
    },
    {
      "reference": "SHOP-10433",
      "label": "3100 Howard Ave, Windsor, ON",
      "lat": "42.2789",
      "lng": "-82.9912",
      "parcels": { "small": 4 },
      "contact": {
        "name": "Priya Raman",
        "phone_number": "+15195550190",
        "instructions": "Side entrance, ask at desk",
        "preference": "meet_at_door"
      }
    }
  ],

  "payment": { "method": "invoice" }
}
```

Response `201`


```
{
  "batch_id": "1f0a8c6e-4b21-4f90-9e77-3d2a5b6c8d10",
  "status": "pending_payment",
  "stop_count": 2,
  "created_at": "2026-09-22T14:03:11Z",

  "pricing": {
    "currency": "CAD",
    "route_price": 22.05,
    "hst": 2.87,
    "charge_total": 24.92,
    "amount_cents": 2492
  },

  "payment": {
    "status": "unpaid",
    "method": "invoice",
    "total": "24.92",
    "covers": ["8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44", "a2d4f1b0-77c3-4e18-9a52-0b6d3e8c4411"]
  },

  "stops": [
    {
      "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
      "index": 0,
      "reference": "SHOP-10432",
      "label": "1823 Wyandotte St E, Windsor, ON",
      "lat": "42.3201",
      "lng": "-83.0187",
      "receiver_name": "Jordan Alvarez",
      "status": "draft",
      "price": "12.46",
      "payment_status": false,
      "delivery_code": "4F7K2Q"
    },
    {
      "errand_id": "a2d4f1b0-77c3-4e18-9a52-0b6d3e8c4411",
      "index": 1,
      "reference": "SHOP-10433",
      "label": "3100 Howard Ave, Windsor, ON",
      "lat": "42.2789",
      "lng": "-82.9912",
      "receiver_name": "Priya Raman",
      "status": "draft",
      "price": "12.46",
      "payment_status": false,
      "delivery_code": "9T1M8C"
    }
  ]
}
```


A route is **one job for the Aerrander** but **N delivery records** — one per stop, each with its own `errand_id`, `delivery_code` and share of the route price. Track them individually; they share the `batch_id`.

4. Minimal request

Everything else is optional.

```
{
  "quote_id": "qt_01J8S3M4K9YV7B2R",
  "pickup": {
    "label": "500 Ouellette Ave, Windsor, ON",
    "lat": "42.3149",
    "lng": "-83.0364",
    "contact": { "name": "Store 14", "phone_number": "+15195550137", "preference": "pickup" }
  },
  "dropoff": {
    "label": "1823 Wyandotte St E, Windsor, ON",
    "lat": "42.3201",
    "lng": "-83.0187",
    "contact": { "name": "Jordan Alvarez", "phone_number": "+15195550188", "preference": "leave_at_door" }
  }
}
```

5. Drop-off instructions

Set them inline on create (`dropoff.contact`), or change them afterwards.

`PUT /v1/errands/{id}/dropoff`

Request

```
{
  "name": "Jordan Alvarez",
  "phone_number": "+15195550188",
  "instructions": "Changed: leave with the concierge in the lobby, buzzer is broken.",
  "preference": "leave_at_door"
}
```

Partial updates are fine — send only the keys you're changing. If the delivery has no drop-off instructions yet, this creates them.

Response `200`

```
{
  "status": true,
  "message": "Dropoff instruction updated",
  "data": {
    "id": "b7a1f0c2-4e39-4d51-a8c2-5f6d9e0b1234",
    "name": "Jordan Alvarez",
    "phone_number": "+15195550188",
    "instructions": "Changed: leave with the concierge in the lobby, buzzer is broken.",
    "preference": "leave_at_door"
  }
}
```

Field	Type	Required	Notes
`name`	string ≤255	yes	receiver's name
`phone_number`	string ≤255	yes	E.164 preferred; used for delivery SMS
`instructions`	string ≤255	no	"Buzzer 4B. Leave with concierge."
`preference`	enum	yes	`leave_at_door` · `meet_at_door` · `meet_at_curb`

The change reaches the Aerrander's app immediately, including mid-route.

Edit window — once the Aerrander is within 1 km of the stop, only `instructions` can change; name, phone and preference are locked. After the stop is completed, nothing can change.

Delivery state	Drop-off edit
up to `in_transit`	all fields
within 1 km of the stop	`instructions` only — others return `409 edit_window_closed`
`delivered` · `cancelled`	rejected

Pickup instructions are the same shape at `PUT /v1/errands/{id}/pickup` , with one extra field: `email` (string, optional).

6. AI item checklist

For marketplace and secondhand pickups: generate condition checks the Aerrander runs through at pickup, plus a suggested size tier and category tags inferred from what the item actually is.

`POST /v1/checklists/generate`

Request

```
{
  "description": "65 inch Samsung QLED TV, wall mounted, selling due to move",
  "quantity": 1,
  "size": "medium",
  "price": 450.00
}
```

Field	Type	Required	Notes
`description`	string	yes	the item as the seller described it
`quantity`	integer	no	how many
`size`	enum	no	the size you *think* it is — the model may correct it
`price`	number	no	asking price, CAD

Response `200`

```
{
  "checklist": [
    "Check the screen for cracks, scratches or dead pixels",
    "Check the bezel and corners for impact damage",
    "Check the rear panel for missing mount screws",
    "Check the stand and feet for bends or missing hardware",
    "Check the ports and cable inputs for bent pins"
  ],
  "suggested_size": "xlarge",
  "suggested_tags": ["Electronics", "Fragile", "Marketplace"]
}
```

Field	Type	Notes
`checklist`	string[]	up to 5 physical condition checks, ≤80 chars each
`suggested_size`	enum or `null`	`small` · `medium` · `large` · `xlarge` — judged from the item, not the quantity
`suggested_tags`	string[]	1–3, from the fixed tag list below

This endpoint **never fails the booking**: if the model is unavailable it returns `{ "checklist": [], "suggested_size": null, "suggested_tags": [] }` with `200`. Treat empty arrays as "no suggestion", not as an error, and let the customer type their own checks.

`suggested_size` is advisory — it can disagree with the size you sent, and it's usually right (a television is not bag-sized no matter what the quantity field says). Re-quote if you accept it.

Tag vocabulary — responses only ever contain these:

```
Marketplace · Food · Electronics · Documents · Clothing
Groceries · Furniture · Gifts · Medical · Fragile
```

Attaching them to a delivery

`POST /v1/errands/{id}/checklist`

```
{ "checklists": ["Check the screen for cracks, scratches or dead pixels", "Check the ports for bent pins"] }
```


```
{
  "status": true,
  "message": "Checklists added successfully",
  "data": [
    { "id": "5c2e1a90-7b43-4f11-9d02-8a6e3f1c0b77", "title": "Check the screen for cracks, scratches or dead pixels"
},
    { "id": "9a71d4e8-2c05-4b8f-a3e6-1d7b902c4f55", "title": "Check the ports for bent pins" }
  ]
}
```


`POST /v1/errands/{id}/tags`

```
{ "tags": ["Electronics", "Fragile"] }
```


```
{
  "status": true,
  "message": "Tags added successfully",
  "data": [
    { "id": "3f8b2c14-6d90-4a72-b5e1-0c9d8e4a7b23", "title": "Electronics" },
    { "id": "7e4a9d02-1b56-4c38-8f90-2a5c6b1d3e84", "title": "Fragile" }
  ]
}
```


Both accept a list of strings, deduplicate, and are safe to call more than once.

7. Delivery tracking

7a. Poll — `GET /v1/errands/{id}/tracking`

The cheap call. Poll every 5–10 s while an Aerrander is engaged, every 60 s before dispatch.


```
{
  "status": true,
  "data": {
    "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
    "delivery_id": "66f2a1c4e9b7d3a50c118f22",
    "status": "in_transit",
    "workflow_phase": "in_transit",
    "is_accepted": true,

    "driver": {
      "id": "66e0b8f1c4a2d35907ab1e44",
      "name": "Sam O.",
      "phone": "+15195550101",
      "image": "https://res.cloudinary.com/aerrand/image/upload/v1/drivers/abc.jpg",
      "rating": 4.9,
      "vehicle_type": "car",
      "total_deliveries": 218,
      "verified": true,
      "city": "Windsor"
    },

    "driver_location": {
      "lat": 42.3110,
      "lng": -83.0250,
      "heading": 118.4,
      "updated_at": "2026-09-23T09:31:02Z"
    },

    "delivery_code": "4F7K2Q",
    "accepted_at": "2026-09-23T09:05:12Z",
    "started_at": "2026-09-23T09:19:44Z",
    "completed_at": null,
    "updated_at": "2026-09-23T09:31:02Z",

    "timeline": [
      { "at": "2026-09-23T09:05:12Z", "state": "AERRANDER_ASSIGNED" },
      { "at": "2026-09-23T09:14:03Z", "state": "AT_PICKUP_LOADING" },
      { "at": "2026-09-23T09:19:44Z", "state": "ROUTE_IN_PROGRESS" }
    ],

    "proof_of_delivery": null,
    "batch": { "id": "1f0a8c6e-4b21-4f90-9e77-3d2a5b6c8d10", "index": 0, "size": 2 }
  }
}
```


On completion, `proof_of_delivery` fills in:


```
"proof_of_delivery": {
  "photo_url": "https://res.cloudinary.com/aerrand/image/upload/v1/pod/8f1c.jpg",
```

```
  "uploaded_at": "2026-09-23T09:41:55Z"
}
```

`driver` is `null` until someone accepts. `driver.phone` is `null` for Aerranders who signed up with Google or Apple — that's expected, not an error; use in-app messaging.

7b. Statuses

status	Meaning	Aerrander assigned
`pending_payment`	created, not paid	no
`pending`	paid, awaiting dispatch	no
`broadcasted`	offered to Aerranders	no
`accepted`	assigned, heading to pickup	yes
`arrived`	at pickup	yes
`picked_up`	items collected	yes
`in_transit`	en route to drop-off	yes
`arrived_dropoff`	at the door, proof photo uploading	yes
`delivered`	complete	yes
`cancelled`	terminal	—

Treat any status you don't recognise as "in progress" rather than an error — the list grows. For "where is it exactly", read `timeline`, not `status`.

7c. Full record — `GET /v1/errands/{id}`

Everything from create, plus everything from tracking, plus:

```
{
  "payment_status": true,
  "distance_km": "6.4",
  "cancellation": null,
  "batch": {
    "id": "1f0a8c6e-4b21-4f90-9e77-3d2a5b6c8d10",
    "index": 0,
    "size": 2,
    "total": "24.92",
    "paid_total": "24.92",
    "stops": [
      { "errand_id": "8f1c...", "index": 0, "label": "1823 Wyandotte St E", "receiver_name": "Jordan Alvarez",
"status": "delivered", "price": "12.46", "payment_status": true }
    ]
  }
}
```

`batch.stops` is only on this call — tracking rows carry the bare `{ id, index, size }`.

7d. Share a tracking link with your customer

`GET /v1/errands/{id}/public` — no auth, the id is the token. Safe subset: status, addresses, driver name and vehicle, live position, timeline. No `delivery_code`, no account data.


```
{
  "success": true,
  "data": {
    "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
    "status": "in_transit",
    "pickup": { "label": "500 Ouellette Ave, Windsor, ON", "lat": "42.3149", "lng": "-83.0364" },
    "dropoff": { "label": "1823 Wyandotte St E, Windsor, ON", "lat": "42.3201", "lng": "-83.0187" },
    "driver": {
      "name": "Sam O.", "image": null,
      "vehicle_model": "Toyota Corolla", "vehicle_type": "car", "plate_number": "CXYZ 123"
    },
    "driver_lat": "42.3110",
    "driver_lng": "-83.0250",
    "timeline": [ { "at": "2026-09-23T09:05:12Z", "state": "AERRANDER_ASSIGNED" } ],
    "created_at": "2026-09-22T14:03:11Z"
  }
}
```


7e. Webhooks


```
{
  "id": "evt_01J8S3P2Q7",
  "type": "errand.in_transit",
  "created_at": "2026-09-23T09:19:44Z",
  "data": {
    "errand_id": "8f1c2b7e-9a34-4d62-b0f1-2c5e7a9d1b44",
    "batch_id": "1f0a8c6e-4b21-4f90-9e77-3d2a5b6c8d10",
    "reference": "SHOP-10432",
    "status": "in_transit",
    "driver": { "name": "Sam O.", "vehicle_type": "car" },
    "occurred_at": "2026-09-23T09:19:44Z"
  }
}
```


Event	Fires when
`errand.payment_confirmed`	paid; Aerrander search starts
`errand.accepted`	Aerrander assigned
`errand.arrived_pickup`	at pickup
`errand.in_transit`	picked up and on the way
`errand.arrived_dropoff`	at the door
`errand.delivered`	complete, with `proof_of_delivery`
`errand.cancelled`	cancelled by any party
`errand.dropoff_updated`	drop-off instructions changed

Signed as `Aerrand-Signature: t=<unix>,v1=<hex hmac_sha256>` over `t + "." + raw_body`, using the raw request bytes. Delivery is at-least-once — deduplicate on `id`.

8. Fields

Top level

Field	Type	Required	Notes
`quote_id`	string	yes	from `POST /v1/quotes`; binds the price
`pickup`	object	yes	see **Location**
`dropoff`	object	one of	single delivery
`dropoffs`	array	one of	1–5 stops; each is a **Location** plus `reference` and `parcels`
`reference`	string ≤255	no	your own order number; echoed everywhere
`vehicle_type`	enum	no	`scooter` · `motorcycle` · `car` · `van` · `truck`
`scheduled_at`	ISO 8601 UTC	no	omit for "as soon as possible"
`parcel`	object	no	single delivery only
`delivery_note`	string	no	free text shown to the Aerrander
`payment`	object	no	`{ "method": "invoice", "email": "ap@example.com" }` — or `"method": "checkout_link"`
`metadata`	object	no	round-tripped untouched; string keys and values

Location (`pickup`, `dropoff`, each `dropoffs[]`)

Field	Type	Required	Notes
`label`	string ≤255	yes	full address as you want it shown
`lat`	string	yes	decimal degrees, e.g. `"42.3201"`
`lng`	string	yes	decimal degrees
`contact`	object	yes	see **Contact**
`reference`	string	no	per-stop order number (multi-stop only)
`parcels`	object	no	per-stop counts (multi-stop only): `{ "small": 2, "medium": 1, "large": 0, "xl": 0 }`

`lat` / `lng` are strings, and they must be real geocoded coordinates — `(0, 0)`, blank or non-numeric values are rejected, because the Aerrander's arrival geofence is checked against them.

Contact (`pickup.contact` , `dropoff.contact`)

Field	Type	Required	Notes
`name`	string ≤255	yes	receiver's name, or the pickup desk/department
`phone_number`	string ≤255	yes	E.164 preferred; used for delivery SMS
`instructions`	string ≤255	no	"Buzzer 4B. Leave with concierge."
`preference`	enum	yes	drop-off: `leave_at_door` · `meet_at_door` · `meet_at_curb` — pickup: `pickup`
`email`	string	no	**pickup only**

Parcel (single delivery)

Field	Type	Required	Notes
`size`	enum or number	yes	`small` · `medium` · `large` · `xl` , or weight in pounds
`quantity`	integer	no	number of items
`description`	string ≤255	no	what's in the parcel
`declared_value`	number	no	CAD; turns on Aerrand Guard (value held in escrow)

9. Enums

```
vehicle_type          scooter | motorcycle | car | van | truck
parcel size           small | medium | large | xl        (or weight in lbs)
checklist size tier   small | medium | large | xlarge
dropoff preference    leave_at_door | meet_at_door | meet_at_curb
pickup preference     pickup
payment method        invoice | checkout_link
currency              CAD
```

`xl` parcels are curbside — send `meet_at_curb`.

10. Returned identifiers

Field	Shape	Use it for
`errand_id`	UUID	every follow-up call: tracking, updates, cancel
`batch_id`	UUID	groups the stops of one route
`delivery_id`	24-char hex	the record the Aerrander's app works from
`delivery_code`	6 chars	the code your receiver gives the Aerrander — share it with them, don't print it on the parcel
`quote_id`	string	binds a price to a booking

11. Errors


```
{
  "error": {
    "code": "service_area_unavailable",
    "message": "Aerrand isn't available at drop-off #2 yet. The closest city we serve is Windsor (41 km away).",
    "details": {
      "pickup": { "inside": true, "city": "windsor" },
      "dropoffs": [
        { "inside": true, "city": "windsor" },
        { "inside": false, "city": null }
      ],
      "nearestCity": { "slug": "windsor", "name": "Windsor", "province": "ON", "distanceKm": 41.2 }
    }
  }
}
```


HTTP	code	Meaning
400	`validation_failed`	`details` maps field → messages
400	`route_over_capacity`	route exceeds one cargo van; split the booking
401	`invalid_api_key`	
404	`errand_not_found`	
409	`quote_expired`	request a new quote
409	`edit_window_closed`	too late to change instructions
409	`cancel_not_allowed`	Aerrander is at the stop, or it's already delivered
412	`business_not_approved`	account still under review
412	`service_area_unavailable`	a pickup or drop-off is outside a served city
429	`rate_limited`	retry with backoff

Check coverage before you offer delivery at checkout: `GET /v1/service-areas`.


```
{
  "serviceAreas": [
    { "slug": "windsor", "name": "Windsor", "province": "ON", "lat": 42.3149, "lng": -83.0364, "radiusKm": 20.0,
"active": true }
  ],
  "updatedAt": "2026-09-02T18:41:07Z"
}
```