

## C++ Programming: C++ Functions

Total Questions: 24

For Answers Click Here: <http://www.eduzip.com/cpp-programming/cpp-functions.html>

1: The signature of a function is its ..... ?

- A. Function code
- B. Prototype
- C. Call
- D. Parameter list

2: What is true about inline functions ?

- A. It's a compulsion on the compiler to make function inline
- B. It's a request to the compiler to make the function inline
- C. It's the indication to the compiler that the function is recursive
- D. It's the indication to the compiler that the function is member function

3: Which member function of class cannot modify its objects attributes ?

- A. friend functions
- B. Private member functions
- C. Constant member functions
- D. Static member functions

4: Which of the following parameter passing mechanism is/are supported by C++ but not in C?

- A. Pass by value
- B. Pass by reference
- C. Pass by value result
- D. All of the above

5: Which of the following type of function is an ideal candidate for being declared inline ?

- A. A function that is small and is not called frequently
- B. A function that is small and is called frequently
- C. A function that is not small and is not called frequently
- D. A function that is not small and is called frequently

6: One of the disadvantage of pass by reference is that the called function may inadvertently corrupt the called data. This is avoided by ?

- A. passing pointers
- B. declaring the formal parameters constant
- C. declaring the actual parameters constant
- D. all of above

7: The library function exit() causes an exit from ?

- A. The loop in which it occurs
- B. The block in which it occurs
- C. The function in which it occurs
- D. The program in which it occurs

8: The getch() library function

- A. returns a character when any key is pressed
- B. returns a character when ENTER is pressed
- C. displays a character on the screen when any key is pressed
- D. does not display a character on the screen

9: When an argument is passed by reference

- A. a variable is created in function to hold the argument value
- B. the function cannot access the argument value
- C. a temporary variable is created in the calling program to hold arguments value
- D. None of these

10: Overloaded function

- A. are a group of functions, with the same value
- B. all have the same number and types of arguments
- C. make life simpler for programmers
- D. may fail unexpectedly due to stress

11: Using turbo C++ library function can ?

- A. color any closed figure
- B. draw lines and circles
- C. write in variety of fonts and sizes
- D. all of above

12: A friend function can be used to ?

- A. avoid arguments between classes
- B. allow access to classes whose source code is unavailable
- C. allow one class to access an unrelated class
- D. increase the versatility of an overloaded operator

13: A static function

- A. should be called when an object is destroyed
- B. is closely connected with an individual object of a class
- C. can be called using the class name and function
- D. is used when a dummy object must be created

14: Dividing a program into functions

- A. is the key to object oriented programming
- B. makes the program easier to conceptualize
- C. makes the program run faster
- D. both (B) and (C)

15: Static Member function

- A. can access any other member function & member variables
- B. can access only static member variables & member functions
- C. can be only called through object of the class
- D. Returns only static data

**Explanation:** Static Member function can access only static member variables & member functions

16: A friend function

- A. is declared as a friend & defined elsewhere in the program

- B. is always an inline function
- C. created objects without initialization
- D. May be a static member function of the class

**Explanation:** A friend function is declared as a friend & defined elsewhere in the program

**17:** Which of the following function prototype is perfectly acceptable?

- A. `int Function(int Tmp = Show());`
- B. `float Function(int Tmp = Show(int, float));`
- C. Both A and B.
- D. `float = Show(int, float) Function(Tmp);`

**18:** Which of the following statement is correct?

- A. C++ enables to define functions that take constants as an argument.
- B. We cannot change the argument of the function that that are declared as constant.
- C. Both A and B.
- D. We cannot use the constant while defining the function.

**19:** Which of the following statement is correct?

- A. Overloaded functions can have at most one default argument.
- B. An overloaded function cannot have default argument.
- C. All arguments of an overloaded function can be default.
- D. A function if overloaded more than once cannot have default argument.

**20:** Which of the following statement will be correct if the function has three arguments passed to it?

- A. The trailing argument will be the default argument.
- B. The first argument will be the default argument.
- C. The middle argument will be the default argument.
- D. All the argument will be the default argument.

**21:** Which of the following statement is incorrect?

- A. Default arguments can be provided for pointers to functions.
- B. A function can have all its arguments as default.
- C. Default argument cannot be provided for pointers to functions.
- D. A default argument cannot be redefined in later declaration.

**22:** Which of the following statement is correct?

- A. Constructors can have default parameters.
- B. Constructors cannot have default parameters.
- C. Constructors cannot have more than one default parameter.
- D. Constructors can have at most five default parameters.

**23:** Which of the following function / type of function cannot be overloaded?

- A. Member function
- B. Static function
- C. Virtual function
- D. Both B and C

**24:** Which of the following function declaration is/are incorrect?

- A. `int Sum(int a, int b = 2, int c = 3);`
- B. `int Sum(int a = 5, int b);`

- C. `int Sum(int a = 0, int b, int c = 3);`
  - D. Both B and C are incorrect.
  - E. All are correct.
-