Scripting Concepts

Practical Exam Programs — Questions & Answers

Q1.   [Dart]

Question:

Create a Dart class that stores student attendance percentage and uses if-else control statements to display:
- Eligible for Exam if attendance >= 75%
- Not Eligible if attendance < 75%

Answer (Code):

```
// 1.  Create a Dart class that stores student attendance percentage and uses
// if-else control statements to display:
// Eligible for Exam if attendance ≥ 75%
// Not Eligible if attendance < 75%

import 'dart:io';

class Student{

    double attendence;

    Student(this.attendence);

    void CheckEligibility()
    {
      if (attendence >= 75)
      {
        print("You are eligible for exam ");
      }
      else{
        print("You are not eligible");
      }
    }
}

void main()
{

  print("Enter your attendence percentage....");
  double attendence =  double.parse(stdin.readLineSync()!);

  Student s1 = Student(attendence);
  s1.CheckEligibility();

}
```

Q2.   [Dart]

Question:

Create a Dart class that calculates the sum of numbers from 1 to N using a loop and displays the result using an object.

Answer (Code):

```
// 2.  Create a Dart class that calculates the sum of numbers from 1 to N
// using a loop and displays the result using an object.

import 'dart:io';
```

```
class SumNatural{

  int n;

  SumNatural(this.n);

  void CalculateSum()
  {
    int sum=0;
    for(int i=1;i<=n;i++)
    {
        sum = sum+i;
    }

    print("Sum:${sum}");
  }

}

void main()
{
  print("Enter a number");
  int n= int.parse(stdin.readLineSync()!);

  SumNatural sum=SumNatural(n);

  sum.CalculateSum();
}
```

Q3.   [Dart]

Question:

Create an Employee class with employee name and salary. Use a control statement to display "High Salary" if salary > 50000, otherwise "Normal Salary".

Answer (Code):

```
// 3.  Create an Employee class with employee name and salary. Use a
// control statement to display "High Salary" if salary > 50000, otherwise
// "Normal Salary".

import 'dart:io';

class employee{

  double salary;
  String name;

  employee(this.name,this.salary);

  void checkSalary()
  {
    if (salary > 50000)
    {
      print("Salary is high");
    }
    else{
      print("Normal salary");
    }
  }
}

void main()
{
  print("Enter Your Name:");
  String name=stdin.readLineSync()!;

  print("Enter salary:");
  double salary = double.parse(stdin.readLineSync()!);
```

```
  employee emp=employee(name, salary);

  emp.checkSalary();


}
```

Q4.   [Dart]

Question:

Write a Dart program using a class that takes a number as input and prints its multiplication table using a for loop.

Answer (Code):

```
// 4.  Write a Dart program using a class that takes a number as input and
// prints its multiplication table using a for loop.

import 'dart:io';

class Table{

  int n;
  Table(this.n);

  void printTable()
  {
    for(int i=0;i<=10;i++)
    {
      print("$n x $i = ${n*i}");
    }
  }
}

void main()
{
  print("Enter number to print table");
  int n = int.parse(stdin.readLineSync()!);

  Table t = Table(n);

  t.printTable();
}
```

Q5.   [Dart]

Question:

Create a Student class in Dart that stores student name and marks of three subjects. Use if-else control statements to calculate the total, average, and grade of the student.

Answer (Code):

```
// 5.  Create a Student class in Dart that stores student name and marks of
// three subjects. Use if-else control statements to calculate the total,
// average, and grade of the student.

import 'dart:io';
class student{

    String name;
    double m1,m2,m3;

    student(this.name,this.m1,this.m2,this.m3);

    void result(){

      double total = m1+m2+m3;
```

```
      double average = total/3;

      if(average >= 75)
      {
        print("Grade A");
      }
      else if(average >=60)
      {
        print("Grade B");
      }
      else{
        print("Grade c");
      }
    }
}

void main()
{

  String name;
  double m1,m2,m3;

  print("Enter your name:");
  name = stdin.readLineSync()!;

  print("Enter your mark1:");
  m1=double.parse(stdin.readLineSync()!);

  print("Enter your mark2:");
  m2=double.parse(stdin.readLineSync()!);

  print("Enter your mark3:");
  m3=double.parse(stdin.readLineSync()!);

  student s1=student(name, m1, m2, m3);

  s1.result();

}
```

Q6.   [TypeScript]

Question:

Create a Contact Management System using TypeScript where users can add, search, display, and delete contacts.

Answer (Code):

```
let contacts:any[]=[];
let choice:string|null;

do{
    choice = prompt(
        "Contact Management System \n"+
        "1.Add Contact \n"+
        "2.Display Contact \n"+
        "3.Search Contact \n"+
        "4.Delete Contact \n"+
        "5.End Program.\n"+
        "Enter Your Choice:"
    );


    switch(choice){

        case "1":

        let name=prompt("Enter your name:");
        let phone=prompt("Enter your phone");
```

```
            contacts.push({
                name:name,
                phone:phone
            });

            alert("Contact added")
            break;

            case "2":
                let result = "Contact List \n";

                for (let contact of contacts){
                    result += contact.name +" -"+contact.phone+"\n";
                }

                alert(result);
                break;

            case "3":
                let searchName = prompt("Enter name to search contact");
                let found = false;

                for(let contact of  contacts)
                {
                    if(contact.name === searchName)
                    {
                        alert("Found: "+contact.name+"-"+contact.phone);
                        found=true
                        break;
                    }
                }
                if(!found)
                {
                    alert("contact is not found");
                }

            case "4":
                let deletename = prompt("Enter name to delete: ");

                contacts = contacts.filter(
                    contact => contact.name != deletename
                );
                alert("Contact deleted.");
                break;

            case "5":
                alert("Program Ended.");
                break;

            default:
                alert("Invalid choice.");

        }

}while(choice != "5");
```

Q7.   [TypeScript]

Question:

Develop a To-Do List application using TypeScript where users can add tasks, view tasks, mark tasks as completed, and delete tasks.

Answer (Code):

```
// 7. Develop a To-Do List application using TypeScript where users can add
// tasks, view tasks, mark tasks as completed, and delete tasks.

let tasks : any[]=[];
let Choice: String|null;
```

```
do{
    Choice=prompt(
        "TO-DO_List\n"+
        "1.Add Task\n"+
        "2.Show Task\n"+
        "3.Complete Task\n"+
        "4.Delete Task\n"+
        "5.Exit\n"+
        "Enter your Choice"
    );

    switch(Choice){

        case "1":
            let taskName= prompt("Enter Task..");

            tasks.push({
                task: taskName,
                completed: false
            });


            alert("Task is added ");
            break;

        case "2":
            let result = "Task List \n\n";

            for(let i=0;i<tasks.length;i++)
            {
                result += (i+1)+"."+tasks[i].task+"-"+
                (tasks[i].completed ? "Completed" : "Pending.." )+"\n";
            }

            alert(result);
            break;

        case "3":
            let completedTask = prompt("Enter task name to complete:");

            for (let task of tasks)
            {
                if(task.task === completedTask)
                {
                    task.completed=true;
                    alert("Task is completed");
                }
            }
            break;

        case "4":
            let deletedTask = prompt("Enter task Name to delete:");

            tasks = tasks.filter(
                task => task.task != deletedTask
            );

            alert("Task is deleted");
            break;

        case "5":
            alert("Program ended");
            break;

        default:
            alert("Invalid Choice");
    }


}while(Choice != "5")
```

Q8.   [TypeScript]

Question:

Develop a calculator using TypeScript that performs addition, subtraction, multiplication, and division based on user input.

Answer (Code):

```
// 8. Develop a calculator using TypeScript that performs addition,
// subtraction, multiplication, and division based on user input.


let num1= Number(prompt("Enter first number :"));
let num2=Number(prompt("Enter second number"));

let choice=prompt(
    "calculator Menu\n"+
    "1.addition\n"+
    "2.subtraction\n"+
    "3.multiplication\n"+
    "4.division\n"+
    "Enter your choice"
);

let result;

switch(choice){

    case "1":
        result = num1+num2;
        alert("Addition: "+result);
        break;


    case "2":
        result = num1-num2;
        alert("Substraction: "+result);
        break;


    case "3":
        result = num1*num2;
        alert("Multiplication: "+result);
        break;


    case "4":
        result = num1/num2;
        alert("Division: "+result);
        break;
}
```

Q9.   [TypeScript]

Question:

Develop a TypeScript class for Student Result that stores marks and calculates the grade using if-else or switch control statements.

Answer (Code):

```
// 9.  Develop a TypeScript class for Student Result that stores marks and
// calculates the grade using if-else or switch control statements.

class Student{

    marks:number;
```

```
    constructor(marks:number){
        this.marks=marks;
    }

    calculate()
    {
        if(this.marks >= 75)
        {
            alert("Grade A");
        }
        else if(this.marks >= 50)
        {
            alert("Grade B")
        }
        else
        {
            alert("Grade C")
        }
    }
}

let marks = Number(prompt("Enter Marks: "));

let s=new Student(marks);

s.calculate()
```

Q10.   [TypeScript]

Question:

Create an Employee class with properties like employee name and salary. Use a control statement to check if the salary is greater than a certain amount and print "High Salary" or "Low Salary".

Answer (Code):

```
// 10.  Create an Employee class with properties like employee name and
// salary. Use a control statement to check if the salary is greater than a
// certain amount and print "High Salary" or "Low Salary".

class Employee{
    name:string;
    salary:number;

    constructor(name:string,salary:number)
    {
        this.name=name;
        this.salary=salary;
    }

    checkSalary()
    {
        if(this.salary >= 50000)
        {
            alert("High Salary");
        }
        else{
            alert("Low Salary");
        }
    }
}

let empname = prompt("Enter Your Name: ")||"";
let salary= Number(prompt("Enter Your Salary: "));

let emp = new Employee(empname,salary);

emp.checkSalary();
```

Q11.   [TypeScript]

Question:

Create a TypeScript class that checks whether numbers from 1 to 20 are even or odd using a loop and if-else statement. Display the result using an object of the class.

Answer (Code):

```
// 11.  Create a TypeScript class that checks whether numbers from 1 to 20
// are even or odd using a loop and if-else statement. Display the result
// using an object of the class.


class NumberCheck{

    checknumber()
    {
        let result = ""

        for(let i=0;i<=20;i++)
        {
            if(i % 2 == 0)
            {
                result += i + " is Even\n";
            }
            else
            {
                result+= i + " is Odd\n";
            }
        }

        alert(result)
    }
}

let obj = new NumberCheck();
obj.checknumber();
```

Q12.   [TypeScript]

Question:

Create a Student class in TypeScript that stores student name and marks of three subjects. Use if-else control statements to determine whether the student has passed or failed and display the result.

Answer (Code):

```
// 12. Create a Student class in TypeScript that stores student name and marks
// of three subjects. Use if-else control statements to determine whether the
// student has passed or failed and display the result.

class Student{
    name:string|null;
    m1:number;
    m2:number;
    m3:number;

    constructor(name:string,m1:number,m2:number,m3:number)
    {
        this.name=name;
        this.m1=m1;
        this.m2=m2;
        this.m3=m3;
    }

    checkResult()
    {
        let total=this.m1+this.m2+this.m3;
        let average = total/3;
```

```
        if(average >=35)
        {
            alert(this.name+" is passed");
        }
        else{
            alert(this.name+" is failed");
        }
    }
}

let s1name=prompt("Enter name of student:") || "";
let mark1=Number(prompt("Enter mark 1:"));
let mark2=Number(prompt("Enter mark 2:"));
let mark3=Number(prompt("Enter mark 3:"));

let ob1=new Student(s1name,mark1,mark2,mark3);

ob1.checkResult();
```

Q13.   [JavaScript/HTML]

Question:

Develop a program where an input field changes background color on focus and displays typed text on keypress.

Answer (Code):

```
<!-- 13. Develop a program where an input field changes background color on
focus and displays typed text on keypress.  -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title></title>
</head>
<body>
    <h2>Event Handling explample</h2>

    <input type="text" id="txt" placeholder="type something">
    <h3 id="output"></h3>

    <script>

        let input=document.getElementById("txt");
        let output=document.getElementById("output");

        input.addEventListener("focus",function(){
            input.style.backgroundColor ="yellow";
        })

        input.addEventListener("keypress",function(){
            output.innerHTML=input.value;
        })
    </script>
</body>
</html>
```

Q14.   [JavaScript/HTML]

Question:

Create a program where text changes color on mouse over and changes size on double click.

Answer (Code):

```
<!-- 14. Create a program where text changes color on mouse over and changes
size on double click. -->
```

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h2 id="txt">Hello JavaScript</h2>
    <script>
        let txt=document.getElementById("txt");

        txt.addEventListener("mouseover",function(){
            txt.style.color="red";
        })

        txt.addEventListener("dblclick",function(){
            txt.style.fontSize = "40px";
        })
    </script>
</body>
</html>
```

Q15.   [JavaScript/HTML]

Question:

Develop a program that detects when a key is pressed (keydown) and when it is released (keyup) and displays both actions.

Answer (Code):

```
<!-- 15. Develop a program that detects when a key is pressed (keydown) and when
it is released (keyup) and displays both actions. -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>

    <h2>Press Any Key</h2>

    <h3 id="output"></h3>

    <Script>
        let output = document.getElementById("output")

        document.addEventListener("keydown",function(event){
            output.innerHTML ="Key Pressed: "+event.key;
        });

        document.addEventListener("keyup",function(event){
            output.innerHTML="Key Released: "+event.key;
        });
    </Script>

</body>
</html>
```

Q16.   [JavaScript/HTML]

Question:

Create a JavaScript program where a button changes color on mouse hover and displays a message on click.

Answer (Code):

```
<!-- 16. Create a JavaScript program where a button changes color on mouse
hover and displays a message on click.  -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <button id="btn">click ME</button>

    <script>
        let btn=document.getElementById("btn");

        btn.addEventListener("mouseover",function(){
            btn.style.backgroundColor="red";
        })

        btn.addEventListener("click",function(){
            alert("Button Clicked");
        })

    </script>
</body>
</html>
```

Q17.   [TypeScript]

Question:

Write a TypeScript program to calculate the sum of all elements in an array.

Answer (Code):

```
// 17. Write a TypeScript program to calculate the sum of all elements in an
// array.


let arr:number[]=[10,20,30,40,50];

let sum=0;

for(let i=0;i<arr.length;i++)
{
    sum = sum + arr[i]
}

alert("Sum: "+sum)
```

Q18.   [JavaScript/HTML]

Question:

Write a JavaScript program to validate a form. Check that username and password fields are not empty and display an alert if validation fails.

Answer (Code):

```
<!-- 18. Write a JavaScript program to validate a form. Check that username and
password fields are not empty and display an alert if validation fails.  -->

<!DOCTYPE html>
<html lang="en">
```

```
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>

    <h2>Login Form</h2>

    <form onsubmit="return validateForm()">
        <input type="text" id="username">
        <br><br>

        <input type="password" id="password">

        <input type="submit" value="submit">
    </form>

    <script>
        function validateForm()
        {
            let username=document.getElementById("username").value;

            let password=document.getElementById("password").value;

            if(username==" "||password=="")
            {
            alert("Username and password cannot be empty");
            return false
            }

            if(password.length < 6)
            {
                alert("Password must be at least 6 latters");
                return false;
            }

            alert("login successfull");
            return true;
        }
    </script>
</body>
</html>
```

Q19.   [JavaScript/HTML]

Question:

Write a JavaScript program that displays the selected value from a dropdown menu.

Answer (Code):

```
<!-- 19. Write a JavaScript program that displays the selected value from a
dropdown menu. -->


<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h2>Select a course</h2>
    <select  id="course" onchange="showValue()">

        <option value="">Select</option>
        <option value="Java">Java</option>
        <option value="Python">Python</option>
        <option value="JavaScript">JavaScript</option>
```

```
    </select>

    <h3 id="output"></h3>
    <script>
        function showValue()
        {
            let course=document.getElementById("course");

            document.getElementById("output").innerHTML =
            "Selected value :"+ course.value
        }
    </script>
</body>
</html>
```

Q20.   [JavaScript/HTML]

Question:

Create a JavaScript program to sort an array of numbers in ascending and descending order.

Answer (Code):

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>

    <script>
        let arr=[2,5,4,3,1,6];

        //ascending
        for(let i=0;i<arr.length;i++)
        {
            for(let j=i+1;j<arr.length;j++)
            {
                if(arr[i]>arr[j])
                {
                    let temp=arr[i]
                    arr[i]=arr[j]
                    arr[j]=temp
                }
            }
        }

        alert("Ascending Order: "+arr);

        //descending
        for(let i=0;i<arr.length;i++)
        {
            for(let j=i+1;j<arr.length;j++)
            {
                if(arr[i]<arr[j])
                {
                    let temp=arr[i];
                    arr[i]=arr[j];
                    arr[j]=temp;
                }
            }
        }
        alert("Descending Order: " + arr);
    </script>
</body>
</html>
```

Q21.   [JavaScript/HTML]

Question:

Develop a program that counts the number of characters entered in a textarea and displays it dynamically.

Answer (Code):

```
<!-- 21. Develop a program that counts the number of characters entered in a
textarea and displays it dynamically.  -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h2>Character Count</h2>
    <textarea  id="txt" rows="5" cols="5"></textarea>
    <h3 id="output">Characters: 0</h3>

    <script>
        let txt=document.getElementById("txt");
        let output = document.getElementById("output");

        txt.addEventListener("keyup",function(){
            let count = txt.value.length;

            output.innerHTML="Characters: "+count;
        })
    </script>
</body>
</html>
```

Q22.   [JavaScript/HTML]

Question:

Create a JavaScript program to calculate simple interest using user input.

Answer (Code):

```
<!-- 22. Create a JavaScript program to calculate simple interest using user input.  -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <script>
        let p=Number(prompt("Enter Principal Amount: "));

        let r=Number(prompt("Enter rate of intrest: "));

        let t=Number(prompt("Enter Time: "))

        let si=(p*r*t)/100

        alert("Simple Intrest: "+si)
    </script>
</body>
</html>
```

Q23.   [JavaScript/HTML]

Question:

Create a JavaScript program to remove duplicate elements from an array.

Answer (Code):

```
<!-- 23. Create a JavaScript program to remove duplicate elements from an array. -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>

    <script>
        let arr=[1,2,2,4,5,2];

        let unique=[];

        for(let i=0;i<arr.length;i++)
        {
            if(!unique.includes(arr[i]))
            {
                unique.push(arr[i]);
            }
        }

        alert("After removing duplicates: "+unique)
    </script>

</body>
</html>
```

Q24.   [JavaScript/HTML]

Question:

Write a JavaScript program that takes marks as input and displays grade based on conditions.

Answer (Code):

```
<!-- 24. Write a JavaScript program that takes marks as input and displays grade
based on conditions.  -->


<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <script>
        let marks= Number(prompt("Enter marks: "));

        if(marks >= 75)
    {
        alert("Grade A")
    }
    else if(marks >= 50){
        alert("Grade B")
    }
    else{
        alert("Grade C")
    }
    </script>
</body>
</html>
```

Q25.   [JavaScript/HTML]

Question:

Write a program to validate a form where:
- Name should not be empty
- Password must be at least 6 characters
- Email should contain '@'

Answer (Code):

```
<!-- 25. Write a program to validate a form where:
● Name should not be empty
● Password must be at least 6 characters
● Email should contain “@”  -->

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h2>Registration Form</h2>

    <form onsubmit="return validateForm()">

        Name: <input type="text" id="name"><br><br>

        Email: <input type="text" id="email"><br><br>

        Passsword: <input type="password" id="pass">

        <input type="submit" value="submit">
    </form>

    <script>
        function validateForm()
        {
            let name=document.getElementById("name").value;

            let email=document.getElementById("email").value;

            let pass=document.getElementById("email").value;

            if(name=="")
            {
                alert("name should not be empty");
                return false;
            }

            if(pass.length<6)
            {
                alert("password must greater that 6 character..")
                return false
            }

            if(!email.includes("@"))
            {
                alert("invalid email.")
                return false;
            }


        }
    </script>
</body>
</html>
```

Q26.   [PHP]

Question:

Develop a PHP-based student registration system where users can enter student details through an HTML form. Validate input data and store records in a database.

Answer (Code):

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Studnet Registration</title>
</head>
<body>
    <h2>Student Registration Form</h2>

    <form method="post">

        Name:
        <input type="text" name=name>
        <br><br>

        Email
        <input type="text" name="email">
        <br><br>

        Mobile:
        <input type="text" name="mobile">

        Course:
        <input type="text" name="course">

        Gender:
        <input type="radio" name="gender" value="male">Male

        <Input type="radio" name="gender" value="female">Female
        <br><br>

        <input type="submit" name="submit" value="register">


    </form>

    <?php

        $conn = mysqli_connect("localhost","root","","studentdb");

        if(isset($_POST['submit']))
        {
            $name = $_POST['name'];

            $email = $_POST['email'];

            $mobile = $_POST['mobile'];

            $course = $_POST['course'];

            $gender = $_POST['gender'];



        //validation

        if($name=="" || $email == "" || $mobile == "" || $course == "" || $gender == "")
            {
            echo "<h3>All fields are required</h3>";
            }
```

```
        elseif(!filter_var($email,FILTER_VALIDATE_EMAIL))
        {
            echo "</h3>Invalid Email</h3>";
        }
        elseif(strlen($mobile) != 10)
        {
            echo "<h3>Mobile must be 10 digits</h3>";
        }
        else
        {
            $sql = "INSERT INTO students(name,email,mobile,course,gender)
                    VALUES('$name','$email','$mobile','$course','$gender')";

            if(mysqli_query($conn,$sql))
            {
                echo "<h3>Registration Successful</h3>";
            }
            else
            {
                echo "<h3>Error</h3>";
            }
        }
        }

        //Display students

        $result = mysqli_query($conn ,"SELECT * FROM students");

        echo "<h2>Register Students</h2>";

        echo "<table border='1' cellpadding='10'>";

        echo "<tr>
                <th>ID</th>
                <th>Name</th>
                <th>Email</th>
                <th>Mobile</th>
                <th>Course</th>
                <th>Gender</th>
            </tr>";

        while($row = mysqli_fetch_assoc($result))
        {
            echo "<tr>";

            echo "<td>".$row['id']."</td>";

            echo "<td>".$row['name']."</td>";

            echo "<td>".$row['email']."</td>";

            echo "<td>".$row['mobile']."</td>";

            echo "<td>".$row['course']."</td>";

            echo "<td>".$row['gender']."</td>";

            echo "</tr>";
        }

        echo "</table>";


    ?>
</body>
</html>
```

Q27.   [PHP]

Question:

Create an online feedback form using PHP that collects user feedback and ratings. Admin page (admin27.php) to view all feedbacks.

Answer (Code):

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Feedback Form</title>
</head>
<body>

    <h2>Online Feedback</h2>

    <form method="post">

        Name:
        <input type="text" name="name">
        <br><br>

        Email:
        <input type="text" name="email">
        <br><br>

        Feedback:
        <textarea name="message"></textarea>
        <br><br>

        Rating:
        <select name="rating">
            <option value="">select</option>
            <option value="1">1</option>
            <option value="2">2</option>
            <option value="3">3</option>
            <option value="4">4</option>
            <option value="5">5</option>
        </select>
        <br><br>

        <input type="submit" name="submit" value="submit">

    </form>


    <?php

        $conn = mysqli_connect("localhost","root","","feedbackdb");

        if(isset($_POST['submit']))
        {
            $name = $_POST['name'];

            $email = $_POST['email'];

            $message = $_POST['message'];

            $rating = $_POST['rating'];

        if($name=="" || $email == "" || $message == "" || $rating == "")
        {
            echo "<h3>All fields are required</h3>";
        }
        else{
            $sql = "INSERT INTO feedback(name,email,message,rating)
                    VALUES('$name','$email','$message','$rating')";

            if(mysqli_query($conn,$sql))
            {
```

```
                    echo "<h3>Thank You For Feedback</h3>";
                }
                else{
                    echo "<h3>Error</h3>";
                }
            }

            }

        ?>
    </body>
    </html>

--- admin27.php ---
<?php
    $conn=mysqli_connect("localhost","root","","feedbackdb");

    $result = mysqli_query($conn,"SELECT * FROM feedback");

    echo "<h3> ALL Feedbacks </h3>";

    echo "<table border='1' cellpadding='10'>";

    echo "<tr>
            <th>ID</th>
            <th>Name</th>
            <th>Email</th>
            <th>Message</th>
            <th>Rating</th>
        </tr>";

    while($row=mysqli_fetch_assoc($result))
    {
        echo "<tr>";

        echo "<td>".$row['id']."</td>";

        echo "<td>".$row['name']."</td>";

        echo "<td>".$row['email']."</td>";

        echo "<td>".$row['message']."</td>";

        echo "<td>".$row['rating']."</td>";

        echo "</td>";
    }

    echo "</table>";
?>
```

Q28.   [PHP]

Question:

Design a PHP application for event registration where users can register for technical events.
Requirements:
- Create event registration form
- Fields: Participant Name, College Name, Event Name, Contact Number
- Validate form inputs
- Store registrations in database
- Display confirmation message
- Show total registered participants

Note: Code file not included in the provided ZIP for this question.

Q29.   [PHP]

Question:

Develop a seminar event management system using PHP to manage seminar registrations.
Requirements:
- Admin can add seminar details
- Students can register for seminars
- Store seminar date, topic, speaker name
- Display upcoming seminars
- Generate participant list
- Use MySQL database connectivity

Note: Code file not included in the provided ZIP for this question.

Q30.   [PHP]

Question:

Create a PHP application that performs bank transactions and handles exceptions.
Requirements:
- Accept account balance and withdrawal amount
- Throw exception if withdrawal amount exceeds balance or negative amount entered
- Use try, catch, finally
- Display appropriate error messages

Note: Code file not included in the provided ZIP for this question.

Q31.   [PHP]

Question:

Develop a PHP login system with exception handling for invalid login attempts.
Requirements:
- Create login form
- Validate username and password
- Throw exceptions for empty fields and invalid credentials
- Use custom exception messages
- Redirect valid users to dashboard

Note: Code file not included in the provided ZIP for this question.

Q32.   [PHP]

Question:

Create a PHP application to manage employee records using MySQL.
Requirements:
- Connect PHP with MySQL
- Perform CRUD: Add, Update, Delete, View Employee
- Display records in table format
- Show database connection success/failure message

Note: Code file not included in the provided ZIP for this question.

Q33.   [PHP]

Question:

Develop a library management system using PHP and MySQL.
Requirements:
- Database connection using mysqli/PDO
- Add new books
- Search books by title
- Issue and return books
- Display available books
- Maintain student and book records

Note: Code file not included in the provided ZIP for this question.

Q34.   [PHP]

Question:

Develop a PHP authentication system using sessions and cookies for secure login.
Requirements:
- Login form with validation
- Use session for active login
- Use cookies for 'Remember User'
- Restrict access without login
- Logout functionality
- Display last login using cookies

Note: Code file not included in the provided ZIP for this question.

Q35.   [PHP]

Question:

Create an online examination portal where sessions maintain exam state and cookies store user preferences.
Requirements:
- Student login system
- Maintain exam timer using session
- Store selected language/theme using cookies
- Prevent unauthorized access
- Submit answers and calculate marks
- Logout after exam completion

Note: Code file not included in the provided ZIP for this question.
