

Table

◆ Copy Table:-

- Copy a SQL table into another table in the same SQL server database.
- Syntax:-
insert into destination_table **select * from** source_table;
Eg. **Insert into** student 1 **select * from** student;

◆ ALTER TABLE:-

- ALTER TABLE statement is used to add, modify or delete columns in an existing table.
- It is also used to rename a table.

- Add Column
- Modify Column
- Drop Column
- Rename Column

◆ ALTER – Add Column:-

- Add columns in SQL table.
- Syntax :-
ALTER TABLE table_name **ADD** column_name column-definition;
Eg. **alter table** student **add** name **varchar**(20);

◆ **ALTER – Modify Column:-**

➤ Modify an existing column in SQL table.

➤ Syntax:-

ALTER TABLE table_name **MODIFY** column_name
column_type;

Eg. **alter table** login **MODIFY** name int(10);

◆ **ALTER – Drop Column:-**

➤ Drop an existing column in SQL table.

➤ Syntax:-

ALTER TABLE table_name **DROP COLUMN**
column_name;

Eg. **alter table** login 1 **drop column** name;

◆ **ALTER –Rename Column:-**

➤ Rename an existing column in SQL table

➤ Syntax:-

ALTER TABLE table_name **RENAME COLUMN**
old_name **to** new_name;

OR

ALTER TABLE login 1 **CHANGE** column_name
datatype;

Eg. **alter table** login 1 **RENAME COLUMN** pass **to**
pass1;

OR

alter table login 1 **change** roll_no id int(20);

Select

◆ What is Select:-

- It is used to query the database and retrieve selected data that follow the conditions we want.
- The SQL SELECT statement is used to fetch the data from a database table which returns this data in the form of a result table.

◆ Clauses in SELECT Statement:-



➤ Syntax:-

SELECT * FROM table_name;

Eg. SELECT * FROM student;

➤ Syntax:-

SELECT column_name FROM table_name;

Eg. SELECT name FROM student;

◆ **SELECT UNIQUE OR SELECT DISTINCT:-**

- **SELECT UNIQUE** is an old syntax which was used in oracle description but later ANSI standard defines **DISTINCT** as the official keyword.

- Syntax:-

SELECT UNIQUE column_name **FROM** table_name;

Eg. **SELECT UNIQUE** name **FROM** student;

OR

SELECT DISTINCT column_name **FROM** table_name;

Eg. **SELECT DISTINCT** name **FROM** student;

◆ **SELECT COUNT:-**

- The **SQL COUNT()** function is used to return the number of rows in a query.
- It is very useful to count the number of rows in a table having enormous data.

- **SELECT COUNT(column_name)**

- **SELECT COUNT(*)**

- **SELECT COUNT(DISTINCT column_name)**

◆ **SELECT COUNT(column_name):-**

- It will return the total number of names of student_table.
- Null fields will not be counted.

- Syntax:-

SELECT COUNT (column_name) FROM table_name;

Eg. **SELECT COUNT (name) FROM** student;

◆ **SELECT COUNT(*):-**

➤ It is used to return the number of records in table.

➤ Syntax:-

SELECT COUNT (*) FROM table_name;

Eg. **SELECT COUNT (*) FROM student;**

◆ **SELECT COUNT(DISTINCT column_name):-**

➤ It will return the total distinct names of student_table.

➤ Syntax:-

**SELECT COUNT(DISTINCT column_name) FROM
table_name;**

Eg. **SELECT COUNT (DISTINCT name) FROM
student;**