

# What breaks without PowerShell

Every one of this tool's 81 checks, classified by how it collects its data and what happens if powershell.exe is unavailable, blocked (AppLocker/WDAC), or a cmdlet fails internally, with the exact command(s) each check runs, taken directly from the collector source.

|              |            |       |         |
|--------------|------------|-------|---------|
| 81           | 28         | 52    | 1       |
| TOTAL CHECKS | UNAFFECTED | BREAK | PARTIAL |

## SYSTEM & HARDWARE

|                                                                                                                                   |                          |      |            |        |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------|------|------------|--------|
| SYS-001                                                                                                                           | Operating System Version | INFO | PowerShell | Breaks |
| Operating System                                                                                                                  |                          |      |            |        |
| collector: system.py field: os_caption                                                                                            |                          |      |            |        |
| POWERSHELL EXPRESSION                                                                                                             |                          |      |            |        |
| Get-CimInstance Win32_OperatingSystem -ErrorAction Stop   Select-Object Caption,Version,BuildNumber,OSArchitecture,LastBootUpTime |                          |      |            |        |
| Documented source: Win32_OperatingSystem.Caption                                                                                  |                          |      |            |        |
| SYS-002                                                                                                                           | Operating System Build   | INFO | PowerShell | Breaks |
| Operating System                                                                                                                  |                          |      |            |        |
| collector: system.py field: os_build                                                                                              |                          |      |            |        |
| POWERSHELL EXPRESSION                                                                                                             |                          |      |            |        |
| Get-CimInstance Win32_OperatingSystem -ErrorAction Stop   Select-Object Caption,Version,BuildNumber,OSArchitecture,LastBootUpTime |                          |      |            |        |
| Documented source: Win32_OperatingSystem.BuildNumber                                                                              |                          |      |            |        |
| SYS-003                                                                                                                           | System Architecture      | INFO | PowerShell | Breaks |
| Operating System                                                                                                                  |                          |      |            |        |
| collector: system.py field: architecture                                                                                          |                          |      |            |        |
| POWERSHELL EXPRESSION                                                                                                             |                          |      |            |        |
| Get-CimInstance Win32_OperatingSystem -ErrorAction Stop   Select-Object Caption,Version,BuildNumber,OSArchitecture,LastBootUpTime |                          |      |            |        |
| Documented source: Win32_OperatingSystem.OSArchitecture                                                                           |                          |      |            |        |
| SYS-004                                                                                                                           | Computer Name            | INFO | PowerShell | Breaks |
| Operating System                                                                                                                  |                          |      |            |        |
| collector: system.py field: computer_name                                                                                         |                          |      |            |        |
| POWERSHELL EXPRESSION                                                                                                             |                          |      |            |        |
| Get-CimInstance Win32_ComputerSystem -ErrorAction Stop   Select-Object Name,Domain,PartOfDomain,TotalPhysicalMemory               |                          |      |            |        |
| Documented source: Win32_ComputerSystem                                                                                           |                          |      |            |        |
| SYS-005                                                                                                                           | CPU                      | INFO | PowerShell | Breaks |
| Hardware                                                                                                                          |                          |      |            |        |
| collector: system.py field: cpu_name                                                                                              |                          |      |            |        |
| POWERSHELL EXPRESSION                                                                                                             |                          |      |            |        |
| Get-CimInstance Win32_Processor -ErrorAction Stop   Select-Object -First 1 Name,NumberOfCores,NumberOfLogicalProcessors           |                          |      |            |        |
| Documented source: Win32_Processor                                                                                                |                          |      |            |        |

|                                                                                                                                                                                                                                                                                                                                                                                                 |                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| <div>SYS-006</div> <div>Installed RAM</div> <div>Hardware</div>                                                                                                                                                                                                                                                                                                                                 | <div>INFO</div> <div>PowerShell</div> <div>Breaks</div>   |
| <div>collector: system.py    field: ram_total_gb</div> <div>POWERSHELL EXPRESSION</div> <div>Get-CimInstance Win32_ComputerSystem -ErrorAction Stop   Select-Object Name,Domain,PartOfDomain,TotalPhysicalMemory</div> <div>Documented source: Win32_ComputerSystem.TotalPhysicalMemory</div>                                                                                                   |                                                           |
| <div>SYS-007</div> <div>Storage Volumes</div> <div>Hardware</div>                                                                                                                                                                                                                                                                                                                               | <div>INFO</div> <div>PowerShell</div> <div>Breaks</div>   |
| <div>collector: system.py    field: volumes</div> <div>POWERSHELL EXPRESSION</div> <div>Get-Volume -ErrorAction Stop   Where-Object { \$_.DriveLetter }   Select-Object DriveLetter,@{Name='SizeGB';Expression={[math]::Round(\$_.Size/1GB,1)}},@{Name='FreeGB';Expression={[math]::Round(\$_.SizeRemaining/1GB,1)}}</div> <div>Documented source: Get-Volume</div>                             |                                                           |
| <div>SYS-008</div> <div>Firmware Type (UEFI/Legacy)</div> <div>Firmware &amp; Security</div>                                                                                                                                                                                                                                                                                                    | <div>INFO</div> <div>Registry</div> <div>Unaffected</div> |
| <div>collector: system.py    field: firmware_type</div> <div>HKLM\SYSTEM\CURRENTCONTROLSET\CONTROL\SECUREBOOT\STATE</div> <div>reg query "HKLM\SYSTEM\CurrentControlSet\Control\SecureBoot\State"</div> <div>Key presence only — no value is read. Key exists → UEFI; absent → Legacy BIOS.</div> <div>Documented source: Registry HKLM\SYSTEM\CurrentControlSet\Control\SecureBoot\State</div> |                                                           |
| <div>SYS-009</div> <div>Secure Boot Enabled</div> <div>Firmware &amp; Security</div>                                                                                                                                                                                                                                                                                                            | <div>HIGH</div> <div>PowerShell</div> <div>Breaks</div>   |
| <div>collector: system.py    field: secure_boot_enabled</div> <div>POWERSHELL EXPRESSION</div> <div>Confirm-SecureBootUEFI -ErrorAction Stop</div> <div>Throws on legacy BIOS systems — handled as NOT_APPLICABLE, not an error.</div> <div>Documented source: UEFI firmware Secure Boot state</div>                                                                                            |                                                           |
| <div>SYS-010</div> <div>TPM Ready</div> <div>Firmware &amp; Security</div>                                                                                                                                                                                                                                                                                                                      | <div>MEDIUM</div> <div>PowerShell</div> <div>Breaks</div> |
| <div>collector: system.py    field: tpm_ready</div> <div>POWERSHELL EXPRESSION</div> <div>Get-Tpm   Select-Object TpmPresent,TpmReady,TpmEnabled</div> <div>Non-elevated sessions get null properties without throwing — reported as UNABLE_TO_COLLECT rather than guessed.</div> <div>Documented source: TPM device state</div>                                                                |                                                           |
| <div>SYS-011</div> <div>System Uptime</div> <div>Operating System</div>                                                                                                                                                                                                                                                                                                                         | <div>INFO</div> <div>PowerShell</div> <div>Breaks</div>   |
| <div>collector: system.py    field: uptime_hours</div> <div>POWERSHELL EXPRESSION</div> <div>Get-CimInstance Win32_OperatingSystem -ErrorAction Stop   Select-Object Caption,Version,BuildNumber,OSArchitecture,LastBootUpTime</div> <div>Documented source: Win32_OperatingSystem.LastBootUpTime</div>                                                                                         |                                                           |

| USERS & ACCOUNT MANAGEMENT                                                                                                       |                                         |          |                   |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|----------|-------------------|
| USR-001                                                                                                                          | Local User Accounts                     | INFO     | PowerShell Breaks |
| Account Inventory                                                                                                                |                                         |          |                   |
| collector: users.py field: local_users                                                                                           |                                         |          |                   |
| POWERSHELL EXPRESSION                                                                                                            |                                         |          |                   |
| Get-LocalUser -ErrorAction Stop   Select-Object Name,Enabled>PasswordRequired>LastLogon,@{Name='SID';Expression={\$_.SID.Value}} |                                         |          |                   |
| Documented source: Local Security Accounts Manager (SAM)                                                                         |                                         |          |                   |
| USR-002                                                                                                                          | Guest Account Disabled                  | HIGH     | PowerShell Breaks |
| Account Inventory                                                                                                                |                                         |          |                   |
| collector: users.py field: guest_account_enabled                                                                                 |                                         |          |                   |
| POWERSHELL EXPRESSION                                                                                                            |                                         |          |                   |
| Get-LocalUser -ErrorAction Stop   Select-Object Name,Enabled>PasswordRequired>LastLogon,@{Name='SID';Expression={\$_.SID.Value}} |                                         |          |                   |
| Documented source: Local Security Accounts Manager (SAM)                                                                         |                                         |          |                   |
| USR-003                                                                                                                          | Accounts With No Password Required      | CRITICAL | PowerShell Breaks |
| Account Inventory                                                                                                                |                                         |          |                   |
| collector: users.py field: accounts_without_password                                                                             |                                         |          |                   |
| POWERSHELL EXPRESSION                                                                                                            |                                         |          |                   |
| Get-LocalUser -ErrorAction Stop   Select-Object Name,Enabled>PasswordRequired>LastLogon,@{Name='SID';Expression={\$_.SID.Value}} |                                         |          |                   |
| Documented source: Local Security Accounts Manager (SAM), PasswordRequired flag                                                  |                                         |          |                   |
| USR-004                                                                                                                          | Administrators Group Membership Count   | MEDIUM   | PowerShell Breaks |
| Privileged Access                                                                                                                |                                         |          |                   |
| collector: users.py field: administrators_group_member_count                                                                     |                                         |          |                   |
| POWERSHELL EXPRESSION                                                                                                            |                                         |          |                   |
| Get-LocalGroupMember -Group 'Administrators' -ErrorAction Stop   Select-Object Name,ObjectClass                                  |                                         |          |                   |
| Documented source: Local Administrators group membership                                                                         |                                         |          |                   |
| USR-005                                                                                                                          | Accounts Inactive > 90 Days             | LOW      | PowerShell Breaks |
| Account Inventory                                                                                                                |                                         |          |                   |
| collector: users.py field: inactive_accounts_90d                                                                                 |                                         |          |                   |
| POWERSHELL EXPRESSION                                                                                                            |                                         |          |                   |
| Get-LocalUser -ErrorAction Stop   Select-Object Name,Enabled>PasswordRequired>LastLogon,@{Name='SID';Expression={\$_.SID.Value}} |                                         |          |                   |
| Documented source: Local Security Accounts Manager (SAM), LastLogon property                                                     |                                         |          |                   |
| USR-006                                                                                                                          | Built-in Administrator Account Disabled | MEDIUM   | PowerShell Breaks |
| Privileged Access                                                                                                                |                                         |          |                   |
| collector: users.py field: builtin_admin_enabled                                                                                 |                                         |          |                   |
| POWERSHELL EXPRESSION                                                                                                            |                                         |          |                   |
| Get-LocalUser -ErrorAction Stop   Select-Object Name,Enabled>PasswordRequired>LastLogon,@{Name='SID';Expression={\$_.SID.Value}} |                                         |          |                   |
| Documented source: Local Security Accounts Manager (SAM)                                                                         |                                         |          |                   |

| AUTHENTICATION & ACCESS CONTROL                                                                                                                                                                                                                   |                                                 |                     |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|---------------------|------------|
| AUTH-001                                                                                                                                                                                                                                          | Minimum Password Length<br>Password Policy      | HIGH External CLI   | Unaffected |
| <b>collector:</b> authentication.py <b>field:</b> min_password_length                                                                                                                                                                             |                                                 |                     |            |
| EXTERNAL COMMAND                                                                                                                                                                                                                                  |                                                 |                     |            |
| secedit /export /cfg <tempfile>.cfg /areas SECURITYPOLICY                                                                                                                                                                                         |                                                 |                     |            |
| Exports to a temp .cfg file, parsed as INI for MinimumPasswordLength / PasswordComplexity / MaximumPasswordAge / PasswordHistorySize / LockoutBadCount / LockoutDuration, then the file is deleted. Requires elevation (exit code 740 otherwise). |                                                 |                     |            |
| Documented source: Local Security Policy, System Access section                                                                                                                                                                                   |                                                 |                     |            |
| AUTH-002                                                                                                                                                                                                                                          | Password Complexity Required<br>Password Policy | HIGH External CLI   | Unaffected |
| <b>collector:</b> authentication.py <b>field:</b> password_complexity_enabled                                                                                                                                                                     |                                                 |                     |            |
| EXTERNAL COMMAND                                                                                                                                                                                                                                  |                                                 |                     |            |
| secedit /export /cfg <tempfile>.cfg /areas SECURITYPOLICY                                                                                                                                                                                         |                                                 |                     |            |
| Exports to a temp .cfg file, parsed as INI for MinimumPasswordLength / PasswordComplexity / MaximumPasswordAge / PasswordHistorySize / LockoutBadCount / LockoutDuration, then the file is deleted. Requires elevation (exit code 740 otherwise). |                                                 |                     |            |
| Documented source: Local Security Policy, System Access section                                                                                                                                                                                   |                                                 |                     |            |
| AUTH-003                                                                                                                                                                                                                                          | Maximum Password Age<br>Password Policy         | MEDIUM External CLI | Unaffected |
| <b>collector:</b> authentication.py <b>field:</b> max_password_age_days                                                                                                                                                                           |                                                 |                     |            |
| EXTERNAL COMMAND                                                                                                                                                                                                                                  |                                                 |                     |            |
| secedit /export /cfg <tempfile>.cfg /areas SECURITYPOLICY                                                                                                                                                                                         |                                                 |                     |            |
| Exports to a temp .cfg file, parsed as INI for MinimumPasswordLength / PasswordComplexity / MaximumPasswordAge / PasswordHistorySize / LockoutBadCount / LockoutDuration, then the file is deleted. Requires elevation (exit code 740 otherwise). |                                                 |                     |            |
| Documented source: Local Security Policy, System Access section                                                                                                                                                                                   |                                                 |                     |            |
| AUTH-004                                                                                                                                                                                                                                          | Password History Size<br>Password Policy        | MEDIUM External CLI | Unaffected |
| <b>collector:</b> authentication.py <b>field:</b> password_history_size                                                                                                                                                                           |                                                 |                     |            |
| EXTERNAL COMMAND                                                                                                                                                                                                                                  |                                                 |                     |            |
| secedit /export /cfg <tempfile>.cfg /areas SECURITYPOLICY                                                                                                                                                                                         |                                                 |                     |            |
| Exports to a temp .cfg file, parsed as INI for MinimumPasswordLength / PasswordComplexity / MaximumPasswordAge / PasswordHistorySize / LockoutBadCount / LockoutDuration, then the file is deleted. Requires elevation (exit code 740 otherwise). |                                                 |                     |            |
| Documented source: Local Security Policy, System Access section                                                                                                                                                                                   |                                                 |                     |            |
| AUTH-005                                                                                                                                                                                                                                          | Account Lockout Threshold<br>Account Lockout    | HIGH External CLI   | Unaffected |
| <b>collector:</b> authentication.py <b>field:</b> lockout_threshold                                                                                                                                                                               |                                                 |                     |            |
| EXTERNAL COMMAND                                                                                                                                                                                                                                  |                                                 |                     |            |
| secedit /export /cfg <tempfile>.cfg /areas SECURITYPOLICY                                                                                                                                                                                         |                                                 |                     |            |
| Exports to a temp .cfg file, parsed as INI for MinimumPasswordLength / PasswordComplexity / MaximumPasswordAge / PasswordHistorySize / LockoutBadCount / LockoutDuration, then the file is deleted. Requires elevation (exit code 740 otherwise). |                                                 |                     |            |
| Documented source: Local Security Policy, System Access section                                                                                                                                                                                   |                                                 |                     |            |

AUTH-006

Account Lockout Duration

Account Lockout

MEDIUMExternal CLIUnaffected

collector: authentication.pyfield: lockout\_duration\_minutes

EXTERNAL COMMAND

secedit /export /cfg <tempfile>.cfg /areas SECURITYPOLICY

Exports to a temp .cfg file, parsed as INI for MinimumPasswordLength / PasswordComplexity / MaximumPasswordAge / PasswordHistorySize / LockoutBadCount / LockoutDuration, then the file is deleted. Requires elevation (exit code 740 otherwise).

Documented source: Local Security Policy, System Access section

AUTH-007

User Account Control (UAC) Enabled

User Account Control

CRITICALRegistryUnaffected

collector: authentication.pyfield: uac\_enabled

HKLM\SOFTWARE\MICROSOFT\WINDOWS\CURRENTVERSION\POLICIES\SYSTEM [ENABLELUA]

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System" /v EnableLUA

Documented source: Registry HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System, EnableLUA

AUTH-008

UAC Consent Prompt Behavior for Administrators

User Account Control

HIGHRegistryUnaffected

collector: authentication.pyfield: uac\_consent\_prompt\_behavior\_admin

HKLM\SOFTWARE\MICROSOFT\WINDOWS\CURRENTVERSION\POLICIES\SYSTEM [CONSENTPROMPTBEHAVIORADMIN]

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System" /v ConsentPromptBehaviorAdmin

Documented source: Registry HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System, ConsentPromptBehaviorAdmin

AUTH-009

Automatic Screen Lock Configured

Session Lock

HIGHHybridUnaffected

collector: authentication.pyfield: screen\_lock\_enabled

1. MACHINE POLICY (CHECKED FIRST)

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System" /v InactivityTimeoutSecs

2. FALLBACK — PER-USER SCREEN SAVER

reg query "HKCU\Control Panel\Desktop" /v ScreenSaveActive

reg query "HKCU\Control Panel\Desktop" /v ScreenSaverIsSecure

reg query "HKCU\Control Panel\Desktop" /v ScreenSaveTimeOut

Step 2 only counts as a lock if ScreenSaveActive=1 AND ScreenSaverIsSecure=1 (password required on resume).

Documented source: Registry HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System\InactivityTimeoutSecs, falling back to HKCU\Control Panel\Desktop (ScreenSaveActive, ScreenSaverIsSecure, ScreenSaveTimeOut)

AUTH-010

Automatic Screen Lock Timeout

Session Lock

MEDIUMHybridUnaffected

collector: authentication.pyfield: screen\_lock\_timeout\_minutes

1. MACHINE POLICY (CHECKED FIRST)

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System" /v InactivityTimeoutSecs

2. FALLBACK — PER-USER SCREEN SAVER

reg query "HKCU\Control Panel\Desktop" /v ScreenSaveActive

reg query "HKCU\Control Panel\Desktop" /v ScreenSaverIsSecure

reg query "HKCU\Control Panel\Desktop" /v ScreenSaveTimeOut

Step 2 only counts as a lock if ScreenSaveActive=1 AND ScreenSaverIsSecure=1 (password required on resume).

Documented source: Registry HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System\InactivityTimeoutSecs, falling back to HKCU\Control Panel\Desktop\ScreenSaveTimeOut

## WINDOWS SECURITY

## SEC-001 Defender Real-Time Protection

CRITICAL

PowerShell

Breaks

Antivirus

**collector:** security.py **field:** defender\_realtime\_protection\_enabled

POWERSHELL EXPRESSION

```
Get-MpComputerStatus -ErrorAction Stop | Select-Object  
RealTimeProtectionEnabled,AntivirusEnabled,MAPSReporting,AntivirusSignatureLastUpdated,IsTamperProtected
```

Documented source: Microsoft Defender status

## SEC-002 Defender Antivirus Enabled

CRITICAL

PowerShell

Breaks

Antivirus

**collector:** security.py **field:** defender\_antivirus\_enabled

POWERSHELL EXPRESSION

```
Get-MpComputerStatus -ErrorAction Stop | Select-Object  
RealTimeProtectionEnabled,AntivirusEnabled,MAPSReporting,AntivirusSignatureLastUpdated,IsTamperProtected
```

Documented source: Microsoft Defender status

## SEC-003 Defender Cloud-Delivered Protection

MEDIUM

PowerShell

Breaks

Antivirus

**collector:** security.py **field:** defender\_cloud\_protection\_enabled

POWERSHELL EXPRESSION

```
Get-MpComputerStatus -ErrorAction Stop | Select-Object  
RealTimeProtectionEnabled,AntivirusEnabled,MAPSReporting,AntivirusSignatureLastUpdated,IsTamperProtected
```

Documented source: Microsoft Defender status

## SEC-004 Defender Signature Age

MEDIUM

PowerShell

Breaks

Antivirus

**collector:** security.py **field:** defender\_signature\_age\_days

POWERSHELL EXPRESSION

```
Get-MpComputerStatus -ErrorAction Stop | Select-Object  
RealTimeProtectionEnabled,AntivirusEnabled,MAPSReporting,AntivirusSignatureLastUpdated,IsTamperProtected
```

Documented source: Microsoft Defender status, AntivirusSignatureLastUpdated

## SEC-005 Defender Tamper Protection

HIGH

PowerShell

Breaks

Antivirus

**collector:** security.py **field:** tamper\_protection\_enabled

POWERSHELL EXPRESSION

```
Get-MpComputerStatus -ErrorAction Stop | Select-Object  
RealTimeProtectionEnabled,AntivirusEnabled,MAPSReporting,AntivirusSignatureLastUpdated,IsTamperProtected
```

Documented source: Microsoft Defender status, IsTamperProtected

SEC-006

SmartScreen Enabled

MEDIUM

Hybrid

Unaffected

Browser Protection

collector: security.py

field: smartscreen\_enabled

1. PER-USER OVERRIDE (CHECKED FIRST)

```
reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\Explorer" /v SmartScreenEnabled
```

2. FALLBACK — POLICY OVERRIDE

```
reg query "HKLM\SOFTWARE\Policies\Microsoft\Windows\System" /v EnableSmartScreen
```

If neither key exists, reported as Microsoft's documented on-by-default state (not a live read).

Documented source: Registry HKCU\Software\Microsoft\Windows\CurrentVersion\Explorer\SmartScreenEnabled, falling back to HKLM\SOFTWARE\Policies\Microsoft\Windows\System\EnableSmartScreen, falling back to Microsoft's documented default (on) when neither override exists

SEC-007

Registered Antivirus Products

INFO

PowerShell

Breaks

Security Center

collector: security.py

field: registered\_av\_products

POWERSHELL EXPRESSION

```
Get-CimInstance -Namespace root\SecurityCenter2 -ClassName AntivirusProduct -ErrorAction Stop | Select-Object displayName
```

Documented source: WMI root\SecurityCenter2\AntivirusProduct

FIREWALL & NETWORK SECURITY

NET-001

Domain Firewall Profile Enabled

HIGH

PowerShell

Breaks

Firewall Profiles

collector: firewall.py

field: domain\_profile\_enabled

POWERSHELL EXPRESSION

```
Get-NetFirewallProfile -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Name = $_.Name; Enabled = [bool]$.Enabled } }
```

Documented source: Windows Defender Firewall profile configuration

NET-002

Private Firewall Profile Enabled

HIGH

PowerShell

Breaks

Firewall Profiles

collector: firewall.py

field: private\_profile\_enabled

POWERSHELL EXPRESSION

```
Get-NetFirewallProfile -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Name = $_.Name; Enabled = [bool]$.Enabled } }
```

Documented source: Windows Defender Firewall profile configuration

NET-003

Public Firewall Profile Enabled

CRITICAL

PowerShell

Breaks

Firewall Profiles

collector: firewall.py

field: public\_profile\_enabled

POWERSHELL EXPRESSION

```
Get-NetFirewallProfile -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Name = $_.Name; Enabled = [bool]$.Enabled } }
```

Documented source: Windows Defender Firewall profile configuration

NET-004

High-Risk Ports Listening

MEDIUM

PowerShell

Breaks

Network Configuration

collector: network.py

field: high\_risk\_ports\_listening

POWERSHELL EXPRESSION

```
Get-NetTCPConnection -State Listen -ErrorAction Stop | Select-Object LocalPort
```

Documented source: Active TCP listeners

NET-005

Network Connection Profiles

INFO

PowerShell

Breaks

Network Configuration

collector: network.py

field: connection\_profiles

POWERSHELL EXPRESSION

```
Get-NetConnectionProfile -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Name = $_.Name; NetworkCategory = $_.NetworkCategory.ToString() } }
```

Documented source: Network Location Awareness

NET-006

DNS Servers Configured

INFO

PowerShell

Breaks

Network Configuration

collector: network.py

field: dns\_servers

POWERSHELL EXPRESSION

```
Get-DnsClientServerAddress -AddressFamily IPv4 -ErrorAction Stop | Where-Object { $_.ServerAddresses.Count -gt 0 } | Select-Object InterfaceAlias,ServerAddresses
```

Documented source: DNS Client configuration

NET-007

Proxy Configured

LOW

Registry

Unaffected

Network Configuration

collector: network.py

field: proxy\_enabled

HKCU\SOFTWARE\MICROSOFT\WINDOWS\CURRENTVERSION\INTERNET SETTINGS [PROXYENABLE]

```
reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\Internet Settings" /v ProxyEnable
```

Documented source: Registry HKCU\Software\Microsoft\Windows\CurrentVersion\Internet Settings, ProxyEnable

WINDOWS UPDATE & PATCH MANAGEMENT

UPD-001

Windows Update Service Running

HIGH

PowerShell

Breaks

Update Service

collector: updates.py

field: wuauserv\_running

POWERSHELL EXPRESSION

```
Get-Service -Name wuauserv -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Status = $_.Status.ToString() } }
```

Documented source: Service Control Manager, wuauserv

UPD-002

Days Since Last Installed Update

MEDIUM

PowerShell

Breaks

Patch Status

collector: updates.py

field: days\_since\_last\_update

POWERSHELL EXPRESSION

```
Get-CimInstance Win32_QuickFixEngineering -ErrorAction Stop | Select-Object HotFixID,@{Name='InstalledOn';Expression={$_.InstalledOn.DateTime}}
```

Documented source: Win32\_QuickFixEngineering, InstalledOn

UPD-003 Automatic Updates Not Paused MEDIUM Hybrid Unaffected  
Update Service

collector: updates.py field: updates\_paused

1. HARD OVERRIDE (CHECKED FIRST)

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\WindowsUpdate\Auto Update" /v NoAutoUpdate

2. PAUSE-UPDATES STATE

reg query "HKLM\SOFTWARE\Microsoft\WindowsUpdate\UX\Settings" /v PauseUpdatesExpiryTime

The value in step 2 is absent (not just empty) when updates are not paused — confirmed live via direct winreg access.

Documented source: Registry HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\WindowsUpdate\Auto Update\NoAutoUpdate, and HKLM\SOFTWARE\Microsoft\WindowsUpdate\UX\Settings\PauseUpdatesExpiryTime

UPD-004 Last Installed Update Date INFO PowerShell Breaks  
Patch Status

collector: updates.py field: last\_update\_date

POWERSHELL EXPRESSION

Get-CimInstance Win32\_QuickFixEngineering -ErrorAction Stop | Select-Object HotFixID,@{Name='InstalledOn';Expression={\$\_.InstalledOn.DateTime}}

Documented source: Win32\_QuickFixEngineering, InstalledOn

## SERVICES

SVC-001 Firewall Service Running CRITICAL PowerShell Breaks  
Security Services

collector: services.py field: firewall\_service\_running

POWERSHELL EXPRESSION

Get-CimInstance Win32\_Service -Filter "Name='mpssvc' OR Name='WinDefend'" -ErrorAction Stop | Select-Object Name,State

Documented source: Service Control Manager / Win32\_Service, mpssvc

SVC-002 Defender Antivirus Service Running CRITICAL PowerShell Breaks  
Security Services

collector: services.py field: defender\_service\_running

POWERSHELL EXPRESSION

Get-CimInstance Win32\_Service -Filter "Name='mpssvc' OR Name='WinDefend'" -ErrorAction Stop | Select-Object Name,State

Documented source: Service Control Manager / Win32\_Service, WinDefend

SVC-003 Remote Registry Service Disabled MEDIUM PowerShell Breaks  
Security Services

collector: services.py field: remote\_registry\_running

POWERSHELL EXPRESSION

Get-Service -Name RemoteRegistry -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Status = \$\_.Status.ToString() } }

Documented source: Service Control Manager, RemoteRegistry

SVC-004 Print Spooler Service Running LOW PowerShell Breaks  
Security Services

collector: services.py field: print\_spooler\_running

POWERSHELL EXPRESSION

Get-Service -Name Spooler -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Status = \$\_.Status.ToString() } }

Documented source: Service Control Manager, Spooler

SVC-005

Automatically Starting Services

INFO

PowerShell

Breaks

Service Inventory

collector: services.py

field: auto\_start\_services

POWERSHELL EXPRESSION

Get-CimInstance Win32\_Service -Filter "StartMode='Auto'" -ErrorAction Stop | Select-Object Name

Documented source: Win32\_Service, StartMode = Auto

PROCESSES & APPLICATIONS

APP-001

Installed Applications Inventory

INFO

Registry

Unaffected

Applications

collector: applications.py

field: installed\_applications

ENUMERATE SUBKEYS + DISPLAYNAME/DISPLAYVERSION/PUBLISHER PER APP

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall"

reg query "HKLM\SOFTWARE\Wow6432Node\Microsoft\Windows\CurrentVersion\Uninstall"

Win32\_Product (WMI) is deliberately avoided — querying it can trigger an MSI repair side effect.

Documented source: Registry Uninstall keys (HKLM/HKCU, 32-bit and 64-bit views)

APP-002

Excessive Startup Entries

LOW

Registry

Unaffected

Applications

collector: applications.py

field: excessive\_startup\_entries

ENUMERATE VALUES IN 4 RUN/RUNONCE KEYS

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run"

reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\Run"

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\RunOnce"

reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\RunOnce"

Documented source: Registry Run/RunOnce keys (HKLM/HKCU)

APP-003

Running Processes

INFO

PowerShell

Breaks

Processes

collector: processes.py

field: running\_processes

POWERSHELL EXPRESSION

Get-Process -ErrorAction Stop | Select-Object Name,Id,@{Name='Path';Expression={ try { \$\_.Path } catch { \$null } }}

Documented source: Process table

APP-004

Processes Running From Unusual Paths

MEDIUM

PowerShell

Breaks

Processes

collector: processes.py

field: processes\_from\_unusual\_paths

POWERSHELL EXPRESSION

Get-Process -ErrorAction Stop | Select-Object Name,Id,@{Name='Path';Expression={ try { \$\_.Path } catch { \$null } }}

Documented source: Process table, executable path

REMOTE ACCESS

|                                                                                                                                                                                                                                                                                                                                                                                                                                      |        |            |            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------------|------------|
| <div>RDP-001 Remote Desktop Enabled</div> <div>Remote Desktop</div>                                                                                                                                                                                                                                                                                                                                                                  | HIGH   | Registry   | Unaffected |
| <div>collector: remote_access.py field: rdp_enabled</div> <div>HKLM\SYSTEM\CURRENTCONTROLSET\CONTROL\TERMINAL SERVER [FDENYTSCONNECTIONS]</div> <div>reg query "HKLM\SYSTEM\CurrentControlSet\Control\Terminal Server" /v fDenyTSConnections</div> <div>Documented source: Registry HKLM\SYSTEM\CurrentControlSet\Control\Terminal Server, fDenyTSConnections</div>                                                                  |        |            |            |
| <div>RDP-002 RDP Requires Network Level Authentication</div> <div>Remote Desktop</div>                                                                                                                                                                                                                                                                                                                                               | HIGH   | Registry   | Unaffected |
| <div>collector: remote_access.py field: rdp_nla_required</div> <div>HKLM\SYSTEM\CURRENTCONTROLSET\CONTROL\TERMINAL SERVER\WINSTATIONS\RDP-TCP [USERAUTHENTICATION]</div> <div>reg query "HKLM\SYSTEM\CurrentControlSet\Control\Terminal Server\WinStations\RDP-Tcp" /v UserAuthentication</div> <div>Documented source: Registry HKLM\SYSTEM\CurrentControlSet\Control\Terminal Server\WinStations\RDP-Tcp, UserAuthentication</div> |        |            |            |
| <div>RDP-003 Remote Assistance Enabled</div> <div>Remote Assistance</div>                                                                                                                                                                                                                                                                                                                                                            | MEDIUM | Registry   | Unaffected |
| <div>collector: remote_access.py field: remote_assistance_enabled</div> <div>HKLM\SYSTEM\CURRENTCONTROLSET\CONTROL\REMOTE ASSISTANCE [FALLOWTOGETHELP]</div> <div>reg query "HKLM\SYSTEM\CurrentControlSet\Control\Remote Assistance" /v fAllowToGetHelp</div> <div>Documented source: Registry HKLM\SYSTEM\CurrentControlSet\Control\Remote Assistance, fAllowToGetHelp</div>                                                       |        |            |            |
| <div>RDP-004 WinRM Service Running</div> <div>Remote Management</div>                                                                                                                                                                                                                                                                                                                                                                | MEDIUM | PowerShell | Breaks     |
| <div>collector: remote_access.py field: winrm_running</div> <div>POWERSHELL EXPRESSION</div> <div>Get-Service -Name WinRM -ErrorAction Stop   ForEach-Object { [PSCustomObject]@{ Status = \$_.Status.ToString() } }</div> <div>Documented source: Service Control Manager, WinRM</div>                                                                                                                                              |        |            |            |

SYSTEM CONFIGURATION & POLICIES

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |        |            |            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------------|------------|
| <div>POL-001 PowerShell Execution Policy</div> <div>PowerShell</div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | MEDIUM | PowerShell | Breaks     |
| <div>collector: policies.py field: risky_execution_policy_scopes</div> <div>POWERSHELL EXPRESSION</div> <div>Get-ExecutionPolicy -List -ErrorAction Stop   ForEach-Object { [PSCustomObject]@{ Scope = \$_.Scope.ToString(); ExecutionPolicy = \$_.ExecutionPolicy.ToString() } }</div> <div>Process scope is deliberately excluded — this tool always launches PowerShell with -ExecutionPolicy Bypass, which would otherwise show as a false positive.</div> <div>Documented source: PowerShell execution policy scope chain (MachinePolicy, UserPolicy, CurrentUser, LocalMachine scopes only)</div> |        |            |            |
| <div>POL-002 PowerShell Script Block Logging Enabled</div> <div>PowerShell</div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | LOW    | Registry   | Unaffected |
| <div>collector: policies.py field: script_block_logging_enabled</div> <div>HKLM\SOFTWARE\POLICIES\MICROSOFT\WINDOWS\POWERSHELL\SCRIPTBLOCKLOGGING [ENABLESCRIPTBLOCKLOGGING]</div> <div>reg query "HKLM\SOFTWARE\Policies\Microsoft\Windows\PowerShell\ScriptBlockLogging" /v EnableScriptBlockLogging</div> <div>Documented source: Registry HKLM\SOFTWARE\Policies\Microsoft\Windows\PowerShell\ScriptBlockLogging</div>                                                                                                                                                                              |        |            |            |

POL-003

Device Installation Restriction Policy Configured

LOW

Registry

Unaffected

Device Policy

collector: policies.py

field: device\_install\_restriction\_enabled

HKLM\SOFTWARE\POLICIES\MICROSOFT\WINDOWS\DEVICEINSTALL\RESTRICTIONS

```
reg query "HKLM\SOFTWARE\Policies\Microsoft\Windows\DeviceInstall\Restrictions"
```

Key presence only.

Documented source: Registry HKLM\SOFTWARE\Policies\Microsoft\Windows\DeviceInstall\Restrictions

DATA & STORAGE SECURITY

STG-001

BitLocker Enabled on OS Drive

CRITICAL

PowerShell

Breaks

Encryption

collector: storage.py

field: bitlocker\_os\_drive\_protected

POWERSHELL EXPRESSION

```
Get-BitLockerVolume -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ MountPoint = $_.MountPoint; ProtectionStatus = $_.ProtectionStatus.ToString(); VolumeType = $_.VolumeType.ToString() } }
```

Confirmed live: throws "Access denied" without elevation.

Documented source: BitLocker Drive Encryption status

STG-002

Fixed Drives Without BitLocker

HIGH

PowerShell

Breaks

Encryption

collector: storage.py

field: bitlocker\_fixed\_drives\_unprotected

POWERSHELL EXPRESSION

```
Get-BitLockerVolume -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ MountPoint = $_.MountPoint; ProtectionStatus = $_.ProtectionStatus.ToString(); VolumeType = $_.VolumeType.ToString() } }
```

Confirmed live: throws "Access denied" without elevation.

Documented source: BitLocker Drive Encryption status, all fixed volumes

STG-003

Removable Drives Without BitLocker

MEDIUM

PowerShell

Breaks

Encryption

collector: storage.py

field: bitlocker\_removable\_unprotected

POWERSHELL EXPRESSION

```
Get-BitLockerVolume -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ MountPoint = $_.MountPoint; ProtectionStatus = $_.ProtectionStatus.ToString(); VolumeType = $_.VolumeType.ToString() } }
```

Confirmed live: throws "Access denied" without elevation.

Documented source: BitLocker Drive Encryption status, removable volumes

STG-004

Non-Default SMB Shares

MEDIUM

PowerShell

Breaks

Shared Folders

collector: storage.py

field: non\_default\_smb\_shares

POWERSHELL EXPRESSION

```
Get-SmbShare -ErrorAction Stop | Select-Object Name,Path
```

Documented source: SMB share configuration

STG-005 Unexpected Write Access on System Directories

LOW PowerShell Breaks

Permissions

collector: storage.py field: system\_dir\_unexpected\_write\_access

POWERSHELL EXPRESSION

(Get-Acl 'C:\Windows' -ErrorAction Stop).Access | ForEach-Object { [PSCustomObject]@{ Identity = \$\_.IdentityReference.Value; Rights = \$\_.FileSystemRights.ToString(); Type = \$\_.AccessControlType.ToString() } }

Documented source: NTFS ACLs on C:\Windows and C:\Program Files

EVENT & LOG AUDITING

LOG-001 Security Log Size Adequate

LOW PowerShell Breaks

Log Configuration

collector: event\_logs.py field: security\_log\_size\_adequate

POWERSHELL EXPRESSION

Get-WinEvent -ListLog Security -ErrorAction Stop | Select-Object MaximumSizeInBytes

Confirmed live: even listing this log's metadata is denied without elevation.

Documented source: Security event log configuration

LOG-002 Failed Logon Events (24h)

MEDIUM PowerShell Breaks

Audit Policy

collector: event\_logs.py field: failed\_logon\_count\_24h

POWERSHELL EXPRESSION

@(Get-WinEvent -LogName Security -ErrorAction Stop -FilterXPath "[\*][System[EventID=4625 and TimeCreated[timediff(@SystemTime) <= 86400000]]]").Count

A zero-match filter throws "No events were found" — handled as a valid 0, not an error.

Documented source: Security event log, Event ID 4625

LOG-003 Logon Event Auditing Enabled

HIGH External CLI Unaffected

Audit Policy

collector: event\_logs.py field: logon\_audit\_policy\_enabled

EXTERNAL COMMAND

auditpol /get /subcategory:Logon /r

/r requests structured CSV output. Requires elevation.

Documented source: Local audit policy, Logon/Logoff subcategory

LOG-004 System Log Available

LOW PowerShell Breaks

Log Configuration

collector: event\_logs.py field: system\_log\_available

POWERSHELL EXPRESSION

Get-WinEvent -ListLog System -ErrorAction Stop | Select-Object IsEnabled

Documented source: System event log configuration

| Device & Peripheral Security                                                                                                                                                                                                                                                                                                                                                                                                                 |                                       |                        |             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|------------------------|-------------|
| DEV-001                                                                                                                                                                                                                                                                                                                                                                                                                                      | USB Storage Installation Policy State | INFORegistryUnaffected | Peripherals |
| <p>collector: devices.py field: usb_storage_policy_state</p> <p>HKLM\SYSTEM\CURRENTCONTROLSET\SERVICES\USBSTOR [START]</p> <pre>reg query "HKLM\SYSTEM\CurrentControlSet\Services\USBSTOR" /v Start</pre> <p>Documented source: Registry HKLM\SYSTEM\CurrentControlSet\Services\USBSTOR, Start</p>                                                                                                                                           |                                       |                        |             |
| DEV-002                                                                                                                                                                                                                                                                                                                                                                                                                                      | Connected USB Devices                 | INFOPowerShellBreaks   | Peripherals |
| <p>collector: devices.py field: usb_devices_connected</p> <p>POWERSHELL EXPRESSION</p> <pre>Get-PnpDevice -Class USB -ErrorAction Stop   Select-Object FriendlyName,Status</pre> <p>Documented source: Plug and Play device tree, USB class</p>                                                                                                                                                                                              |                                       |                        |             |
| DEV-003                                                                                                                                                                                                                                                                                                                                                                                                                                      | Bluetooth Adapter Present             | INFOPowerShellBreaks   | Peripherals |
| <p>collector: devices.py field: bluetooth_present</p> <p>POWERSHELL EXPRESSION</p> <pre>Get-PnpDevice -Class Bluetooth -ErrorAction SilentlyContinue   Select-Object FriendlyName,Status</pre> <p>Documented source: Plug and Play device tree, Bluetooth class</p>                                                                                                                                                                          |                                       |                        |             |
| DEV-004                                                                                                                                                                                                                                                                                                                                                                                                                                      | Webcam Access Setting                 | INFORegistryUnaffected | Peripherals |
| <p>collector: devices.py field: webcam_access_setting</p> <p>HKCU\SOFTWARE\MICROSOFT\WINDOWS\CURRENTVERSION\CAPABILITYACCESSMANAGER\CONSENTSTORE\WEBCAM [VALUE]</p> <pre>reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\CapabilityAccessManager\ConsentStore\webcam" /v Value</pre> <p>Documented source: Registry HKCU\Software\Microsoft\Windows\CurrentVersion\CapabilityAccessManager\ConsentStore\webcam</p>                 |                                       |                        |             |
| DEV-005                                                                                                                                                                                                                                                                                                                                                                                                                                      | Microphone Access Setting             | INFORegistryUnaffected | Peripherals |
| <p>collector: devices.py field: microphone_access_setting</p> <p>HKCU\SOFTWARE\MICROSOFT\WINDOWS\CURRENTVERSION\CAPABILITYACCESSMANAGER\CONSENTSTORE\MICROPHONE [VALUE]</p> <pre>reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\CapabilityAccessManager\ConsentStore\microphone" /v Value</pre> <p>Documented source: Registry HKCU\Software\Microsoft\Windows\CurrentVersion\CapabilityAccessManager\ConsentStore\microphone</p> |                                       |                        |             |

BROWSER & INTERNET SECURITY

BRW-001 Installed Browsers Inventory

INFOHybridUnaffected

Browsers

collector: browser.py field: installed\_browsers

1. DETECT + LOCATE (PER KNOWN BROWSER)

reg query "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\App Paths\msedge.exe"  
(repeated for chrome.exe, firefox.exe, brave.exe, opera.exe)

2. VERSION NUMBER, ONLY FOR BROWSERS FOUND

(Get-Item -LiteralPath '<path from step 1>' -ErrorAction Stop).VersionInfo.ProductVersion

Same App Paths lookup Windows itself uses to resolve a bare executable name.

Documented source: Registry App Paths / Uninstall keys, executable file version info

BRW-002 Edge SmartScreen Enabled

MEDIUMRegistryUnaffected

Browsers

collector: browser.py field: edge\_smartscreen\_enabled

HKLM\SOFTWARE\POLICIES\MICROSOFT\EDGE [SMARTSCREENENABLED]

reg query "HKLM\SOFTWARE\Policies\Microsoft\Edge" /v SmartScreenEnabled

No policy → reported as Microsoft's documented on-by-default state.

Documented source: Registry HKLM\SOFTWARE\Policies\Microsoft\Edge\SmartScreenEnabled, falling back to Microsoft's documented default (on) when no policy override exists

BRW-003 Browser Proxy Override Configured

LOWRegistryUnaffected

Browsers

collector: browser.py field: browser\_proxy\_override

HKCU\SOFTWARE\MICROSOFT\WINDOWS\CURRENTVERSION\INTERNET SETTINGS [PROXYENABLE]

reg query "HKCU\Software\Microsoft\Windows\CurrentVersion\Internet Settings" /v ProxyEnable

Documented source: Registry HKCU\Software\Microsoft\Windows\CurrentVersion\Internet Settings

BACKUP & RECOVERY

BKP-001 System Restore Enabled

MEDIUMHybridPartial

Recovery

collector: backup.py field: system\_restore\_enabled

1. POLICY OVERRIDE (CHECKED FIRST)

reg query "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\SystemRestore" /v DisableSR

2. FALLBACK — POWERSHELL

@(Get-ComputerRestorePoint -ErrorAction Stop).Count

Step 1 alone answers the check when System Restore is explicitly disabled by policy. Step 2 (elevation-required) only runs when no policy override is present.

Documented source: Registry HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\SystemRestore\DisableSR, falling back to PowerShell Get-ComputerRestorePoint

BKP-002 Windows Backup Service State

INFOPowerShellBreaks

Backup

collector: backup.py field: sdrsvc\_service\_state

POWERSHELL EXPRESSION

Get-Service -Name SDRSVC -ErrorAction Stop | ForEach-Object { [PSCustomObject]@{ Status = \$\_.Status.ToString() } }

Documented source: Service Control Manager, SDRSVC

BKP-003

Recovery Partition Present

Recovery

LOW

PowerShell

Breaks

collector: backup.py    field: recovery\_partition\_present

POWERSHELL EXPRESSION

Get-Partition -ErrorAction Stop | Select-Object Type

Documented source: Partition table, Recovery type

generated from config/audit\_rules.json + collector source · reg query commands are a manual-verification equivalent of the tool's own winreg calls