



Router0

Physical Config CLI Attributes

IOS Command Line Interface

```

Router(config-if)#exit
Router(config)#interface FastEthernet1/0
Router(config-if)#exit
Router(config)#int fa0/0
Router(config-if)#ip ad 192.168.1.100 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)#int fa4/0
Router(config-if)#ip ad 192.168.3.100 255.255.255.0
Router(config-if)#no sh

%LINK-5-CHANGED: Interface FastEthernet4/0, changed state to down
Router(config-if)#int fa0/5
%Invalid interface type and number
Router(config)#int fa5/0
Router(config-if)#ip ad 192.168.4.100 255.255.255.0
Router(config-if)#no sh

%LINK-5-CHANGED: Interface FastEthernet5/0, changed state to down
Router(config-if)#ro eigrp 100
% Invalid input detected at '^' marker.

Router(config-if)#ro eigrp 100
Router(config-router)#net 192.168.1.0
Router(config-router)#net 192.168.3.0
Router(config-router)#net 192.168.4.0
Router(config-router)#exit
Router(config)#

```

Copy Paste

Router1

Physical Config CLI Attributes

IOS Command Line Interface

--- System Configuration Dialog ---

Would you like to enter the initial configuration dialog? [yes/no]:

Press RETURN to get started!

```
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet4/0
Router(config-if)#ip ad 192.168.3.200 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet4/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet4/0, changed state to up

Router(config-if)#int fa5/0
Router(config-if)#ip ad 192.168.5.200 255.255.255.0
Router(config-if)#no sh

%LINK-5-CHANGED: Interface FastEthernet5/0, changed state to down
Router(config-if)#no eigrp 100
Router(config-router)#net 192.168.3.0
Router(config-router)#
%DUAL-5-NEIGHCHANGE: IP-EIGRP 100: Neighbor 192.168.3.100 (FastEthernet4/0) is up: new adjacency

Router(config-router)#net 192.168.5.0
Router(config-router)#exit
Router(config)#
```

Copy Paste

Router3

Physical Config CLI Attributes

IOS Command Line Interface

```
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#ip ad 192.168.2.100 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

Router(config-if)#int fa4/0
Router(config-if)#ip ad 192.168.5.100 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet4/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet4/0, changed state to up

Router(config-if)#int fa5/0
Router(config-if)#ip ad 192.168.6.100 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet5/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet5/0, changed state to up

Router(config-if)#no eigrp 100
Router(config-router)#net 192.168.2.0
Router(config-router)#net 192.168.5.0
Router(config-router)#net 192.168.6.0
Router(config-router)#
Router(config-router)#exit
Router(config)#
```

Copy Paste

