

```

<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <title>Notes App</title>
  <link rel="stylesheet"
href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bootstrap.min.css"
integrity="sha384-ggOyR0iXCbMQv3Xipma34MD+dH/1fQ784/j6cY/iJTQUOhcWr7x9JvoRxT2M
Zw1T" crossorigin="anonymous">
</head>

<body>

  <nav class="navbar navbar-expand-lg navbar-dark bg-dark">
    <a class="navbar-brand" href="#">Magic Notes</a>
    <button class="navbar-toggler" type="button" data-toggle="collapse"
data-target="#navbarSupportedContent"
    aria-controls="navbarSupportedContent" aria-expanded="false" aria-label="Toggle
navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto">
        <li class="nav-item active">
          <a class="nav-link" href="#">Home <span class="sr-only">(current)</span></a>
        </li>

        </ul>
        <form class="form-inline my-2 my-lg-0">
          <input class="form-control mr-sm-2" id="searchTxt" type="search"
placeholder="Search" aria-label="Search">
          <button class="btn btn-outline-success my-2 my-sm-0"
type="submit">Search</button>
        </form>
      </div>
    </nav>

    <div class="container my-3">

```

nikta dhar n=ibar

```

<h1>Welcome To Magic Notes</h1>
<div class="card">
  <div class="card-body">
    <h5 class="card-title">Add a note</h5>
    <div class="form-group">
      <textarea class="form-control" id="addTxt" rows="3"></textarea>
    </div>
    <button class="btn btn-primary" id="addBtn">Add Note</button>
  </div>
</div>
<hr>
<h1>Your Notes</h1>
<hr>
<div id="notes" class="row container-fluid"> </div>
</div>

<script src="https://code.jquery.com/jquery-3.3.1.slim.min.js"
integrity="sha384-q8i/X+965DzO0rT7abK41JStQIAqVgRVzpbzo5smXKp4YfRvH+8abtTE1Pi6jiz
o"
  crossorigin="anonymous"></script>
<script src="https://cdnjs.cloudflare.com/ajax/libs/popper.js/1.14.7/umd/popper.min.js"
integrity="sha384-UO2eT0CpHqdSJQ6hJty5KVphtPhzWj9WO1clHTMGa3JDZwrnQq4sF86dIH
NDz0W1"
  crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/js/bootstrap.min.js"
integrity="sha384-JjSmVgyd0p3pXB1rRibZUAYoIIy6OrQ6VrjIEaFf/nJGzIxFDsf4x0xIM+B07jRM"
  crossorigin="anonymous"></script>
<script src="js/app.js"></script>
</body>

</html>

```

Java script codes

```

console.log("Welcome to notes app. This is app.js");
showNotes();

// If user adds a note, add it to the localStorage
let addBtn = document.getElementById("addBtn");

```

```

addBtn.addEventListener("click", function(e) {
  let addTxt = document.getElementById("addTxt");
  let notes = localStorage.getItem("notes");
  if (notes == null) {
    notesObj = [];
  } else {
    notesObj = JSON.parse(notes);
  }
  notesObj.push(addTxt.value);
  localStorage.setItem("notes", JSON.stringify(notesObj));
  addTxt.value = "";
  // console.log(notesObj);
  showNotes();
});

// Function to show elements from localStorage
function showNotes() {
  let notes = localStorage.getItem("notes");
  if (notes == null) {
    notesObj = [];
  } else {
    notesObj = JSON.parse(notes);
  }
  let html = "";
  notesObj.forEach(function(element, index) {
    html += `
      <div class="noteCard my-2 mx-2 card" style="width: 18rem;">
        <div class="card-body">
          <h5 class="card-title">Note ${index + 1}</h5>
          <p class="card-text"> ${element}</p>
          <button id="${index}" onclick="deleteNote(this.id)" class="btn btn-primary">Delete
Note</button>
        </div>
      </div>`;
  });
  let notesElm = document.getElementById("notes");
  if (notesObj.length != 0) {
    notesElm.innerHTML = html;
  } else {
    notesElm.innerHTML = `Nothing to show! Use "Add a Note" section above to add notes.`;
  }
}

// Function to delete a note

```

```

function deleteNote(index) {
//  console.log("I am deleting", index);

    let notes = localStorage.getItem("notes");
    if (notes == null) {
        notesObj = [];
    } else {
        notesObj = JSON.parse(notes);
    }

    notesObj.splice(index, 1);
    localStorage.setItem("notes", JSON.stringify(notesObj));
    showNotes();
}

```

```

let search = document.getElementById('searchTxt');
search.addEventListener("input", function(){

    let inputVal = search.value.toLowerCase();
    // console.log('Input event fired!', inputVal);
    let noteCards = document.getElementsByClassName('noteCard');
    Array.from(noteCards).forEach(function(element){
        let cardTxt = element.getElementsByTagName("p")[0].innerText;
        if(cardTxt.includes(inputVal)){
            element.style.display = "block";
        }
        else{
            element.style.display = "none";
        }
        // console.log(cardTxt);
    })
})

```

/*

Further Features:

1. Add Title
2. Mark a note as Important
3. Separate notes by user
4. Sync and host to web server

*/