1. **The online flight reservation system enables users to search for flights by destination, date, and class, displaying available options with real-time seat availability. Users can register, log in, and manage their reservations via a personal dashboard. The booking process includes selecting flights, choosing seats, entering passenger details, and making secure payments through an integrated payment gateway. Admins can manage flight schedules, seat inventory, and user accounts using an advanced admin panel. Users receive booking confirmation emails with e-tickets and can view their booking history and travel itineraries. The website is fully responsive, ensuring an optimal experience on all devices.The airline reservation system is a web-based system that helps in consolidating flight data - flight schedules, seat availability, flight fares and reservations from all airlines with the help of global distribution systems and provides real-time inventory and rates for customers and travel agents to book flight tickets online.**

- Administrator User Login Page
- Forgot Password Page
- Search Flight Page
- Book Ticket Page
- Ticket Payment Page
- My Ticket Page
- Cancel Ticket Page
- Customer Feedback
- Admin Report
- Search Flight Page
- View Booking Status Page
- Print Ticket Page

Code:

```
<!DOCTYPE html>
<html>
<head>
  <title>Online Flight Reservation System</title>
  <style>
```

```
body {
    margin: 0;
    font-family: Arial, sans-serif;
    background: #f2f6fc;
}
header {
    background: #123c69;
    color: white;
    padding: 20px;
    text-align: center;
}
nav {
    background: #205493;
    padding: 12px;
    text-align: center;
}
nav button {
    background: white;
    color: #123c69;
    border: none;
    padding: 10px 15px;
    margin: 4px;
    cursor: pointer;
    border-radius: 5px;
}
section {
    display: none;
```

```
    padding: 25px;
    max-width: 850px;
    margin: auto;
}
#home {
    display: block;
}
.card {
    background: white;
    padding: 20px;
    margin: 15px 0;
    border-radius: 8px;
    box-shadow: 0 2px 8px #ccc;
}
input, select {
    padding: 10px;
    margin: 8px 0;
    width: 95%;
    border: 1px solid #aaa;
    border-radius: 5px;
}
.action {
    background: #123c69;
    color: white;
    border: none;
    padding: 10px 18px;
    border-radius: 5px;
```

```
            cursor: pointer;
        }
        .cancel {
            background: #d9534f;
            color: white;
            border: none;
            padding: 8px 12px;
            cursor: pointer;
            border-radius: 5px;
        }
        h2 {
            color: #123c69;
        }
    </style>
</head>
<body>
<header>
    <h1>✈ Online Flight Reservation System</h1>
    <p>Book Your Flight Easily and Comfortably</p>
</header>
<nav>
    <button onclick="showPage('home')">Home</button>
    <button onclick="showPage('search')">Search Flights</button>
    <button onclick="showPage('bookings')">My Bookings</button>
    <button onclick="showPage('admin')">Admin</button>
</nav>
```

```
<!-- HOME PAGE -->
<section id="home">
  <div class="card">
    <h2>Welcome to Flight Booking</h2>
    <p>Find flights, compare fares and reserve your tickets easily.</p>
    <button class="action" onclick="showPage('search')">
      Book a Flight
    </button>
  </div>
</section>
<!-- SEARCH FLIGHTS -->
<section id="search">
  <div class="card">
    <h2>Search Available Flights</h2>
    <label>From:</label>
    <select id="source">
      <option value="Chennai">Chennai</option>
      <option value="Hyderabad">Hyderabad</option>
      <option value="Bangalore">Bangalore</option>
      <option value="Delhi">Delhi</option>
      <option value="Mumbai">Mumbai</option>
    </select>
    <label>To:</label>
    <select id="destination">
      <option value="Delhi">Delhi</option>
      <option value="Mumbai">Mumbai</option>
      <option value="Chennai">Chennai</option>
```

```
            <option value="Hyderabad">Hyderabad</option>
            <option value="Bangalore">Bangalore</option>
        </select>
        <label>Travel Date:</label>
        <input type="date" id="travelDate">
        <label>Passengers:</label>
        <input type="number" id="passengers" min="1" max="10" value="1">
        <button class="action" onclick="searchFlights()">
            Search Flights
        </button>
    </div>
    <div id="flightResults"></div>
</section>
<!-- MY BOOKINGS -->
<section id="bookings">
    <h2>My Flight Bookings</h2>
    <div id="bookingList"></div>
</section>
<!-- ADMIN PAGE -->
<section id="admin">
    <div class="card">
        <h2>Admin - Add New Flight</h2>
        <input type="text" id="flightName" placeholder="Airline Name">
        <input type="text" id="flightFrom" placeholder="Source City">
        <input type="text" id="flightTo" placeholder="Destination City">
        <input type="number" id="flightPrice" placeholder="Ticket Price">
        <input type="number" id="flightSeats" placeholder="Available Seats">
```

```
        <button class="action" onclick="addFlight()">
            Add Flight
        </button>
    </div>
    <div id="adminList"></div>
</section>
<script>
let flights = [
    {
        id: 1,
        name: "Air India",
        from: "Chennai",
        to: "Delhi",
        price: 5500,
        seats: 20
    },
    {
        id: 2,
        name: "IndiGo",
        from: "Hyderabad",
        to: "Mumbai",
        price: 4200,
        seats: 15
    },
    {
        id: 3,
```

```
        name: "Vistara",
        from: "Bangalore",
        to: "Delhi",
        price: 6000,
        seats: 10
    },
    {
        id: 4,
        name: "IndiGo",
        from: "Chennai",
        to: "Bangalore",
        price: 3500,
        seats: 25
    }
];
let bookings = [];
let selectedDate = "";
function showPage(page) {
    document.querySelectorAll("section").forEach(section => {
        section.style.display = "none";
    });
    document.getElementById(page).style.display = "block";
    if (page === "bookings") {
        displayBookings();
    }
    if (page === "admin") {
        displayAdmin();
```

```
    }
}
function searchFlights() {
    let from = document.getElementById("source").value;
    let to = document.getElementById("destination").value;
    let date = document.getElementById("travelDate").value;
    let count = Number(document.getElementById("passengers").value);
    let results = document.getElementById("flightResults");
    if (from === to) {
        alert("Source and destination cannot be the same!");
        return;
    }
    if (!date) {
        alert("Please select a travel date!");
        return;
    }
    if (date < new Date().toISOString().split("T")[0]) {
        alert("Please select a future date!");
        return;
    }
    if (count < 1 || count > 10) {
        alert("Please enter between 1 and 10 passengers.");
        return;
    }
    selectedDate = date;
    let available = flights.filter(f =>
        f.from.toLowerCase() === from.toLowerCase() &&
```

```
        f.to.toLowerCase() === to.toLowerCase() &&
        f.seats >= count
    );
    results.innerHTML = "<h2>Available Flights</h2>";
    if (available.length === 0) {
        results.innerHTML += "<p>No flights available for this route.</p>";
        return;
    }
    available.forEach(f => {
        results.innerHTML += `
            <div class="card">
                <h3>${f.name}</h3>
                <p>From: ${f.from}</p>
                <p>To: ${f.to}</p>
                <p>Price per person: ₹${f.price}</p>
                <p>Available Seats: ${f.seats}</p>
                <p>Total Fare: ₹${f.price * count}</p>
                <button class="action"
                    onclick="bookFlight(${f.id}, ${count})">
                    Book Ticket
                </button>
            </div>
        `;
    });
}

function bookFlight(id, count) {
```

```
    let flight = flights.find(f => f.id === id);
    if (!flight || flight.seats < count) {
        alert("Not enough seats available!");
        return;
    }
    let name = prompt("Enter passenger name:");
    if (!name || !name.trim()) {
        alert("Please enter a passenger name.");
        return;
    }
    flight.seats -= count;
    let booking = {
        bookingId: "FL" + Date.now(),
        passenger: name.trim(),
        flight: flight.name,
        from: flight.from,
        to: flight.to,
        date: selectedDate,
        passengers: count,
        total: flight.price * count,
        status: "Confirmed",
        flightId: flight.id
    };
    bookings.push(booking);
    alert("Flight booked successfully!\nBooking ID: " + booking.bookingId);
    displayBookings();
}
```

```
function displayBookings() {
    let list = document.getElementById("bookingList");
    if (bookings.length === 0) {
        list.innerHTML = "<p>No bookings available.</p>";
        return;
    }
    list.innerHTML = "";
    bookings.forEach((b, index) => {
        list.innerHTML += `
            <div class="card">
                <h3>${b.flight}</h3>
                <p>Passenger: ${b.passenger}</p>
                <p>Booking ID: ${b.bookingId}</p>
                <p>Route: ${b.from} to ${b.to}</p>
                <p>Date: ${b.date}</p>
                <p>Passengers: ${b.passengers}</p>
                <p>Total Amount: ₹${b.total}</p>
                <p>Status: ${b.status}</p>
                ${b.status === "Confirmed" ?
                `<button class="cancel"
                    onclick="cancelBooking(${index})">
                    Cancel Booking
                </button>` : ""}
            </div>
        `;
    });
}
```

```
function cancelBooking(index) {
    let booking = bookings[index];
    if (booking.status !== "Confirmed") {
        return;
    }
    if (confirm("Are you sure you want to cancel this booking?")) {
        let flight = flights.find(f => f.id === booking.flightId);
        if (flight) {
            flight.seats += booking.passengers;
        }

        booking.status = "Cancelled";
        alert("Booking cancelled successfully!");
        displayBookings();
    }
}
function addFlight() {
    let name = document.getElementById("flightName").value.trim();
    let from = document.getElementById("flightFrom").value.trim();
    let to = document.getElementById("flightTo").value.trim();
    let price = Number(document.getElementById("flightPrice").value);
    let seats = Number(document.getElementById("flightSeats").value);
    if (!name || !from || !to || price <= 0 || seats <= 0) {
        alert("Please enter valid flight details!");
        return;
    }
    if (from.toLowerCase() === to.toLowerCase()) {
```

```
        alert("Source and destination cannot be the same!");
        return;
    }
    flights.push({
        id: Date.now(),
        name: name,
        from: from,
        to: to,
        price: price,
        seats: seats
    });
    alert("New flight added successfully!");
    document.getElementById("flightName").value = "";
    document.getElementById("flightFrom").value = "";
    document.getElementById("flightTo").value = "";
    document.getElementById("flightPrice").value = "";
    document.getElementById("flightSeats").value = "";
    displayAdmin();
}
function displayAdmin() {
    let list = document.getElementById("adminList");
    list.innerHTML = "<h2>Flight Details</h2>";
    flights.forEach(f => {
        list.innerHTML += `
            <div class="card">
                <h3>${f.name}</h3>
                <p>${f.from} to ${f.to}</p>
```

```
            <p>Price: ₹${f.price}</p>
            <p>Available Seats: ${f.seats}</p>
        </div>
    `;
  });
}
</script>
</body>
</html>
```

OUTPUT:

