1. **The online beauty parlour appointment booking system allows users to browse available services, view stylist profiles, and check appointment slots in real-time. Users can register, log in, and manage their appointments through a personal dashboard. The booking process includes selecting services, choosing a stylist, selecting a date and time, and making secure payments via an integrated payment gateway. Admins can manage service offerings, stylist schedules, and user accounts through a comprehensive admin panel. Users receive appointment confirmation emails and reminders, with the option to reschedule or cancel appointments through their dashboard. The website is fully responsive, ensuring an optimal experience on all devices. This website helps customers to search for any beauty parlour and book appointments as they preferable date and time.**
   Have reservations calendar

   - Create, edit, and cancel reservations
   - Lockout unavailable hours
   - Get the crucial information for each date on

   the calendar Customers' personal account page

   - Upcoming reservations
   - Reservations history
   - Personal data

   Salon manager and staff member in order to control and manage reservations.

   - Upcoming reservations
   - Reservations calendar
   - Add reservation
   - Edit reservations
   - Send an SMS or call to the customer
   - customers leave feedback about their experiences and learn from their suggestions.

   Accept online payments as a whole payment or as a partial deposit with Stripe or PayPal or with one of the available payments

- Require full payment or a deposit
- Accept PayPal or Stripe
- Automatic cancellation of unpaid reservations
- We have more than twenty different payments platforms integration add-ons

Code:

```
<!DOCTYPE html>
<html>
<head>
  <title>Beauty Parlour Appointment System</title>
  <style>
    body {
      margin: 0;
      font-family: Arial, sans-serif;
      background: #fff0f5;
    }
    header {
      background: #ad1457;
      color: white;
      text-align: center;
      padding: 20px;
    }
    nav {
      background: #880e4f;
      text-align: center;
      padding: 12px;
    }
    nav button {
      padding: 10px 15px;
      margin: 4px;
      border: none;
      border-radius: 5px;
      cursor: pointer;
    }
    section {
      display: none;
      max-width: 850px;
      margin: auto;
      padding: 25px;
    }
```

```
        #home {
            display: block;
        }
        .card {
            background: white;
            padding: 20px;
            margin: 15px 0;
            border-radius: 8px;
            box-shadow: 0 2px 7px #ddd;
        }
        input, select {
            width: 95%;
            padding: 10px;
            margin: 8px 0;
            border: 1px solid #ccc;
            border-radius: 5px;
        }
        .action {
            background: #ad1457;
            color: white;
            padding: 10px 16px;
            border: none;
            border-radius: 5px;
            cursor: pointer;
        }
        .cancel {
            background: #d32f2f;
            color: white;
            padding: 8px 12px;
            border: none;
            border-radius: 5px;
            cursor: pointer;
        }
        h2 {
            color: #ad1457;
        }
    </style>
</head>
<body>
<header>
    <h1>💇 Beauty Glow Parlour</h1>
    <p>Look Beautiful, Feel Confident!</p>
</header>
```

```
<nav>
  <button onclick="showPage('home')">Home</button>
  <button onclick="showPage('services')">Services</button>
  <button onclick="showPage('booking')">Book Appointment</button>
  <button onclick="showPage('appointments')">My Appointments</button>
  <button onclick="showPage('admin')">Admin</button>
</nav>
<!-- HOME PAGE -->
<section id="home">
  <div class="card">
    <h2>Welcome to Beauty Glow Parlour</h2>
    <p>Enjoy professional beauty and personal care services.</p>
    <button class="action" onclick="showPage('services')">
      Explore Services
    </button>
  </div>
</section>
<!-- SERVICES -->
<section id="services">
  <h2>Our Beauty Services</h2>
  <div id="serviceList"></div>
</section>
<!-- BOOKING -->
<section id="booking">
  <div class="card">
    <h2>Book Your Appointment</h2>
    <label>Customer Name:</label>
    <input type="text" id="customerName"
      placeholder="Enter your name">
    <label>Mobile Number:</label>
    <input type="tel" id="mobile"
      placeholder="Enter 10-digit mobile number"
      maxlength="10">
    <label>Select Service:</label>
    <select id="serviceSelect"></select>
    <label>Appointment Date:</label>
    <input type="date" id="appointmentDate">
    <label>Appointment Time:</label>
    <select id="appointmentTime">
      <option value="">Select Time</option>
      <option>10:00 AM</option>
      <option>11:00 AM</option>
```

```
            <option>12:00 PM</option>
            <option>02:00 PM</option>
            <option>03:00 PM</option>
            <option>04:00 PM</option>
            <option>05:00 PM</option>
        </select>
        <button class="action" onclick="bookAppointment()">
            Confirm Appointment
        </button>
    </div>
</section>
<!-- APPOINTMENTS -->
<section id="appointments">
    <h2>My Appointments</h2>
    <div id="appointmentList"></div>
</section>
<!-- ADMIN -->
<section id="admin">
    <div class="card">
        <h2>Admin - Add New Service</h2>

        <input type="text" id="newService"
            placeholder="Service Name">

        <input type="number" id="newPrice"
            placeholder="Service Price">

        <input type="number" id="newDuration"
            placeholder="Duration in minutes">

        <button class="action" onclick="addService()">
            Add Service
        </button>
    </div>

    <div id="adminList"></div>
</section>

<script>

// Available beauty services
let services = [
    {
```

```
        id: 1,
        name: "Hair Cutting",
        price: 300,
        duration: 30
    },
    {
        id: 2,
        name: "Facial",
        price: 800,
        duration: 60
    },
    {
        id: 3,
        name: "Hair Styling",
        price: 500,
        duration: 45
    },
    {
        id: 4,
        name: "Manicure",
        price: 400,
        duration: 40
    },
    {
        id: 5,
        name: "Pedicure",
        price: 500,
        duration: 45
    },
    {
        id: 6,
        name: "Bridal Makeup",
        price: 5000,
        duration: 120
    }
];

let appointments = [];

// Page navigation
function showPage(page) {

    document.querySelectorAll("section").forEach(s => {
```

```
        s.style.display = "none";
    });

    document.getElementById(page).style.display = "block";

    if (page === "services") displayServices();
    if (page === "booking") loadServices();
    if (page === "appointments") displayAppointments();
    if (page === "admin") displayAdmin();
}

// Display services
function displayServices() {

    let list = document.getElementById("serviceList");

    list.innerHTML = "";

    services.forEach(service => {

        list.innerHTML += `
            <div class="card">
                <h3>${service.name}</h3>
                <p>Price: ₹${service.price}</p>
                <p>Duration: ${service.duration} minutes</p>

                <button class="action"
                    onclick="selectService(${service.id})">
                    Book Now
                </button>
            </div>
        `;
    });
}

// Load services into booking dropdown
function loadServices() {

    let select = document.getElementById("serviceSelect");

    select.innerHTML = '<option value="">Select Service</option>';

    services.forEach(service => {
```

```
        select.innerHTML += `
            <option value="${service.id}">
                service.name — ₹{service.price}
            </option>
        `;
    });
}

// Select a service
function selectService(id) {

    showPage("booking");

    document.getElementById("serviceSelect").value = id;
}

// Book appointment
function bookAppointment() {

    let name = document.getElementById("customerName").value.trim();
    let mobile = document.getElementById("mobile").value.trim();
    let serviceId = Number(document.getElementById("serviceSelect").value);
    let date = document.getElementById("appointmentDate").value;
    let time = document.getElementById("appointmentTime").value;

    let service = services.find(s => s.id === serviceId);

    if (!name || !/^[0-9]{10}$/.test(mobile) ||
        !service || !date || !time) {

        alert("Please enter all valid appointment details!");
        return;
    }

    let today = new Date();
    today.setHours(0, 0, 0, 0);

    let selectedDate = new Date(date + "T00:00:00");

    if (selectedDate < today) {
        alert("Please select today or a future date!");
        return;
```

```
    }

    // Prevent double booking for the same time
    let alreadyBooked = appointments.some(a =>
        a.date === date &&
        a.time === time &&
        a.status === "Confirmed"
    );
    if (alreadyBooked) {
        alert("This time slot is already booked!");
        return;
    }
    let appointment = {
        id: "APT" + Date.now(),
        name: name,
        mobile: mobile,
        service: service.name,
        price: service.price,
        date: date,
        time: time,
        status: "Confirmed"
    };
    appointments.push(appointment);
    alert("Appointment booked successfully!\nAppointment ID: " + appointment.id);
    document.getElementById("customerName").value = "";
    document.getElementById("mobile").value = "";
    document.getElementById("serviceSelect").value = "";
    document.getElementById("appointmentDate").value = "";
    document.getElementById("appointmentTime").value = "";
    showPage("appointments");
}
// Display appointments
function displayAppointments() {
    let list = document.getElementById("appointmentList");

    list.innerHTML = "";
    if (appointments.length === 0) {
        list.innerHTML = "<p>No appointments booked yet.</p>";
        return;
    }
    appointments.forEach((a, index) => {
        list.innerHTML += `
            <div class="card">
```

```
            <h3>${a.service}</h3>
            <p>Appointment ID: ${a.id}</p>
            <p>Customer: ${a.name}</p>
            <p>Mobile: ${a.mobile}</p>
            <p>Date: ${a.date}</p>
            <p>Time: ${a.time}</p>
            <p>Price: ₹${a.price}</p>
            <p>Status: ${a.status}</p>
            ${a.status === "Confirmed" ?
            `<button class="cancel"
               onclick="cancelAppointment(${index})">
               Cancel Appointment
            </button>` : ""}
         </div>
      `;
   });
}
// Cancel appointment
function cancelAppointment(index) {
   if (confirm("Do you want to cancel this appointment?")) {
      appointments[index].status = "Cancelled";
      alert("Appointment cancelled successfully!");
      displayAppointments();
   }
}
// Admin add service
function addService() {
   let name = document.getElementById("newService").value.trim();
   let price = Number(document.getElementById("newPrice").value);
   let duration = Number(document.getElementById("newDuration").value);
   if (!name || price <= 0 || duration <= 0) {
      alert("Please enter valid service details!");
      return;
   }
   services.push({
      id: Date.now(),
      name: name,
      price: price,
      duration: duration
   });
   alert("New service added successfully!");
   document.getElementById("newService").value = "";
   document.getElementById("newPrice").value = "";
```

```
    document.getElementById("newDuration").value = "";
    displayAdmin();
}
// Admin service list
function displayAdmin() {
    let list = document.getElementById("adminList");
    list.innerHTML = "<h2>Available Services</h2>";
    services.forEach(service => {
        list.innerHTML += `
            <div class="card">
                <h3>${service.name}</h3>
                <p>Price: ₹${service.price}</p>
                <p>Duration: ${service.duration} minutes</p>
            </div>
        `;
    });
}
// Initial display
displayServices();
</script>
</body>
</html>
```

Output:

