3. The online bus ticket booking system enables users to search for buses by route, date, and time, and view available seats. Users can create an account, log in, and manage their bookings through a personal dashboard. The booking process includes selecting seats, filling out passenger details, and making secure payments via an integrated payment gateway. Admins can manage bus schedules, seat availability, and user accounts through an admin panel. Users receive booking confirmation emails and can view their booking history. The website is mobile-responsive, ensuring easy access on all devices.Admin
In this system, the admin can maintain all the Bus information and maintain Bus category, comments etc. In this system, the admin can maintain the registered users, manage news, and the admin can generate reports and manage the whole system.Login:
Login Module includes various utilities like User Authentication, Change Password and Forgot
Password.
Registration:
This website provides some facilities users can be Registered in this website. user can use this
facility so user can make a registration.
Book the Ticket:
In this module, the admin can add a new bus category using this module. Bus Category contains
like Volvo, Slipper coach, coach etc.
Update Bus Information:
In this module, the admin can add or Update Bus using this module. It contains information
about the Bus type, photo, description, Location of the tour, Available Seats in Bus etc.
Cancel the Booking Ticket:
In this Module, the User can cancel the booking Ticket.
Comments:
In this Module, Users can Post Comments on a particular Bus.
Report Generation:
This module is used to generate a report.
Code:

```
<!DOCTYPE html>
<html>
<head>
<title>Online Bus Ticket Booking System</title>
<style>
body {
    font-family: Arial;
```

```
    background: #f1f4f9;
    margin: 0;
}
header {
    background: #153e75;
    color: white;
    text-align: center;
    padding: 22px;
}
nav {
    background: #102d55;
    padding: 12px;
    text-align: center;
}
nav button {
    padding: 10px 15px;
    margin: 5px;
    border: none;
    cursor: pointer;
    border-radius: 5px;
}
.container {
    width: 85%;
    margin: 25px auto;
    background: white;
    padding: 22px;
    border-radius: 10px;
}
input, select {
    width: 90%;
    padding: 10px;
    margin: 8px;
}
.action {
    background: #153e75;
    color: white;
    padding: 10px 15px;
    border: none;
    border-radius: 5px;
    cursor: pointer;
```

```
}
.bus {
   background: #eaf1fc;
   padding: 15px;
   margin: 12px;
   border-radius: 8px;
}
section {
   display: none;
}
#home {
   display: block;
}
</style>
</head>

<body>

<header>
<h1>Online Bus Ticket Booking System</h1>
<p>Book Your Bus Tickets Easily</p>
</header>

<nav>
<button onclick="show('home')">Home</button>
<button onclick="show('login')">Login</button>
<button onclick="show('search')">Search Bus</button>
<button onclick="show('tickets')">My Tickets</button>
<button onclick="show('admin')">Admin</button>
</nav>

<div class="container">

<section id="home">
<h2>Welcome to Bus Booking</h2>
<p>Book your bus tickets online with ease.</p>
<h3>Our Services</h3>
<ul>
<li>Search Available Buses</li>
<li>Seat Availability</li>
```

```
<li>Online Ticket Booking</li>
<li>Ticket Cancellation</li>
<li>Booking History</li>
</ul>
</section>

<section id="login">
<h2>User Login / Registration</h2>
<input type="text" id="username"
placeholder="Enter Your Name">

<input type="email" id="email"
placeholder="Enter Email">

<input type="password" id="password"
placeholder="Enter Password">

<button class="action" onclick="login()">
Login / Register
</button>

<p id="loginMsg"></p>
</section>

<section id="search">
<h2>Search Buses</h2>

<label>From</label>
<input type="text" id="from"
placeholder="Enter Source">

<label>To</label>
<input type="text" id="to"
placeholder="Enter Destination">

<label>Journey Date</label>
<input type="date" id="date">

<button class="action" onclick="searchBus()">
Search Bus
```

```
</button>

<div id="busList"></div>
</section>

<section id="tickets">
<h2>My Booking History</h2>
<div id="ticketList"></div>
</section>

<section id="admin">
<h2>Admin Dashboard</h2>

<h3>Add New Bus</h3>

<input type="text" id="busName"
placeholder="Bus Name">

<input type="text" id="busFrom"
placeholder="Source">

<input type="text" id="busTo"
placeholder="Destination">

<select id="busType">
<option>Volvo AC</option>
<option>Sleeper Coach</option>
<option>Non AC</option>
<option>Seater Coach</option>
</select>

<input type="number" id="busPrice"
placeholder="Ticket Price">

<input type="number" id="seats"
placeholder="Available Seats">

<button class="action" onclick="addBus()">
Add Bus
</button>
```

```
<h3>Manage Buses</h3>
<div id="adminList"></div>

<h3>Booking Report</h3>
<button class="action" onclick="report()">
Generate Report
</button>
<p id="reportResult"></p>

</section>

</div>

<script>

let buses = [
{
name:"Chennai Express",
from:"Chennai",
to:"Bangalore",
type:"Volvo AC",
price:850,
seats:30
},
{
name:"Royal Travels",
from:"Chennai",
to:"Madurai",
type:"Sleeper Coach",
price:650,
seats:25
},
{
name:"Green Line",
from:"Chennai",
to:"Coimbatore",
type:"Non AC",
price:500,
seats:20
```

```
}
];

let tickets = [];
let currentUser = "";

function show(id) {

document.querySelectorAll("section").forEach(s=>{
s.style.display="none";
});

document.getElementById(id).style.display="block";

if(id==="admin") adminBuses();
if(id==="tickets") viewTickets();

}

function login() {

let name=document.getElementById("username").value;
let password=document.getElementById("password").value;

if(name.trim()==="" || password.trim()==="") {
alert("Enter username and password");
return;
}

currentUser=name;

document.getElementById("loginMsg").innerHTML=
"Welcome "+name+"! Login Successful.";

}

function searchBus() {

let from=document.getElementById("from").value.toLowerCase();
let to=document.getElementById("to").value.toLowerCase();
```

```
let date=document.getElementById("date").value;

if(!from || !to || !date) {
alert("Enter all search details");
return;
}

let result=buses.filter(b=>
b.from.toLowerCase()===from &&
b.to.toLowerCase()===to &&
b.seats>0
);

let output="";

result.forEach((b,i)=>{

let index=buses.indexOf(b);

output+=`
<div class="bus">
<h3>${b.name}</h3>
<p>From: ${b.from}</p>
<p>To: ${b.to}</p>
<p>Bus Type: ${b.type}</p>
<p>Price: ₹${b.price}</p>
<p>Available Seats: ${b.seats}</p>
<button class="action"
onclick="bookTicket(${index})">
Book Ticket
</button>
</div>`;

});

document.getElementById("busList").innerHTML=
output || "No buses available.";

}
```

```
function bookTicket(index) {

if(!currentUser) {
alert("Please login first");
show("login");
return;
}

let bus=buses[index];

let count=Number(prompt("Enter number of seats:"));

if(!Number.isInteger(count) || count<=0 ||
count>bus.seats) {
alert("Invalid seat selection");
return;
}

let passenger=prompt("Enter passenger name:");

if(!passenger || !passenger.trim()) return;

let ticket={
id:Date.now(),
user:currentUser,
passenger:passenger,
bus:bus.name,
from:bus.from,
to:bus.to,
date:document.getElementById("date").value,
seats:count,
total:count*bus.price,
status:"Confirmed"
};

bus.seats-=count;
tickets.push(ticket);

alert("Ticket Booked Successfully!\n"+
"Total Amount: ₹"+ticket.total+
```

```
"\nTicket ID: "+ticket.id);

searchBus();

}

function viewTickets() {

let output="";

tickets.forEach((t,i)=>{

if(t.user===currentUser) {

output+=`
<div class="bus">
<h3>${t.bus}</h3>
<p>Passenger: ${t.passenger}</p>
<p>Route: ${t.from} to ${t.to}</p>
<p>Journey Date: ${t.date}</p>
<p>Seats: ${t.seats}</p>
<p>Total: ₹${t.total}</p>
<p>Status: ${t.status}</p>
<button class="action"
onclick="cancelTicket(${i})">
Cancel Ticket
</button>
</div>`;

}

});

document.getElementById("ticketList").innerHTML=
output || "No tickets booked.";

}

function cancelTicket(index) {
```

```
if(confirm("Cancel this ticket?")) {

let ticket=tickets[index];

let bus=buses.find(b=>b.name===ticket.bus);

if(bus) bus.seats+=ticket.seats;

tickets.splice(index,1);

viewTickets();

alert("Ticket Cancelled Successfully");

}

}

function addBus() {

let name=document.getElementById("busName").value;
let from=document.getElementById("busFrom").value;
let to=document.getElementById("busTo").value;
let type=document.getElementById("busType").value;
let price=Number(document.getElementById("busPrice").value);
let seats=Number(document.getElementById("seats").value);

if(!name || !from || !to || price<=0 ||
!Number.isInteger(seats) || seats<=0) {
alert("Enter valid bus details");
return;
}

buses.push({
name:name,
from:from,
to:to,
type:type,
price:price,
seats:seats
```

```
});

alert("Bus Added Successfully");

adminBuses();

}

function adminBuses() {

document.getElementById("adminList").innerHTML=
buses.map((b,i)=>`
<div class="bus">
<b>${b.name}</b>
<p>${b.from} to ${b.to}</p>
<p>Price: ₹${b.price}</p>
<p>Seats: ${b.seats}</p>
<button class="action"
onclick="deleteBus(${i})">
Delete Bus
</button>
</div>
`).join("");

}

function deleteBus(index) {

if(confirm("Delete this bus?")) {
buses.splice(index,1);
adminBuses();
}

}

function report() {

document.getElementById("reportResult").innerHTML=
"Total Buses: "+buses.length+
"<br>Total Bookings: "+tickets.length+
```

```
"<br>Total Revenue: ₹"+
tickets.reduce((sum,t)=>sum+t.total,0);

}

</script>

</body>
</html>
```

Output:

