

Functional Extensionality for Refinement Types

Niki Vazou
IMDEA

Michael Greenberg
Pomona College


WG 2.8, 2021

Functional Extensionality for Refinement Types

“Two functions are equal,
if their values are equal at every argument.”

$\text{funExt} :: \forall a\ b. f:(a \rightarrow b) \rightarrow g:(a \rightarrow b) \rightarrow (x:a \rightarrow \{f\ x = g\ x\}) \rightarrow \{f = g\}$

short for
 $\{v:() \mid f\ x = g\ x\}$



`funExt :: $\forall a\ b. f:(a \rightarrow b) \rightarrow g:(a \rightarrow b) \rightarrow (x:a \rightarrow \{f\ x = g\ x\}) \rightarrow \{f = g\}$`

`incrNat :: Int \rightarrow Int`

`incrNat x = if 0 \leq x then 0 else x + 1`

`incrInt :: Int \rightarrow Int`

`incrInt x = x + 1`

`type Nat = {v:Int | 0 \leq v}`

`incrEq :: x:Nat \rightarrow {incrNat x = incrInt x}`

`incrEq _ = ()`

`incrFEq :: () \rightarrow { incrNat = incrInt }`

`incrFEq _ = funExt incrNat incrInt incrEq`

`incrEqMap :: xs:[Nat] \rightarrow {map incrNat xs = map incrInt xs}`

`incrEqMap _ = incrFEq ()`

`funExt :: $\forall a\ b. f:(a \rightarrow b) \rightarrow g:(a \rightarrow b) \rightarrow (x:a \rightarrow \{f\ x = g\ x\}) \rightarrow \{f = g\}$`

Problem 1: Result type forgets the domain

`incrEq :: $x:\text{Nat} \rightarrow \{\text{incrNat } x = \text{incrInt } x\}$`

`incrEq _ = ()`

`incrFEq :: () $\rightarrow \{\text{incrNat} = \text{incrInt}\}$`

`incrFEq _ = funExt incrNat incrInt incrEq`

`incrEqMap :: $xs:[\text{Nat}] \rightarrow \{\text{map incrNat } xs = \text{map incrInt } xs\}$`

`incrEqMap _ = incrFEq ()`

`funExt :: $\forall a\ b. f:(a \rightarrow b) \rightarrow g:(a \rightarrow b) \rightarrow (x:a \rightarrow \{f\ x = g\ x\}) \rightarrow \{f = g\}$`

Problem 1: Result type forgets the domain

`incrEq :: $x:\text{Nat} \rightarrow \{\text{incrNat } x = \text{incrInt } x\}$`

`incrEq _ = ()`

`incrFEq :: () $\rightarrow \{\text{incrNat} = \text{incrInt}\}$`

`incrFEq _ = funExt incrNat incrInt incrEq`

`incrEqMap :: $xs:[\text{Nat}] \rightarrow \{\text{map incrNat } xs = \text{map incrInt } xs\}$`

`incrEqMap _ = incrFEq ()`

$\text{funExt} :: \forall a\ b. f:(a \rightarrow b) \rightarrow g:(a \rightarrow b) \rightarrow (x:a \rightarrow \{f\ x = g\ x\}) \rightarrow \{f = g\}$

Problem 1: Result type forgets the domain

$\text{incrEq} :: x:\text{Nat} \rightarrow \{\text{incrNat}\ x = \text{incrInt}\ x\}$

$\text{incrEq}\ _ = ()$

$\text{incrFEq} :: () \rightarrow \{\text{incrNat} = \text{incrInt}\}$

$\text{incrFEq}\ _ = \text{funExt}\ \text{incrNat}\ \text{incrInt}\ \text{incrEq}$

$\text{incrEqMap} :: xs:[\text{Int}] \rightarrow \{\text{map}\ \text{incrNat}\ xs = \text{map}\ \text{incrInt}\ xs\}$

$\text{incrEqMap}\ _ = \text{incrFEq}\ ()$

$\text{incrBad} :: \{\text{incrNat}\ (-2) = \text{incrInt}\ (-2)\} \text{ — i.e., } 0 = -1$

$\text{incrBad}\ _ = \text{incrFEq}\ ()$

$\text{funExt} :: \forall a\ b. f:(a \rightarrow b) \rightarrow g:(a \rightarrow b) \rightarrow (x:a \rightarrow \{f\ x = g\ x\}) \rightarrow \{f = g\}$

Problem 2: Domain only appears positively

At instantiation we can pick **any** domain, e.g.,

$a := \{v:\text{Int} \mid \text{false}\}$

Under the empty domain, we can trivially prove **anything**

$\text{incrFEq} :: () \rightarrow \{ \text{incrInt} = \text{plus2} \}$

$\text{incrFEq}\ _ = \text{funExt incrInt plus2}$

$(\backslash_ \rightarrow ()) \text{ — } x:\{v:\text{Int} \mid \text{false}\} \rightarrow \{\text{incrInt}\ x = \text{plus2}\ x\}$

$\text{eqBad} :: () \rightarrow \{ \text{incrInt}\ 0 = \text{plus2}\ 0 \} \text{ — i.e., } 1 = 2$

$\text{eqBad}\ _ = \text{incrFEq}\ ()$

Problem 1: Result type forgets the domain

Problem 2: Domain only appears positively

Solution: Type-indexed equality

$\text{PEq } a \{e_l\} \{e_r\}$

“ e_l is equal to e_r on type a ”

Problem 1: Result type forgets the domain

Problem 2: Domain only appears positively

Solution: Type-indexed equality

$\text{PEq } a \{e_l\} \{e_r\}$

$f:(a \rightarrow b) \rightarrow g:(a \rightarrow b)$
 $\rightarrow (x:a \rightarrow \text{PEq } b \{f\ x\} \{g\ x\})$
 $\rightarrow \text{PEq } (a \rightarrow b) \{f\} \{g\}$



Domain appears
negatively in the result!

PEq: Type-indexed equality

data PEq :: * → * **where**

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

e.g.,

XEq incrNat incrInt ...

:: PEq (Nat → Int) {incrNat} {incrInt}

PEq: Type-indexed equality

data PEq :: * → * **where**

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: x:a → y:a → { x = y }
→ PEq a {x} {y}

e.g.,

XEq incrNat incrInt ...

:: PEq (Nat → Int) {incrNat} {incrInt}

PEq: Type-indexed equality

data PEq :: * → * where

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: x:a → y:a → { x = y }
→ PEq a {x} {y}

What if a is function???

PEq: Type-indexed equality

data PEq :: * → * where

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: AEq a ⇒ x:a → y:a → { x ≡ y }
→ PEq a {x} {y}

What if a is function???

AEq: axiomatised equality

AEq: axiomatised equality

class AEq a **where**

$(\equiv) :: a \rightarrow a \rightarrow \text{Bool}$

$\text{reflP} :: x:a \rightarrow \{x \equiv x\}$

$\text{symmP} :: x:a \rightarrow y:a \rightarrow \{x \equiv y \Rightarrow y \equiv x\}$

$\text{transP} :: x:a \rightarrow y:a \rightarrow z:a \rightarrow \{x \equiv y \wedge y \equiv z \Rightarrow x \equiv z\}$

e.g., $x :: \text{Nat} \vdash \text{reflP} (\text{incrInt } x) :: \{\text{incrInt } x \equiv \text{incrInt } x\}$
 $:: \{\text{incrNat } x \equiv \text{incrInt } x\}$

PEq: Type-indexed equality

data PEq :: * → * **where**

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: AEq a ⇒ x:a → y:a → { x ≡ y }
→ PEq a {x} {y}

e.g., XEq incrNat incrInt \$ \x →
BEq (incrNat x) (incrInt x) \$ reflP (incrInt x)
:: PEq (Nat → Int) {incrNat} {incrInt}

PEq: Type-indexed equality

data PEq :: * → * **where**

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: AEq a ⇒ x:a → y:a → { x ≡ y }
→ PEq a {x} {y}

CEq :: x:a → y:a → ctx:(a → b) → PEq a {x} {y}
→ PEq b {ctx x} {ctx y}

e.g., XEq incrNat incrInt \$ \x →
BEq (incrNat x) (incrInt x) \$ reflP (incrInt x)
:: PEq (Nat → Int) {incrNat} {incrInt}

PEq: Type-indexed equality

data PEq :: * → * **where**

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: AEq a ⇒ x:a → y:a → { x ≡ y }
→ PEq a {x} {y}

CEq :: x:a → y:a → ctx:(a → b) → PEq a {x} {y}
→ PEq b {ctx x} {ctx y}

e.g., CEq incrNat incrInt map \$
XEq incrNat incrInt \$ \x →
BEq (incrNat x) (incrInt x) \$ reflP (incrInt x)
:: PEq ([Nat] → [Int]) {map incrNat} {map incrInt}

PEq: Type-indexed equality

data PEq :: * → * **where**

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: AEq a ⇒ x:a → y:a → { x ≡ y }
→ PEq a {x} {y}

CEq :: x:a → y:a → ctx:(a → b) → PEq a {x} {y}
→ PEq b {ctx x} {ctx y}

e.g., CEq incrNat incrInt map \$
XEq incrNat incrInt \$ \x →
BEq (incrNat x) (incrInt x) \$ reflP (incrInt x)
:: PEq ([Nat] → [Int]) {map incrNat} {map incrInt}

PEq: Type-indexed equality

data PEq :: * → * where

XEq :: f:(a → b) → g:(a → b)
→ (x:a → PEq b {f x} {g x})
→ PEq (a → b) {f} {g}

BEq :: AEq a ⇒ x:a → y:a → { x ≡ y }
→ PEq a {x} {y}

CEq :: x:a → y:a → ctx:(a → b) → PEq a {x} {y}
→ PEq b {ctx x} {ctx y}

\xs → CEq (map incrNat) (map incrInt) (\f → f xs) \$

CEq incrNat incrInt map \$

XEq incrNat incrInt \$ \x →

BEq (incrNat x) (incrInt x) \$ reflP (incrInt x)

:: xs:[Nat] → PEq ([Int]) {map incrNat xs} {map incrInt xs}

Can I convert **PEq back to SMT equality?**

```
\xs → CEq (map incrNat) (map incrInt) (\f → f xs) $  
      CEq incrNat incrInt map $  
      XEq incrNat incrInt $ \x →  
        BEq (incrNat x) (incrInt x) $ reflP (incrInt x)  
:: xs:[Nat] → PEq ([Int]) {map incrNat xs} {map incrInt xs}
```

Can I convert **PEq** back to SMT equality?


We defined a class for this conversion

```
class AEq a  $\Rightarrow$  SMTEq a where  
  toSMT :: x:a  $\rightarrow$  y:a  $\rightarrow$  PEq a {x} {y}  $\rightarrow$  {x = y}
```

which comes with a default instance

```
assume instance AEq a  $\Rightarrow$  SMTEq a where  
  toSMT _ _ _ = ()
```

Can I convert **PEq** back to SMT equality?



* the more equalities, the more consistent the system

Is PEq expressive?

We used PEq to prove

Monoid laws for Endofunctors (64 LoC)

Monad & Monoid laws for Reader (243 LoC)

`monadLeftIdentity :: a:a → f:(a → Reader r b) → PEq (Reader r b) {bind (pure a) f} {f a}`

`monadRightIdentity :: m:(Reader r a) → PEq (Reader r a) {bind m pure} {m}`

`monadAssociativity :: m:(Reader r a) → f:(a → Reader r b) → g:(b → Reader r c)
→ PEq (Reader r c) {bind (bind m f) g} {bind m (kleisli f g)}`

Is PEq expressive?

We used PEq to prove

Monoid laws for Endofunctors (64 LoC)

Monad & Monoid laws for Reader (243 LoC)

Is PEq an equivalence?

Paper-and-pencil proofs for toy core calculus

Equivalence properties proofs within Liquid Haskell

PEq is reflexive by “classy induction”

-- (1) Property Definition by Refined typeclass

```
class Reflexivity a where  
  refl :: x:a → PEq a {x} {x}
```

-- (2) Base case (AEq types)

```
instance AEq a ⇒ Reflexivity a where  
  refl a = BEq a a (reflP a)
```

-- (3) Inductive case (function types)

```
instance Reflexivity b ⇒ Reflexivity (a → b) where  
  refl f = XEq f f (\a → refl (f a))
```

Functional Extensionality for Refinement Types

Problem: Naive axiom forgets the domain type
which leads to inconsistencies, i.e., proves false

Solution: Type Indexed Equality
which is verbose, but expressive and consistent