

# Getting started with Competitive Programming

## Week 12 – Dynamic Programming

### Problem : Knapsack for all subsets

Given are a sequence of  $N$  positive integers  $A_1, A_2, \dots, A_N$  and another positive integer  $S$ .

For a non-empty subset  $T$  of the set  $\{1, 2, \dots, N\}$ , let us define  $f(T)$  as follows:

$f(T)$  is the number of different non-empty subsets  $\{x_1, x_2, \dots, x_k\}$  of  $T$  such that

- $A_{x_1} + A_{x_2} + \dots + A_{x_k} = S$ .

Find the sum of  $f(T)$  over all  $2^N - 1$  subsets  $T$  of  $\{1, 2, \dots, N\}$ . Since the sum can be enormous, print it modulo 998244353.

### Constraints

- All values in input are integers.
- $1 \leq N \leq 3000$
- $1 \leq S \leq 3000$
- $1 \leq A_i \leq 3000$

---

### Input

Input is given from Standard Input in the following format:

```
N S
```

```
A_1, A_2, \dots, A_N
```

### Output

Print the sum of  $f(T)$  modulo 998244353.

---

### Sample Input 1

```
3 4
2 2 4
```

### Sample Output 1

```
6
```

For each  $T$ , the value of  $f(T)$  is shown below. The sum of these values is 6.

- $f(\{1\})=0$
- $f(\{2\})=0$
- $f(\{3\})=1$  (One subset  $\{3\}$  satisfies the condition.)
- $f(\{1,2\})=1$  ( $\{1,2\}$ )
- $f(\{2,3\})=1$  ( $\{3\}$ )
- $f(\{1,3\})=1$  ( $\{3\}$ )
- $f(\{1,2,3\})=2$  ( $\{1,2\}, \{3\}$ )

---

### Sample Input 2

```
5 8
9 9 9 9 9
```

### Sample Output 2

```
0
```

---

### Sample Input 3

```
10 10
3 1 4 1 5 9 2 6 5 3
```

### Sample Output 3

```
3296
```