

PORTAL QA · ROUND 1

Add Service modal audit

May 15, 2026

First QA pass on the + **Add service** flow under Clients → client detail. Both bugs were spotted by Nikko while sanity-checking the modal on the portal. Both are **HIGH severity** and together they break the template-seed flow end to end:

- The “(0 tasks)” count suffix on template options is wrong (templates with phases + subtasks still read 0) and not present on the original at all.
- After creating a service from a template, the resulting board's To Do column is empty — template phases don't seed cards.

The second is the more consequential: it means the template feature on the portal is non-functional. The agency loses the whole point of templates (consistent project structure, no recreation on every new service) until this lands.

Workspace state at time of QA: Templates page reads 3 *ACTIVE* · 29 *ARCHIVED*. The 3 active templates are all Custom (“New template”). All built-in templates (Brand Refresh, Account Management, etc.) are in the Archived bucket — that's a data state choice on this workspace, not a bug. If the agency wants those available again, restore them from the Archived section.

2 findings · 2 HIGH · 0 MED · 0 LOW · 0 INFO

Status legend: **HIGH** blocks scanning / breaks workflow · **MED** meaningful divergence · **LOW** polish · **INFO** matches or working as intended.

Each finding carries two chips. **Severity** (HIGH / MED / LOW / INFO) maps to impact. **History tag** (**FROM PREVIOUS QA** = carried over from prior QA, **NEW** = surfaced this round) shows which items the dev has been sitting on vs. fresh observations. **FROM PREVIOUS QA** items need triage first.

HIGH severity

HIGH

NEW

Template options append a “(0 tasks)” count that is wrong, and not present on the original

Where to see: Same dropdown (Top → Clients → + Add service → Template). Open the dropdown and read the label on each option.

Portal: Every Custom template option renders as “*New template (0 tasks)*”. Nikko verified that at least one of those Custom templates has **1 phase + 1 subtask** in it (open the template on the Templates page to confirm), so the “(0 tasks)” annotation is reading the wrong data — either it’s counting only the wrong collection (e.g. top-level tasks on the template, which don’t exist; the data lives on `phases[].subtasks[]`) or the field path is broken outright.

Original: Template options are listed by name only, with no count suffix. The Templates page (per-template detail) carries the count (“7 phases · 6 onboarding items”) where it earns its keep; the Add Service dropdown isn’t the right surface for that metric.

Fix: Two options, pick one:

Option A (recommended) — drop the count suffix entirely. Matches the original. The Templates page is the source of truth for what each template contains; the user can open it from the rail to inspect. Add Service dropdown reads cleaner without the suffix.

Option B — fix the count to be accurate. If the team wants the suffix to stay, compute it as `template.phases.reduce((n, p) => n + (p.subtasks?.length ?? 0), 0)` + the phase count, e.g. “`{template.name} · {phaseCount} phases · {subtaskCount} tasks`”. Label it consistently with the Templates page (which uses “phases · onboarding items”).

Either way, the current “(0 tasks)” is wrong and should not ship.

HIGH

NEW

Service created from a template has an empty To Do column — template content does not seed cards

Where to see: Top → Clients → client detail → + Add service → pick any template that has content (Custom or built-in, once HIGH #1 is fixed) → Create. Open the resulting service board.

Portal: Board renders with all five columns present (To Do / In Progress / Blocked / Needs Review / Done) but **To Do is empty**. None of the chosen template's phases became cards. The user has to manually populate the board from scratch, which defeats the purpose of seeding from a template.

Compounded by HIGH #1 + HIGH #2: the user can't even pick a built-in template, and the Custom ones the dropdown does offer claim to have 0 tasks. So the user picks a Custom template hoping their previously-configured phases will seed the board, and instead they get an empty board. The template feature is effectively broken end to end on the portal.

Original: After create, the new service's board has **one card per phase** in the To Do column. Each card carries:

- The phase name as the card title (e.g. “Discovery interviews”, “Moodboards”).
- The phase's subtasks as the card's checklist (5 subtasks → 5 unchecked checkboxes on the card).
- Default status To Do, Medium priority, no assignee, no due date (the AM fills those in as the service moves).

User can immediately drag a card into In Progress or assign it. The whole point of templates is that the AM doesn't have to recreate the project structure for every service — the seed materialises on create.

Fix: Wire the create-service handler to seed cards from the chosen template's phases. Pseudocode for the source-side flow:

```
async function addService(clientId, serviceData) {
  const service = await createService(clientId, serviceData);
  if (serviceData.templateId) {
    const tpl = getTemplate(serviceData.templateId);
    for (const phase of tpl.phases) {
      await createCard({
        serviceId: service.id,
        title: phase.name,
        column: 'todo',
        checklist: phase.subtasks.map(s => ({ label: s.name, complete: false })),
      });
    }
  }
}
```

```
    });  
  }  
}  
}
```

If the create-service endpoint already accepts a *templateId* param, the seeding may be expected to happen server-side — in that case the server is silently swallowing the phases. Add a server log + manual repro on a single-phase template to find where the loop is dropping.

After fix: spot-check with a multi-phase template (e.g. Brand Refresh has 6 phases). Create a service, open the board, confirm 6 cards land in To Do, each with their subtasks as the checklist.

Build checklist

Every actionable finding (HIGH / MED / LOW). INFO items are listed in the body but not in the checklist. Tick each as it ships.

**HIGH**

Template options append a “(0 tasks)” count that is wrong, and not present on the original

Two options, pick one:

Option A (recommended) — drop the count suffix entirely. Matches the original. The Templates page is the source of truth for what each template contains; the user can open it from the rail to inspect. Add Service dropdown reads cleaner without the suffix.

Option B — fix the count to be accurate. If the team wants the suffix to stay, compute it as `template.phases.reduce((n, p) => n + (p.subtasks?.length ?? 0), 0)` + the phase count, e.g. “`{template.name} · {phaseCount} phases · {subtaskCount} tasks`”. Label it consistently with the Templates page (which uses “phases · onboarding items”).

Either way, the current “(0 tasks)” is wrong and should not ship.

**HIGH****Service created from a template has an empty To Do column — template content does not seed cards**

Wire the create-service handler to seed cards from the chosen template's phases. Pseudocode for the source-side flow:

```
async function addService(clientId, serviceData) {
  const service = await createService(clientId, serviceData);
  if (serviceData.templateId) {
    const tpl = getTemplate(serviceData.templateId);
    for (const phase of tpl.phases) {
      await createCard({
        serviceId: service.id,
        title: phase.name,
        column: 'todo',
        checklist: phase.subtasks.map(s => ({ label: s.name, complete: false })),
      });
    }
  }
}
```

If the create-service endpoint already accepts a *templateId* param, the seeding may be expected to happen server-side — in that case the server is silently swallowing the phases. Add a server log + manual repro on a single-phase template to find where the loop is dropping.

After fix: spot-check with a multi-phase template (e.g. Brand Refresh has 6 phases). Create a service, open the board, confirm 6 cards land in To Do, each with their subtasks as the checklist.