

An Open Source Smart home Platform

Niklas Harnish

12/05/2023

Supervisor: Dr Amna Asif

B.Sc. (Hons) Computer Science

Number of words = 0

This includes the body of the report only

Declaration of Originality

Put some text similar to the following in here:

I certify that the material contained in this dissertation is my own work and does not contain unreferenced or unacknowledged material. I also warrant that the above statement applies to the implementation of the project and all associated documentation. Regarding the electronically submitted work, I consent to this being stored electronically and copied for assessment purposes, including the School's use of plagiarism detection systems in order to check the integrity of assessed work.

I agree to my dissertation being placed in the public domain, with my name explicitly included as the author of the work.

Name:

Date:

Abstract

Put your abstract here. You should create a short abstract (200 words at maximum) which is on a page by itself. The abstract should be a very high-level overview: for example 1–2 sentences on the aims of the project, 1–2 sentences on the kind of design, implementation, or empirical work undertaken, and 2–3 sentences summarising the primary contribution or findings from your work. The abstract appears in the front matter of the report: after your title page but before the table of contents.

what should go in here:

aims

design

implementation

findings and primary contribution

If you want to dedicate to someone in particular

Acknowledgements

General acknowledgements . . .

your supervisor, your family, your friends, . . .

Contents

1	Introduction	1
1.1	Aims & Objectives	1
1.2	Project Overview	1
2	Background	2
2.1	IoT System Architectures	2
2.2	The Smart Home System	2
2.3	APIs and Web Interfaces	3
2.3.1	Request Response	3
2.3.2	Event Driven	4
2.4	Security	4
2.5	Networking	4
2.6	Open Source and Licensing	4
3	Implementation	5
3.1	Technology Choices	5
3.1.1	Rust	5
3.1.2	gRPC	6
3.1.3	Typescript & VueJS	6
3.1.4	Raspberry Pi	6
3.2	Server & Hub	6
3.2.1	Server Start Up	6
3.2.2	Device Registration	7
3.2.3	Security	7
3.2.4	Threads & Concurrency	7
3.2.5	Device API	7
3.3	Device Library	7
3.4	Example Device	7
3.5	Networking	7
3.6	Web & CLI Frontend	7
3.7	Open Source	7
A	Original Project Proposal	9
B	Another Appendix Chapter	10

List of Figures

List of Tables

1 Introduction

Will write a couple of words about the project here, similar projects, inspirations etc. Citation here to remember how to do it :)

actually
write this
section

1.1 Aims & Objectives

When researching available smart home technology, one major gap I came across was the availability of open source software. While options exist for someone interested in connecting their proprietary device to an open source platform (view), there was no solution for anyone looking to build their own device and then connect it to an open source hub. In fulfilling this goal, to build an open source platform for both devices and the hub they will connect to, there are multiple objectives that will need to be met along the way:

find the
link to
this

1. Create a Library and API (Application Programming Interface) for building smart home devices.
2. Build a Server with an API for the smart home devices to communicate with. This will act as a hub and will control clients connected to it.
 - a) This API should be well documented, so a user can interact with the hub, without using the Library.
3. Create a frontend, which will be populated with devices currently connected to the smart home. It will also be used to control clients connected to the server.
 - a) The API provided by the server for this frontend should also be easy to use, so the user can create their own frontend environment.
4. The code of all of the above should be hosted in a public repository, with instructions for how to build and use every component of the system.
 - a) An appropriate license should also be selected for this repository, so the code within it can be copied or modified by third parties.
 - b) This repository should provide important links and provide information on the inner workings of the system, to support interested parties.

1.2 Project Overview

Each bullet point below would give a small summary of the section

1. **Background Research**
2. **Design of the System & Technology Decisions**
3. **Implementation**
4. **Results**
5. **Conclusion and Reflection**

ask about
this sec-
tion

2 Background

2.1 IoT System Architectures

Kamienski et al. describe a simple three layer architecture of an IoT system in [8]. Within this architecture, the top layer is the "Input System", from which any data that will influence the decisions of the IoT system will come from. Included in this are sensors, but also user facing interfaces. The second layer, known as the "Process System", is where any algorithms are run and system behavioral decisions are made. The goal of this layer is to gain an "improved understanding of the system where the data comes from" [8]. The bottom layer is the "Output System", which are where decisions made by the Process System will be enacted. This is often represented as the devices connected to the IoT system.

This three layer architecture is expanded upon by Bansal and Kumar within [3], where three more architectures are described which expand upon the ideas within the three layer architecture. They are however more specialized than the three layer architecture. The first of these is a "Middleware Based" architecture, which can take many forms, but is usually combined with another type of architecture, with a middleware layer. The different types are described in detail by Zhang et al. in [12]. The second is known as a "Fog Based" architecture, where certain tasks, usually those with less processing requirements, are calculated on device to reduce latency. More computationally expensive tasks are however calculated on a server in the cloud [10].

The most relevant architecture to this report is known as a "Service Based" architecture (SBA). The SBA is defined around the concept of the Service Oriented Architectural (SOA) style [6] of software design. SOA is defined by the Open Group Foundation as an "architectural style that supports service-orientation", where a service is a "logical representation of a repeatable business activity that has a specified outcome" [1]. Each service is a "black box" any device interacting with it. Other devices use interfaces and API endpoints to make requests to the service and receive a result. A SOA is composed of many different services. In SBA, services are used to offer device functionality using interfaces, often using web based concepts such as SOAP or REST APIs [4]. This allows devices with different capabilities and purposes to interact with the same system, allowing for an IoT system that is more flexible.

2.2 The Smart Home System

Sethi and Sarangi [10] define six components that need to be present within a social IoT setting. A social IoT system is defined as a IoT system where devices form relationships with other devices. While our smart home system will not be a social IoT system, some of these concepts are still of interest. These are:

1. ID: the device within the system needs to have a way of identifying it.
2. Meta-data: the device should have information regarding its form and purpose

Add section about which one I chose: Service Based Architecture

ask if this is ok with citation as its quite similar

3. Security Controls: the system should have some way of distinguishing between different users. It should also be able to distinguish what types of devices it can connect to or can connect to it.
4. Service Discovery: each device should be able to discover other devices connected to the system and what services they offer.

There are some specific constraints specific to Smart Homes. Reliability is a key concern, due to the lack of a trained professional being available to fix any issues that arise. This is contrast to more industrial IoT settings, where there might be someone to fix any issues that arise. Another concern is the security and privacy of the system. Due to smart homes inherently having access to sensitive data (due to their position in someone's home), one must ensure that the system is both ethically sound and secure. The issue of security is further discussed in Subsection 2.4.

further
add to
this sec-
tion, just
not sure
what yet

2.3 APIs and Web Interfaces

The book "Designing Web APIs" makes an important distinction about APIs that can often be forgotten by developers. "Although APIs are designed to work with other programs, they're mostly intended to be understood and used by humans writing those other programs" [7] (Chapter 1). Do to this reality, one must remember to design APIs appropriately. To help the API designer in doing that, there are multiple pre-defined architectural standards that they can use.

2.3.1 Request Response

"Request Response" APIs (RRA) expose their interface through a web server, to which clients can make requests. A client will request data and will receive a response from the server. Common formats for requests and responses include JavaScript Object Notation (JSON) and Extensible Markup Language (XML). [7].

One popular type of RRA is known as Representational State Transfer (REST). Two important properties of REST is that it is used in Client-Server scenarios and that every request is stateless [5]. This means that every API request from the client to the server, must contain all information required to complete that request, without the server storing any of that information. Instead, all state is stored on the client. While this constraint might seem strange, it makes any API implementing REST easily scalable, and potentially easier/faster to build. The downside being inherently increased network traffic, with less control application behavior. [5].

Another popular implementation of a RRA is known as the Remote Procedure Call Architecture (RPC). The key difference between RPC and REST is that RPC is about making an action on the server. In REST the client supplies the server with the information required to take an action, whereas using RPC the client tells the server what action to take. RPC APIs can usually express more nuance in their requests and are generally stateful. While RPC usually uses JSON or XML for requests and responses, there are multiple implementations, such as Google's gRPC and Apache Thrift, which do not. These are usually serialized and therefore consume less network traffic than non-serialized formats such as the aforementioned JSON [7].

2.3.2 Event Driven

Event driven APIs go in a different direction than RRAs. Instead of the client continuously requesting information from the server, the client registers with the Server once, then whenever there is an update the server sends the client a message notifying it of an update. This completely resolves the need for polling, the client continuously requesting updates from the server, which is often present in RAA API designs [7].

Web sockets are a type of Event Driven API that utilize a bidirectional TCP connection between server and client. Unlike the previously mentioned API styles, a connection on a web socket stays active until closed [2]. Due to the bidirectional TCP connections both client and server can send one another packets, even at the same time [7]. This is in contrast to REST and RPC protocols, where only the client can contact the server. This comes at the downside of scalability, as a server must maintain a connection with every device that is connected with the server. Additionally, there are also issues when a client is on an unstable connection, as web sockets expect a client to stay connected, with the client having to reinitiate the connection if it is dropped [7].

The final type of API that deserves a short mention is the Web Hook. Web hooks work in an unconventional manner, where the initiator of an exchange gives a URL to their own API endpoint. This URL is then used by the receiver. Whenever a new event for the initiator occurs, the receiver will send information about the event to the URL [7]. While at face value this may seem like an obvious solution in an IOT based environment, where devices are often waiting for an event from the central server, it makes less sense when one realizes that every device connected to this webhook will need to host some sort of HTTP server, to receive the API requests. This makes it unsuitable, especially in environments where IOT devices are low powered, embedded systems devices. Web hooks are often used in server to server communication, as in such a scenario they are trivial to set up (as servers will most likely already be setup to receive API requests) [7].

2.4 Security

Requires more research and testing to find a good solution, will be written and implemented later.

2.5 Networking

I don't think this section is very interesting, so I will probably not write about this in background, however it will be mentioned in the implementation, that I left it mostly up to the user

2.6 Open Source and Licensing

Not sure about this section either, perhaps speak about how some open source projects are managed and different possible licenses. This does not sound interesting either.

Add section about which one I chose: RPC, specifically gRPC

Remove this text and write this section

Remove this text

Remove this text

3 Implementation

3.1 Technology Choices

This section will discuss choices that have been made throughout the project regarding technology used and justifications for their usage.

3.1.1 Rust

There were a few requirements when choosing an appropriate programming language for this project:

1. Performance: There are two aspects to performance within this project. Performance considerations and optimization are vital on IOT devices themselves, due to their limited on-board processing power. On the other hand, while performance on servers is definitely important, it is significantly easier to scale server-performance, by simply adding more servers (horizontal scaling) or by improving the hardware of any individual server (vertical scaling), than it is to improve performance of an IoT device. This is especially true of an IoT device that is already deployed.
2. Stability: Another important requirement when choosing a language is the stability of code written in the language. This does not necessarily mean that code written in that language, or running on a runtime in that language, is inherently unstable, however it is more of a consideration about if the language enables and encourages a programmer to write code that is memory-safe and handles errors correctly. This is important in an IoT environment, as devices are expected to run for long periods. What is the point of a security camera if it's software crashes every couple days, due to an obscure memory out of bounds error?
3. Security: While no language is inherently "hack-proof" or secure, there are ways a language can encourage behaviors that can lead to better outcomes in security. A blog-post by the "Microsoft Security Response Centre" states that 70% of all vulnerabilities assigned a CVE (Common Vulnerabilities and Exposures) each year are due to memory corruption errors [11]. In the post the languages "C" and "C++" are specifically referred to as being part of this problem. As mentioned in subsection 2.4, security is of particular importance in smart home systems, so ensuring a method or language that enables secure code is chosen is of particular importance.
4. Ease of Use and Comfort: While not particularly important in the final product, having a language that is easy to develop in can make the developer experience easier and can lead to faster iteration on ideas, perhaps leading to a better final result. That being said, developer familiarity with a language can more than make up this difference. A seasoned C++ developer will be able to iterate faster and produce a better product in C++, than if they are using an "easy" language, that they are not as familiar with.

After some deliberation, the language that was chosen for this project was Rust. While C/C++'s performance rivals and often surpasses rust, the difference is often quite marginal [9], due to all three being compiled to machine code. What makes Rust different, is its headline feature, known as the "borrow checker". While the details of the borrow checker are out of scope of this paper, it can ensure that at compile-time, the code is memory safe. While there are ways to circumvent this (using the "unsafe" keyword), this has to be explicitly done. Due to the code being guaranteed memory safe at compile time, outside the aforementioned unsafe blocks, Rust code is known for its ability to run long-term without running into crashes. Additionally, Rust code is a popular choice for embedded devices, due to being able to compile without a standard library (this has to be enabled), giving it flexibility in a project such as this.

I have decided to use Rust for both the Server and Clients. While Rust might be a somewhat obvious choice for IoT clients, it is less so for servers. Due to the "borrow checker", while Rust might be safe, it is often said to be harder to write than traditional languages. This makes it more questionable as the primary language for the server, due to it being a less constrained platform (view performance section above). While servers are theoretically almost infinitely horizontally scalable, in practice this is often not the case, especially in a smart-home's case, as they have to fit in someone's home and generally should be affordable. Therefore ensuring that the server can run on as many devices as possible, be it a Raspberry-Pi, or a modern desktop, is an important goal to strive for. The "difficulty" aspect of Rust can be largely counteracted by personal familiarity with the language. Additionally, having a stable server is very important, especially since all IoT devices will need to frequently communicate with this server, an aspect which Rust excels at. For these reasons I have chosen Rust as the primary programming language of the Server and Client parts of this project.

3.1.2 gRPC

3.1.3 Typescript & VueJS

3.1.4 Raspberry Pi

3.2 Server & Hub

3.2.1 Server Start Up

```
1 #[derive(clap::Parser, Debug)]
2 #[command(author, version, about, long_about = None)]
3 struct Args {
4     ///Run an additional JSON frontend api endpoint, all json requests
5     #[arg(long, default_value_t = false)]
6     json_frontend: bool,
7 }
8
9 const DEFAULT_PORT: u16 = 2302;
10
11 #[tokio::main]
```

```

12 async fn main() -> anyhow::Result<()> {
13     let args = Args::parse();
14
15     let local_ip = local_ip().map_err(|e| {
16         eprintln!("Error getting local ip address
17             You can try setting it manually using --set-ip:{{ip}}
18         return e;
19     })?;
20
21     let port = DEFAULT_PORT;
22     let grpc_address = SocketAddr::new(local_ip, port);

```

3.2.2 Device Registration

3.2.3 Security

3.2.4 Threads & Concurrency

3.2.5 Device API

3.3 Device Library

3.4 Example Device

3.5 Networking

3.6 Web & CLI Frontend

3.7 Open Source

Bibliography

- [1] Soa source book.
- [2] Websockets living standard, Jan 2024.
- [3] S. Bansal and D. Kumar. Iot ecosystem: A survey on devices, gateways, operating systems, middleware and communication. *International journal of wireless information networks*, 27(3):340–364, 2020.
- [4] I.-R. Chen, J. Guo, and F. Bao. Trust management for soa-based iot and its application to service composition. *IEEE transactions on services computing*, 9(3):482–495, 2016.
- [5] R. T. Fielding. Architectural styles and the design of network-based software architectures. *UCI Donald Bren School of Information & Computer Sciences*, 2000.
- [6] D. Guinard, V. Trifa, S. Karnouskos, P. Spiess, and D. Savio. Interacting with the soa-based internet of things: Discovery, query, selection, and on-demand provisioning of web services. *IEEE transactions on services computing*, 3(3):223–235, 2010.
- [7] B. Jin. *Designing Web APIs : building APIs that developers love*. O’Reilly, Beijing, 1st edition. edition, 2018.
- [8] C. Kamienski, R. Prati, J. Kleinschmidt, and J. Soininen. Designing an open iot ecosystem. Belem, Brazil, 2019.
- [9] I. Plauska, A. Liutkevičius, and A. Janavičiūtė. Performance evaluation of c/c++, micropython, rust and tinygo programming languages on esp32 microcontroller. *Electronics (Basel)*, 12(1):143, 2023.
- [10] P. Sethi and S. R. Sarangi. Internet of things: Architectures, protocols, and applications. *Journal of electrical and computer engineering*, 2017:1–25, 2017.
- [11] M. Team. A proactive approach to more secure code. *MSRC Blog / Microsoft Security Response Center*, Jul 2019.
- [12] J. Zhang, M. Ma, P. Wang, and X. dong Sun. Middleware for the internet of things: A survey on requirements, enabling technologies, and solutions. *Journal of Systems Architecture*, 117:102098, 2021.

ask about
SOA
source
book cita-
tion

A Original Project Proposal

Put a copy of your proposal here

B Another Appendix Chapter

This could be about your experiments