Exercise 12

Elisa Schöpf, Leon Krieger, Nikola Adzic

June 11, 2026

Contents

1 Setup and Basic Execution **1**

2 Profiling **1**

3 Code Understanding **2**

4 Optimization **2**

1 Setup and Basic Execution

LCC3 fib.lua results:

```
100 x fibonacci_naive(30)     time:  13.7866 s  --  832040
10000000 x fibonacci_tail(30) time:  15.8393 s  --  832040
25000000 x fibonacci_iter(30) time:  12.2847 s  --  832040
```

The median of averages from 20 runs was 13.7609 s

2 Profiling

Initially, only the benchmark was profiled using profile.lua (`https://github.com/2dengine/profile.lua`). This however only shows a profile of the functions, making it unusable for optimizations on the lua interpreter itself.
After that, `perf` was used. The results were more informative:

```
[...]
# Samples: 116K of event 'cycles:u'
# Event count (approx.): 114068069768
#
# Children      Self  Command  Shared Object     Symbol
# ........  ........  .......  .................  ......................
#
    79.12%    78.18%  lua      lua               [.] luaV_execute
            |
            |--14.88%--0
            |          |
            |           --14.61%--luaV_execute
            |
            |--7.37%--0x281c900060080
            |          luaV_execute
[...]
```

Additionally, manual counting of OPs was included to see, which OPs were called the most:

```
--- Opcode Statistics ---
EQI             : 310000031
LTI             : 271946237
GETTABUP        : 135973068
ADD             : 135973068
MOVE            : 35000103
LOADI           : 25000001
CLOSURE         : 10000001
VARARGPREP      : 4
SETTABUP        : 3
--------------------------
```

3 Code Understanding

There are two major phases in the Lua interpreter, script compilation and script execution. The interpreter first goes through the program code to convert it into Lua bytecode instructions. This bytecode is then executed by Lua's virtual machine. The majority of it is handled by the `luaV_execute` function. This function consists of a large switch statement which checks against different OP_IDs to determine what to do.

The compile time was measured by using `luac`, which only compiles the program and doesn't execute it. This pre-compiled bytecode was then used to measure the execution time. We can clearly see that the compilation time for the benchmark is minuscule compared to the execution time.

```
Compilation Median:     00.0083 sec
Execution Median:       37.4024 sec
```

As seen on the `perf` report, the interpreter spends a lot of time in `luaV_execute`. As expected, this takes a lot of time and is inefficient.
`LUA_USE_JUMPTABLE` helps with that by enabling direct-threaded dispatch in the virtual machine using GCC/Clang computed gotos. This replaces the large switch statement, thus increasing performance. The jumptable only works with gcc/clang and is turned automatically on when compiled with either of those. It can be turned off by passing `-DLUA_USE_JUMPTABLE=0` to the compiler.

```
 Function                        :  With      :  Without   :  Speedup :
100 x fibonacci_naive(30)        :  13.7866 s :  13.8432 s :  x 1.004 :
10000000 x fibonacci_tail(30)    :  15.8393 s :  19.2325 s :  x 1.214 :
25000000 x fibonacci_iter(30)    :  12.2847 s :  14.7320 s :  x 1.199 :
Median of averages               :  13.7609 s :  14.7412 s :  x 1.071 :
```

The speedup column reveals how much faster the program is executed when gotos are utilized. The performance gains do differ across different implementations. The recursive implementation `fibonacci_naive` shows barley any improvement, most likely due the overhead of the function constantly calling itself and managing those recursive layers. Both the tail-recursive and iterative implementations see a speedup of $\sim$20%. They spend most of their time executing the same small sequence of operations over and over again, which the jumptable improves.

4 Optimization

Applying heuristics to OP_ADD resulted in 1.4% performance increase Using all optimizations above and -fprofile-generate + -fprofile-use resulted in 9.6% performance increase