A PRECISION-FIRST METHOD FOR GETTING REAL RESULTS FROM AI

# The Exact Method

*A complete system for getting AI to do what you need: prompting, tool selection, chaining, verification, and real applied work. Written October 2026.*

---

*This isn't a collection of prompts to copy. It's the underlying method, explained once, so it still works on a problem nobody wrote an example for.*

CONTENTS


· Introduction

*01* The Mindset Shift

*02* Precision Prompting

*03* Tool Selection

*04* Chaining AI Tools

*05* Verifying What AI Tells You

*06* Applied Examples

*07* Making Videos With Claude

*08* Connecting Claude to Your Apps

· Sources and Where to Check

# Introduction

Most of what's sold online as "AI mastery" falls into one of two traps. Either it promises you'll make thousands of dollars within days of buying, which almost never happens and usually isn't even possible, or it teaches you "prompts" without teaching you *why* those prompts work, which means the moment your situation is slightly different from the example, you're stuck again.

This guide does neither. It won't promise you a result by a certain date, because nobody honestly can. What it will do is hand you a method, worked out on real projects and not just theorized, for getting AI to do what you need, whether that's writing code, building a Pinterest presence, designing something that doesn't scream "made by AI," writing copy, or running a product search. The method is the same every time. Only the application changes.

If you follow this and still don't get a result, that's useful information too; it means something in your specific situation needs adjusting, not that the method is a lie. That's the honest version of this, and it's the only version worth trusting.

# *01* The Mindset Shift

Think back to the last time you asked an AI tool for something and the answer came back... fine. Not wrong, not useless, just not quite it. Maybe you asked for a caption and got something generic. Maybe you asked for code and it technically ran but wasn't what you pictured. Maybe you asked for advice and got something you could've found in the first Google result.

What did you do next? If you're like almost everyone, you did one of two things. Either you gave up and used the mediocre answer anyway, or you tried again with a longer prompt, more words, more "please make it better," more explaining. And maybe that helped a little. But chances are, the second answer still wasn't quite right either, and you were left with that nagging feeling that you were just... bad at this. That AI is this powerful thing everyone talks about, and somehow you're not getting the magic everyone else seems to be getting.

Here's the thing: you weren't bad at it. You were using the wrong lever.

Let's slow down and look at what happened in that moment. When you wrote a longer, more detailed prompt the second time, what you were really doing was putting in more *effort*. More typing, more explaining, more trying. That instinct, that "if it's not working, push harder," is one of the most deeply trained habits humans have, because it works in a lot of areas of life. Studying longer gets you a better grade. Practicing more gets you better at a sport. Working more hours gets a project done faster. Effort and result are linked almost everywhere you look.

But there's a second, much rarer way to get a better result, and it has nothing to do with effort at all. It's understanding what's going on underneath the thing you're trying to do.

Here's an example, away from AI entirely, that makes this easy to feel. Picture two students preparing for a math test. One of them studies by going through every single practice problem in the textbook, one at a time, memorizing how each one is solved. That takes hours and hours. The other student doesn't touch the practice problems much at all. Instead, they spend their time making sure they understand the underlying rule, the principle, that every one of those problems is built on. When the test comes, the first student freezes the moment a problem looks even slightly different from the ones they memorized, because they never understood the "why," only the "what." The second student, the one who understood the principle, can solve a problem they've never seen before, because they're not recalling an answer. They're applying a rule that works on anything built from it.

That second student isn't smarter. They didn't work harder, either; if anything, they worked less. They just aimed their effort at a different target: understanding, instead of memorizing.

This is the exact same shift that makes the difference with AI. The instinct to write a longer, more effortful prompt is aiming at the wrong target. It's the "memorize every practice problem" approach. What works is understanding what's really being asked of the AI, what information it's missing, what's true about the task you're handing it, before you type a single word. Once you understand that, the prompt almost writes itself, because you're not guessing anymore. You're specifying.

Every method in the rest of this guide comes back to this one idea. Not "try harder." Understand the principle, once, and apply it to anything built on it, the same way a real understanding of math lets you solve a problem you've never seen before.

# *02* Precision Prompting

## Part A: Finding the Idea (The Narrowing Method)

Let's start with a scenario that has nothing to do with AI at all.

Imagine you stop a random stranger on the street and ask them: "What's a good business idea?"

What happens? At best, you get something generic. "Maybe try dropshipping." "Have you thought about freelancing?" Answers that could apply to literally anyone, because the stranger knows nothing about you. They don't know what you're good at. They don't know how much time you have. They don't know what you've already tried and failed at. They don't know your budget. With zero information to work from, the only kind of answer they *can* give you is a generic one, because a specific, useful answer requires specific information that they simply don't have.

Now imagine instead that you ask the exact same question to a close friend who knows what they're talking about in business. What do they do? They almost never just answer immediately. They ask you questions first. "What are you actually good at?" "How many hours a week can you realistically put into this?" "Have you tried anything like this before, and what happened?" "What's your budget to get started?" Only after they've gathered that information do they give you advice, and when they do, it's specific to you. It accounts for your actual situation. It's useful in a way the stranger's answer never could be, because your friend built their answer from real context instead of guessing.

Here's the part that's easy to miss: AI works exactly like the stranger on the street, by default. When you type "give me the best ways to make money online" into an AI tool, you are the random stranger, and the AI has nothing to work with except those few words. It doesn't know your skills. It doesn't know your time. It doesn't know what you've already tried. So, just like the stranger, it gives you something generic. Not because the AI is bad, and not because you did anything wrong, exactly, but because you asked a question that does not contain enough information to produce a specific, useful answer. No amount of "please be more specific" tacked onto that same vague question will fix it, because the problem isn't your tone, it's the missing information.

So here's the actual fix, and it's simpler than it might sound: instead of expecting one perfect question to produce the final answer, treat the whole process like a conversation that gets narrower every time you speak. You start broad on purpose. Then you take whatever the AI gave you, and you use it to ask a second, more specific question. Then maybe a third, narrower still. Each question adds real information the AI didn't have before, the same way your friend's questions did, except here, you're the one asking the AI the first broad question, and then narrowing based on what comes back.

Let's walk through exactly how this worked in a real case, step by step, with the actual kind of prompts used, so there's no ambiguity about what this looks like in practice. One setting matters before you start: the word "research" in these prompts only means research if the tool can look things up. Turn on web search, or the tool's deep research mode, before you send them. With search off, the AI answers from memory, and a shortlist from memory is a guess dressed up as research (Chapter 5 explains why).

Step one. The very first prompt wasn't "give me a business idea." It was something closer to: *"Research beginner-friendly ways to make money on Pinterest."* Notice this is still somewhat broad, deliberately. The point of this first prompt isn't to get the final answer. It's to generate a shortlist of real, researched options worth looking into further. This produced a list of seven or eight different methods, things like affiliate marketing, selling digital products, driving traffic to a blog, and a few others, each with a brief description.

Step two. None of those seven or eight methods were detailed enough to act on yet. So the next prompt took that exact list and narrowed it: *"Research each of these methods individually, and tell me which two are the most effective."* This is a completely different kind of question than the first one. The AI isn't guessing anymore. It's working from real information it gathered in step one, and it's being asked something much more specific: not "what should I do," but "which of these specific options, that you yourself just researched, holds up."

That second prompt is what produced something usable, a narrowed-down, researched answer specific enough to build a real decision on. The budget-organizer product mentioned earlier in this guide, and the Pinterest niche it was built around, both came directly out of this exact two-step process.

Notice what each step contributed, because this is the part worth really sitting with. The first prompt's job was never to be the final answer. Its job was to generate real material, a researched shortlist, for the second prompt to narrow down. If you'd skipped straight to "give me the two best ways to make money on Pinterest" without that first broad step, there would have been no shortlist for the AI to narrow from, and you'd be back to the stranger-on-the-street problem: a generic-sounding answer that only looks specific.

The rule, in its simplest form: if the question you're about to ask is something a knowledgeable friend would need to ask you two or three follow-up questions before they could answer well, don't ask AI that question directly. Narrow first. Ask the broad version, use what comes back to ask a narrower version, and keep going until what you're holding is something specific enough to act on.

## Part B: Executing the Idea (The One-Action-Per-Step Method)

Once you know *what* you're building, a second, completely different problem shows up, and it's worth understanding this one from scratch too, because the fix for it is not the narrowing method from Part A. It's something else entirely.

Imagine you're training a brand-new employee on their very first day, and you want them to reorganize a messy stockroom. You could say: "Go organize the stockroom." What happens? They'll do *something*, because they have to do something, but it almost certainly won't match what you had in your head. Maybe they organize by size when you wanted it by category. Maybe they throw out things you wanted kept. Maybe they spend four hours on a section you didn't even care about and ignore the one that mattered. None of this is because the new employee is incompetent. It's because you left a hundred small decisions open, and every single one of those gaps got filled in by *their* best guess, not yours.

Now imagine instead you'd said: "Step one, take every box off the bottom shelf and put it on the floor in the middle of the room. Step two, sort those boxes into three piles: electronics, cables, and everything else. Step three, put the electronics pile back on the bottom shelf, left to right, largest to smallest." There's no guessing left. Every single instruction is one, and only one, concrete action. The new employee isn't making decisions anymore. They're executing yours.

This is exactly, precisely what happens when you ask AI to build something complex, like an app or a piece of code, in one broad prompt. "Build me an app that does X, Y, and Z" sounds like a complete instruction, but it's closer to "go organize the stockroom." It leaves an enormous number of small decisions open: what order should things happen in, what should it look like, how should edge cases be handled, what's the priority if two things conflict. The AI *has* to fill every one of those gaps with its own best guess, because you didn't specify, and the more gaps you leave, the further the result can drift from what you pictured.

The fix is a two-stage process, and the rule that makes the whole thing work is this: **every single step must contain exactly one action.** Not "step one: set up the database and add the user model." That's two actions wearing a single step's clothing, and it leaves the AI to decide how and when to sequence them. It has to be: "step one: create the database." Then, separately: "step two: add the User model." One action. One step. Nothing left for the AI to decide about ordering, scope, or sequencing.

Here is the full two-stage process, in order, with exactly what you'd type at each stage.

Stage one: get the plan. First, explain what you want built, in as much real detail as you have. Then, explicitly ask for a step-by-step guide where every step is one action: something like, *"Turn this into a step-by-step guide to build it. Every step must contain exactly one action. If a step would require doing two things, split it into two separate steps."* The AI will hand back a guide. Read through it. If you spot any step that secretly contains two actions, that's the moment to catch it, before moving on.

Stage two: convert the plan into an execution prompt. Take that finished guide and ask the AI to turn it into a prompt for whatever tool will build it, for example a coding agent: *"Turn this guide into a detailed prompt for an AI coding agent to execute. Keep every step as exactly one action."* What comes out the other end is a prompt so specific that the execution tool isn't creatively interpreting anything anymore. It's just following instructions, one at a time, in order, the same way the trained employee in the stockroom example was just following yours.

Why split this into two separate tools and two separate stages, instead of asking one AI to plan and build in the same breath? Because planning and executing are different skills, and most AI tools are noticeably better at one than the other. A tool built specifically for executing code is usually not built to do open-ended research and planning well. A tool built for reasoning and planning is usually not built to reliably execute code. Asking one tool to be excellent at both, in a single conversation, usually gets you a worse result on both halves than splitting the work between a planner and an executor and letting each one do what it's built for.

There is one more simple way to remove guesswork that the methods above do not cover: show the AI a sample. If you want product descriptions in a certain style, do not only describe the style. Paste two or three descriptions you like and say, "Write the new one in the same style as these examples." Anthropic's own prompting guide recommends three to five examples. It says they work best when they are relevant to your task, different enough from each other that the AI does not copy one pattern, and clearly separated from the rest of your prompt, for example by labelling each one "Example 1," "Example 2," and so on. Two things to add. Say what the examples are for: "These show the tone and length I want, not the content to repeat." And change the examples when your task changes, because an example that is too close to the new job will get copied almost word for word.

## Part C: When You Don't Know What to Narrow (Let AI Interview You)

Part A's narrowing method assumes something important: that you, the one doing the narrowing, know which details matter. Most of the time that's true. You know your budget, your time, your skill level, even if nobody's asked you yet. But every so often you run into a question where you don't know what information would change the answer, because the topic is unfamiliar enough that you can't tell which of your own details are even relevant. You know *what* you want. You don't know which five facts about your situation would shape a good answer to it.

There's a simple fix for exactly this gap, and it's really just the narrowing method run in reverse. Instead of you guessing what context the AI needs and trying to supply it all up front, you hand that job to the AI itself. You tell it, directly, not to answer yet. Tell it to ask you whatever questions it needs answered first, in order to give you a specific, well-reasoned response instead of a generic one, and to hold off on the actual answer until it has what it needs.

This works for a specific, mechanical reason, not because it's a clever trick. A model has absorbed an enormous number of examples of what a good advisor, consultant, or expert typically asks before giving advice in a given domain, because that pattern shows up constantly in whatever it was trained on. So even when you can't articulate which of your own details matter, the AI very often can, because it's seen the shape of "here's what a knowledgeable person would ask before answering this kind of question" thousands of times before, across thousands of different domains. You're not asking it to read your mind. You're asking it to apply a pattern it already has a strong model of.

Here's what that looks like in practice, worked through on a concrete example: someone trying to figure out how to price their freelance services for the first time. Asked directly, "how much should I charge," an AI has almost nothing to work with and will hand back a generic range pulled from nowhere in particular. Instead, the better opening move is something like: *"I'm trying to figure out how to price my freelance work and I'm not sure what matters here. Before you answer, ask me whatever questions you need to give me a specific answer instead of a generic range. Ask one at a time, and wait for my answer before asking the next."* What typically comes back isn't a price. It's a first question, maybe about the specific service being offered. The answer to that shapes the second question, maybe about experience level or existing portfolio. The third might ask about the local or online market being sold into. By the fourth or fifth answer, the AI has assembled exactly the kind of context a real, knowledgeable friend would have gathered before giving an opinion, except none of it had to be identified in advance by the person asking.

That one-at-a-time detail is worth taking seriously rather than treating as a minor style choice. Asking for every question in one single batch is faster, but each question is written without knowing any of the other answers, so they can't build on each other. Asking one at a time lets each new question respond to what was just said, the same way a real conversation with a person works, and it's what makes the later questions get noticeably sharper and more specific than the first one.

It's worth naming plainly what this is, since it's easy to miss: this is Part A's narrowing method, just pointed in the opposite direction. In Part A, you ask progressively narrower questions of the AI. Here, the AI asks progressively narrower questions of you. Same underlying principle in both directions: a specific answer requires specific information, and somebody has to go get that information before a good answer is possible. Part A hands that job to you. Part C hands it to the AI, for exactly the situations where you're not equipped to do it yourself.

Two things worth watching for when you use this. First, a model will sometimes try to wrap up and give you an answer before it's gathered enough, especially after just one or two questions. If the answer that follows still feels like it could apply to several different people in your position, that's the signal to push back directly: tell it plainly that it doesn't have enough yet, and ask it to keep going. Second, not every question it asks will be a good one. Treat a weak or irrelevant question the way you'd treat one from a human consultant who misread your situation: answer it briefly if you have to, but feel free to say so and redirect if it's clearly off track. The method hands the AI the job of finding out what it doesn't know. It doesn't hand it infallibility.

## Part D: Strengthening a Single Answer (Show the Work, Then Check It Twice)

Parts A through C are all about the same first half of the problem: getting the AI to the point where it has the right information in front of it before it answers. Part D is about the other half, the part that still trips people up even after the information is right: once the AI has what it needs, how do you get it to reason through that information correctly, instead of pattern-matching its way to a confident-sounding answer that skips the real logic? This matters most for one specific kind of question: one with a checkable right answer, a calculation, a yes-or-no judgment call based on evidence, a multi-step comparison, a piece of logic with a correct conclusion. It matters far less for open-ended writing or creative work, where there usually isn't a single "correct" output to converge on.

Picture a math teacher who requires students to show their work, not just write down the final number. Two students can both write "42" as an answer. One of them worked through the problem step by step and arrived there legitimately. The other pattern-matched from a similar-looking problem, skipped the real logic, and got lucky, or didn't, with no way to tell which from the final number alone. The teacher who demands the work isn't being difficult. They know that a process you can inspect catches errors a bare final answer hides completely, and that forcing the steps to be written out in the first place often catches the mistake *before* it reaches the final line, not just after.

Layer one: make it show the work. The practical version of this, for AI, is almost embarrassingly simple: explicitly tell it to reason through the problem step by step before giving you the final answer, rather than jumping straight to a conclusion. This is a specific instruction, not a vague "be thorough", and the measured results are dramatic enough to be worth knowing precisely rather than taking on faith. Researchers at the University of Tokyo (Kojima and colleagues, 2022) measured this directly on GPT-3-class models: on a set of grade-school arithmetic word problems called MultiArith, accuracy went from 17.7 percent with a direct answer to 78.7 percent when the model was told to reason step by step first, before answering. On GSM8K, a harder set of grade-school math problems, it went from 10.4 percent to 40.7 percent. That's not a marginal tweak, that's the difference between mostly wrong and mostly right, from adding one instruction. Here is why the jump was that dramatic on those specific 2022-era models, and what that means for using this today: those models had no real built-in habit of reasoning before answering, so the instruction was supplying something that was almost entirely missing. Current frontier models already reason step by step far more by default than that generation did, so the size of the jump you'll see today is smaller. The instruction is still free, still real, and still worth giving explicitly rather than assuming it's happening automatically, but expect a genuine improvement, not a repeat of a five-times accuracy jump. Testing whether it still moves the needle on whichever specific model you're using, rather than assuming 2022's numbers still hold today, is the Re-Evaluation Method from Chapter 3, applied here instead of to tool selection.

Layer two: don't trust one attempt, trust agreement. The second layer builds directly on top of the first, rather than replacing it, and it comes from a related but separate piece of research. Picture a jury instead of a single judge. One person's verdict, reached alone, can be wrong for all sorts of reasons: a detail they missed, a bias they didn't notice in themselves, a plausible-sounding but incorrect chain of reasoning they talked themselves into. Twelve people independently reaching the same verdict, having reasoned through the same evidence separately rather than discussing it together first, is a meaningfully stronger signal, not because any one juror is smarter than the others, but because an error specific to one person's reasoning is unlikely to be the exact same error twelve separate people all make independently. Researchers at Google (Wang and colleagues) formalized this for AI reasoning under the name self-consistency: instead of accepting one step-by-step answer, generate several of them independently, using the same step-by-step approach from layer one, and then take whichever final answer shows up most often, rather than whichever one arrived first. On the same kind of grade-school math problems, this measurably beat single-attempt step-by-step reasoning by 17.9 percentage points. On a separate algebra word-problem set, it beat it by 12.2 points, and on a set of science and commonsense reasoning questions, by 6.4 points. Smaller gains than layer one's, but a real, separate improvement stacked on top of it, not a repeat of the same effect.

The practical version of this, without needing any special settings most people don't have access to: for a question with a real right answer that matters to get correct, don't settle for the first response. Open a fresh conversation, or ask for the problem to be solved again from scratch, two or three separate times, each one reasoning through it step by step independently rather than being shown the previous attempt. If the answers agree, that agreement is real information, closer to the twelve-juror verdict than the one-judge opinion. If they don't agree, that disagreement is just as valuable: it's telling you the question is harder, more ambiguous, or more poorly specified than it looked, and it's exactly the kind of signal that should trigger the verification habit from Chapter 5, rather than just picking whichever answer sounds most confident. Asking for "three different approaches" inside a single reply isn't the same thing and shouldn't be mistaken for it: an AI writing out three alternatives back to back in one response tends to let each one lean on what it just wrote, rather than reasoning through the problem fresh each time, the way separate attempts do.

Know where this layer doesn't apply, the same way it mattered to know where the narrowing method and the interview method don't apply. This is specifically a tool for questions with a checkable answer. Running the same creative writing prompt five times and picking whichever version showed up most often is a meaningless exercise, because there's no single correct caption or headline for five independent attempts to converge on. Save this one for the moments where being right has a right answer to be.

## The Staged Prompting Rule

There's one more layer here, and it's easy to miss because it applies to the prompts themselves, not just to the final guide they produce. The same "one action at a time" discipline that governs the final step-by-step guide should also govern the sequence of prompts you use to get there. Don't ask for everything in one shot. Stage it.

Here's exactly how that worked on a real, tested task: designing a Pinterest pin graphic to promote an Amazon affiliate product, for a complete beginner.

The first prompt asked only for the foundation, nothing else: *"Research the Pinterest algorithm and SEO, and build the most effective design approach based on that research."* Notice what's deliberately missing from this prompt: nothing about making it look professional, nothing about avoiding an AI-made look, nothing about the final design itself. Just the research foundation. This produced specific findings: pins perform best in a 2:3 vertical ratio, Pinterest's algorithm reads both the text overlay and the actual visual content of the image, and real keyword research, using terms people search for on Pinterest, needs to happen before any design decisions get made.

The second prompt was kept completely separate on purpose: *"Research what makes a design look obviously AI-generated, and identify how to avoid those issues in this one."* This is a different research task entirely. It surfaced a different list of findings: warped or distorted background elements, unnaturally perfect symmetry, inconsistent shadows and lighting between elements in the same image, and overly smooth, "plastic-looking" textures. None of this showed up in the first prompt, and it shouldn't have, because combining "make it effective" and "make it not look fake" into a single request makes it dangerously easy for the AI to address one of those goals and quietly ignore the other.

Only after both of those research passes were complete did the third prompt ask for the final execution guide, using the exact same one-action-per-step format from Part B: *"Turn this into a step-by-step guide to build the design, incorporating both the Pinterest research and the anti-AI-look findings. Every step must be exactly one action."* What came back was specific and usable: set the canvas to a 2:3 ratio, anchor the design around one product photo, and add a text overlay containing the researched keyword phrase. Then check the overlay for distortion, the background for warping, and the lighting for consistency across every element. Only then finalize the title and description using that same keyword.

Look closely at what each of the three separate prompts contributed, because none of them were replaceable by the others. The first prompt grounded the entire design in real platform behavior instead of guesswork, so the result was a pin built to perform on Pinterest specifically, not just a nice-looking one. The second prompt caught a category of problem that would have gone completely unnoticed if it had been folded into the first request, because "effective" and "doesn't look AI-made" are two different questions that deserve two different research passes. The third prompt is what turned both of those research passes into something that could be built, one concrete action at a time, with nothing left for the AI to guess about.

A named, tested version of this same shape: step-back prompting. Staging broad before narrow across separate topics, platform research, then anti-AI-look research, then execution, is one way to apply this rule. There's a second, narrower version worth knowing specifically, because it's been formally tested with real numbers behind it rather than just argued for. Researchers at Google DeepMind (Zheng and colleagues, 2023) found that before asking a specific, detailed question, asking the general version of that exact same question first, and letting the AI answer that first, measurably improves the specific answer that follows. It's a subtly different move than the Pinterest example above: that example staged two different research topics before execution; step-back prompting stages one single topic, general then specific, before answering it at all. If you wanted to know whether a particular dropshipping product was worth committing budget to, the step-back version wouldn't start with the narrow question. It would first ask something like what generally makes a product succeed in that category, and only then ask about the specific product, so the specific answer gets built on top of real context instead of being evaluated in isolation. Tested against standard prompting on a large language model, this produced 27 percent better results on a question set about facts that change over time (TimeQA), and 7 and 11 percentage points better results on physics and chemistry questions (MMLU), compared with the same model answering directly. It didn't help everywhere, though, since the same research found close to no benefit, and occasionally a small loss, on simple factual questions or ones that were already general to begin with: this is specifically a tool for multi-step reasoning, not something to bolt onto every single prompt regardless of what it's asking.

That's precision prompting, in full, with nothing left unexplained: narrow before you ask anything broad, keep every prompt focused on one job instead of several, and convert the final result into steps so specific that executing them requires zero decisions, only actions.

# *03* Tool Selection

Before we get into the actual list of tools, here is what kind of chapter this is, because it's different from the last one.

Chapters 1 and 2 taught you a way of thinking, a method. That kind of thing doesn't expire. The principle behind understanding math instead of memorizing it was just as true twenty years ago as it is today, and it'll still be true twenty years from now. This chapter is the opposite. It's a snapshot of which specific tools are good at which specific things, right now, and tools change constantly. A plugin that's essential today might be outdated in six months. A model that's weak at something today might be the best option at it next year. So this chapter has two jobs: first, to hand you the current picture; and second, to teach you how to keep that picture updated yourself, because the method for figuring out "what's good right now" doesn't expire, even though the specific answer does.

Here's a story that makes the "don't get attached to what's best right now" point better than any abstract advice could. When ChatGPT first came out, it was the only real conversation in the room. There was no serious competitor. Then Gemini was released, and within a surprisingly short window, it had taken over a huge chunk of that conversation. It wasn't a close fight or a gradual shift. It happened fast. The lesson here isn't "Gemini is better than ChatGPT" or vice versa, because that'll be a different answer by the time you're reading this anyway. The lesson is: whichever tool feels like the obvious default today got that position by replacing something that used to feel just as permanent. Google, for context, is one of the two or three richest companies on earth. Never assume any current leader is locked in, and never assume any current also-ran is out of the race for good.

With that mindset in place, here's the field as it stands, broken into sections: the base models themselves, their built-in "custom assistant" features, the ways to save your own instructions and notes so any of them can use them, coding-specific tools and plugins, and tools for e-commerce and content work specifically.

## The Three Main Models

**ChatGPT.** Strong, general-purpose, and currently considered the strongest option specifically for image generation among the major paid tools. It also has the deepest plugin and connector ecosystem of the three, which we'll get into below. Beyond that general reputation, a handful of specific, distinctive features are worth knowing about individually, because each one solves a different problem. **Projects** give you an isolated workspace, its own instructions, its own uploaded files, its own memory, so working on several unrelated things at once doesn't bleed context between them; best field of use is anyone juggling multiple separate clients or topics who doesn't want one conversation's details leaking into another. **Memory** quietly stores your preferences and past decisions and pulls them back up automatically in new chats, which is most valuable for recurring work where you'd otherwise have to re-explain your situation, your niche, your tone, every single time. **Deep Research** is a different mode, not just a longer answer. It runs a multi-step investigation, issuing a sequence of its own searches, reading what it finds, and returning a structured, cited report, which takes anywhere from five to thirty minutes rather than seconds. Best field of use: the broad, first-stage research pass from Chapter 2's narrowing method, when you need depth before narrowing down. The output should still go through the verification habits in Chapter 5 and not be trusted outright. **Agent mode** lets ChatGPT operate a browser or desktop on its own, clicking, filling in forms, pulling data, and OpenAI reports strong results for it on standard benchmarks for computer-operating tasks; best field of use is repetitive, multi-step data-entry or research-gathering tasks, with a human still watching anything that touches money or sends something irreversible. Turning on web browsing also matters for accuracy. OpenAI's GPT-5 system card reports that, with browsing on, about 9.6 percent of the claims in the main GPT-5 model's answers contained an error (4.5 percent for its thinking model), against 12.9 percent for GPT-4o. On SimpleQA, a hard trivia test run without browsing, the hallucination rate was 47 percent. Those are different tests, so don't read them as a before and after. The practical lesson stands: for anything where being factually right matters, make sure browsing is on instead of trusting the model's built-in knowledge.

**Gemini.** Its free tier is excellent, strong enough that plenty of people use it as their primary tool without ever paying for anything, and that free tier isn't a stripped-down demo either, it includes real voice conversation, image generation, and even a version of its deep-research mode at no cost. Beyond the free tier, Gemini has a few specific strengths worth calling out individually. Its **context window**, the amount of text and material it can hold in one conversation, is large enough to take in roughly 1,500 pages of material in a single sitting. That matters directly for Chapter 2's narrowing method: an entire codebase, every page of a long contract, or weeks of notes can go in at once instead of being split into chunks that lose track of each other. A higher-effort reasoning mode exists specifically for hard mathematical and scientific problems that benefit from exploring several possible approaches before settling on one, which is overkill for everyday tasks but useful when a problem has that kind of real complexity. Its **Google Workspace integration** is a real, practical strength, not just a nice-to-have: because it sits inside Gmail, Docs, Sheets, and Calendar natively, it can do things like find a specific email from weeks ago and schedule a meeting about it in the same request, which no competitor can currently match simply because they don't have access to those apps. But it has a specific, confirmed flaw worth knowing before you build a workflow around it: when you're using its image generator inside an ongoing chat, it does not reliably carry instructions forward the way normal conversation does. Tell it "from now on, every image needs this specific detail," and it will say "understood," but the very next image you ask it to generate often won't include that detail, because image generation runs more like a fresh request each time than like the rest of the conversation. This is a documented, reported pattern, distinct from how Gemini handles regular text memory. The practical fix, and this is worth doing rather than just reading: reattach your full styling instructions to every single image-generation prompt, every time, instead of assuming it remembers the one you gave it three messages ago.

There's a second lesson buried in that same discovery, and it's worth pulling out on its own, because it applies far beyond Gemini. If you ask a tool directly whether it has a certain limitation, its answer is a real, useful data point, but it is not the final word. A tool's self-report about its own capabilities can be wrong, outdated, or incomplete. Always check a tool's claim about itself against an outside source before you build a whole process around it. That habit will save you from believing something confidently wrong.

**Claude.** Capable and strong, especially for writing, research, and longer documents, but it has a well-documented tendency to be overly agreeable, often described as being a "yes-man." Ask it "is this a good idea?" and it will frequently find a way to say yes and explain why, even when a more critical answer would serve you better. Anthropic itself studies this flaw, and a lot of regular users bring it up. The fix isn't a plugin you install, it's a specific kind of instruction: tell it directly to argue against your idea first, or to list every real risk before giving an opinion, before it's allowed to agree with you. You can also sidestep the problem entirely for certain tasks by routing the actual judgment call through a different model instead, which is exactly what Chapter 4 covers in detail. Where Claude pulls ahead, beyond the general "good writer" reputation, is in holding a large, messy body of material in mind at once and reasoning about how its parts affect each other. Its large context window is built to hold a sizeable existing codebase, a long technical specification, or a stack of related documents in a single conversation, without losing track of earlier material as the conversation grows. This shows up concretely in two related strengths. First, genuine refactoring and architecture work, understanding not just how to write a new piece of code but how a change to one part of an existing system will cascade into every other part that depends on it, which is the harder and more valuable half of real software work. Second, diagnostic reasoning before execution, producing an actual plan, what will change, what could realistically break, where an existing design has already backed itself into a corner, rather than jumping straight to writing code and hoping it holds up. Best field of use: any task that starts from a large, already-existing body of material, a real codebase, a dense specification combining technical requirements with business decisions, a long research document, rather than a short, self-contained request with no real history behind it.

## Beyond the Big Three: Perplexity, Grok, and DeepSeek

ChatGPT, Gemini, and Claude get most of the attention, but they're not the only tools worth having in rotation, and three others are worth knowing specifically, each for a different reason rather than as a weaker backup to the big three.

**Perplexity** isn't really a chatbot in the same sense as the other three, it's built around being a research and search tool first. Every answer comes with numbered citations tied directly to specific claims, so instead of trusting a confident-sounding paragraph, you can click straight through to the actual source it came from, which connects directly to Chapter 5's verification method: a tool that shows its sources by default makes the "check" step faster and easier than a tool that doesn't. It also has a feature called Spaces, which keeps the questions, findings, and files for one ongoing research project grouped together instead of scattered across separate, disconnected chats. Pro-tier accounts can also switch which underlying model answers a question, choosing between several different ones depending on the task, rather than being locked into one. Best field of use: any research-heavy step in the narrowing method from Chapter 2, especially the first, broad research pass, where having an instantly checkable source for each claim matters more than a creative or conversational answer.

**Grok**, built by xAI, has one unique capability none of the other major tools can match: live, native access to real-time posts on X (formerly Twitter), which means it can be asked what's being said or trending on that platform right now, not what was true as of its last training update. It also currently supports an unusually large context window, letting it take in an especially large volume of documents or conversation in one sitting. Best field of use: anything that depends on knowing what's happening on social media right now rather than in general, real-time trend-spotting for content and affiliate marketing, gauging live public reaction to something, or research that specifically needs current social sentiment rather than historical consensus, which ties directly into the product-research and content-ideation steps covered in Chapter 6.

**DeepSeek** takes a completely different angle from the other tools on this list: it's built to deliver strong, capable reasoning, particularly on math, logic, and technical or coding problems, at a dramatically lower cost than the premium tools, and it regularly makes its underlying models available for anyone to inspect or even run themselves, rather than keeping everything closed. It's noticeably less suited to creative writing, marketing copy, or anything that benefits from a warmer, more conversational tone, it's built for precision over personality. Best field of use: technical, logic-heavy, or coding-adjacent tasks for anyone who is cost-conscious, especially relevant given how expensive the premium tiers of the major tools can get, a strong option rather than a compromise.

## Custom Assistants: Gems, Custom GPTs, and Projects

All three major tools let you build a saved, reusable version of themselves tuned to a specific job, so you're not re-explaining your situation every single time you open a new chat. They're not the same feature wearing different names, though. Each one is better suited to a different kind of use.

**Gemini Gems** are free, even on Gemini's free tier, and they live directly inside the Google apps you probably already use: Gmail, Docs, Sheets, Slides. Best field of use: if your workflow already happens inside Google's ecosystem, like managing a spreadsheet of product research or drafting emails to suppliers, a Gem tuned to that exact task saves you from re-explaining your setup every time, for free.

**ChatGPT Custom GPTs** are the only one of the three with a real public marketplace attached, the GPT Store, where other people's custom assistants are searchable and some creators even earn money from usage. Best field of use: if you want to either use a specialized assistant someone else already built and refined for a specific, common task, or eventually build and share your own, Custom GPTs are the only option of the three built for that kind of public discovery.

**Claude Projects (and Skills)** are built around holding a large amount of context and documents over a long period, and for staying consistent across a drawn-out piece of work rather than a single quick task. Best field of use: a long-running piece of writing, a research project with a lot of source material, or any workflow where you're coming back to the same body of context over and over across many sessions, rather than a one-off quick question.

## Making AI Write Like a Person

Everything so far has been about getting AI to give you the right answer. This section is about how that answer sounds, which matters the moment the text goes out under your name: an email to a client, a caption, a product description, a piece of freelance copy.

AI writing has a recognizable sound, and most readers pick it up faster than they can explain it. Chapter 6 covers what that costs a brand in trust. The cause is a handful of habits that repeat. One habit alone means nothing, because people use all of them too. What gives the text away is several piling up in one paragraph, the way one repeated word is fine but the same sentence shape ten times in a row starts to feel mechanical.

The habits fall into five groups. The first is importance inflation and promotional filler: phrases like "plays a crucial role," "a testament to," and "marks a pivotal moment," and words like vibrant, robust, seamless and comprehensive, which make an ordinary fact sound like a brochure. The second is empty endings and tidy contrasts: a clause stuck on the end of a sentence only to sound analytical ("...highlighting its importance to the city"), and the "it's not just X, it's Y" pattern. The third is vague sources and invented details: "experts say" and "studies show" with nothing attached, and made-up numbers, quotes or product features that sound specific but have nothing behind them. The fourth is formatting: bold on every key phrase, bullets that each start with a bold label, headers on a three-line answer, emoji. The fifth is shape: recaps ("In conclusion"), closing offers ("Let me know if you'd like..."), openers that agree with you ("You're absolutely right"), lists that always have exactly three items, and a new synonym every time the same thing comes up, where a person would just repeat the word.

This list comes from Wikipedia's volunteer editors, who review large amounts of AI-written submissions and keep a public list of the signs they look for. Most of it covers problems only Wikipedia has, like broken citation formatting. About a third applies to ordinary writing, and that third is what the instructions in this section are built from. Nobody has proven why models write this way. One plausible explanation is that training rewards answers that sound polished and important, which pushes the style toward exactly these habits. Treat that as a theory, not a fact.

The fix is a custom instruction, and it works for the same reason as Chapter 1. You could fight these habits one answer at a time, asking for "less corporate" and "no bullet points" in every prompt. That is the effort lever. A custom instruction is the understanding lever: you spot the pattern once, write it down once as a rule, and the tool applies it to everything it writes for you afterward. ChatGPT, Claude and Gemini all have a place in their settings for exactly this, a block of text added in the background to every conversation.

Why three instructions and not one? About 80 percent of the three is identical, because the models share most of their habits. The rest differs because each tool has habits of its own. A 2025 study (Sun and colleagues, ICML) found that a simple classifier could tell which of five major chat models (ChatGPT, Claude, Gemini, Grok, DeepSeek) wrote a text about 97 percent of the time, so the habits are consistent enough to name. In plain terms, and treat these as tendencies, since every new version shifts them: ChatGPT leans on bold text, headers, bullets, closing offers and em dashes. Claude tends to open by agreeing with you, stack hedges, use many em dashes and semicolons, and repeat a few pet phrases. Gemini tends to run long by default, use italics for emphasis, and open with "Here is a breakdown." Space matters too. ChatGPT's free plan allows only 1,500 characters of custom instructions (paid plans allow 5,000), so a line aimed at a habit that tool doesn't have takes room from one that matters.

Each instruction also keeps its banned list short. A long banned-word list is hard for a model to follow and pushes it toward odd substitutes, so the instructions ban only a few of the strongest tells and spend the rest on positive rules: lead with the answer, use concrete facts, repeat the exact term, vary sentence length.

The three ready-to-paste versions are in the free Plain Voice file. All three versions use the same rules, adapted to each tool's habits, and each was tested on real writing tasks. Your tool and plan can behave differently, so do the five-minute check from that file once. Here is where each one goes. In ChatGPT: Settings, then Personalization, then Custom Instructions, with the "Enable customization" switch on. In Claude: click your initials, then Settings, then Instructions for Claude, which applies to every chat. To limit it to one piece of work, paste it into that Project's instructions. In Gemini: Settings & help, then Personal context, then Instructions for Gemini. Google says Gemini decides for each prompt whether to use them, and users report they get ignored in new chats, so the reliable route is a Gem with the instruction pasted into it. Menus change, so check the current location the way the Re-Evaluation Method describes.

Three habits make it work well in practice. First, the instruction says plain prose unless you ask, so when you do want a table or a list, ask for it by name and the explicit request wins. Second, test before trusting: ask for the same real task once before and once after, then compare the formatting, the first line, the last line, and any banned phrase. If a line changed nothing, delete it. Third, check it again every few months. This is the same lesson as Boris Cherny's advice in the Claude Code entry below: instructions are patches for the weaknesses of one model version, and a newer version can make them useless or even harmful.

Here is what this doesn't do. It is not a way to beat AI detectors. Detectors disagree with each other and flag human writing, and in a 2025 study (Russell and colleagues, ACL), people who use ChatGPT heavily for writing spotted AI text accurately, even after it had been run through "humanizer" tools. Readers are the real audience, and the instructions remove the patterns readers notice. It also fixes the surface, not the substance: a vague request gets a vague answer in plainer words, so the narrowing method still does the heavy lifting. It reduces invented details, because the instruction tells the tool to use only facts you gave it or leave a placeholder, but it can't remove them, so Chapter 5 still applies and every fact gets checked before you send. And it is not meant for hiding AI use where a school, employer or publisher requires you to disclose it.

Best field of use: writing you'll send as yourself, where tone matters more than formatting, such as client emails, social captions, product descriptions and freelance copy. It does up front the AI-phrasing scan that Chapter 6's email example does at the end, and the final scan is still worth keeping. It's less useful for code, data tables, or documents where you want heavy structure. For those, ask for the format by name or switch the instruction off for that chat.

## Your Own Notes, Readable by Any AI: Obsidian

Earlier in this chapter, ChatGPT's Memory, Claude's Projects and Gemini's Gems all do the same job: they hold your context so you don't have to re-explain it every time. They also all keep it inside that one company's tool. **Obsidian** is the other way to do it, and the idea is simple. It's a free note-taking app where every note is a plain text file in an ordinary folder on your own computer. Because the notes are ordinary files, any AI tool that can read a folder can read them. Claude Code can be pointed straight at the folder, and plugins connect Obsidian more tightly to Claude and other coding agents. Your notes aren't locked inside any one tool, so they survive a switch from one AI to another, which, given the ChatGPT-to-Gemini story earlier in this chapter, is the point.

The pattern people use most is to collect research into the vault (Obsidian's Web Clipper saves web pages as notes), then let the AI write summaries, link related notes and answer questions from them. Andrej Karpathy described a version of this: raw material goes in one folder, the AI writes an organized, cross-linked set of notes from it, and a later pass checks those notes for gaps and contradictions. He reported it working well at around 100 articles and 400,000 words, and called his own setup a hacky collection of scripts. Graphify, from the plugin list below, can also write its map of a codebase out as an Obsidian vault you can browse.

The app is free, including for work. Optional extras are Sync, which keeps your notes on several devices (about $4 a month billed yearly), Publish (about $8 a month), and a voluntary commercial license ($50 a year).

A few honest limits matter more than the hype you'll see online. It is not a design tool. People who use it for design mostly use Canvas, a free whiteboard for arranging notes, images, PDFs and web pages, or keep their research and references in it. It won't produce a design. "It gives AI a memory" is also overstated: the AI reads whole files into its working space, so it works best with a few hundred notes and gets slower and costlier as the vault grows. The AI can also change your notes. It can edit, rename or delete files, so before you let it write anything, copy the vault, track it with Git, and let the AI write only into one folder while your own notes stay read-only. Plugins can reach your whole computer, and Obsidian itself says it can't limit what a plugin does, so leave Restricted Mode on until you trust a plugin. This part moves quickly: one popular connector, with 87,000 installs, was archived by its owner in May 2026, so prefer the simplest setup that works. Everything the AI reads is sent to the AI company, so keep private notes out of the folder it can see. Chapter 5 applies as well, because notes the AI writes can contain invented facts, so label them. And watch for the tinkering trap: time spent organizing notes instead of producing work.

Best field of use: long-running work with a growing pile of material you keep returning to, such as a research project, content planning, the specs and decisions of a coding project, or client notes for freelancing. Start small: one folder, a handful of real notes, no plugins, and add something only when a real problem shows up. It isn't worth it for one-off tasks, or if you don't yet have notes worth keeping.

## What Not to Paste Into AI, and Where Your Data Goes

Everything in this guide asks you to give AI more information: your situation, your constraints, your drafts. That is what makes the answers specific. But there is a second question that gets asked far less often: what happens to what you typed?

The honest answer is that it depends on the tool, the plan, and a setting you may never have opened. On the free and personal plans of the big tools, your chats can be used to improve the model, depending on how the setting is switched. On business and API plans, the rules are usually stricter, and the default is usually that your data is not used for training. Since you are probably on a personal plan, the setting is yours to check.

Here is where it stands for the three main tools at the time of writing.

ChatGPT has a switch called "Improve the model for everyone." You find it in Settings, then Data controls. When it is off, new conversations are not used to train OpenAI's models. ChatGPT also has Temporary Chat, a chat that does not appear in your history, does not create or update memories, and is not used to improve the models. OpenAI says temporary chats may still be kept for up to 30 days for safety reasons, so "temporary" does not mean "instantly erased."

Claude changed its rules in 2025. On the Free, Pro, and Max plans, you are asked to choose whether your chats can be used to improve Claude. If you allow it, your data can be kept for five years. If you do not, the normal 30-day period stays. Chats you delete are not used for future training. The business products (Team and Enterprise) and the API are not part of this change. You can change your choice at any time: click your name, then Settings, then Privacy, and look for the training switch (called "Help improve Claude" or "Help Improve our AI models", depending on the version).

Gemini's control is called Keep Activity (in some versions, Gemini Apps Activity). You find it under Settings & help, then Activity. With it off, Google may still keep your chats for a limited time to run the service, and chats that a human reviewer has already looked at can be kept longer.

One more thing all three now have is memory. Memory is useful, because the tool remembers facts about you. It also means an old detail can quietly shape a new answer. When you want a clean, unbiased answer, or you are about to type something sensitive, use the temporary or incognito chat mode, or switch memory off.

The settings are the smaller part of this. The bigger part is a habit: decide before you paste. A simple rule covers almost everything.

Do not paste passwords, API keys, payment card numbers, or government ID numbers into any AI tool, ever. There is no task where you need to.

Do not paste another person's private details (a client's full email thread, a customer list with names and addresses) unless you are sure the tool's rules allow it and that you have the right to share it. Replace names, emails, and numbers with placeholders such as "Client A" first. The AI does not need the real name to write a good reply, and this takes ten seconds.

Do not paste anything covered by a contract or an NDA.

Treat everything else the way you would treat an email: probably fine, but not something you would put on a public wall if you could avoid it.

Menu names and defaults change often, so treat the paths above as a map and not a promise. Open each setting once, read what it says today, and choose on purpose. It takes about two minutes, and you only do it once.

## Coding Tools

**Codex** and **Claude Code** are, by a wide margin, two of the strongest options for writing and executing code with AI right now, and they're good at different things, each worth understanding in real depth rather than as a one-line label.

**Codex** is built around a cloud-native, parallel-first way of working, and that design choice is the whole story of what it's good at. Instead of running one task at a time in front of you, it can take on several coding tasks at once, each in its own isolated sandbox in the cloud. You don't need to clone a repository locally or configure dependencies on your own machine first, because Codex sets all of that up itself, remotely, for each task. Hand it several bug fixes or small features at the same time, and it works through all of them in parallel instead of making you wait for one to finish before starting the next, which directly addresses a real bottleneck for a small team or a solo developer with more of a backlog than time. It doesn't just write code and hand it back. It reads the existing repository first, implements the change, runs the test suite against what it wrote, and iterates on its own if something fails. Then it produces a pull request with a description of what changed and why, ready for a human to review instead of a wall of code with no explanation. Best field of use: clearing a backlog of several smaller, fairly well-defined tasks at once, or any workflow where juggling multiple projects' local environments would otherwise eat up real time, rather than one large, deeply interconnected architectural task that benefits more from a single sustained line of reasoning.

**Claude Code** takes the opposite shape: deep, interactive, and built around staying in close, deliberate contact with one complex task rather than spreading across many smaller ones. A few specific features explain why it holds up so well for that kind of work. **Subagents** let it spin off a separate task into its own fresh, isolated context, with its own full set of tools but none of the clutter from the main conversation, and report back only the finished result, which keeps a long, complex session from slowly filling up with irrelevant back-and-forth from a side investigation. **Plan Mode** forces a pause before anything gets built: Claude lays out what it intends to change and waits for your approval before touching any code. That matters a great deal for multi-file work, because jumping straight to implementation on something architecturally complex is how a result quietly drifts from what you pictured, the same failure the one-action-per-step method in Chapter 2 is built to prevent from the prompting side. **Hooks** go a step further than a written instruction in a project file, which Claude can still misread or deprioritize under pressure: a hook can automatically run a linter or the test suite after every single edit, or flatly block a write to a sensitive file, turning a suggestion into something closer to a guaranteed rule. And context itself is managed deliberately rather than left to pile up: clearing unrelated history between tasks, and a rewind feature that can restore both the code and the conversation to an earlier checkpoint, matter in practice because a cluttered, unfocused context quietly degrades output quality long before the model runs out of room entirely. Best field of use: complex, multi-file work on a single existing codebase, especially anything that benefits from a real plan-then-build sequence and genuine governance over what gets touched, rather than a stack of smaller, independent tasks better suited to running in parallel.

One more thing about Claude Code is worth knowing specifically because it cuts against the instinct to keep adding more custom instructions over time, and it comes directly from the person who built the tool. Boris Cherny, who built Claude Code, said in a Y Combinator interview about the Opus 5 release (summer 2026) that people who are not building agent products should, every six months, delete their CLAUDE.md file, their skills, and their hooks, then see what the model does without them, because the result might surprise them. According to a written transcript of the same interview, the host said Anthropic had deleted over 80 percent of Claude Code's own system prompt, and Cherny's explanation was that much of that prompt had been correcting behavior the newer model no longer needs correcting. His reasoning: most of the custom instructions people accumulate were written as patches for a weakness in whichever model version was current at the time. When a newer, stronger model arrives, an old patch can do more than become unnecessary. It can make the new model perform worse by boxing in judgment it now has but isn't allowed to use. The recommendation is not to delete everything and leave it empty. Delete it, watch what breaks or gets worse, and add back only the instructions that turn out to be necessary, one at a time, instead of restoring the whole pile out of habit. This is really the Re-Evaluation Method from earlier in this chapter, aimed inward at your own setup instead of outward at which tool is best, and it's worth doing on a calendar reminder, not just reading once and agreeing with.

Plenty of developers run Codex and Claude Code side by side rather than picking one, using each for what it's built for, which also sets up the cross-model critique pattern covered in Chapter 4.

**Cursor** is a different kind of tool from the other two, worth a full entry of its own rather than a passing mention: it's a full code editor built from the ground up around AI, rather than a command-line agent you run alongside your existing editor. A few of its features specifically solve problems the other tools don't address as directly. Every change it makes shows up as a side-by-side diff before it's applied, so you're reviewing exactly what changed, line by line, the same way you'd review a colleague's work, rather than trusting a summary of what happened. It also runs each task in its own isolated copy of the project, so an experimental or risky change can't damage your actual, working codebase until you deliberately decide to merge it in. For anyone managing more than just their own personal projects, it has real team-oriented controls built in: shared rules everyone's AI follows consistently, a record of what was changed and by whom, and settings that control whether code or data gets retained anywhere outside your own systems. It also connects directly to GitHub and GitLab, including a feature that automatically reviews a pull request and leaves comments on it before a human ever looks. Best field of use: day-to-day bug fixes and smaller features on a team that specifically wants to see and approve every change before it lands, or any project where an audit trail of what the AI did and why matters, rather than a single developer who just wants the fastest possible path to working code.

One more thing worth flagging if you're using **GitHub Copilot**: it has a specific, well-documented friction point where asking it to make changes to your code sometimes causes it to create its own separate branch to do so, which then causes real friction when you try to push those changes to GitHub normally. It's not a dealbreaker, but it's something to expect and plan around rather than discover by accident.

Whatever tool you pick, the code it writes still needs checking before real users touch it. The end of the coding example in Chapter 6 explains how, and Chapter 5 explains what to watch for when an agent can act on its own.

## Coding Plugins

A plugin, in this context, is an add-on that changes how a coding tool like Claude Code behaves, usually by giving it a specific habit or capability it doesn't have by default, either by injecting extra rules into every request it makes, or by giving it an entirely new command it can run. Every plugin below is a real, public project, not a theoretical idea, and most of them are open-source, meaning the actual code behind them is publicly viewable on GitHub by anyone, including you, before you decide whether to trust it.

**Everything-claude-code** is worth starting with, because the story behind it is a useful piece of context, not just a feature list. It was built by a single developer who reportedly won an Anthropic hackathon with an early version, then open-sourced the whole thing under the name "Everything Claude Code." It has since become one of the most-starred developer repositories on GitHub, at over 280,000 stars as of October 2026. It's a public GitHub repository anyone can inspect before installing. According to its repository page in October 2026, it contains 71 specialized agents, each acting like an expert in one part of the coding process, 311 skills that only activate when they're relevant, and 97 slash commands, so a single short command replaces what would otherwise be a long, repeated paragraph of instructions typed out by hand. The repository itself makes no measured claims about savings. Online reports of big cost cuts are anecdotes, so treat them that way. Why it works: rather than relying on you remembering to ask for planning, review, and security checks separately every time, it bundles that entire lifecycle into one installable package, so the habits are there by default instead of depending on your memory in the moment. Best field of use: a default, all-in-one upgrade for almost any serious coding project, especially if you don't want to assemble a toolkit of five or six separate plugins yourself.

**Ponytail** takes a specific, narrow angle: before writing any code, it makes the AI stop and check whether a simpler, shorter approach would already solve the problem, and only escalates to something more complex if the simple version doesn't hold up. In its own published benchmark (39 tasks, the Opus 5.5 model, five runs per task, compared with the same agent without the plugin), its README reports 53 percent less code, 41 percent less agent time, 26 percent lower cost, and 45 percent fewer tokens. Those are the maker's own numbers, not an independent test. Every shortcut it takes gets marked directly in the code with a comment explaining what a sturdier version would look like later, so nothing is hidden, it's just deferred. Why it works: AI tools left on their own tend to over-build, adding structure and flexibility nobody asked for "just in case," and this plugin forces the simplest working answer first, which is usually most of what the task needed anyway. It's also a public GitHub repository, and it isn't locked to Claude Code either, its README says it works with 20 different coding agents. Best field of use: any task where bloated, over-engineered code is a real risk, which in practice is most everyday coding work.

**Graphify** solves a different problem entirely: once a codebase has more than a handful of files, an AI exploring it by searching file by file tends to miss how different parts connect to each other. Graphify fixes this by building an actual knowledge graph of the whole project, stored in your own files, nothing gets sent anywhere you don't control. It works in two passes: first, a fast, deterministic parsing pass reads the raw structure of your code, classes, functions, imports, how everything calls everything else, with no AI involved at all for this part. Second, it hands anything that isn't pure code, documentation, design notes, even screenshots or whiteboard photos, to an AI specifically to pull out the concepts and relationships inside them. The result is a single, queryable map of the whole project, which meaningfully cuts down how many tokens get spent on every future question, since the AI can look up the map instead of re-reading raw files from scratch each time. It has passed 92,000 stars on its public GitHub repository and works across roughly 20 different coding assistants, not just Claude Code. It can also write its map out as an Obsidian vault you can browse, as covered earlier in this chapter. Best field of use: larger projects with many interconnected files, where an AI without this kind of map keeps missing how a change in one place breaks something somewhere else.

**Claude-mem** is a companion worth pairing with the above, since it solves a problem neither of them touches: by default, every new coding session starts from zero, with no memory of what happened yesterday. Claude-mem gives the tool persistent memory across sessions, so it can pick up where things left off instead of needing to be re-briefed from scratch every time you open it. Best field of use: any project you're working on across multiple days or weeks, rather than a single one-off session.

**Feature-dev** specifically enforces planning before any code gets written at all. Best field of use: any task complex enough that jumping straight into code tends to produce something that technically works but doesn't match what you pictured. That is the problem the one-action-per-step method in Chapter 2 solves from the prompting side. This plugin enforces the same discipline from the tool side, as a backstop in case a prompt slips through without it.

**Code-review** automatically checks for vulnerabilities and problems before you push changes, rather than relying on you, or a future reviewer, to catch them by hand. Best field of use: catching real security and logic issues before they ship, not after.

**Frontend-design** specifically targets the "obviously AI-generated" look that web pages built by AI tend to fall into by default, the same purple-gradient, same-font, same-layout pattern covered in Chapter 6. Best field of use: any task that produces a visual, user-facing page.

**Kombai Gallery** tackles that exact same "AI-slop" problem from a completely different angle, and it's worth a detailed look because it solves something the plugins above don't. Rather than telling an AI tool what to avoid after the fact, it gives it something real to copy from before it ever starts: a free library of more than 20,000 curated, real UI designs, full screens, individual components, landing pages, dashboards, organized by category, that you or your coding agent can browse and reference directly. The actual mechanism is worth understanding, because it's the reason this works better than a plain text instruction like "make it look professional." An AI generating a page from a plain-language description alone has nothing concrete to work from, so it defaults to the same small handful of patterns it saw most often in its training data, the exact purple-gradient, same-font sameness this whole thread of the guide keeps coming back to. Handing it a specific, tasteful design as a visual reference first replaces that vague instruction with an actual concrete target, the same underlying principle as the narrowing method from Chapter 2, a vague request produces a vague, generic result, and a specific one doesn't. It's built to be used with any coding agent, not just one tool in particular, Claude Code, Cursor, and Codex are all explicitly supported, so it slots into whichever coding setup from this chapter you're already using rather than requiring you to switch tools. It comes from the same company behind a broader AI design-to-code platform. That company ran its own benchmark of more than 40 frontend designs against generic coding agents and reports its platform ahead. It published the prompts, but the results appear only in a chart, so treat this as a vendor claim, not an independent result. Best field of use: the exact moment described in Chapter 6's design section, right before generating any visual, user-facing page, pull a real reference from the gallery first and hand it to your coding agent alongside the one-action-per-step guide from Chapter 2, instead of describing the look you want in words alone and hoping it lands.

**Security-guidance** and **typescript-lsp** round out the practical side. The first keeps security-specific concerns in focus throughout a project rather than as an afterthought; the second plugs the AI into a real type-checking system instead of letting it guess at types based on surrounding patterns, which catches a category of error pattern-matching alone would miss. Best field of use: security-guidance for anything handling user data or payments; typescript-lsp for any project written in TypeScript.

**The github plugin** connects a coding tool directly to your GitHub account and repositories. Best field of use: any workflow where you want the AI to open pull requests, check issues, or interact with your repository directly, instead of you copying code back and forth by hand.

**The "superpowers" trilogy** is a set of plugins focused specifically on planning workflows, and it's one of the two plugins most commonly recommended alongside Everything Claude Code itself. Best field of use: projects where the planning phase is complex enough to deserve dedicated tooling, not just a single prompt.

**Awesome Claude Plugins**, built by a company called Composio, orchestrates Claude Code across more than 500 outside services from one place. Best field of use: when a project needs to connect to many different external tools and APIs, and configuring each connection manually, one at a time, would eat up real time.

**Omniroute** is a self-hosted gateway that automatically switches between AI providers the moment you hit a usage limit, instead of just stopping you cold. Best field of use: if you're on a free or lower-tier plan and regularly run into usage caps mid-task.

One more find worth naming specifically, because it connects directly to the next chapter: there's an official Codex plugin built for Claude Code that adds commands for a built-in adversarial review, where Codex is specifically used to critique Claude Code's own work. Best field of use: exactly the cross-model critique pattern covered in Chapter 4, except here it's built directly into the tooling instead of something you have to set up by hand.

## Tools for E-commerce and Content

Both ChatGPT and Claude now have merchant-facing Shopify connectors, meaning you can manage a live store from inside a chat, checking sales, updating a listing, without opening the Shopify dashboard separately. Gemini's Shopify integration is different in kind, not just in degree: it's a developer-focused tool inside Gemini CLI, meant for building a Shopify app or theme in code, not for running a store day to day. Best field of use: ChatGPT or Claude's connectors if you're managing a live store and want to do it from chat; Gemini CLI's integration only if you're building custom Shopify functionality from scratch.

**TrendTrack** is consistently named across independent sources as a leading tool specifically for dropshipping product and trend research. Best field of use: the product-discovery stage covered in Chapter 6's e-commerce example, finding what's trending before committing budget to it.

**Jasper** is built specifically for marketing copy at scale, distinct from a general-purpose assistant. Best field of use: producing a high volume of ad copy or product descriptions that follow proven marketing structures, when you need more volume than hand-crafting each piece individually would allow.

**Canva AI** handles visual content generation and is explicitly built for people without design skills. Best field of use: quick, on-brand social visuals and product graphics, when speed matters more than full creative control.

**Higgsfield** is a multi-model video and image platform, and it's trending for a real reason: it's specifically strong at producing high-quality short-form video ad creatives fast, which matters a great deal for anyone running paid social ads where testing many different video hooks quickly is a genuine competitive advantage. It's now integrated directly inside ChatGPT as a plugin, not just a separate standalone app.

## The Re-Evaluation Method

Everything above reflects the state of things in October 2026, when this guide was written. None of it is guaranteed to still be accurate by the time you're reading this, and that's not a flaw in the guide, it's just the nature of a fast-moving industry, the same lesson as the ChatGPT-to-Gemini story earlier in this chapter. Here is the actual, repeatable process for keeping this current yourself, rather than just trusting whatever you read first.

First, never trust a single source, and never trust a tool's claim about itself without checking it against something outside that tool, the same lesson from the Gemini image-generation example earlier in this chapter. Second, look specifically for complaints and friction points from people who use a tool daily, not just polished marketing pages, because the real limitations of a tool show up in user frustration long before they show up in official documentation. Third, when a new tool or plugin claims to be the best at something, check how many independent sources say the same thing, rather than trusting one glowing review, since one enthusiastic post proves nothing on its own. This is the same verification discipline covered in full in Chapter 5, applied specifically to the question of which tools are worth your time.

# *04* Chaining AI Tools

Imagine you're building a house. You wouldn't hire one person and ask them to pour the foundation, run the electrical wiring, install the plumbing, and put up drywall, even if that one person was reasonably capable at all four. You'd hire a foundation crew for the foundation, an electrician for the wiring, a plumber for the plumbing. Not because any one of them couldn't technically attempt the other jobs, but because each of them has spent years getting excellent at one specific part of the process, and stacking all four jobs onto one generalist produces a worse house than splitting the work across specialists, every time.

This is obvious when it's a house. It's much less obvious when it's AI, because every AI tool looks like the same kind of thing from the outside, a text box you type into, and it's easy to assume that if a tool can technically attempt a task, it's just as good at that task as any other tool you could've used instead. It usually isn't. Some tools are built and trained to be excellent researchers and planners. Others are built and trained to execute code, or write ad copy, or generate images, reliably. Asking one of them to do another's job, just because it's technically capable of trying, tends to produce a worse result than splitting the work the way you would on that job site: the right specialist for each part.

## Chaining Is Becoming Standard Practice

Before getting into exactly how to do this, it's worth knowing that chaining specialized AI tools together isn't a clever workaround one person figured out. It's quickly becoming the standard, documented way serious teams use AI, and the evidence for that is worth knowing, because it tells you this approach is worth the extra step, not just worth trying once.

Microsoft's open-source Agent Framework documents this pattern as a standard building block. Its documentation shows a sequential pipeline in which one agent researches, a second writes, and a third edits, and a feedback loop in which a reviewer sends the work back to the writer until it is approved. Each agent handles only its own part of the task before passing the work along. That is not a hobbyist's idea. A company the size of Microsoft ships the pattern in its official tooling.

The adoption numbers back this up. Databricks, one of the largest platforms companies use to build and run AI systems, reported in its 2026 State of AI Agents report that use of multi-agent workflows on its platform grew 327 percent in four months, from June to October 2025. That is a fast shift in how teams build with AI.

There is a cost to skipping this, too. The usual failure is one tool and one giant prompt for everything. The output comes out inconsistent and generic, and nobody notices because it happens slowly, and then the time goes into re-prompting and cleaning it up by hand. A chained process mostly avoids that. No independent study that measures this cost was found, so the guide claims no figure for it.

This is not only for large companies with engineering teams. A solo creator can run a whole content operation this way: research a topic thoroughly once, then use that same research to produce a blog post, social captions, and video scripts, instead of starting from a blank, under-researched prompt for every platform.

Splitting work across specialized steps is also usually cheaper, because the expensive model only runs on the steps that need it. The DeepSeek and Claude chain later in this chapter is one example.

With all of that as real-world grounding, here are the three distinct ways to apply this, each one solving a different problem.

## Pattern One: Chain by Role

This is the house-building idea applied directly. Pick a tool to do the research and planning, and a different tool, built specifically for the thing you're trying to produce, to execute it. This is the same research, write, review shape that Microsoft's Agent Framework documents, applied at whatever scale fits your own project.

Here's exactly how this works in practice, for a coding project. The execution tool in this case, something like Codex, is built to write and run code reliably. It is not built to be a strong open-ended researcher, and asking it to both research your idea from scratch and then build it tends to produce weaker results on both halves than splitting the job.

So instead, the first step happens in a different tool entirely, something like Gemini, which is a stronger general-purpose researcher and planner. You'd explain the concept in full detail there, and work through the narrowing method and the one-action-per-step guide from Chapter 2, entirely inside that planning tool. The output of that process is a long, extremely detailed, already-converted prompt, the exact kind described in Chapter 2's two-stage method.

Only then does that finished prompt move to the execution tool. You're not asking Codex to figure out what to build, you're handing it a finished, zero-ambiguity instruction set and asking it to execute. The research tool never touches the code. The execution tool never has to guess at the plan. Each one does only the part it's built for.

The exact same structure applies outside of coding, and it's worth seeing it applied somewhere completely different to understand how general it really is. In content production, a documented, production-grade version of this looks like: Ingest, Brief, Draft, QA, Publish. A research stage gathers real source material first, a brief stage turns that material into a clear plan for what the piece needs to cover, a draft stage writes it, a QA stage checks that draft against the brief and the research before anything goes out, and only then does it publish. Notice this is the exact same shape as the coding example: research and planning happen completely separately from execution, and a check happens before anything ships.

Planning gets its own deliberate step for a reason. If you ask the execution tool to plan in the same conversation where it also produces the final output, you ask one tool to be excellent at two different skills at once, and in practice it tends to be worse at the planning half than a tool, or a dedicated stage, built for it. That is the failure described earlier in this chapter: skipping the separate planning stage entirely.

## Pattern Two: Chain Around a Limitation

The second pattern isn't about picking the best specialist for each job. It's about using a second step specifically to patch around a real, known flaw in the first one, instead of just living with the flaw or hoping it goes away.

Remember Gemini's image-generation problem from Chapter 3: inside an ongoing chat, its image generator doesn't reliably carry instructions forward the way the rest of the conversation does. Tell it "every image from now on needs this specific detail," and it will acknowledge that instruction, but the next image it generates often won't include it, because image generation behaves more like a fresh, isolated request each time than like normal chat memory.

Here's the actual chained process that works around this, step by step, with exactly what that looks like in practice. First, use Gemini's regular text mode to produce the design brief itself, using the research-based method from Chapter 2: research the platform's algorithm and best practices, then research and fix anything that would look obviously AI-generated, exactly as covered in that chapter's staged prompting example. That text-mode conversation holds context completely normally; this part of the flaw doesn't apply here at all.

Second, take the finished brief from that conversation and turn it into the actual image-generation prompt, the same way described in Chapter 2. Here's the part that makes this a genuine workaround rather than just hoping for the best: every single time you ask for a new image, re-attach the full styling instructions to that specific prompt, in full. A real version of what gets re-attached, word for word, every time: "2:3 vertical ratio, text overlay must stay within the top third of the image, no distorted or warped background elements, consistent lighting direction across every element, keyword phrase from the research included in the overlay text." That block gets pasted into every single image request, not referenced back to, because referencing back to it is exactly what doesn't work.

This is a different kind of chaining than Pattern One. You're not moving between two different tools built for two different jobs. You're moving between two different modes of the same tool, because one of those modes has a documented memory flaw the other doesn't, and the fix is a small, repeatable habit, not a different piece of software.

## Pattern Three: Chain for Critique

The third pattern tackles a problem that's specific to how these tools tend to behave toward their own output. Remember Claude's tendency, covered in Chapter 3, to be overly agreeable, to find a way to validate an idea rather than stress-test it. This isn't unique to Claude. A 2024 study (Panickssery and colleagues, NeurIPS) found that language models recognize their own writing and rate it higher than other models' writing, a pattern the authors call self-preference. In plain terms, a model tends to be more forgiving toward output it produced itself than toward output from a different model.

The practical fix follows directly from that finding: instead of asking a tool to review its own work, which is exactly the scenario it's most likely to rubber-stamp, hand that same output to a different model and ask for a critical review specifically. A different model has no reason to defend decisions it didn't make itself, so its critique tends to surface real blind spots, missed risks, or flaws the original model would likely have talked itself past.

Here's what that looks like worked through on a real kind of task. Say ChatGPT writes a first draft of ad copy for a product. Instead of asking ChatGPT itself "is this good," which tends to produce "yes, and here's why," that draft gets handed to a different model, Gemini for example, with a specific instruction: find every weak point in this, don't comment on anything that's already working. A critique run this way tends to surface exactly the kind of thing a self-review smooths over: a claim that's stated more strongly than it can be backed up, a call to action that's technically present but vague, a tone that doesn't match the platform it's meant to run on. None of that is guaranteed to be caught by the same model that just finished congratulating itself on the draft.

This pattern is more than a passing tip: it has already been built into real tooling. There's an official Codex plugin for Claude Code that adds a built-in adversarial review command, where Codex is specifically brought in to critique work Claude Code just produced. That's this exact pattern, cross-model critique, already formalized as a one-command feature instead of something you have to manually set up by copying output between two separate chats yourself. It is also the same reviewer role that appears in Microsoft's Agent Framework writer-and-reviewer loop, here running across two different companies' models instead of one framework's internal agents. One published six-stage workflow combines the tools this way: Claude Code for planning and first drafts, Codex for the harder multi-file implementation, and then a separate, independent security and logic review in read-only mode. A figure of 30 to 50 percent more issues caught has been attached to this workflow online, but no independent measurement was found, so treat the idea as sound and the number as unproven. The reason it should help is that each tool has blind spots the other does not share, the same principle behind Chapter 5's "ask a different model" step, applied one stage earlier, before a real-world result is what catches the problem.

## Four Reported Chains Using the Exact Tools From Chapter 3

Everything above explains the three patterns in the abstract. Here are four specific chains, each built from named tools covered in Chapter 3. They are workflows that developers and reviewers have written up, not results measured for this guide.

Perplexity researches, Claude Code builds. This is Pattern One in its most direct form. A real, worked example: before choosing a database for a project, the research step goes to Perplexity first, something like "what are the best databases for microservices right now, compare the leading options with current sources," which comes back with a sourced, citation-backed comparison instead of a guess. Only once that comparison is in hand does the second step happen, briefing Claude Code on the specific findings and asking it to design the actual architecture, schema, indexing, and connection handling around the option the research supports. Some teams using this two-step sequence report fewer architecture changes mid-project (anecdotal), because the decision was checked against current, sourced information before any code got written, not after.

DeepSeek reasons, Claude writes the code. A second reported version of Pattern One, and useful for a cost-conscious beginner specifically because of what it does to price. A harder, more ambiguous request, one that involves real architectural decisions rather than a small, well-defined fix, goes first to DeepSeek, which is specifically strong at exactly this kind of structured reasoning, as covered in Chapter 3, and comes back with a structured plan: the architecture decisions, the implementation steps, and the key trade-offs already worked out. That plan then becomes the input for Claude, which turns it into actual, production-ready code. The reasoning behind routing it this way instead of sending everything straight to Claude: DeepSeek's output costs a fraction of Claude's per unit of text (check both providers' price pages, because prices change often). Offloading the expensive reasoning step to the cheaper tool and keeping Claude for the coding step it's strongest at should cut cost on harder tasks without giving up quality on the step that matters most. For simpler, well-defined tasks, this same documented setup skips the reasoning step entirely and sends the request straight to Claude, because the extra step isn't worth the added time when the task was never ambiguous to begin with, a useful reminder that chaining is a tool for hard tasks, not a ritual to apply to everything.

Gemini scans the codebase, Claude executes inside it. A practitioner-reported version of Pattern One, run entirely inside Cursor rather than across separate tools. Gemini is given the broader, full-codebase view first, used specifically to scan and understand how an existing project fits together before any change is made, and Claude is then used to write and execute the code, working from the context Gemini already mapped out. The developer who documented this ran it at roughly 30 hours a week and paired it with two habits worth borrowing regardless of which tools you use. One is keeping detailed, up-to-date project documentation that the planning model can read. The other is breaking the work into an explicit step-by-step implementation plan before execution starts, the same one-action-per-step discipline from Chapter 2.

Claude Code and Codex, run as a full two-way pipeline. The most structured of the four, and it's worth seeing the whole sequence rather than just the critique step covered above. Claude Code opens the process, used interactively to understand the task and produce a real planning document before any code exists. It then writes the first draft of smaller, more contained pieces, staying in that same interactive session for quick back-and-forth fixes. Codex takes over specifically for the harder part, multi-file changes that touch several parts of the project at once, running its own tests until they pass rather than stopping at code that merely looks right. Only then does the review stage happen, Codex auditing the result in a separate, read-only pass specifically for security and logic problems, the kind of issue, a timing vulnerability, a missing rate limit, insecure secret storage, that's easy for the tool that wrote the code to miss simply because it already believes its own reasoning.

## Why These Three, and Not Just One

Here is why these are three separate patterns instead of one general "use multiple tools" rule, because each one solves a different problem, and reaching for the wrong one wastes effort without fixing anything.

Chain by role when the task itself has two different phases, like planning and execution, and no single tool is strong at both; this is the pattern with the most independent evidence behind it, from Microsoft's own framework to the measurable cost of skipping it. Chain around a limitation when a specific tool has a known, documented flaw, and the fix is a deliberate habit built around that flaw rather than a different tool altogether. Chain for critique when you need an honest, unbiased second opinion on something a tool already produced, and asking that same tool to review itself would just get you more of the same confidence it already had.

# *05* Verifying What AI Tells You

Picture a friend giving you directions somewhere you've never been. They say it with total confidence: "turn left at the gas station, it's maybe ten minutes from there." No hesitation, no "I think," just a flat, certain statement. You'd probably follow it without a second thought, because confidence reads as competence. We're wired to trust someone who sounds sure of themselves more than someone who hedges, even though, if you think about it, how sure someone sounds and how correct they are have nothing to do with each other. Your friend could be remembering a completely different gas station from three years ago and have no idea.

This matters enormously for AI, more than it does for a person, for a specific reason worth sitting with: an AI tool never hesitates the way a person does when they're unsure. It doesn't trail off, lower its voice, or add a nervous "I think" when it's guessing. It states a wrong answer in exactly the same confident, complete sentence it uses for a correct one. There's no tone-of-voice cue to catch, because there's no tone of voice at all, just equally confident text either way.

This is a documented problem, not a vague worry. A 2025 paper from researchers at Technion, Oxford, and the Hebrew University found that models can give wrong answers with high confidence even when they know the correct one, and that methods built on the model's own uncertainty miss many of these cases. A confident tone is not evidence of anything.

The scale is worth knowing too. Rates differ by model and task. OpenAI's GPT-5 system card reports that, with browsing on, about 4.5 to 9.6 percent of the claims in its newest models' answers still contained an error, and on a hard trivia test run without browsing the rate was around 40 to 47 percent. This is a regular feature of how these tools work, present in every major model to different degrees. And the real-world consequences are not hypothetical: as of 19 October 2026, Damien Charlotin's public AI Hallucination Cases database lists 2,202 court cases worldwide in which someone submitted AI-fabricated material, such as invented citations, as if it were real.

Here is, in plain terms, why this happens at all, because the mechanism explains the finding above instead of leaving it as a strange coincidence. OpenAI's own researchers (Kalai and colleagues, September 2025) make the same argument: models are trained and scored in ways that reward confident guessing over saying "I don't know." An AI model isn't looking anything up the way a search engine does, checking a fact against a stored, verified record and reporting back what it finds. It's doing something closer to predicting the next most statistically likely word, over and over, based on patterns it absorbed during training. Most of the time, the most likely next words happen to line up with what's true, because true statements tend to be the ones repeated most often and most consistently in whatever it learned from. But when a model doesn't have the real answer sitting somewhere in what it learned, it doesn't have a built-in alarm that goes off and makes it say "I don't know." It just keeps predicting the next most plausible-sounding word anyway, and a plausible-sounding sentence, grammatically speaking, reads exactly as confident whether or not the underlying content is true. That's the actual root of the problem: these tools are built to always produce a fluent, confident-sounding continuation, not built to flag their own uncertainty, so fabricated answers and accurate answers come out wearing the exact same tone of voice, because the tone was never connected to the truth of the content to begin with.

So this chapter isn't about being paranoid or distrustful of AI in general. It's about knowing that a confident-sounding answer and a correct answer are two completely different things, and building one specific habit for telling them apart.

## A Real Case, Walked Through in Full

Here's exactly how this played out in a real situation, step by step, because the abstract version of "verify things" is much less useful than seeing precisely what triggered it and what was done.

This happened early on, when first getting into Amazon affiliate marketing. Affiliate links come in two forms: a long, full link, or a short version, something like amzn.to, that's easier to share. The question of which one to use came up, so the natural move was to ask an AI directly: which is better, the short link or the full one? ChatGPT answered with total confidence: use the short link. It gave several reasons that sounded completely reasonable at the time, clean, easy to share, nothing about the explanation raised any red flags.

Weeks later, something didn't add up. Pins on Pinterest were generating real outbound clicks, people were clicking through, but Amazon's own dashboard wasn't registering those clicks at all. That mismatch, a real number from one place not matching a real number from another, is the actual trigger that mattered here. Not a vague feeling of doubt about ChatGPT in general, a concrete piece of reality that didn't line up with what had been confidently recommended weeks earlier.

That mismatch is what prompted going back and asking the exact same question to a different tool: short link or full link, which is better. Gemini gave the opposite answer. Short links, it explained, are likely to lose their tracking ID in the shortening process, which would explain clicks happening on Pinterest's end without ever registering on Amazon's end. On top of that, posting a large volume of content containing amzn.to-style shortened links can get flagged as spam-like behavior by Pinterest itself, a second, completely separate reason to avoid them that the first answer never mentioned at all.

Two things mattered in deciding whether to trust this second, contradicting answer over the first one. First, the sources Gemini's explanation pointed to were checkable, official sources, not vague claims with nothing behind them. Second, and this is the part that confirmed it rather than just made it more plausible: switching from short links to full links fixed the problem. The missing clicks started showing up correctly on Amazon's side. That's the real test, not which explanation sounded more convincing, but whether acting on it solved the real problem that triggered the whole check in the first place.

## The Three-Step Method, Named Explicitly

Pulling the method out of that story so it's usable on its own, stated as plainly as possible:

Step one: the trigger. The signal to go back and verify something isn't a general feeling of suspicion toward AI, and it isn't a scheduled habit of double-checking everything on principle. It's a real-world result that doesn't match what you were told. Clicks not registering when they should have been is a real-world mismatch. If everything is working the way it was described, there's no need to go back and re-check it. The mismatch is the trigger, not paranoia.

It helps to be specific about what counts as a reliable trigger here, because not every uneasy feeling qualifies, and treating every vague doubt as a trigger would mean never finishing anything. A reliable trigger is something you can point to and measure: a number that should have gone up and didn't, a feature that should work and throws an error instead, a result you can observe directly and compare against what you were told to expect. An unreliable, non-trigger is a background feeling of "I'm not totally sure about this," with nothing concrete behind it, the kind of doubt that follows you around on everything regardless of whether anything has gone wrong. The difference matters because chasing the second kind endlessly is exhausting and unproductive, while the first kind is specific, has a clear stopping point once it's resolved, and is exactly the situation this method is built for. If you can't point to the actual mismatched number, outcome, or behavior, you don't have a trigger yet, you have a hunch, and a hunch on its own isn't worth derailing your work over.

Step two: the check. Ask a different AI tool the exact same question, not the same tool again, since re-asking the same tool tends to just produce a confident restatement of the same answer. Weigh the new answer specifically by whether it points to something checkable: a real, named, official source, not just a more confident-sounding restatement. This step has real, independent backing behind it too, worth knowing: in testing, a real share of one major model's high-confidence answers were found to be directly contradicted once checked against a different model entirely, a concrete demonstration that confidence and accuracy are not the same thing, even within one single tool's own answers.

Two things are worth understanding in more depth here, because "just ask a different one" is easy to say but easy to apply badly if you don't know why it works. The first is why a different model is more likely to catch an error at all, rather than just making the same mistake again in different words. Different AI models are built by different companies, trained on different mixes of source material, and refined using different internal techniques and review processes. That means their blind spots, the specific gaps or distortions in what they absorbed during training, don't fully overlap. A gap in one model's training data is often simply not a gap in another's, because they didn't learn from an identical set of material in an identical way. That's the actual mechanical reason cross-checking works: it's not that a second opinion is magically more trustworthy by default, it's that the two models are likely to be wrong in different places, so an error specific to one of them has a real chance of standing out clearly against an answer from the other.

The second thing worth understanding is what makes a source "checkable" versus just sounding like one. A checkable source is something you could, in principle, go verify yourself without having to trust anyone's word for it: a named official page, a platform's own stated policy, a specific document you could pull up and read. An uncheckable source is something that sounds authoritative but gives you nothing to go confirm: "studies show," "experts agree," "it's widely known that," with no study, no expert, and no named source attached. The instruction in Chapter 3's "Making AI Write Like a Person" section tells the tool to name its sources or drop the claim, which helps, but it doesn't replace checking. The second kind of phrasing can appear in a confident, well-written answer just as easily as the first, so it's worth specifically scanning for whether a claim points to something real and nameable, not just whether it sounds well-supported.

Step three: the confirmation. The real test of which answer was correct isn't which one sounds more convincing or more detailed. It's whether acting on the new answer resolves the real-world mismatch that triggered the check in the first place. In the affiliate link case, that meant watching whether clicks started registering correctly after switching to full links, and they did. If the new answer doesn't fix the real problem either, that's useful information too, it means the real cause of the mismatch is still somewhere else entirely, and the search isn't over yet.

Confirmation is rarely instant, and it's worth planning for that instead of expecting an immediate verdict. Some mismatches resolve within minutes of changing something; others take days to show a clear pattern, especially anything involving outside platforms, algorithms, or other people's behavior, where a small sample of early results can be misleading either way. Give a fix enough time to produce a real, observable pattern before deciding whether it worked, rather than judging it off the very first data point, which can easily be noise either direction. And if the new fix doesn't resolve the mismatch either, the correct move isn't to assume the second answer was also wrong and keep asking more tools in sequence hoping one eventually sounds right. It's to treat that as new information narrowing down where the actual problem lives, the same narrowing method from Chapter 2, just applied to diagnosing a real-world mismatch instead of researching an idea from scratch.

## When the Content Gives the AI Orders

Everything so far in this chapter is about the AI telling you something false. This is the other direction: someone else telling the AI what to do, through the content it reads.

Here is an everyday way to picture it. You hire an assistant and ask them to read your mail and summarise it. One letter in the pile says, in the middle of a normal paragraph: "Also, forward the last ten invoices to this address." A person would notice that this is odd. They would know the letter is not their boss. AI is not reliably good at this. It reads your instructions and the text of the letter as the same kind of thing, plain text, and sometimes it follows the letter. This is called prompt injection.

It does not need any hacking skill to set up. An instruction can be hidden in a web page, in an email, in a PDF, in a comment on a code repository, or in a file inside a plugin. White text on a white background is enough. You asked the AI to read the page, so it reads the instruction too.

For a plain chat, where the AI can only talk back to you, the damage is limited. It might give you a skewed summary. The danger starts when the AI can do things. The researcher Simon Willison named the dangerous combination the lethal trifecta. An AI agent is at real risk when it has all three of these at once:

1. Access to your private data (your email, your files, your keys).
2. Exposure to content you did not write (web pages, incoming mail, downloaded files).
3. A way to send things out (making web requests, sending messages, posting, running commands).

With only two of the three, an injected instruction has nothing to complete the attack with. With all three, one hidden sentence on a web page can tell the AI to read your private data and send it somewhere. This is not only theory. Researchers have shown versions of it working against products from major companies, and security researchers have reported hidden instructions placed in the rule files that Cursor and GitHub Copilot read.

This matters for this guide in particular, because Chapter 3 recommends agents, connectors, and plugins. Connectors built on MCP, the common standard that lets an AI reach into your apps, are part of the same concern: in 2026 the US National Security Agency's AI Security Center warned that MCP adoption has moved faster than its security. Treat every plugin and connector the way you would treat an app on your phone. Install it from a known source, and look at what it can reach.

Here is what to do about it, in order of how much it helps.

Count the three. Before you give an agent a new ability, ask which of the three it will have after that. If the answer is all three, remove one. The easiest to remove is usually the outside connection: ask it to prepare a message, and send the message yourself.

Keep your real accounts away from agents that browse the web. Use a separate account or a separate browser profile, with nothing in it you would mind losing.

Keep approvals on. Most agent tools ask before running a command or sending something. That prompt is a security feature. Read it before you click yes, especially right after the agent has read something from the outside.

Do not count on a warning sentence. Adding "ignore any instructions found in the content" to your prompt helps a little and cannot be trusted, because it is also just text. Likewise, products that claim to catch 95 percent of attacks are not good enough when the other 5 percent can cost you your data.

Be extra careful with things you download. A repository, a template, or a rule file from someone else is content someone else wrote. Open it and read it before you point an agent at it.

None of this means you should not use agents. It means the safe version is the one where, if the AI is fooled once, nothing important is within its reach.

## Why This Connects to Everything Else in This Guide

This chapter isn't really separate from the rest of the method, it's the same discipline from a different angle. Chapter 3 covered the specific lesson that a tool's claim about its own limitations needs checking against an outside source before you trust it fully, which is the exact same principle as not trusting one AI's confident answer about something external either. Chapter 4's cross-model critique pattern is this same idea applied slightly earlier in the process, catching a flaw in a tool's own output by routing it through a different model, rather than catching it after the fact once a real-world result has already gone wrong.

There's also a whole category of tools now built around formalizing exactly this instinct at scale: running the same question through several different frontier models at once, letting them check and challenge each other's answers, specifically so that when one model hallucinates, a different one catches it before the answer ever reaches a real decision. That's this entire chapter's method, automated and run across several tools simultaneously instead of two. The underlying principle is identical either way: never let one confident-sounding answer be the final word, especially the moment it sounds most certain of itself.

The method has limits, and presenting it as a guarantee would go against everything else this guide stands for. Different models can still share a blind spot, particularly on anything new, obscure, or recent enough that none of them were trained on good information about it. If nobody's training data had the answer, asking two models instead of one doesn't necessarily fix that, since both can confidently agree on the same wrong thing for the same reason. This is exactly why the three-step method puts a real-world result, not just a second opinion, as the actual final check in step three. A second AI opinion raises or lowers your confidence in an answer. A real-world result, clicks registering again, code running, a page loading, is the only thing that confirms it.

# *06* Applied Examples

Everything up to this point has been the method itself: how to narrow a question until it's specific enough to act on, how to turn an idea into a guide with zero ambiguity left in it, which tools do what, how to chain them together, and how to catch a wrong answer before it costs you something real. This chapter is where all five of those pieces get run against five real, different situations, to prove the method isn't just a coding trick wearing a bigger label. Each section below walks through a real, worked case: what was asked, what came back, and what it produced.

## Coding: An Affiliate Bridge Page

The task: build a simple web page whose only job is to hold a set of affiliate links for an Amazon-affiliate business, something commonly called a "bridge page."

Before writing a single line of code, the narrowing method from Chapter 2 pointed to something worth knowing first: what makes a page like this work, and what risks come with it. That first research pass surfaced something a beginner typing "build me a bridge page" into an AI tool would never be warned about on their own: a page that's just a redirect, with no real content behind it, carries genuine risk. This caution is backed by specific regulation. In the US, the FTC's Endorsement Guides, a formal set of rules at 16 CFR Part 255, require that any affiliate relationship be disclosed "clearly and conspicuously," and the disclosure has to sit near the top of the page, before any affiliate link appears, not buried in fine print or hidden behind a "read more" click. One 2026 industry guide reports that the FTC has moved from warning letters to consent orders that name small brands, not just agencies, so smaller operators are not below the radar. That is a different risk profile than a few years ago, and it's the kind of detail that research before building catches and a rushed "just build it" prompt never would.

The second research pass, kept deliberately separate from the first, targeted what makes a coded page look obviously AI-generated: the same Inter-font, purple-gradient-on-white, identical hero-cards-testimonial-CTA layout covered in Chapter 3's tool research. This research is worth taking seriously for a reason beyond aesthetics too: consumer trust data backs up why this matters commercially. A December 2025 survey of 8,000 consumers by Klaviyo and Datalily found that visible AI-generated marketing makes 7 percent of people trust a brand more and 31 percent trust it less, more than four times as many pushed away as pulled in. A page that visibly looks AI-made is more than a cosmetic miss: it works against the page's entire purpose.

Only after both research passes were complete did the final step convert everything into the one-action-per-step execution guide from Chapter 2. The steps were:

1. Write one sentence naming who the page is for and what problem it solves.
2. Write a short, specific intro naming the product category.
3. Add a one-line affiliate disclosure near the very top of the page.
4. Pick a font that isn't Inter, Roboto, or Arial.
5. Pick a palette that isn't a purple gradient on white.
6. Define an explicit, non-stock section order instead of letting the AI default to the standard template.
7. Generate the page.
8. Check it against both research passes: is the disclosure clearly placed, and does the layout avoid the common AI tells?

## Before You Launch: Checking the Code Nobody Read

The steps above get you a working page. Working is not the same as safe, and a beginner has a particular blind spot here: the page runs, it looks right, so it feels finished.

The data on this is not encouraging. In 2025, the security company Veracode tested more than 100 AI models on 80 coding tasks. About 45 percent of the code they produced contained a security flaw. Bigger and newer models did not do meaningfully better. They had become better at writing code that runs, not at writing code that is safe. The models do not know your page will have real visitors. They write what works.

A bridge page with no login and no database has little to leak, which is a real reason to keep a first project simple. The risk grows quickly the moment you store anything about other people: emails, accounts, orders.

A real example shows what that looks like. In 2026, a researcher reported that a flaw in the app builder Lovable let anyone with a free account see the source code and database credentials of other people's projects created before November 2025. The report says it stayed open for 48 days. Separately, an earlier study of 1,645 apps built with the same tool found that 170 of them let anyone read personal information, and that about 70 percent had a database protection feature called row-level security turned off. Those figures come from news coverage and not from the tool's maker, so take the exact numbers as reported, but the pattern is the lesson: the app looked fine from the outside, and the settings behind it were open.

Here is a short routine, in the same one-action-per-step style as the rest of this chapter.

1. Search the whole project for any password, key, or token written directly into the code. Anything like that belongs in a separate settings file that never gets published, not in the page itself.
2. If a key was ever pasted into a chat, a screenshot, or a public file, treat it as stolen. Create a new one and delete the old one. Changing it takes a minute. Not changing it can cost far more.
3. If your project uses a database, find the setting called row-level security and turn it on. In plain words, it is a rule that says each visitor can only see their own rows of data. Without it, anyone who finds the address can often read everything.
4. Test it the way a stranger would. Open the site in a private window, without logging in, and try to reach pages and data that should be hidden. If you can see it, so can everyone.
5. Hand the code to a different AI model and ask for a security review only: "List every security problem in this code, ordered by how serious it is. Do not rewrite anything yet." This is the cross-model critique from Chapter 4, used where it matters most.
6. Fix the problems one at a time, then repeat step 5.

This will not make code perfect. It catches the most common failures, the ones that have caused real exposures, in about half an hour.

## E-commerce: Choosing a Dropshipping Product for a Home Decor Store

The task: find a dropshipping product worth building a small store around, within a home decor niche specifically, rather than guessing at whatever's trending this week on any one platform.

The narrowing method ran in four real stages. The first, broad pass researched what sells well in dropshipping generally, and it produced exactly the kind of generic, chase-whatever's-viral list the narrowing method in Chapter 2 warns about, long on trending gadgets and short on anything built to last. The second pass narrowed to sizing up home decor as a category worth committing to, and this is where market data changed the picture, though not in a clean way. Estimates of the 2026 dropshipping market differ widely by research firm, from about $343 billion to over $540 billion, with growth forecasts of roughly 20 to 28 percent a year (SaleHoo's roundup of Grand View Research and Global Market Insights figures). No single reliable figure for home decor's share was found. Because the sources disagree this much, the pass treated market size as a rough signal only and moved on to the narrower checks below. That research pass also surfaced a useful warning: a product trending in a video is not, on its own, evidence that a smaller seller can profitably compete on it. Differentiation and a defensible niche matter more than catching a trend first.

The third pass narrowed to the real audience already in hand: home decor specifically. This produced a shortlist filtered for actual dropshipping viability, lightweight, low breakage risk, photographs well: LED mood lamps, faux plants, ceramic vases, woven throw blankets, LED strip lights, modular wall shelving, peel-and-stick wallpaper. The fourth and final pass narrowed to one choice from that list, modular wall shelving, and surfaced specific numbers: an $18 to $30 price point converts well and supports add-on purchases, and demand peaks seasonally in January around New Year home-organization behavior. It also surfaced an honest trade-off to know before committing budget. Bulky items like shelving trigger dimensional-weight shipping costs that can eat into margin in a way a smaller item like a candle holder never would, and unclear installation instructions are a documented common cause of returns in this category. These figures came from that research pass and were not independently checked, so confirm them before committing budget.

Nothing about this four-stage process guessed. Every narrowing step added a checkable piece of information the step before it didn't have, exactly the discipline from Chapter 2, and it surfaced a real risk (the shipping cost trade-off) that a shallower, one-shot "what should I dropship" prompt would have missed entirely.

## Content & Affiliate Marketing: Building an Audience From Scratch

The task: go from no audience at all to a working affiliate marketing account, which is the real situation this entire guide grew out of. The platform in this case happened to be Pinterest, but nothing about the method below depends on that specific platform; the same sequence applies just as directly to a blog, a YouTube channel, or an Instagram page, because the method is about how the research and the content get built, not about which platform hosts it.

The starting prompt was deliberately broad, asking for beginner-friendly ways to make money on the chosen platform, which returned seven or eight real methods worth considering. The next prompt narrowed that list down to the two most effective, and that narrowing process is exactly what produced both the niche, home decor and lifestyle content, and the specific product idea, a budget-organizer PDF aimed at people managing irregular income, that became the actual business.

Everything that followed ran through the tool-chaining and verification habits from Chapters 4 and 5, not as separate exercises but as the actual day-to-day operation of the account. Visual content was built using the staged, research-first prompting method from Chapter 2: platform research first, an "avoid looking AI-generated" pass second, and only then the execution guide, every single time, not just once as a one-off exercise. When ChatGPT confidently recommended short affiliate links and the real click numbers coming from the platform didn't match what Amazon was reporting, that mismatch triggered the exact three-step verification process from Chapter 5, and it was a checkable, official source, not just a more confident restatement, that ultimately resolved it.

The specific platform is incidental here. What made this work, and what would make the same approach work on a different platform entirely, is the sequence itself: narrow before committing to a niche, research and verify before publishing instead of guessing, and treat a real-world mismatch as the signal to go check an answer rather than something to shrug off.

## Three Rules That Protect You While You Sell

Selling with AI-made material brings three legal and platform questions that beginners tend to find out about too late. This is general information and not legal advice, and rules differ by country, so check the ones that apply to where you live and where your audience is.

Label what the platform tells you to label. TikTok's rules, as summarised by a marketing agency, say content that AI creates or significantly changes, if it shows realistic people, voices, or scenes, should carry a label. The summary says the label should be visible on the video itself and not only in the caption. Separately, affiliate content counts as commercial content on TikTok. Before you post, switch on the "Disclose commercial content" option in the post settings and put a tag such as #ad at the start of the caption. Posts that skip this can have their reach limited or be removed. These details come from an agency's summary and not from TikTok's own page, so read TikTok's current rules before you rely on them. When in doubt, label.

Never have AI write reviews or testimonials. In 2024 the US Federal Trade Commission finalised a rule that bans creating or buying fake reviews and testimonials, including ones written by AI. A law firm's summary says the FTC can seek up to $52,000 per violation. The practical meaning for you: you can use AI to draft a product description, but you cannot have it invent a customer saying "this changed my life," and you cannot post made-up results. Quote real customers with their permission, or leave it out.

Know what you own. In 2025 the US Copyright Office reported that prompting alone, even with many detailed prompts, does not give you copyright over what the AI produces. Material you change, arrange, or write yourself can be protected, but the AI's own contribution cannot. In plain terms: if you sell a logo, a template, or a design that AI made in one click, somebody else can copy it and you may have little legal ground to stop them. The fix is the same advice this guide gives for quality: do real work on top. Edit it, combine it, and add your own writing and decisions. That makes it more protectable, and it also makes it look less like everyone else's.

## Freelancing: Email Copywriting for E-commerce Clients

The task: deliver a fast, high-quality freelance email copywriting service for e-commerce clients, specifically from the position of a complete beginner with no prior copywriting experience.

The research-first foundation surfaced something most beginners wouldn't know to prioritize: automated lifecycle email flows, welcome sequences, abandoned-cart emails, post-purchase follow-ups, generate a wildly disproportionate share of total email revenue, about 41 percent of all email revenue from about 5.3 percent of sends, according to Klaviyo's 2026 email benchmarks (their default attribution window likely overstates email's absolute contribution, so read it as a comparison). That single fact reframes the entire service: the highest-leverage thing a beginner freelancer can offer isn't a one-off promotional email, it's a short set of automated flows set up once and then running indefinitely. The structural backbone that research also surfaced, the PAS framework, problem, agitate, solution, along with the rule that each email should carry exactly one call to action, not several competing for attention, gave the actual copy a reliable shape to follow rather than starting from a blank page every time.

The second research pass, checking specifically for what makes AI-written copy read as obviously AI-generated, mattered more than it might first seem, because the freelance market itself is now actively pricing around exactly this distinction. In Upwork's 2024 earnings release, freelancers doing AI-related work earned hourly rates 44 percent higher than other freelancers. Being able to use AI well, and specifically to use it without producing the generic, instantly-recognizable AI tone covered in that research pass, is more than a quality concern: it puts you in a different, higher-paying tier of the freelance market, one that is already forming in real pricing data.

The final execution guide combined both research passes into the nine-step process from Chapter 2. In short: gather the client's product, audience, and one real objection; structure the email with the PAS framework; write one subject line under 50 characters; write preview text that extends rather than repeats it; write the body with exactly one call to action. Then scan for overused AI phrasing, uneven sentence rhythm, and generic, could-run-anywhere abstraction, and replace each with something concrete and specific to the client. The custom instruction from Chapter 3's "Making AI Write Like a Person" section does much of this scan before the draft exists, but the final check is still worth keeping.

## Design That Doesn't Look AI-Generated

The task: this one isn't really a separate skill from the other four, since every one of them touches on it somewhere, the social graphic, the bridge page, the email copy all needed this same pass. It earns its own section here because it matters on its own, specifically for anyone doing freelance design or print-on-demand work, where the final visual output is the entire product being sold.

The findings from Chapter 3's tool research hold up here in full. Inter, Roboto, or Arial as the font, a purple gradient on a white background, the identical stock section order, rounded cards around everything, and decorative pill badges and emojis scattered through a layout for no functional reason are the well-documented tells that make a visual read as machine-made at a glance, before a viewer registers why.

This is worth attention beyond style, because the evidence says readers notice. In one survey of more than 4,000 Americans (Joe Youngblood, reported by Search Engine Journal in 2025), people picked out the AI image about 72 percent of the time when shown real and AI versions side by side, though accuracy ranged from 18 percent for one image to 89 percent for another. In a separate 2025 survey (Hookline), 40 percent said they would view a brand more negatively for using AI-generated content, and only 10 percent more favorably. Together with the Klaviyo and Datalily numbers in the bridge page example above, visible AI-made marketing costs a brand more trust than it earns.

The fix, covered in full in Chapter 2's staged prompting method, is the same every time: define the constraints, a specific font, a specific palette, a specific, deliberate layout order, before generating anything, rather than trying to fix a generic result after the fact. A result built from real constraints from the start simply doesn't produce the tells in the first place, which is a fundamentally different, more reliable process than generating something generic and then asking an AI to "make it look less AI-made," a request that tends to just produce a different flavor of the same underlying problem. The same logic applies to text: Chapter 3's "Making AI Write Like a Person" section covers a standing instruction that keeps AI writing from falling into its usual habits in the first place.

# *07* Making Videos With Claude

Short vertical video (Reels, Shorts, TikToks) is where most attention online goes now, and it's also where AI output is easiest to spot. A viewer decides in about a second whether a video looks like every other AI video, and scrolls if it does. This chapter applies the whole method to that one job: you give Claude a script, voice files and a written brief, and Claude builds the video in code, renders it, checks it and sends you the file. You never open an editing app, and you don't need to know how to code.

It's the same two moves as every other chapter. Say exactly what you want, which here means the brief. Then check what you get, which here means a fixed list of checks run on every render. Everything else in this chapter (the setup, the prompts, the skills, the outside tools) exists to make those two moves easier. The free guide The Video Brief covers the short version of this workflow; this chapter is the full one, with the reasons behind each step and what was learned from using it on real Reels.

## Why AI Videos All Look the Same

Every decision you don't make gets made for you. Ask for "a cool video" and the AI has to choose a font, colours, how text appears, how fast things move, what the ending looks like. It fills each blank with its default, and the defaults are the same for everyone, because they come from the most common patterns in what the model learned from. That's the whole reason AI-made videos share a look: drop shadows on every card, text that pops in letter by letter, glowing gradients, slides that sit still while a voice talks over them.

This is the narrowing problem from Chapter 2 in a new form. A vague request produces a generic answer; a precise one doesn't. A better video tool won't fix it, because the tool still has to fill the blanks somehow. Fewer blanks will. The brief later in this chapter is simply a list of every blank, so none get left for the default.

## The Setup

You need four things, and only two of them are accounts you sign up for.

| WHAT | WHAT IT DOES | COST, AS OF NOVEMBER 2026 |
|---|---|---|
| Claude with Claude Code | Writes the video as code, renders it and checks the render | Included in the Pro, Max and Ultra plans |
| Remotion | Turns the code into an MP4 file | Free for individuals and companies of three people or fewer. Larger companies need a Company License, from $25 a month per person writing Remotion code |
| ffmpeg | Audio, loudness, cutting and export | Free |
| ElevenLabs | Makes the voiceover | Starter plan: $6 a month for 30,000 credits |
| Higgsfield (optional) | Generates AI footage and images from inside Claude | Paid plan needed; plans start at $9 a month for 120 credits (October 2026) |

Claude installs Remotion and ffmpeg itself. Remotion is the engine that matters most: it treats a video as a web page that changes frame by frame, which is exactly the kind of thing Claude writes well. Its license is the one cost people miss. It's free for individuals and small teams, but a company of four or more needs a paid license, so check where you stand before you build a business on it.

**The voice, and the license that comes with it**

ElevenLabs' free plan has no commercial license. Their help center says it plainly: "The free plan does not include a commercial license and cannot be used for any commercial purpose." Audio from the free plan that you publish also has to credit ElevenLabs. If your videos promote anything you sell, whether a product, a service or your own business, that's commercial use, so you need a paid plan.

In practice it costs very little. The Starter plan is $6 a month, includes the commercial license and comes with 30,000 credits. On the Eleven v4 model one character of script costs one credit, and a 45-second Reel script runs about 600 to 1,000 characters. That's enough for more than 30 Reels a month.

**Connecting ElevenLabs to Claude**

Claude makes the voice files through an API key, which is a password for software. Chapter 5 explained why anything that can act on your accounts should have as little power as possible, and a restricted key is how you do that here: it can only do what you allow and only spend what you allow.

1. Go to elevenlabs.io/app/developers/api-keys and click Create API key. Name it, for example claude-voiceovers.

2. Turn on Restrict Key and set a credit limit below your plan's total, for example 20,000 on Starter.
3. Under Endpoints, set Text to Speech to Access, Voices to Read and Models to Access. Leave every other endpoint on No Access.
4. Leave Restrict by IP address off (cloud workspaces change their address), keep Auto-disable if leaked on, then create the key and copy it. ElevenLabs shows it only once.
5. Open Voices, then My Voices, and copy the voice ID of each voice you use, with its settings: model, stability and similarity.

PROMPT · HAND OVER THE KEY

*Save this ElevenLabs API key and these voice IDs in a private settings file that only you read. Never put the key in a command, a log or a message. API key: [paste]. [Speaker 1] voice ID: [paste]. [Speaker 2] voice ID: [paste]. Model: [for example eleven_v4]. Stability: [0.5]. Similarity: [0.75].*

*Whenever you make a voice file, also save its word timings (ElevenLabs returns them with the audio), so every cue can land on its word. Then test it: make one short line in each voice and send me the two files.*

If Claude reports that it can't reach ElevenLabs, its workspace is blocking the connection: open Settings, then Capabilities, turn on network access, and ask again. And remember that a key pasted into a chat stays in that chat's history. That's why the restrictions and the credit limit matter: if the key ever leaks, the damage has a ceiling, and you can delete it and make a new one in a minute.

PROMPT · SETUP

*Set up this workspace for making vertical videos with Remotion. First, check for a Node.js version the current Remotion supports, plus ffmpeg and ffprobe. Install anything missing and tell me what you installed. Then create a blank Remotion project for 1080x1920 video at 30 fps, render a two-second test video with one line of text, and confirm the file plays and is 1080x1920 at 30 fps. If Remotion can't download its browser for rendering, use a Chromium that is already installed. Finally, tell me in a few lines what is ready and what still needs me.*

*Run it once per workspace. Cloud workspaces can reset; if yours does, run it again.*

## The Brief

The brief is the narrowing method's final, narrow prompt, written once per video. It has six blocks, and each one exists because leaving it out causes a specific, predictable problem.

TEMPLATE · THE BRIEF

*Goal and viewer. Who it's for, in one line: [for example, people who use ChatGPT for everyday decisions]. What they should do after watching: [for example, get the free PDF from the bio].*

*Script. One line per voice file: [file name] · [speaker] · [the exact line]. Words that must appear on screen: [list them exactly, or write "your choice"].*

*Look. Colours as hex codes: background [ ], text [ ], accent [ ], mistakes [ ]. Fonts, by name: headlines [ ], body [ ]. References: [two or three frames or videos, and what to take from each].*

*Timing. Time everything to the real voice files, never to an estimate. Pauses: [for example 0.3 s between lines, 0.5 s before the call to action]. Hold the last frame [about 1 s] after the last word.*

*Never. [for example: nothing covers the presenter's hand; no text over busy screen text; no stretch of empty screen; no drop shadows, glows or bouncing text; nothing that appears in a single frame; "link in bio" never as plain text].*

*Export. 1080x1920, 30 fps, voice at about -14 LUFS, peaks under -1 dB.*

Goal and viewer comes first because every later choice depends on it: a video for students who need an essay to sound like them looks and paces differently from one for founders choosing a tool. Write for one person, not an audience.

The script block is where most videos are already lost, before any animation exists. Read every line and ask whether it makes the next line necessary. A viewer decides line by line whether to keep watching, so a flat third line means the payoff in line seven is never seen.

The look block needs hex codes and font names, not adjectives. "Clean and modern" is a blank; "#10261C background, #ECE8DD text, #6BE0A0 accent, Archivo for headlines" is a decision. References belong here too, with what to take from each one. More on that later in this chapter.

The timing block stops the most common technical flaw: captions and cards that land a beat after the word they belong to. Half a second late is enough to feel wrong. Claude can only time things to the word if the voice files come with word timings, which is why the setup prompt asks for them.

The never-list does the most work, and it's where your taste goes. Every item on it is a default you've already seen and rejected. It grows with each video: whenever you catch something you don't want, add it, and it never comes back.

The export block exists because without it a video can go out at 720x1280 with the voice at -20 LUFS, quieter than everything around it in the feed. That exact mistake happened on an early video made for this guide, and it's why the numbers are now fixed in every brief.

## The First Three Seconds

If viewers leave in the first three seconds, nothing after that matters. When the first Reels made with this workflow were measured, average watch time was under three seconds on every one of them: the videos were finished, timed and checked, and almost nobody saw past the opening. A high skip rate is almost always a hook problem, so before anything gets recorded, the hook gets its own review.

- The opening line has to be on screen in the very first frame, as text, because many viewers watch with the sound off and the first frame is also the one people see while scrolling.
- It should name something specific (a number, a named thing, a real mistake) and leave a question open that the viewer wants closed. A category ("the best AI tools") gives nothing to be curious about.
- The first real piece of value should land within about five to ten seconds, not after a setup.
- Don't reuse one opening formula across videos. If three Reels in a row start with the same word, the account starts to feel like a template too.
- Consider a loop: if the last line leads straight back into the first, a viewer who reaches the end often watches the start again, and the replay counts.

PROMPT · AUDIT THE HOOK

*Here's my script. Before we record anything, audit the first line as the only thing a scrolling viewer will see. Score it, then tell me what question it opens, whether it works as on-screen text with the sound off, and whether line two makes line three necessary. Give me three stronger openings that keep the same promise, and don't change anything else yet.*

## Three Prompts, in Order

The video gets built in three steps, and the order matters. Each step is cheap to fix and the next one is expensive, so you catch problems where they cost the least.

PROMPT 1 · BRIEF TO STORYBOARD

*Here's my brief. Before building anything, write a storyboard: one row per shot, with start and end times taken from the real lengths of the voice files; what's on screen and how it enters and leaves; and one sentence per shot on why it is there at that moment. Check every shot against the never-list. If anything in the brief is unclear, ask instead of guessing. Don't build anything until I approve the storyboard.*

*Read the "why" column first. A shot that can't say why it's there is usually filler.*

PROMPT 2 · BUILD, RENDER, CHECK

*The storyboard is approved. Build the video in Remotion. Time every cue to the word it belongs to, using the word timings. Before the full render, render stills of the three busiest moments and check them against the never-list. Fix anything that fails, then render the full video.*

*After the render, check it yourself before you show me: the timing against the voice at every cut; any frame that pops, flashes or goes black, including frame-by-frame sheets around every moment something appears; empty stretches, overlaps and cut-off text; the loudness and the resolution. Send me the video, a contact sheet of frames and a short list of what you checked and what you fixed.*

*Stills first saves time. A full render takes minutes, and a still shows most problems in seconds.*

The third prompt is the fix message, and it's the one most people get wrong. Vague feedback gets you a guess. Precise feedback gets you a fix.

| VAGUE | PRECISE |
|---|---|
| "Make it better." | "0:22: the card covers the presenter's hand. Move the cards up so the hand is clear." |
| "The ending drags." | "The end card holds for about 7 s. Cut it to 1 s after the last word." |
| "Fix the captions." | "From 0:19 the captions are about 0.5 s late. Time them to the word timestamps." |
| "It looks too plain." | "0:31 to 0:38: the box just sits there. Give it a designed look and one movement that shows what the rule does." |

The pattern is the same every time: where it happens (the timestamp), what is wrong, and what to do instead. Put every note in one message so Claude fixes them all in one pass, and ask for the new lines or the new plan before it rebuilds anything big. A rebuild costs minutes; reading a changed line costs seconds.

## The Eight Checks

Watch every render on your phone, once with sound and once without. This is Chapter 5's verification step applied to video: Claude's report that "everything looks good" is a claim, and the render is the evidence.

| CHECK | WHAT TO LOOK FOR |
|---|---|
| Timing | Every caption and card lands on its word, not after it |
| Dead time | Any pause where nothing moves and nobody speaks |
| Overlaps | Text or cards on top of a face, a hand or other text |
| Empty space | Large areas with nothing in them, especially at the end |
| The first three seconds | The hook works with the sound off |
| Readability | Small text that's fine on a laptop and unreadable on a phone |
| Loudness | About -14 LUFS. Quieter voices sound weak next to other videos |
| Resolution | 1080x1920 at 30 fps |

With the skills below installed, Claude runs most of these before you watch. Two of its tools are worth knowing by name. A pop scan compares every frame with the next and flags anything that appears or vanishes too fast to see properly. A contact sheet lays out frames on one image so a problem that lasts a fraction of a second becomes visible at a glance. Neither is perfect: an automatic scan catches big jumps, but a small element that appears in one frame, such as a strike-through or an underline, can slip past. That's what frame-by-frame sheets around each cue are for. On one Reel made for this guide, the scan flagged a headline typing in letter by letter: every new letter was a one-frame pop that nobody had noticed watching at full speed.

## Skills: Giving Claude Tested Rules

A skill is a folder of instructions Claude loads for one kind of job, such as building in Remotion, avoiding certain visual habits or checking a render. A plugin bundles several skills, sometimes with tools. Without them, Claude falls back on its defaults, which is where AI slop comes from. With them, it follows rules someone has already tested on real videos.

PROMPT · INSTALL A SKILL

*Install this skill from [GitHub link] into ~/.claude/skills/. Before you install anything, read its README and SKILL.md and tell me in one line whether anything looks unsafe or needs an API key. Install only the parts I name.*

A skill is someone else's instructions, and often someone else's code. Chapter 5's rule applies in full: read what it does before it runs, install from a known source, and check the license, because some free skills forbid commercial use.

### The core skills

| SKILL | WHAT IT DOES | WHERE TO GET IT |
|---|---|---|
| Remotion skills (official) | How to build, animate, caption and render in Remotion. Maintained by the Remotion team | github.com/remotion-dev/skills |
| ffmpeg-llm | Accurate ffmpeg commands for audio, cutting, loudness and export | github.com/rendi-api/ffmpeg-llm |
| storyboard-architect and brand-lock-extractor | Brief to timed shot list with a reason per shot; your colours, fonts and rules in one brand file | github.com/whystrohm/shotkit |
| content-principles | The psychology of short-form scripts: one viewer, every line earning the next, specific words over vague ones | github.com/aiwithremy/contentprinciples |
| watch | Lets Claude watch a video from a link or a file, through frames and a transcript | github.com/bradautomates/claudevideo |

### The anti-slop toolkit

"AI slop" is the look people now recognise in a second. These skills exist to remove it, and they work in different ways, so they're worth combining.

**no-slop-motion** (github.com/ferndesk/no-slop-motion) is a banned list, standing rules and a step-by-step approval process for animated videos, plus scripts that scan a render for pops, flashes and black frames and make contact sheets. Its default banned list, in plain words: drop shadows on boxes and cards; glows, round colour gradients and dark frame edges; grids of cards in place of an explanation; a screen that sits still like a slide; text parked at the top while the action happens below; anything that appears or vanishes within one or two frames; glitch transitions; movement at a constant speed and bouncy overshoot; colour filters in place of chosen colours; quotes shown as tweet screenshots; more than one call-to-action in one frame; a sound effect on every landing; and a voice stitched from one-line clips. That list is the best starting never-list there is.

**Impeccable** (github.com/pbakaus/impeccable) is the most widely used design-quality skill, with about 105,000 GitHub stars. Its detector applies 62 fixed rules to flag the usual AI design habits and needs no API key. It's built for interfaces, so it suits the look of scenes built from web code, which Remotion scenes are, not timing or editing.

**claude-motion-design** (github.com/howseen-ai/claude-motion-design) does motion design in plain web code with no Remotion license, with four stills to approve before the full render. A security-graded skills

directory flags that it installs packages while it runs, so read what it installs first. **Claude Video 2.0** (github.com/ItssssJack/claude-video-2) lets you pick from 21 visual styles and checks its own frames; its optional AI clips use a paid Higgsfield key. **video-use** (github.com/browser-use/video-use) is for raw footage rather than animation: it cuts filler words and dead space and adds short audio fades so cuts never click.

**More proven skills**

**HyperFrames** by HeyGen (github.com/heygen-com/hyperframes) is an open-source engine that turns HTML and animation into MP4, Apache 2.0 licensed with no per-render fees, and a real alternative to Remotion. **IT Reelsmaker** (github.com/itpartypattaya/reels-montage) is for talking-head footage: it cuts pauses and retakes by the audio, adds word-timed subtitles and keeps text off faces. **claude-code-video-toolkit** (github.com/digitalsamba/claude-code-video-toolkit) is a complete video workspace under the MIT license, and **apple-design** (github.com/dickwu/apple-design-skill) is a design review grounded in Apple's interface guidelines, with a check for templated looks. Two to check before any commercial use: video-editor-skills uses CC BY-NC 4.0, which rules out commercial use, and motion-graphics-skills is published as "All Rights Reserved".

## Reference Videos: Borrow the Motion, Not the Work

The hardest block of the brief to write in words is motion: how things enter, move and leave, and how fast. "Smooth" and "dynamic" are blanks. A reference video is the most precise answer there is, because it shows the motion instead of describing it.

The best free source right now is prompt-motion.com, a gallery of motion videos made with Claude, each shown with the prompt or skill behind it. You can filter by type (Product UI, Phone, Charts, Kinetic type, Diagrams, Particles and more), and every entry links to the person who made it. The site states that videos and prompts belong to their creators, which sets the rule for using it: borrow the idea and the motion, never the design, the brand or the words, and credit the creator if you share their prompt.

Here's the process that worked for this guide's own Reels, and the detail that made the difference.

1. Pick a video for its motion and pace, not its colours.
2. Record your screen while it plays and send the recording to Claude.
3. Ask for a full inventory first: every motion, effect and transition in order, with rough timings. Check that list against the video yourself. The first attempt at this for this guide missed most of the source's features and came out static next to the original; a frame-by-frame inventory fixed it.

4. Have Claude rebuild the whole inventory in your own colours, fonts, shapes and words, then run your never-list over it. Popular references often use banned habits (letter-by-letter typing, glowing orbs, gradient backgrounds); swap each for something that does the same job.
5. Keep the result as a reference: the rendered video plus its template file, with every timing in one table and every word as a setting. Every later video that uses that animation starts from the reference, so the quality stays the same from video to video, and nothing gets rebuilt from memory.

PROMPT · REBUILD A REFERENCE

*Here is a screen recording of a reference video. First, list every motion and feature in it, in order, with rough timings: how each element enters, moves and leaves, and every transition. Wait for me to check the list. Then rebuild every item as a short reference video in my brief's colours, fonts and words. Copy the idea, the motion and the pace; don't copy the colours, shapes, brand or text. Check the remake against my never-list, and save it as a template where every timing sits in one table and every word is a setting.*

A reference doesn't mean every video uses every effect. It means every effect is ready when a video needs it.

## AI Footage Inside Claude: Higgsfield

Remotion draws everything with code: text, shapes, layouts, phone screens. It can't film a person, a product on a table or a street at night. Higgsfield, already mentioned in Chapter 3 as a video platform, generates that kind of footage, and it now has a connector for Claude. Through it Claude can reach Higgsfield's image and video models (Kling, Seedance, Veo and Nano Banana among them), pick one, set it up, run the generation and show you the result in the chat. It can also upscale, remove backgrounds, extend a clip, keep a character consistent across shots, and make voiceovers.

The split that works: generated footage for the shots code can't draw, code for everything else. Text, captions, timing, layout and the end card stay in Remotion, where they're precise and cheap to change. A generated clip goes into the Remotion project like any other video file, and the brief's look and never-list still apply to everything around it.

**Connecting it**

1. In Claude, open Settings, then Connectors, and click Add custom connector.

2. Name it Higgsfield and paste the server address: https://mcp.higgsfield.ai/mcp
3. Click Connect, sign in to Higgsfield and approve access. On a company Claude plan, an admin may have to allow the address first.
4. In Claude Code, Higgsfield works through its command-line tool instead: npm i -g @higgsfield/cli, then higgsfield auth login, then npx skills add higgsfield-ai/skills.

**What it costs, and how to keep it from surprising you**

You need an active paid Higgsfield plan, and every generation Claude runs spends credits from it. The unlimited offers on Higgsfield's own website don't apply to generations made through Claude. As of October 2026, plans start at $9 a month for 120 credits, with Pro at $29 a month for 600. As a rough guide, a 5-second Kling 3.0 clip costs about 8 credits and a 4-second Veo 3.1 clip about 40, so the model choice can change the cost of the same shot five times over. Prices changed several times in 2026, so check the pricing page before you choose.

There's no hard spending cap for Claude. You can tell it a limit, but that's an instruction, not a lock, and Chapter 5 already showed why an instruction is not a guarantee. The safe pattern is to make Claude ask first, every time.

PROMPT · ONE AI CLIP

*Using Higgsfield, make one [5]-second vertical clip: [the shot: subject, setting, camera position and movement, light]. Before you make anything, tell me which model you'll use, the settings and the credit cost, and wait for my yes. Stay under [N] credits in this chat. Then add the clip to the video at [timestamp] and run the eight checks again.*

**Before a generated clip goes out**

- License. The free plan has restricted commercial rights. Check Higgsfield's terms for your plan before you use a clip in anything that sells.
- Files. Claude can't pass files from the chat to Higgsfield. Upload reference images in Higgsfield itself, or give Claude a direct link.
- Checks. A generated clip gets the eight checks plus one: look for warped hands, faces and lettering in every frame, because that's where generated video still fails most.

- Labels. Platforms have rules for labelling AI-made footage, and the sources list covers TikTok's. Check the rule where you post.

## From Render to Post

A finished render still has three jobs left. The cover frame should repeat the hook, because it's what shows on your profile grid. The caption should claim only what the video shows, name what the free resource gives for that video specifically, and send people to the link in your bio rather than a URL. Three specific hashtags beat a wall of broad ones. And posting itself can be handed to Claude through a connector, which is the subject of the next chapter.

Then measure, but measure the right things. Raw views mostly reflect how many people already follow you. The numbers that tell you what to change are how many viewers are still there at three seconds (that's the hook's grade), average watch time (the middle's grade), and shares per view (the strongest signal you can earn, because a share is someone putting their name on your video). A video with views and no follows is a profile problem; a video with no views is a hook problem. Treat them differently.

## What This Won't Do

It won't give you taste. Claude follows the brief and the rules; whether the result is good is your call, made on your phone with the sound off. It can't catch what it doesn't check, so ask for the contact sheet and the check list with every render. Skills, references and generated footage are other people's work, so read them, credit them and check their licenses. And a precise brief makes a better video. It doesn't guarantee views, which is why the first three seconds get their own review every time.

# *08* Connecting Claude to Your Apps

Everything up to now has Claude producing things you then carry somewhere yourself: a post you paste, a file you upload, a caption you copy. A connector removes that last step. It lets Claude act inside your other apps directly, posting the Reel, creating the pin, updating the product page. That's a real time saving, and it's also exactly the third leg of the lethal trifecta from Chapter 5, the ability to send things out. So this chapter is as much about how to limit a connector as how to set one up.

## What a Connector Is

Connectors are built on MCP, the common standard that lets an AI tool reach into other software. Claude has a directory of native connectors, one per app, made by Anthropic or by the app's maker. For an app that isn't in the directory, you add a custom connector by pasting its server address, which is how the Higgsfield connector in Chapter 7 works.

Composio takes a different approach. Instead of one connector per app, it's a single connector that reaches more than 1,000 apps: Instagram, Pinterest, Gmail, Google Sheets, Notion, GitHub, Slack, Gumroad and many more. Claude doesn't get 1,000 apps' worth of tools at once. It gets a few general tools: one to search for the right action in the right app, one to manage which accounts are connected, and one to run actions. When you ask for something in an app you haven't connected yet, Claude gives you a sign-in link for that app; you approve it once in your browser, and from then on Claude can act there. More than one account per app is supported, such as a work and a personal Gmail.

Best field of use: anything you'd otherwise do by hand in several apps after Claude finishes the real work, such as posting, filing, updating listings and moving data between tools. It's at its best for apps that have no native Claude connector.

## Setting It Up

1. In Claude, open Settings, then Connectors, and click Add custom connector.
2. Name it Composio and paste this address: https://connect.composio.dev/mcp
3. Click Connect and sign in to Composio. A free account works.

4. Ask Claude to do something in an app, for example "list my Gumroad products". Claude replies with a sign-in link for that app. Open it, approve, tell Claude you're done, and it checks that the connection is active before it does anything.
5. In Claude Code, install Composio's command-line tool instead (the install command is on Composio's setup page) and run composio login.

Cost: Composio's free Hobby plan includes 100,000 tool calls a month, of which up to 20,000 can go to apps Composio manages the sign-in for, and searching for tools doesn't count. That's far more than one person posting and updating a few products will use. The Pro plan is $29 a month and mainly raises limits. The apps themselves keep their own rules and costs.

## What It Looks Like in Practice

These are real jobs run through Composio while marketing this guide, with the detail each one taught. The details matter, because every app's connection has its own catch, and the catch is where things go wrong.

**Posting Instagram Reels.** Instagram publishes in two steps: first the video is uploaded as a "container" and processed, then the container is published. Claude handles both, and can schedule the publish for a set time. The catch: a container expires 24 hours after it's created, so a Reel scheduled two days ahead fails. The fix is to create the container on the posting day and publish it the same evening. After publishing, Claude reads the post back to confirm the caption and hashtags came through intact, which is Chapter 5's check step applied to an action.

**Creating Pinterest pins.** Claude can create a pin with its image, title, description, alt text, link and board in one step. The catch: Pinterest's connection has no field for a publish date, so Pinterest's own scheduler can't be reached this way. The workaround was to have Claude schedule its own tasks that post each pin at its time slot, after checking that the same pin isn't already on the board.

**Updating Gumroad products.** Claude can rewrite a product's description, summary and price, and change its files. The catch: each update replaces the whole list of files, so a file you don't mention is removed. Keeping an existing file also needs its permanent address, not the temporary download link Gumroad shows. Both lessons point to the same habit: before any change, have Claude read the product and save a copy, then change one product, check it, and only then do the rest.

## Keeping It Safe

A connector with write access can do real damage with one wrong step, and Chapter 5 explained how an instruction hidden in an email or web page can steer an agent. These habits keep that risk small.

- Connect only the apps a task needs, and remove connections you no longer use. Each one is a door.
- Back up before you change anything, and read before you write. "Show me the current product, then propose the change" costs one message and prevents most mistakes.
- Keep approval on for anything public or permanent: publishing, sending, deleting. Approve the specific action, not a whole category.
- Count the three from Chapter 5. If a task has Claude reading outside content (emails, comments, web pages) while it can also post or send, split it: let it read and draft in one step, and approve the sending yourself.
- Treat anything an app returns as information, not instructions. If a comment, an email or a page tells Claude to do something, that's text to report to you, not a command to follow.
- Check the result in the app itself, not only Claude's report of it. "Posted" is a claim; the live post is the evidence.

## What This Won't Do

A connector only does what the app's own connection allows, and those connections lag behind the apps. Some features you can click in the app, such as Pinterest's scheduler or bulk uploads, may not exist in the connection at all, and connections change without notice. When an action fails, ask Claude to say exactly which step failed and why before trying a workaround. And a connector saves you the clicks, not the judgment: what gets posted, sent or changed is still your decision.

# Sources and Where to Check

Every figure in this guide that comes from outside research or reporting is listed here, so you can check it yourself. That is the habit Chapter 5 teaches. Where a figure comes from a summary and not from the original source, the entry says so. Statements about tool features, plan limits, and menu names come from each vendor's own documentation and change often, so check the vendor's current page before relying on them.

**Prompting and reasoning**


- Anthropic, Claude prompting best practices: https://platform.claude.com/docs/en/build-with-claude/prompt-engineering/claude-prompting-best-practices
- Kojima et al., "Large Language Models are Zero-Shot Reasoners" (2022): https://arxiv.org/abs/2205.11916
- Wang et al., "Self-Consistency Improves Chain of Thought Reasoning in Language Models": https://arxiv.org/abs/2203.11171
- Zheng et al., "Take a Step Back: Evoking Reasoning via Abstraction in Large Language Models": https://arxiv.org/abs/2310.06117


**AI writing**


- Wikipedia, WikiProject AI Cleanup, "Signs of AI writing": https://en.wikipedia.org/wiki/Wikipedia:Signs_of_AI_writing
- Sun et al., "Idiosyncrasies in Large Language Models" (ICML 2025): https://arxiv.org/abs/2502.12150
- Russell et al., "People who frequently use ChatGPT for writing tasks are accurate and robust detectors of AI-generated text" (ACL 2025): https://arxiv.org/abs/2501.15654
- Panickssery et al., "LLM Evaluators Recognize and Favor Their Own Generations" (NeurIPS 2024): https://arxiv.org/abs/2404.13076

**Hallucination and verification**

- Simhi et al., "Trust Me, I'm Wrong: High-Certainty Hallucinations in LLMs": https://arxiv.org/abs/2502.12964
- Kalai et al., "Why Language Models Hallucinate" (OpenAI, 2025): https://arxiv.org/abs/2509.04664
- OpenAI GPT-5 system card, as summarised by Implicator.ai: https://www.implicator.ai/gpt-5-cuts-claim-errors-to-9-6-with-browsing-system-card-shows/
- Damien Charlotin, AI Hallucination Cases database (2,202 cases on 19 October 2026): https://www.damiencharlotin.com/hallucinations/

**Chaining and tools**

- Databricks, State of AI Agents 2026, as reported by IntelligentCIO: https://www.intelligentcio.com/north-america/2026/01/27/databricks-report-reveals-rapid-rise-of-multi-agent-ai-systems-in-the-enterprise/
- Microsoft Agent Framework, workflow orchestration documentation (mirror): https://mintlify.wiki/microsoft/agent-framework/workflows/orchestration
- Ponytail README (maker's own benchmark): https://github.com/DietrichGebert/ponytail
- Everything Claude Code repository page: https://github.com/affaan-m/everything-claude-code
- Boris Cherny, Y Combinator interview on Opus 5, as transcribed by Reporails: https://dev.to/reporails/opus-5-delete-your-claudemd-9ga
- Kombai's own frontend test, written up on DEV Community (vendor-run): https://dev.to/astrodevil/i-tested-kombai-vs-claude-sonnet-45-for-frontend-one-was-35-faster-2gem

**Video and connectors**

- ElevenLabs help center, "Can I publish the content I generate on the platform?" (search the title at help.elevenlabs.io)
- Remotion license and pricing: https://www.remotion.dev/license
- no-slop-motion repository (banned list and render scans): https://github.com/ferndesk/no-slop-motion
- Impeccable repository: https://github.com/pbakaus/impeccable
- Prompt Motion gallery: https://prompt-motion.com

- Higgsfield, "How to Connect Higgsfield to Claude or ChatGPT": https://higgsfield.ai/creator-hub/help-center/integrations/how-do-i-connect-higgsfield-to-ai-agent
- Higgsfield, "How to Generate AI Videos in Claude With the Higgsfield MCP Connector" (May 2026): https://higgsfield.ai/blog/Generate-AI-Videos-From-Claude-with-Higgsfield-MCP
- Higgsfield plan prices and credit costs, as reported by AI Eating the World (October 2026): https://www.aieatingtheworld.com/articles/higgsfield-ai-pricing
- Composio setup instructions: https://connect.composio.dev/api/onboarding/setup
- Composio pricing: https://composio.dev/pricing
- Composio, "20 Best Claude Connectors" (August 2026): https://composio.dev/blog/best-claude-connectors
- Meta, Instagram content publishing documentation: https://developers.facebook.com/docs/instagram-platform/content-publishing

**Privacy, security, and legal**

- Anthropic, Updates to Consumer Terms and Privacy Policy (28 August 2025): https://www.anthropic.com/news/updates-to-our-consumer-terms
- OpenAI, Data controls FAQ: https://help.openai.com/en/articles/7730893-data-controls-faq
- Simon Willison, "The lethal trifecta for AI agents": https://simonwillison.net/2025/Jun/16/the-lethal-trifecta/
- TechInformed on the NSA warning about MCP security gaps (1 June 2026): https://techinformed.com/nsa-warns-enterprises-over-security-gaps-in-ai-agent-protocol/
- Veracode 2025 GenAI Code Security Report, as covered by SD Times: https://sdtimes.com/security/ai-generated-code-poses-major-security-risks-in-nearly-half-of-all-development-tasks-veracode-research-reveals/
- The Next Web, report on exposed Lovable projects (April 2026): https://thenextweb.com/news/lovable-vibe-coding-security-crisis-exposed
- FTC fake reviews rule, as summarised by Hunton: https://hunton.com/hunton-retail-law-resource/ftc-issues-final-rule-targeting-fake-consumer-reviews-and-testimonials-including-those-generated-by-artificial-intelligence-ai-and-online-bots
- US Copyright Office AI report Part 2, as summarised by the Authors Guild: https://authorsguild.org/news/us-copyright-office-ai-report-part-2-what-authors-should-know/

- TikTok AI labelling and branded content rules, as summarised by Darkroom (an agency summary, not TikTok's own page): https://www.darkroomagency.com/observatory/what-brands-need-to-know-about-tiktok-new-rules-2026
- FTC influencer disclosure rules 2026, Beancount guide (industry summary): https://beancount.io/blog/2026/08/12/ftc-influencer-disclosure-rules-2026-guide

**Markets and consumers**

- eMarketer on the Klaviyo and Datalily consumer survey (December 2025): https://www.emarketer.com/content/visible-ai-marketing-four-times-more-likely-cost-brands-trust-than-build
- Search Engine Journal on consumer detection studies (2025): https://www.searchenginejournal.com/studies-reveal-consumers-easily-detect-ai-generated-content/543620/
- SaleHoo, dropshipping market size roundup: https://www.salehoo.com/learn/dropshipping-market-size
- Klaviyo email benchmarks, as summarised by 8x: https://eightx.co/blog/average-klaviyo-flow-revenue-contribution-benchmarks
- Upwork Q4 2024 results, as reported by PYMNTS: https://www.pymnts.com/gig-economy/2025/upwork-demand-for-ai-talent-drove-record-revenue-in-2024/