The background of the slide is a complex field of purple lines with arrows, representing electric or magnetic field lines. These lines are curved and flow from the top and bottom towards the center, where they appear to converge or diverge. The lines are more densely packed in some areas and more spread out in others, creating a dynamic, swirling pattern.

# How physics simulations work: simulating particles in electric and magnetic fields

Nikolaj Roager Christensen

Student Colloquium in Physics and Astronomy, Aarhus University

March 2021

# Numerical integration of ordinary differential equations: motion of charged particles in electromagnetic fields

## Introduction

Theory and physical background 10 min

Euler's Method and the 4th order Runge-Kutta Method 15 min

- Euler's Method

- Higher order Runge-Kutta methods

- Demonstration, particles in a solenoid

Embedded algorithms, and adaptive step size 15 min

- Dormand Prince 5 (4) method

- Demonstration: magnetic dipole

## Conclusion

- If time permits, the cyclotron

# Introduction, what and why

- ▶ Numerical simulations are important.

# Introduction, what and why

- ▶ Numerical simulations are important.
- ▶ Testing setups, non-analytical systems.

# Introduction, what and why

- ▶ Numerical simulations are important.
- ▶ Testing setups, non-analytical systems.
- ▶ Demonstration, charged particles in electric and magnetic fields.
- ▶ Analytically known and not.

# Introduction, what and why

- ▶ Numerical simulations are important.
- ▶ Testing setups, non-analytical systems.
- ▶ Demonstration, charged particles in electric and magnetic fields.
- ▶ Analytically known and not.
- ▶ Simulations are not experiments!

# Theory: Classical non-relativistic particles

- ▶ Some repetition from Electrodynamics

# Theory: Classical non-relativistic particles

- ▶ Some repetition from Electrodynamics
- ▶ The Lorentz force+N2:

$$\vec{F} = q(\vec{v} \times \vec{B} + \vec{E}).$$
$$m\ddot{\vec{r}}(t) = q(\dot{\vec{r}}(t) \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)).$$



# Theory: Classical non-relativistic particles

- ▶ Some repetition from Electrodynamics
- ▶ The Lorentz force+N2:

$$\vec{F} = q(\vec{v} \times \vec{B} + \vec{E}).$$
$$m\ddot{\vec{r}}(t) = q(\dot{\vec{r}}(t) \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)).$$

- ▶ Only 1 particle! so pre-programmed depending on the setup.


# Theory: Classical non-relativistic particles

- ▶ Some repetition from Electrodynamics
- ▶ The Lorentz force+N2:

$$\vec{F} = q(\vec{v} \times \vec{B} + \vec{E}).$$
$$m\ddot{\vec{r}}(t) = q(\dot{\vec{r}}(t) \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)).$$

- ▶ Only 1 particle! so pre-programmed depending on the setup.
- ▶ Could use potentials  $\phi(\vec{r}, t)$   $\vec{A}(\vec{r}, t)$  and Hamiltonian, or Lagrangian.
- ▶ Other systems would have other differential equations.


# Known results, cyclotron motion $\vec{B}$ fields



# Known results, cyclotron motion $\vec{B}$ fields

- Magnetic forces do no work:

$$dW_{\vec{B}} = \vec{F}_B \cdot d\vec{r} \propto (\vec{v} \times \vec{B}) \cdot \vec{v} = 0.$$




# Known results, cyclotron motion $\vec{B}$ fields

- Magnetic forces do no work:

$$dW_{\vec{B}} = \vec{F}_B \cdot d\vec{r} \propto (\vec{v} \times \vec{B}) \cdot \vec{v} = 0.$$

- $(\vec{v} = \vec{v}_{\perp} + \vec{v}_{\parallel})$ :

$$|\vec{F}_B| = |q(\vec{v} \times \vec{B})| = |qv_{\perp}B|.$$



# Known results, cyclotron motion $\vec{B}$ fields


- Magnetic forces do no work:

$$dW_{\vec{B}} = \vec{F}_B \cdot d\vec{r} \propto (\vec{v} \times \vec{B}) \cdot \vec{v} = 0.$$

- $(\vec{v} = \vec{v}_{\perp} + \vec{v}_{\parallel})$ :

$$|\vec{F}_B| = |q(\vec{v} \times \vec{B})| = |qv_{\perp}B|.$$

- Same as Centripetal force:  
Cyclotron motion



# Known results, cyclotron motion $\vec{B}$ fields

- Magnetic forces do no work:


$$dW_{\vec{B}} = \vec{F}_B \cdot d\vec{r} \propto (\vec{v} \times \vec{B}) \cdot \vec{v} = 0.$$

- $(\vec{v} = \vec{v}_{\perp} + \vec{v}_{\parallel})$ :


$$|\vec{F}_B| = |q(\vec{v} \times \vec{B})| = |qv_{\perp}B|.$$

- Same as Centripetal force:  
Cyclotron motion
- Cyclotron radius and  
frequency:

$$R = \frac{v_{\perp} m}{|q|B} \quad \omega_c = \frac{|q|B}{m}.$$



# What we expect to see




“Cyclotron motion”

Solenoid with  $N = 1000$  turns per  $m$ ,  $I = 5$  A,  $r = 1$  m,  $|\vec{B}| \approx 6$  mT.

Proton with  $E_{kin} = 1$  MeV/ $c^2$  ( $|v| \approx 3.195 \times 10^5$  m/s)



# What we expect to see




“Cyclotron motion”


$$R \approx 0.5 \text{ m} \sin(\theta) \quad T = \frac{2\pi}{\omega_c} \approx 10 \mu\text{s}$$

# What we expect to see

Analytical: proton in a solenoid, side/front-view




Analytical: proton in a solenoid, speed



“Cyclotron motion”

$$R \approx 0.5 \text{ m} \sin(\theta) \quad T = \frac{2\pi}{\omega_c} \approx 10 \mu\text{s}$$

# What we expect to see



(Actually from my simulation)

# Ordinary differential equation's.

- Sources: Zeigler et al. Theory of Modeling and Simulation (Third edition) chapter 3
- We have:

$$\ddot{\vec{r}}(t) = \frac{q}{m}(\dot{\vec{r}}(t) \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)).$$

# Ordinary differential equation's.

- ▶ Sources: Zeigler et al. Theory of Modeling and Simulation (Third edition) chapter 3
- ▶ We have:

$$\ddot{\vec{r}}(t) = \frac{q}{m}(\dot{\vec{r}}(t) \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)).$$

- ▶ Algorithms exists for ODEs:

$$\dot{\mathbf{X}} = f_{ode}(\mathbf{X}(t), t).$$

# Ordinary differential equation's.

- Sources: Zeigler et al. Theory of Modeling and Simulation (Third edition) chapter 3
- We have:

$$\ddot{\vec{r}}(t) = \frac{q}{m}(\dot{\vec{r}}(t) \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)).$$

- Algorithms exists for ODEs:

$$\dot{\mathbf{X}} = f_{ode}(\mathbf{X}(t), t).$$

- Here:

$$\mathbf{X} = \begin{pmatrix} \vec{r} \\ \dot{\vec{r}} \end{pmatrix} \quad f_{ode}(\mathbf{X}, t) = \begin{pmatrix} \dot{\vec{r}} \\ \frac{q}{m}(\dot{\vec{r}} \times \vec{B}(\vec{r}, t) + \vec{E}(\vec{r}, t)) \end{pmatrix}.$$

# The ODE to solve


```
auto ODE = [...](const state_type Data, state_type &
    dDatadt, const double t){
    //Extract position and velocity from data
    vec pos = vec(Data[0],Data[1],Data[2]);
    vec velocity = vec(Data[3],Data[4],Data[5]);

    //Lorentz+Newtons 2nd law
    vec F = Charge*(Fields.get_Efield(pos,t)+
        cross(velocity,Fields.get_Bfield(pos,t)));
    vec dVdt = F*Inv_mass;

    //Save derivative of data
    dDatadt[0]=velocity.x;
    ...
};
```

# Solving differential equations

- We know only  $\mathbf{X}(t_0)$  and  $t_0$  and  $f_{ode}$ .




- Bernard P. Zeigler et al.  
Theory of Modeling and  
Simulation (Third edition),  
chapter 3



# Solving differential equations

- We know only  $\mathbf{X}(t_0)$  and  $t_0$  and  $f_{ode}$ .
- Can we find  $\mathbf{X}(t_0 + h)$  for  $h > 0$ ?




- Bernard P. Zeigler et al.  
Theory of Modeling and  
Simulation (Third edition),  
chapter 3

# Solving differential equations

- ▶ We know only  $\mathbf{X}(t_0)$  and  $t_0$  and  $f_{ode}$ .
- ▶ Can we find  $\mathbf{X}(t_0 + h)$  for  $h > 0$ ?
- ▶ (Explicit Forward) Euler's Method:

$$\mathbf{X}(t_0 + h) = \mathbf{X}(t_0) + hf_{ode}(\mathbf{X}(t_0), t_0).$$

- ▶ Multiple steps  
 $t_0, t_1 = t_0 + h, \dots, t_i, \dots$
- ▶ Bernard P. Zeigler et al.  
Theory of Modeling and  
Simulation (Third edition),  
chapter 3




# Solving differential equations

- ▶ We know only  $\mathbf{X}(t_0)$  and  $t_0$  and  $f_{ode}$ .
- ▶ Can we find  $\mathbf{X}(t_0 + h)$  for  $h > 0$ ?
- ▶ (Explicit Forward) Euler's Method:

$$\mathbf{X}(t_0+h) = \mathbf{X}(t_0) + hf_{ode}(\mathbf{X}(t_0), t_0).$$

- ▶ Multiple steps  
 $t_0, t_1 = t_0 + h, \dots, t_i, \dots$
- ▶ Can this be justified?
- ▶ Bernard P. Zeigler et al.  
Theory of Modeling and Simulation (Third edition),  
chapter 3



# Why does this work? What is the error

- ▶ Multiple justifications for why.

# Why does this work? What is the error

- ▶ Multiple justifications for why.
- ▶ First 2 terms in Taylor series Zeigler et al.:

$$\mathbf{X}(t_0 + h) = \mathbf{X}(t_0) + hf_{ode}(\mathbf{X}(t_0), t_0) + h^2 \dots + \dots$$

# Why does this work? What is the error

- ▶ Multiple justifications for why.
- ▶ First 2 terms in Taylor series Zeigler et al.:

$$\mathbf{X}(t_i + h) = \mathbf{X}(t_i) + hf_{ode}(\mathbf{X}(t_i), t_i) + h^2 \dots + \dots$$

- ▶ Local error  $h^2$ . Global error:  $h^1$ .

# Why does this work? What is the error

- ▶ Multiple justifications for why.
- ▶ First 2 terms in Taylor series Zeigler et al.:

$$\mathbf{X}(t_i + h) = \mathbf{X}(t_i) + hf_{ode}(\mathbf{X}(t_i), t_i) + h^2 \dots + \dots$$

- ▶ Local error  $h^2$ . Global error:  $h^1$ .
- ▶ Argument suggests we need  $\dot{f}_{ode}, \ddot{f}_{ode}, \dots$

# The Runge Kutta steppers

- In general:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = \int_{t_i}^{t_{i+1}} \dot{\mathbf{X}}(t) dt.$$

- L. Zheng, X. Zhang, Modeling and Analysis of Modern Fluid Problems, 2017, chapter 8:



# The Runge Kutta steppers

- In general:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = \int_{t_i}^{t_{i+1}} f_{ode}(\mathbf{X}(t), t) dt.$$

- *Mean Value theorem for integrals*  $t_i \leq \tau \leq t_{i+1}$ .

- L. Zheng, X. Zhang, Modeling and Analysis of Modern Fluid Problems, 2017, chapter 8:

# The Runge Kutta steppers

- In general:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = \int_{t_i}^{t_{i+1}} f_{ode}(\mathbf{X}(t), t) dt = hf_{ode}(\mathbf{X}(\tau), \tau).$$

- *Mean Value theorem for integrals*  $t_i \leq \tau \leq t_{i+1}$ .

- L. Zheng, X. Zhang, Modeling and Analysis of Modern Fluid Problems, 2017, chapter 8:

# The Runge Kutta steppers

- In general:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = hf_{ode}(\mathbf{X}(\tau), \tau).$$

- *Mean Value theorem for integrals*  $t_i \leq \tau \leq t_{i+1}$ .
- Guess  $\tau = t_i$ . Good guess, if  $\dot{f}_{ode} \approx 0$ .

- L. Zheng, X. Zhang, Modeling and Analysis of Modern Fluid Problems, 2017, chapter 8:

# The Runge Kutta steppers

- In general:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = hf_{ode}(\mathbf{X}(\tau), \tau).$$

- *Mean Value theorem for integrals*  $t_i \leq \tau \leq t_{i+1}$ .
- Guess  $\tau = t_i$ . Good guess, if  $\dot{f}_{ode} \approx 0$ .
- More generally, (*Explicit and single step*), Runge-Kutta family:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = \int_{t_i}^{t'} f_{ode}(\mathbf{X}(t_i), t_i) dt + \dots \int_{t^{(m)}}^{t_{i+1}} f_{ode}(\mathbf{X}(t_i), t_i) dt.$$

- L. Zheng, X. Zhang, Modeling and Analysis of Modern Fluid Problems, 2017, chapter 8:

# The Runge Kutta steppers

- ▶ In general:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = hf_{ode}(\mathbf{X}(\tau), \tau).$$

- ▶ Mean Value theorem for integrals  $t_i \leq \tau \leq t_{i+1}$ .
- ▶ Guess  $\tau = t_i$ . Good guess, if  $\dot{f}_{ode} \approx 0$ .
- ▶ More generally, (*Explicit* and *single step*), Runge-Kutta family:

$$\begin{aligned}\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) &= \int_{t_i}^{t'} f_{ode}(\mathbf{X}(t_i), t_i) dt + \dots \int_{t^{(m)}}^{t_{i+1}} f_{ode}(\mathbf{X}(t_i), t_i) dt, \\ &= \sum_{j=1}^m h_j f_{ode}(\mathbf{X}(\tau_j), \tau_j).\end{aligned}$$

- ▶ Use  $f_{ode}(\mathbf{X}(t_i), t_i)$  to approximate  $\mathbf{X}(\tau_1)$ .
- ▶ L. Zheng, X. Zhang, Modeling and Analysis of Modern Fluid Problems, 2017, chapter 8:

# Runge Kutta methods

- More commonly written:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j \mathbf{K}_j$$

- Martha L. Abell, James P. Braselton, Differential Equations with Mathematica (Fourth Edition), 2016:

# Runge Kutta methods

- More commonly written:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j \mathbf{K}_j$$

- Estimate  $\mathbf{K}_j$ :

$$\mathbf{K}_1 = f_{ode}(\mathbf{X}(t_i), t_i)$$

$$\mathbf{K}_2 = f_{ode}(\mathbf{X}(t_i) + ha_{21}\mathbf{K}_1, t_i + c_2h)$$

$$\mathbf{K}_3 = f_{ode}(\mathbf{X}(t_i) + ha_{31}\mathbf{K}_1 + ha_{32}\mathbf{K}_2, t_i + c_3h)$$

$$\vdots$$

- Martha L. Abell, James P. Braselton, Differential Equations with Mathematica (Fourth Edition), 2016:

# Runge Kutta methods

- ▶ More commonly written:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j \mathbf{K}_j$$

- ▶ Estimate  $\mathbf{K}_j$ :

$$\mathbf{K}_1 = f_{ode}(\mathbf{X}(t_i), t_i)$$

$$\mathbf{K}_2 = f_{ode}(\mathbf{X}(t_i) + ha_{21}\mathbf{K}_1, t_i + c_2h)$$

$$\mathbf{K}_3 = f_{ode}(\mathbf{X}(t_i) + ha_{31}\mathbf{K}_1 + ha_{32}\mathbf{K}_2, t_i + c_3h)$$

$$\vdots$$

- ▶ Want exact for  $p$ 'th order polynomial.
- ▶ Martha L. Abell, James P. Braselton, Differential Equations with Mathematica (Fourth Edition), 2016:



# Runge Kutta methods

- More commonly written:

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j \mathbf{K}_j$$

- Estimate  $\mathbf{K}_j$ :

$$\mathbf{K}_1 = f_{ode}(\mathbf{X}(t_i), t_i)$$

$$\mathbf{K}_2 = f_{ode}(\mathbf{X}(t_i) + ha_{21}\mathbf{K}_1, t_i + c_2h)$$

$$\mathbf{K}_3 = f_{ode}(\mathbf{X}(t_i) + ha_{31}\mathbf{K}_1 + ha_{32}\mathbf{K}_2, t_i + c_3h)$$

$$\vdots$$

- Want exact for  $p$ 'th order polynomial.
- Taylor series analogy: error  $h^p$ .
- Martha L. Abell, James P. Braselton, Differential Equations with Mathematica (Fourth Edition), 2016:

# Higher order methods

- 2nd order (Heun's method):

$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = \frac{h}{2}(\mathbf{k}_1 + \mathbf{k}_2)$$

$$\mathbf{k}_1 = f_{ode}(\mathbf{X}(t_i), t_i)$$

$$\mathbf{k}_2 = f_{ode}(\mathbf{X}(t_i) + h\mathbf{k}_1, t_i + h)$$

# Higher order methods

- 4th order, often simply called the Runge Kutta method:


$$\mathbf{X}(t_{i+1}) - \mathbf{X}(t_i) = \frac{h}{6}(\mathbf{k}_1 + 2\mathbf{k}_2 + 2\mathbf{k}_3 + \mathbf{k}_4)$$

$$\mathbf{k}_1 = f_{ode}(\mathbf{X}(t_i), t_i)$$

$$\mathbf{k}_2 = f_{ode}\left(\mathbf{X}(t_i) + \frac{h}{2}\mathbf{k}_1, t_i + \frac{h}{2}\right)$$

$$\mathbf{k}_3 = f_{ode}\left(\mathbf{X}(t_i) + \frac{h}{2}\mathbf{k}_2, t_i + \frac{h}{2}\right)$$

$$\mathbf{k}_4 = f_{ode}(\mathbf{X}(t_i) + h\mathbf{k}_3, t_i + h)$$



Wikipedia-user HilberTraum,  
published under creative  
commons: CC BY-SA 4.0

# The General explicit Runge Kutta method

- ▶ General explicit, single step, fixed size, Runge Kutta method

# The General explicit Runge Kutta method

- ▶ General explicit, single step, fixed size, Runge Kutta method
- ▶ Expressed in Butcher tableau:

$c_1 = 0$			
$c_2$	$a_{21}$		
$c_3$	$a_{31}$	$a_{32}$	
$c_n$	$a_{n1}$	$a_{n2}$	$\dots$
<hr/>			
	$b_1$	$b_2$	$\dots$

# Euler Implementations

```
state_type Data = Data0;
state_type dDatadt;
size_t time_res = T/timestep;
for (size_t i = 1; i < time_res; ++i)
{
    double t=i*dt;
    ODE(Data,dDatadt,t);
    //Euler time evolution
    Data+=timestep*dDatadt;

    save_step( Data , i*timestep );
};
```

## RK4 Implementations (1/2)

```
state_type Data = Data0;
state_type temp=Data0;
state_type K1,K2,K3,K4;
size_t time_res = T/timestep;
for (size_t i = 1; i < time_res; ++i)
{
    double t=i*timestep;

    //substep 1
    ODE(Data,K1,t);

    //substep 2
    temp=Data+timestep*K1/2;
    ODE(temp,K2,t+timestep/2);
```

## RK4 Implementations (2/2)

```
//substep 3
```

```
temp=Data+timestep*K2/2;  
ODE(temp,K3,t+timestep/2);
```

```
//substep 4
```

```
temp=Data+timestep*K3;  
ODE(temp,K4,t+timestep);
```

```
//Read data
```

```
Data+=timestep*(K1+2.0*K2+2.0*K3+K4)/6.0;  
save_step( Data , i*timestep );
```

```
}
```



## “Correct” way

```
#include <boost/array.hpp>
#include <boost/numeric/odeint.hpp>
using namespace boost::numeric::odeint;
typedef boost::array< double, 6 > state_type;
...
size_t steps = integrate_const(
    runge_kutta4< state_type >(),
    ODE,    //Lorentz-force
    Data0 , //{pos0,v0}
    0.0 ,   //t0=0
    T ,     //max time
    timestep , //length of each step
    save_step //User defined save data function
);
```

# Does it work

- ▶ Test, same proton in a solenoid use  $\theta = 60^\circ$  reference, had:

$$R \approx 0.5 \text{ m} \sin(\theta) \approx 0.45 \text{ m} \quad T = \frac{2\pi}{\omega_c} \approx 10 \mu\text{s}$$

# Does it work

- ▶ Test, same proton in a solenoid use  $\theta = 60^\circ$  reference, had:

$$R \approx 0.5 \text{ m} \sin(\theta) \approx 0.45 \text{ m} \quad T = \frac{2\pi}{\omega_c} \approx 10 \mu\text{s}$$

- ▶ Compare Analytic, Euler, Runge-Kutta 4.

# Does it work

- ▶ Test, same proton in a solenoid use  $\theta = 60^\circ$  reference, had:

$$R \approx 0.5 \text{ m} \sin(\theta) \approx 0.45 \text{ m} \quad T = \frac{2\pi}{\omega_c} \approx 10 \mu\text{s}$$

- ▶ Compare Analytic, Euler, Runge-Kutta 4.
- ▶ Consider  $\theta = 60^\circ$  at different  $h$ .

# Does it work


- ▶ Test, same proton in a solenoid use  $\theta = 60^\circ$  reference, had:

$$R \approx 0.5 \text{ m} \sin(\theta) \approx 0.45 \text{ m} \quad T = \frac{2\pi}{\omega_c} \approx 10 \mu\text{s}$$

- ▶ Compare Analytic, Euler, Runge-Kutta 4.
- ▶ Consider  $\theta = 60^\circ$  at different  $h$ .
- ▶ Check error on  $|\vec{v}|$ ,  $R = \sqrt{y^2 + z^2}$  and  $x(t)$ .

# At a glance, 3D view


$$h = t_{i+1} - t_i = 0.01 \mu\text{s}$$



3129 steps

# At a glance, 3D view


$$h = t_{i+1} - t_i = 0.1 \mu\text{s}$$



312 steps

# At a glance, 3D view

$$h = t_{i+1} - t_i = 1.0 \mu\text{s}$$




31 steps.




# At a glance, front view, no border

Euler method, front-view




# At a glance, front view, no border


RK4, front-view




# Constant radius?



# Constant radius?



# Error as function of $h$



# Adaptive step size, why


- ▶  $h$  must be small “enough”

# Adaptive step size, why

- ▶  $h$  must be small “enough”
- ▶ Hard to pick, and may change:

# Adaptive step size, why


- ▶  $h$  must be small “enough”
- ▶ Hard to pick, and may change:
- ▶ Inhomogeneous fields (here, a true dipole)





# Adaptive step size, why


- ▶  $h$  must be small “enough”
- ▶ Hard to pick, and may change:
- ▶ Inhomogeneous fields (here, a true dipole)
- ▶ Time dependent fields (here the cyclotron, bad example)



Ernest O. Lawrence, 1934, U.S. Patent 1,948,384; image in Public Domain.

# Adaptive step size, why


- ▶  $h$  must be small “enough”
- ▶ Hard to pick, and may change:
- ▶ Inhomogeneous fields (here, a true dipole)
- ▶ Time dependent fields (here the cyclotron, bad example)
- ▶ Let the computer pick  $h$ .



# Example, magnetic dipole

- True dipole:

$$\vec{B} = \frac{\mu_0}{4\pi r^3} \left[ 3\hat{r}(\vec{m} \cdot \hat{r}) - \vec{m} \right].$$




# Example, magnetic dipole

- True dipole:

$$\vec{B} = \frac{\mu_0}{4\pi r^3} \left[ 3\hat{r}(\vec{m} \cdot \hat{r}) - \vec{m} \right].$$

- Weak field, little change, long steps.



Arbitrarily set

$$\frac{\mu_0}{4\pi} |\vec{m}| = 0.155 \text{ T/m}^3.$$


Protons with speed around  
10 000 m/s

# Example, magnetic dipole

- True dipole:

$$\vec{B} = \frac{\mu_0}{4\pi r^3} \left[ 3\hat{r}(\vec{m} \cdot \hat{r}) - \vec{m} \right].$$

- Weak field, little change, long steps.
- strong field, large change, short steps.



Arbitrarily set

$$\frac{\mu_0}{4\pi} |\vec{m}| = 0.155 \text{ T/m}^3.$$


Protons with speed around  
10 000 m/s

# Example, magnetic dipole

- ▶ True dipole:

$$\vec{B} = \frac{\mu_0}{4\pi r^3} \left[ 3\hat{r}(\vec{m} \cdot \hat{r}) - \vec{m} \right].$$

- ▶ Weak field, little change, long steps.
- ▶ strong field, large change, short steps.
- ▶ No analytical solution (afaik.)



Arbitrarily set

$$\frac{\mu_0}{4\pi} |\vec{m}| = 0.155 \text{ T/m}^3.$$

Protons with speed around  
10 000 m/s

# Runge-Kutta Adaptive step size, how

- ▶ Reduce  $h$  until the “error” is small enough

# Runge-Kutta Adaptive step size, how

- ▶ Reduce  $h$  until the “error” is small enough
- ▶ Use 2 different order methods,  $\mathbf{x}^{(p+1)}(t_{i+1})$ ,  $\mathbf{x}^{(p)}(t_{i+1})$ .



# Runge-Kutta Adaptive step size, how

- ▶ Reduce  $h$  until the “error” is small enough
- ▶ Use 2 different order methods,  $\mathbf{x}^{(p+1)}(t_{i+1})$ ,  $\mathbf{x}^{(p)}(t_{i+1})$ .
- ▶ Approximate “Error” as  $\mathbf{E} = |\mathbf{x}^{(p+1)}(t_{i+1}) - \mathbf{x}^{(p)}(t_{i+1})|$ .

# Runge-Kutta Adaptive step size, how

- ▶ Reduce  $h$  until the “error” is small enough
- ▶ Use 2 different order methods,  $\mathbf{x}^{(p+1)}(t_{i+1})$ ,  $\mathbf{x}^{(p)}(t_{i+1})$ .
- ▶ Approximate “Error” as  $\mathbf{E} = |\mathbf{x}^{(p+1)}(t_{i+1}) - \mathbf{x}^{(p)}(t_{i+1})|$ .
- ▶ Adjust step size to keep the error(s) small (Implementations differ!).

Dormand, J. R.; Prince, P. J. (1980), "A family of embedded Runge-Kutta formulae", Journal of Computational and Applied Mathematics

(1)

# Runge-Kutta Dormand Prince 5 (4)

- ode45 in Matlab, `scipy.solve_ivp` in Python ,  
`RungeKutta_dopri5` in `boost::odeint`.

$$\mathbf{X}^{(5)}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j^{(5)} \mathbf{k}_j$$

$$\mathbf{X}^{(4)}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j^{(4)} \mathbf{k}_j.$$

$$\mathbf{k}_i = f_{ode}(\mathbf{X}(t_i) + h \sum_j^{i-1} a_{ki} \mathbf{k}_j, t_i + c_3 h).$$

# Runge-Kutta Dormand Prince 5 (4)

- ▶ ode45 in Matlab, `scipy.solve_ivp` in Python ,  
`RungeKutta_dopri5` in `boost::odeint`.

$$\mathbf{X}^{(5)}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j^{(5)} \mathbf{k}_j$$

$$\mathbf{X}^{(4)}(t_{i+1}) - \mathbf{X}(t_i) = h \sum_{j=1}^m b_j^{(4)} \mathbf{k}_j.$$

$$\mathbf{k}_i = f_{ode}(\mathbf{X}(t_i) + h \sum_{j=1}^{i-1} a_{ji} \mathbf{k}_j, t_i + c_i h).$$

- ▶ 7  $\mathbf{k}_i$ 's (actually 6 by clever re-usage).  
Dormand, J. R.; Prince, P. J. (1980), "A family of embedded Runge-Kutta formulae", Journal of Computational and Applied Mathematics

# Butcher Tableau of Dormand Prince (5) 4

$c_i$	$a_{ij}$	...						
0								
$\frac{1}{5}$	$\frac{1}{5}$							
$\frac{3}{10}$	$\frac{3}{40}$	$\frac{9}{40}$						
$\frac{4}{5}$	$\frac{40}{45}$	$-\frac{56}{15}$	$-\frac{32}{9}$					
$\frac{5}{8}$	$\frac{19372}{6561}$	$-\frac{25360}{2187}$	$\frac{64448}{6561}$	$-\frac{212}{729}$				
$\frac{9}{8}$	$\frac{9017}{3168}$	$-\frac{355}{33}$	$\frac{46732}{5247}$	$\frac{49}{176}$	$-\frac{5103}{18656}$			
1	$\frac{35}{384}$	0	$\frac{500}{1113}$	$\frac{125}{192}$	$-\frac{2187}{6784}$	$\frac{11}{84}$		
$/b^{(5)}$	$\frac{35}{384}$	0	$\frac{500}{1113}$	$\frac{125}{192}$	$-\frac{2187}{6784}$	$\frac{11}{84}$	0	
$/b^{(4)}$	$\frac{5179}{57600}$	0	$\frac{7571}{16695}$		$\frac{393}{640}$	$-\frac{92097}{339200}$	$\frac{187}{2100}$	$\frac{1}{40}$

# Runge-Kutta Dormand Prince 5 (4)

- Step size correction (Dormand Prince):

$$h_{new} = 0.9h_{old} \left[ \frac{\delta}{||E||} \right]^{\frac{1}{p+1}}$$

# Runge-Kutta Dormand Prince 5 (4)

- Step size correction (Dormand Prince):

$$h_{new} = 0.9h_{old} \left[ \frac{\delta}{||E||} \right]^{\frac{1}{p+1}}$$

- Step size correction (Me):

$$h_{new} = \min_j \left( 0.9h_{old} \left[ \frac{\delta_j}{E_j} \right]^{\frac{1}{p}} \right), \quad E_j > \delta_j : \text{reject}$$

$$\delta_j = \min(\delta_{abs}, |\mathbf{X}_j(t_i)|\delta_{rel}) \sqrt{\frac{h_{old}}{T}}.$$

# Runge-Kutta Dormand Prince 5 (4)

- Step size correction (Dormand Prince):

$$h_{new} = 0.9h_{old} \left[ \frac{\delta}{||E||} \right]^{\frac{1}{p+1}}$$

- Step size correction (Me):


$$h_{new} = \min_j \left( 0.9h_{old} \left[ \frac{\delta_j}{E_j} \right]^{\frac{1}{p}} \right), \quad E_j > \delta_j : \text{reject}$$

$$\delta_j = \min(\delta_{abs}, |\mathbf{X}_j(t_i)|\delta_{rel}) \sqrt{\frac{h_{old}}{T}}.$$

- Scale by step size  $\frac{h_{old}}{T}$ , "Fail safe"  $\sqrt{\dots}$ .  
Dormand, J. R.; Prince, P. J. (1980), "A family of embedded Runge-Kutta formulae", Journal of Computational and Applied Mathematics




# Does it work?




My version relative and absolute error  $10^{-6}$ . 94 steps (+ 14 rejected).

# Does it work?




Odeint library relative and absolute error  $10^{-7}$ . 92 steps.

# Does it work?




Does it work?

## Adaptive timesteps




My version, adaptive step size.

## Another curious result




$T = 0.2 \text{ ms}$

## Another curious result



$T = 0.3 \text{ ms}$


## Another curious result



$$T = 0.6 \text{ ms}$$

Magnetic “mirror” or “bottle”.


# Another curious result



Wikipedia user WikiHelper2134 , Public Domain.



## Another curious result



Tandem Mirror Experiment, The Lawrence Livermore National Laboratory, 1978.

# Conclusion

- ▶ Simulating particles in electric and magnetic fields.

# Conclusion


- ▶ Simulating particles in electric and magnetic fields.
- ▶ Numerically solving ordinary differential equations
- ▶ Reasonable agreement with known results.
- ▶ Can easily be generalized to other systems.

# Conclusion

- ▶ Simulating particles in electric and magnetic fields.
- ▶ Numerically solving ordinary differential equations
- ▶ Reasonable agreement with known results.
- ▶ Can easily be generalized to other systems.
- ▶ Limitation, simulations are not experiments.

# Example, cyclotron


- Electric field accelerates, magnetic contains.



Ernest O. Lawrence, 1934, U.S.  
Patent 1,948,384; image in  
Public Domain.

# Example, cyclotron


- ▶ Electric field accelerates, magnetic contains.
- ▶ Single gap, oscillating field.



Ernest O. Lawrence, 1934, U.S.  
Patent 1,948,384; image in  
Public Domain.

# Example, cyclotron

- ▶ Electric field accelerates, magnetic contains.
- ▶ Single gap, oscillating field.
- ▶ Uses classical Cyclotron frequency




Ernest O. Lawrence, 1934, U.S.  
Patent 1,948,384; image in  
Public Domain.

# Example, cyclotron

- ▶ Electric field accelerates, magnetic contains.
- ▶ Single gap, oscillating field.
- ▶ Uses classical Cyclotron frequency
- ▶ Analytical final speed, in principle path.

$$\frac{R|q|B}{m} = v_{\perp}$$




Ernest O. Lawrence, 1934, U.S. Patent 1,948,384; image in Public Domain.




# can it be simulated

- ▶ with fixed step size, looks bad 4999 points




# can it be simulated

- ▶ with fixed step size, looks bad 4999 points
- ▶ my adaptive method, error:  $10^{-6}$
- ▶ Looks great but 2 million points.



# can it be simulated

- ▶ with fixed step size, looks bad 4999 points
- ▶ my adaptive method, error:  $10^{-6}$
- ▶ Looks great but 2 million points.
- ▶ odeint library



# can it be simulated

- ▶ with fixed step size, looks bad 4999 points
- ▶ my adaptive method, error:  $10^{-6}$
- ▶ Looks great but 2 million points.
- ▶ odeint library
- ▶ non-continuous ode are bad.

