

67 - Identity UserManager and SignInManager

За да въведем частни параметри като град и пол, използваме наш custom IdentityUser class, който вграждаме като generic parameter:

UserManager & SignInManager

services

UserManager<IdentityUser>

- CreateAsync
- DeleteAsync
- UpdateAsync
- Etc...

methods

SignInManager<IdentityUser>

- SignInAsync
- SignOutAsync
- IsSignedIn
- Etc...

```
AccountController.cs | RegisterViewModel.cs | HomeController.cs
EmployeeManagement.Controllers.AccountContro
using EmployeeManagement.ViewModels;
using Microsoft.AspNetCore.Mvc;

namespace EmployeeManagement.Controllers
{
    0 references
    public class AccountController : Controller
    {
        [HttpGet]
        0 references
        public IActionResult Register()
        {
            return View();
        }
        [HttpPost]
        0 references
        public IActionResult Register(RegisterViewModel model)
        {
            return View();
        }
    }
}
```

from parameter type parameter name
insert class

Създаваме нов ctor, съответно извикваме необходимото namespace + private fields:

```

1  using EmployeeManagement.ViewModels;
2  using Microsoft.AspNetCore.Identity;
3  using Microsoft.AspNetCore.Mvc;
4
5  namespace EmployeeManagement.Controllers
6  {
7      1 reference
8      public class AccountController : Controller
9      {
10         private readonly UserManager<IdentityUser> userManager;
11         0 references
12         ctor public AccountController(UserManager<IdentityUser> userManager,
13                                     SignInManager<IdentityUser> signInManager)
14         {
15             this.userManager = userManager;
16         }
17     }
18 }

```

Ctrl. - no private field

В част [101 – Async and await in C# example](#) се обяснява по-подробно за Async:

Async = asynchronous (Несинхронен) метод, който трябва да се избягва. Той изисква променливата да бъде тип await, а типът на върнатия резултат Task<>

Използваме имейл за име на потребителя и отделно неговия имейл.

```

[HttpPost]
0 references
public async Task<IActionResult> Register(RegisterViewModel model)
{
    if (ModelState.IsValid) Tag helper in view asp-validation-for let's user name = email email = email
    {
        var user = new IdentityUser { UserName = model.Email, Email = model.Email };
        var result = await userManager.CreateAsync(user, model.Password);

        if (result.Succeeded) bool Cookie: session = false permanent = true
        {
            await signInManager.SignInAsync(user, isPersistent: false);
            return RedirectToAction("index", "home");
        }

        foreach (var error in result.Errors) else display all errors from validation errors
        {
            ModelState.AddModelError(string.Empty, error.Description);
        }
    }
}

```

Използваме временни бисквитки за сесията, които се унищожават при затваряне на браузъра.

```

using EmployeeManagement.ViewModels;
using Microsoft.AspNetCore.Identity;
using Microsoft.AspNetCore.Mvc;
using System.Threading.Tasks;

namespace EmployeeManagement.Controllers
{
    public class AccountController : Controller
    {
        private readonly UserManager<IdentityUser> userManager;
        private readonly SignInManager<IdentityUser> signInManager;
    }
}

```

```

public AccountController(UserManager<IdentityUser> userManager,
    SignInManager<IdentityUser> signInManager)
{
    this.userManager = userManager;
    this.signInManager = signInManager;
}

[HttpGet]
public IActionResult Register()
{
    return View();
}

[HttpPost]
public async Task<IActionResult> Register(RegisterViewModel model)
{
    if (ModelState.IsValid)
    {
        var user = new IdentityUser { UserName = model.Email, Email =
model.Email };
        var result = await userManager.CreateAsync(user, model.Password);

        if (result.Succeeded)
        {
            await signInManager.SignInAsync(user, isPersistent: false);
            return RedirectToAction("index", "home");
        }

        foreach (var error in result.Errors)
        {
            ModelState.AddModelError(string.Empty, error.Description);
        }
    }

    return View(model);
}
}

```

При изпращане на празни полета или елементарна парола като abc извежда грешки:

User Registration		User Registration	
- The Email field is required. - The Password field is required.		- Passwords must be at least 6 characters. - Passwords must have at least one digit ('0'-'9'). - Passwords must have at least one lowercase ('a'-'z'). - Passwords must have at least one uppercase ('A'-'Z').	
Email		Email	david@abv.bg
The Email field is required.			
Password		Password	
The Password field is required.			
Confirm password		Confirm password	
Register		Register	

User Registration

- Password and confirmation password do not match.
- Passwords must have at least one non alphanumeric character.

Email	Email
david@abv.bg	david@abv.bg
Password	Password
Confirm password	Confirm password
Password and confirmation password do not match.	
Register	Register

Username

Password

Интересното е, че в БД, паролата е в криптиран вид.

[illegible]

Register POST Action

```
[HttpPost]
public async Task<IActionResult> Register(RegisterViewModel model)
{
    if (ModelState.IsValid)
    {
        var user = new IdentityUser
        {
            UserName = model.Email,
            Email = model.Email
        };

        var result = await userManager.CreateAsync(user, model.Password);

        if (result.Succeeded)
        {
            await signInManager.SignInAsync(user, isPersistent: false);
            return RedirectToAction("index", "home");
        }

        foreach (var error in result.Errors)
        {
            ModelState.AddModelError(string.Empty, error.Description);
        }
    }

    return View(model);
}
```

Направих опит вместо string.Empty, да бъде просто "" – работи и по двата начина

Save password?

Username

Password

Save

Never

```
foreach (var error in result.Errors)
{
    ModelState.AddModelError("", error.Description);
}
```