

**Print Resolution:** No

**Application(s):** Automated Print & Apply, Data Communications Labeling, Panel Identification, Wire & Cable Marking

**Max Labels Per Day:** 7,000+ labels/day

**Hours of Operation:** 24 hrs / 7 days

**Max Label Width:** 2.000"

**Min Label Width:** 0.250" (6.35 mm)

**Max Print Width:** 2.000"

**Max Label Height:** 3.000" (76.20 mm)

**Min Label Height:** 0.750" (19.05 mm)

**Max Wire Diameter:** 0.600" (15.24 mm)

**Min Wire Diameter:** 0.060" (1.52 mm)

**Label Roll Diameter:** Cartridge

**Operating System:** Windows® 2000/NT/XP

**Machine Cycle Time:** 4.5-5.0 Seconds

**Applicator Cycle Time:** 4.5 - 5 seconds

**Color Capability:** Single Color Printing

**Bar Code Type:** 2D and 1D (Linear)

**PC Connectivity:** Yes

**Peripheral Printing:** Yes

**Stand Alone Printing:** No

**Connectivity Options:** USB, Serial RS-232C, Ethernet, PCMCIA, CompactFlash®

**Portability:** No

**Memory:** 8MB Internal Memory

**Memory Card:** 64MB RAM included and expandable using PCMCIA or CompactFlash

**Electrical:** 90-264 VAC, 47-63 Hz

**Operating Temperature:** 50° to 105°F (10° to 41°C)

**Storage Transportation:** 0° to 140° F (-18° to 60° C)

**Dimensions:** 17.75" H x 14.50" W x 22.50"D (450.9mm x 368.3mm x 571.5mm)

**Weight:** 85lbs (38.5 kg)