

BP-PR200 PLUS
BP-PR300 PLUS
BP-PR600 PLUS



Specifications

RoHS Compatibility:	Yes
Print Resolution:	300 dpi
Print Speed:	up to 9.8 inches per second
Print Technology:	Thermal Transfer
Application(s):	Wire & Cable Marking, Data Communications Labeling, Wire & Cable Marking - ADM, General & Industrial Labeling
Max Labels Per Day:	5,000 labels/day
Hours of Operation:	12hrs / 5days
Max Label Width:	4.560"
Min Label Length:	0.200"
Max Print Width:	4.150"
Max Print Length:	78"
Max Liner Width:	4.720"
Min Liner Width:	1.000"
Color Capability:	Single Color Printing
Bar Code Type:	2D and 1D (Linear)
PC Connectivity:	Yes
Peripheral Printing:	Yes
Stand Alone Printing:	No
Connectivity Options:	Serial, USB 2.0 and Ethernet 10/100
Portability:	No
Memory:	64MB
Materials Supported:	Cont. and Heatex, Notched, Die Cut, Sleeve
Continuous vs Die Cut Labels:	Can print both continuous and die cut labels.
Options:	Peel and Present
Dimensions:	10.800 "H x 9.500 "W x 17.600 "D
Weight:	20 lbs
Warranty:	12 Months - See Terms and Conditio