

Wraptor™ Wire ID Printer



Specifications

Print Resolution:	No
Application(s):	Automated Print & Apply, Data Communications Labeling, Panel Identification, Wire & Cable Marking
Max Labels Per Day:	7,000+ labels/day
Hours of Operation:	24 hrs / 7 days
Max Label Width:	2.000"
Min Label Width:	0.250" (6.35 mm)
Max Print Width:	2.000"
Max Label Height:	3.000" (76.20 mm)
Min Label Height:	0.750" (19.05 mm)
Max Wire Diameter:	0.600" (15.24 mm)
Min Wire Diameter:	0.060" (1.52 mm)
Label Roll Diameter:	Cartridge
Operating System:	Windows® 2000/NT/XP
Machine Cycle Time:	4.5-5.0 Seconds
Applicator Cycle Time:	4.5 - 5 seconds
Color Capability:	Single Color Printing
Bar Code Type:	2D and 1D (Linear)
PC Connectivity:	Yes
Peripheral Printing:	Yes
Stand Alone Printing:	No
Connectivity Options:	USB, Serial RS-232C, Ethernet, PCMCIA, CompactFlash®
Portability:	No
Memory:	8MB Internal Memory
Memory Card:	64MB RAM included and expandable using PCMCIA or CompactFlash
Electrical:	90-264 VAC, 47-63 Hz
Operating Temperature:	50° to 105°F (10° to 41°C)
Storage Transportation:	0° to 140° F (-18° to 60° C)
Dimensions:	17.75" H x 14.50" W x 22.50"D (450.9mm x 368.3mm x 571.5mm)
Weight:	85lbs (38.5 kg)