



K.D.ENGINEERS INDIA PVT. LTD.

www.kdengineers.in
Plot No. 56A , Gali No. 6 Krishna Colony Industrial Area
Sector -25, Faridabad - 121004
Mobile/Whatsapp: +91-9953336623 L_malik_kdengrs@gmail.com

Terminal Crimping Machine

Name	2T European Type Terminal Crimping Machine		
NO.	Specification		
1	2T European Type Terminal Crimping Machine		
	Model	KDE-2TS	
	Power supply	AC 220V	
	Crimping force	2T	
	Motor power	0.75kw	
	Stroke	30mm	
	Size	340*300*736mm	
	Weight	80KG	
	Applicable mold	OTP mold(applicator)	
	Applicable wire	Less than 3.3mm ² (12AWG). Depends on actual terminal.	
	Crimping speed	Adjustable	
	Display	LCD, English display	
	Crimping force adjustment	Scale knob	

Feature

- 1) Adopt ultra-quiet and energy-saving design.
- 2) Equipped with safety cover.
- 3) LCD screen, can set the crimping speed.
- 4) 30mm/40mm stroke is optional.
- 5) The slider and the slideway adopt needle roller cage bearings, which do not need to refuel and completely prevent jamming.
- 6) The closed stroke is adjustable (10mm, the adjustment unit is 0.02mm).
- 7) The upper knob can adjust the crimping force, the operation is more convenient.
- 8) Fast cassette mold base, easy to change mold, saving time.
- 9) The mold base is highly interchangeable, and can be customized to install with Japanese mold, Korean mold, European mold.

Pictures



Crimping force
adjustment



Movable protective cover



LCD display

PROMOTION Cutting Stripping Machine, pls contact us for further information



1-4 cores cable
cutting stripping
machine Stripping
outer and inner skin at
one time



Auto feeding loose terminal crimping machine



Full auto wire cut strip crimp machine