



K.D.ENGINEERS INDIA PVT. LTD.

Plot No. 56A , Gali No. 6 Krishna Colony Industrial Area,

Sector -25, Faridabad - 121004

Mobile/Whatsapp: +91-9953336623 , +91-9350962939 E-mail: info@kdengineers.in / kdengrs@gmail.com



SPECIFICATIONS

Name	Wire tape spot winding machine		
	Model	KDE-5760	
	Air pressure	0.4-0.6MPa	
	Machine size	450*350*500mm, 48kg	
	Tape type	PVC / velvet / acetic acid tape	
	Power	AC220V 50HZ 200W	
	Cable type	Single wire or multiple wire bundles after intermediate point crimping	
	Work efficiency	24/min	
	Winding position accuracy	±3mm	
	Winding overlap accuracy	±2mm, depends on product	
	Cable length required	≥100mm	
	Cable diameter	3-6mm	
	Tape width	10-45mm	
	Tape length	30-35mm	
	Structure	Drum diameter 65mm, brush width 57mm.	

Feature

This equipment is suitable for wire harness winding after intermediate point crimping and general bundling of wires.

Adopting the winding structure with a drum and a brush, it can correspond to a wide range of tape widths and wire harness diameters.

Using the copper wheel feeding principle, the structure is stable and reliable, the operation is simple and convenient, and the labor intensity of workers can be significantly reduced.