



SPECIFICATIONS

KDE -S200

Terminal cross section

	Parameters Name	Parameters Datas
	Motor speed (cut/grind)	2800RPM/1400 RPM
	Cutting range diameter	0.01sqmm---70sqmm
	Cutting speed	Manual
	Cutting wheel diameter	OD ϕ 110 x Thickness 0.5 x hole ϕ 20mm
	Etched part	Professional Terminal Section Cleaning Fluid
	Corrosion Time	5 to 30 sec
	Grinding speed	Manual (adjustable)
	Grinding disc diameter	100mm, roughness 1000# 2000# optional
	Dedicated terminal clamp	1PCS
	Voltage	220V/50HZ
	Corrosion part Corrosion time	5-30sec
	Imaging system	1/3" professional CCD high-definition imaging system(3M pixels (CCD gigabit network. The card access screen is clear and transmission speed Fast and stable))
	Terminal dedicated analysis measurement	1PCS
	Magnification:	20X~200X continuous zoom
	Optical lens	0.7~4.5X (Hong Kong joint venture) Pumisico End stop
	Software version	version V3.2, enhanced measurement tools including compression ratio, etc.
	Lighting source	All white adjustable LED lighting device (cold light)
	Warranty period	1 year

Introduction

The terminal cross section analyzer is a precision testing and analysis equipment for the quality inspection of the wiring harness industry.

The analyzer system consists of an integrated terminal cutting and grinding equipment, optical sampling imported from Japan, corrosion cleaning, and cross-sectional image acquisition system., wiring harness terminal picture measurement and analysis system, using cutting and grinding integrated equipment, the latest patented technology, cutting and grinding is completed at one time, which fully guarantees the flatness requirements of the terminal. The complete detection system can complete the processing and analysis of a terminal within 5 minutes, which greatly improves the speed of sub-section quality inspection.

The operation is simple, convenient and fast, adopting Japanese high-definition image acquisition system, accurate measurement and analysis escort your production.

Feature

1. 00# marble base: To ensure the parallel installation of the motor and the guide rail, the equipment is more stable.
2. Ball screw driven the movement: There is no cutting shaking, and it is easy to operate manually.
3. Linear wide guide: To ensure the straightness of the movement, to ensure the stability of cutting.
4. Stainless steel fixture: Versatility and corrosion resistance.
5. Adjustable workbench.
6. High precision standard glass sheet, accuracy 1um, ensure the measurement accuracy.
7. Velcro Abrasive Sandpaper: Quick and easy replacement.

