

:matches() CSS pseudo-class - WD

The `:matches()` (formerly `:any()`) pseudo-class checks whether the element at its position in the outer selector matches any of the selectors in its selector list. It's useful syntactic sugar that allows you to avoid writing out all the combinations manually as separate selectors. The effect is similar to nesting in Sass and most other CSS preprocessors.

Usage

Global

% of all users

30

?

13.14% + 78.39% = 91.53%

unprefixed:

13.14% + 62.48% = 75.62%

Current aligned	Usage relative	Date relative	Apply filters	Show all	?								
IE	Edge	Firefox	Chrome	Safari	Opera	iOS Safari	Opera Mini	Android Browser	Blackberry Browser	Opera Mobile	Chrome for Android	Firefox for Android	
				3.1-4									
			4-14	5	10-12.1	3.2-6.1							
		2-3.6	115-64	15.1-8	115-51	17-8.4		2.1-3					
6-10	12-17	34-65	2465-72	29-11.1	1452-57	29-11.4		14-4.4.4	7	12-12.1			
11	18	366	2473	212	1458	212.1	all	167	110	146	1471	364	
		367-68	2474-76	212.1-TP		212.2							

CSS nesting drafts

- Селектор отношений `:has()`

Задаёт стили родительскому селектору, который имеет перечисленных потомков

Черновик рабочей группы – www.w3.org/TR/selectors-4/#relational

```
/* Все ссылки, в которых есть <span> */  
a:has(> span)
```

```
/* Все секции, в которых нет заголовков */  
section:not(:has(h1, h2, h3, h4, h5, h6))
```