

OIL INDIA LIMITED (OIL) - DULIAJAN HEADQUARTERS

DOCUMENT: DDR_W093_142.pdf (Daily Drilling Report (DDR))

WELL ID: W-093 | FORMATION: Barail Coal-Shale | INTERVAL: 3,410 m â 3,448 m

DATE: 2026-01-19 | AUTHOR: Sr. Drilling Supt. R.K. Borgohain (OIL Duliajan)

SHA-256 INTEGRITY HASH: cdc24cd09837fca22cbd2126a8e4b5f55b812853d1c03393bfd3dac05e7c4ce0

EXTRACTED EVENT: Mud Loss @ 3428 m

SEVERITY: CRITICAL | LOSS RATE: 15.4 bbl/hr

MITIGATION: 25 bbl High-Concentration LCM Pill (15 ppb Medium Nut-Plug + 10 ppb Coarse Flake M

SUMMARY: Daily Drilling Report #142 for Well Nahorkatiya-093 documenting severe 15.4 bbl/hr mud losses at 3,428 m in Barail Coal-Shale and successful stabilization using 25 bbl Nut-Plug/Mica/CaCO3 LCM pill. VERBATIM OPERATIONAL LOG: 08:30 - 11:00 HRS: Drilling 8-1/2" hole in Barail Coal-Shale from 3,418 m to 3,428 m with 1.24 sg KCl-Polymer mud. At 3,428 m, encountered sudden drilling break (ROP jumped from 18.2 to 27.4 m/hr) followed by 180 psi SPP drop and dynamic mud loss of 15.4 bbl/hr into micro-cleated coal fractures. Reduced flow rate from 2,150 LPM to 1,750 LPM. Spotted 25 bbl LCM pill (15 ppb Medium Nut-Plug + 10 ppb Coarse Flake Mica + 8 ppb Sized CaCO3 150-micron) across 3,415-3,448 m. Soaked for 45 mins under 150 psi squeeze pressure. Full returns re-established; dynamic seepage <0.8 bbl/hr.

SECURITY WATERMARK: CONFIDENTIAL - OIL INDIA LTD - eRTMAC-NWIS VERIFIED