

OIL INDIA LIMITED (OIL) - DULIAJAN HEADQUARTERS

DOCUMENT: MudLog_W098_Barail.pdf (Geological Mud Logging Report)

WELL ID: W-098 | FORMATION: Barail Coal-Shale & Kopili Shale | INTERVAL: 3,100 m â 4,010 m

DATE: 2025-11-24 | AUTHOR: Geolog / OIL Mud Logging Unit #07

SHA-256 INTEGRITY HASH: 973ef34924d81b49f48c17b8c966c66ea4902d9e2cd1aa5e4347fbbc4b3a5576

EXTRACTED EVENT: Mud Loss & Connection Gas @ 3405 m

SEVERITY: HIGH | LOSS RATE: 14.2 bbl/hr

MITIGATION: 25 bbl Sized CaCO3 (50-150 micron) + 15 ppb Mica pill; Driller's Method well kill

SUMMARY: Final Mud Logging & Pore Pressure Report for Nahorkatiya-East-098 covering Barail coal fracture losses (3,405 m) and Kopili Shale high-pressure gas kick (3,790 m). VERBATIM OPERATIONAL LOG: LITHOLOGY & GAS LOG (3,400â 3,445 m): Cuttings consist of 45% black vitreous sub-bituminous coal with orthogonal cleat planes, 35% dark grey fissile carbonaceous shale, and 20% fine argillaceous sandstone. At 3,405 m MD (3,368 m TVD), mud pit active sensor recorded 14.2 bbl/hr dynamic loss. Pumped pre-mixed 25 bbl CaCO3 (50-150 micron) + 15 ppb Mica pill; fracture network bridged effectively within 65 minutes.

SECURITY WATERMARK: CONFIDENTIAL - OIL INDIA LTD - eRTMAC-NWIS VERIFIED