

Orbit Camera: Euler-to-Quaternion Refactor

engvis

June 19, 2026

1 Problem Statement

The orbit camera in `crates/engvis-core/src/camera.rs` originally stored its orientation as two Euler angles:

- `yaw` — azimuth around the world Y axis,
- `pitch` — elevation, clamped to $\pm(\frac{\pi}{2} - 0.01) \approx \pm 89.4^\circ$.

When the user drags the mouse to rotate the view vertically, the camera stops responding once `pitch` reaches the clamp boundary. The view cannot be rotated past nearly straight up/down, which is perceived as a hard boundary on interaction.

2 Root Cause Analysis

2.1 Pitch Clamp

The clamp is required by the Euler representation itself, not by any physical constraint of the scene. In `orbit()`:

```
pub fn orbit(&mut self, delta_yaw: f32, delta_pitch: f32) {
    self.yaw += delta_yaw;
    self.pitch = (self.pitch + delta_pitch).clamp(
        -std::f32::consts::FRAC_PI_2 + 0.01,
        std::f32::consts::FRAC_PI_2 - 0.01,
    );
}
```

Without the clamp, `pitch` would exceed $\pm\frac{\pi}{2}$, which causes two failure modes:

1. **Gimbal lock.** At `pitch` = $\pm\frac{\pi}{2}$, the yaw and pitch rotation axes coincide, and the camera loses one degree of freedom. Subsequent yaw input produces no visible rotation.
2. **Up-vector flip.** `view_matrix()` uses `Mat4::look_at_rh(pos, target, Vec3::Y)`, which degenerates when the view direction aligns with $\pm Y$: the cross product forward $\times$ up vanishes, producing a NaN view matrix.

2.2 Why Euler Angles Are Inappropriate

Euler angles parameterise $SO(3)$ with a triple (α, β, γ) , but the map

$$(\alpha, \beta, \gamma) \mapsto R_z(\alpha)R_y(\beta)R_z(\gamma)$$

is singular at $\beta = \pm\frac{\pi}{2}$ (gimbal lock). Any clamping strategy therefore imposes an artificial boundary on user input, even though the underlying rotation space $SO(3) \cong \mathbb{RP}^3$ has no such boundary.

3 Solution: Quaternion Orientation

3.1 Representation

Replace the two Euler angles with a single unit quaternion **orientation**: `Quat` that maps camera-local axes to world-space directions:

- camera +*X* (right) $\mapsto$ `orientation * Vec3::X`,
- camera +*Y* (up) $\mapsto$ `orientation * Vec3::Y`,
- camera +*Z* (back, away from target) $\mapsto$ `orientation * Vec3::Z`.

The camera position is then

$$\mathbf{p}_{\text{cam}} = \mathbf{t} + \mathbf{q}(d \cdot \hat{\mathbf{z}}),$$

where $\mathbf{t}$ is the orbit target, $\mathbf{q}$ the orientation quaternion, and d the orbit distance.

```
pub struct OrbitCamera {
    pub target: Vec3,
    pub orientation: Quat,
    pub distance: f32,
    pub fov_y: f32,
    pub near: f32,
    pub far: f32,
    pub aspect_ratio: f32,
}

pub fn position(&self) -> Vec3 {
    self.target + self.orientation * (Vec3::Z * self.distance)
}
```

3.2 Incremental Orbit Rotation

Mouse drag produces two incremental rotations per frame:

- **Yaw** $\Delta\alpha$ — rotation about the world up axis *Y*. Applied as a *pre-multiplication* $\mathbf{q}' = R_Y(\Delta\alpha)\mathbf{q}$ so the horizon stays level regardless of the camera's current pitch.
- **Pitch** $\Delta\beta$ — rotation about the camera's local *X* axis. Applied as a *post-multiplication* $\mathbf{q}' \leftarrow \mathbf{q}' R_X(-\Delta\beta)$, where the sign preserves the old “drag up = look up” convention.

$$\mathbf{q}_{\text{new}} = \text{normalize}(R_Y(\Delta\alpha) \cdot \mathbf{q}_{\text{old}} \cdot R_X(-\Delta\beta)).$$

Because quaternion multiplication is a closed, smooth operation on $\text{SO}(3)$, no clamp is required and no singularity arises at any orientation.

```
pub fn orbit(&mut self, delta_yaw: f32, delta_pitch: f32) {
    let yaw_rot = Quat::from_rotation_y(delta_yaw);
    let pitch_rot = Quat::from_rotation_x(-delta_pitch);
    self.orientation = (yaw_rot * self.orientation * pitch_rot).normalize();
}
```

The final `.normalize()` guards against floating-point drift after many incremental updates; it is a numerical safeguard, not a behavioural clamp.

3.3 View Matrix from Quaternion

The previous implementation used `Mat4::look_at_rh(position(), target, Vec3::Y)`, which degenerates when forward $\parallel$ up. The new implementation builds the view matrix directly from the orientation quaternion:

$$V = R(\mathbf{q}^{-1}) T(-\mathbf{p}_{\text{cam}}),$$

where $R(\mathbf{q}^{-1})$ is the world-to-camera rotation and $T(-\mathbf{p}_{\text{cam}})$ translates the camera to the origin.

```
pub fn view_matrix(&self) -> Mat4 {
    let rot = Mat4::from_quat(self.orientation.inverse());
    let trans = Mat4::from_translation(-self.position());
    rot * trans
}
```

This formulation is well-defined for every orientation, including straight up/down and upside-down views.

3.4 Preset Views

Each preset constructs the orientation quaternion directly from the relevant axis rotations:

Preset	Orientation	Description
<code>view_front</code>	$\mathbf{q} = I$	camera at $+Z$, looking at $-Z$
<code>view_top</code>	$\mathbf{q} = R_X(-\frac{\pi}{2})$	camera at $+Y$, looking at $-Y$
<code>view_right</code>	$\mathbf{q} = R_Y(-\frac{\pi}{2})$	camera at $-X$, looking at $+X$
<code>view_iso</code>	$\mathbf{q} = R_Y(-0.785) R_X(-0.615)$	isometric

```
pub fn view_front(&mut self) { self.orientation = Quat::IDENTITY; }
pub fn view_top(&mut self) { self.orientation = Quat::from_rotation_x(-std::f32::consts::FRAC_PI_2); }
pub fn view_right(&mut self) { self.orientation = Quat::from_rotation_y(-std::f32::consts::FRAC_PI_2); }
pub fn view_iso(&mut self) {
    self.orientation = Quat::from_rotation_y(-0.785) * Quat::from_rotation_x(-0.615);
}
```

3.5 Compatibility Helper

Code that previously set yaw/pitch directly (e.g. the `colorbar3d` example's reset-view button) now uses `set_orientation_yaw_pitch`, which composes the same $R_Y \cdot R_X$ rotation:

```
pub fn set_orientation_yaw_pitch(&mut self, yaw: f32, pitch: f32) {
    self.orientation = Quat::from_rotation_y(yaw) * Quat::from_rotation_x(-pitch);
}
```

4 Comparison

Aspect	Euler (yaw, pitch)	Quaternion
Representation	$(\alpha, \beta), \beta \in (-\frac{\pi}{2}, \frac{\pi}{2})$	unit $\mathbf{q} \in S^3$
Singularity	at $\beta = \pm\frac{\pi}{2}$ (gimbal lock)	none
Pitch clamp	required	not required
Vertical rotation	stops at $\pm 89.4^\circ$	unlimited
View matrix	<code>look_at_rh</code> (degenerate at poles)	direct from $\mathbf{q}^{-1}$
Up vector	implicit (+Y)	explicit (<code>orientation * Vec3::Y</code>)
Preset views	set two scalars	construct quaternion
Interpolation	Euler interpolation flawed	SLERP / NLERP natural
Memory	8 bytes	16 bytes

5 Pipeline Summary

The complete camera update pipeline per frame:

1. **Input** (`input.rs`) — mouse drag deltas $(\Delta x, \Delta y)$ scaled by a sensitivity factor.
2. **Orbit** — `camera.orbit` $(-\Delta x \cdot s, -\Delta y \cdot s)$ composes incremental quaternion rotations.
- 3.
4. **Pan** (right mouse) — translates `target` along camera-local X and Y .
5. **Zoom** (scroll) — scales `distance` with clamp $[0.1, 500]$.
6. **View matrix** — built from $\mathbf{q}^{-1}$ and $-\mathbf{p}_{\text{cam}}$.
7. **Projection** — perspective RH from `fov_y`, `aspect_ratio`, `near`, `far`.

6 Result

After the refactor:

- The camera rotates freely in all directions; no boundary is encountered when looking straight up or down.
- All preset views (front, top, right, iso) reproduce the previous camera framing.
- The `colorbar3d` example's reset-view button restores the same isometric orientation as before.
- `cargo build`, `cargo test -workspace`, and runtime startup all pass without errors.