

---

# Thesis proposal

---

Nil Adell Mill  
January 2020

Institute of Neuroinformatics,  
ETH Zurich & Zurich University

## 1 Introduction & Background

Drug discovery—the process by which a potential new medicine is identified—is a complex process that encompasses the intersection of several fields (such as biology, statistics, chemistry or pharmacology). The entire process is a long and costly endeavor, with a typical time-frame of 10 to 20 years till market release and an estimated cost between 2 and 3 billion USD [Schneider, 2019, Scannell et al., 2012], with only 1 out of 10000 synthesized molecules obtaining market approval. Many of these dropouts happening at the early stages of the entire process. Subsequently, there is a need for tools that enable us to identify better drug candidates.

One of the most promising directions is to improve the *in-silico* methods, which are relatively cheap and quick, making them an interesting solution. *In-silico* simulations then cover two main aspects: **predictive modelling**, meaning modeling the dynamics of the human body—such that any effect relevant to the drug or the disease will be captured by it—and **generative modelling**, i.e. methods to generate good candidates by being effective at exploring the vast space of possible compounds, estimated to be on the order of  $10^{60}$  [Reymond et al., 2012]. Several computational approaches have been used over the years, from molecular dynamics simulations to data-driven statistical methods [Hung and Chen, 2014, Kuhn et al., 2016]. Among the possible approaches, deep learning (DL) has shown signs to be a potential game-changer in drug-discovery [Dargan et al., 2019].

DL has been able to capitalize on the exponential growth of data and the higher availability of computational resources. DL has had remarkable success in computer vision (CV) [Guo et al., 2016] and natural language processing (NLP) [Young et al., 2018], and has become the go-to solution for any problem in these two fields. For instance, in the case of CV, where we deal with images, a key element of any architecture’s success is the use of convolutional layers—one will mainly observe convolutional neural networks (CNNs) when analyzing the state of the art in CV—which introduces a structural prior based on the structure of the data [Fukushima, 1980, LeCun, 1989, Ulyanov D., Vedaldi A., 2018]. A similar approach can be proposed to we deal with biological and molecular data by leveraging their graph representations. Efforts in generalizing the convolution operator on non-euclidian structures have given rise to graph convolutional neural networks (GCNNs) [Wu et al., 2019]. GCNNs, then, pose an opportunity to drug discovery due to their capacity to deal natively with graph data [Sun et al., 2019].

Nevertheless, there is a set of shared challenges for *in-silico* models. One of them is unifying the different aspects of drug-discovery by incorporating all the relevant biological and chemical information when designing possible candidate molecules. An initial success story on that line is a recent paper [Zhavoronkov et al., 2019] where the authors describe a deep learning method by which they are able to discover, synthesize, and test in an animal model, inhibitors of discoidin domain receptor 1 (DDR1)—a kinase implicated in fibrosis—in less than two months.

Those promising results, albeit encouraging, are just the tip of the iceberg. There is still a long way until a model can satisfactorily capture the biological complexity of an arbitrary target and produce promising candidates. On top of that, there is an added dimension, as such model should account for the variability from patient to patient and be able to generate a molecule that accommodates for all the genotypic and phenotypic variants, or otherwise generate different candidates for each of the populations of interest. That is especially important for hypercomplex diseases, such as cancer, where a genotypically heterogeneous tumoral population

may appear within a single patient [Boland and Yurgelun, 2017]. These diverse tumor subpopulations may, in turn, react distinctly to a drug, leading to an evolutionary pressure that can complicate the treatment prognosis [Enriquez-Navas et al., 2015].

The aforementioned example illustrates the need for the development of models that can be conditioned based on a large set of biological factors, and meaningfully account for these when generating a compound or evaluating a compound’s effect. In other words, there is a need to adopt precision medicine methods.

Finally, from a more holistic perspective, it is of interest to develop multi-scale models that integrate a system’s complexity at all different levels. For instance, a model that can learn protein-compound interactions—commonly known as the docking problem—while at the same time use this information to predict effects of the introduction of the compound on the larger protein-protein interaction (PPI) network [Sun et al., 2019].

## Aim & Methods

The aim of this thesis has two distinct though interconnected objectives. On the one hand, to analyze how the explicit use of GCNNs may open new opportunities when dealing with biological and chemical data. On the other hand, to explore how modeling the biology at different scales (e.g. molecular structure v.s. molecular interaction network) may help to create better models, and, additionally, to evaluate how these different scales may be integrated.

The project would be based on the ideas about GCNNs for drug discovery in presented literature [Sun et al., 2019], which will be expanded and tested in a wider framework for drug design recently proposed in an article [Born et al., 2019]. In that context, two main areas of application appear. One of them is to re-design the generative model, for instance by reframing the variational autoencoders used for molecule generation to architectures that operate over graphs [Simonovsky and Komodakis, 2018, Li et al., 2018a, Li et al., 2018b]. The second area is to improve the predictive model, by finding better ways to assess the activity of these molecules and their relevance as drug candidates. In the specific case of the mentioned drug discovery framework, it is done by using a critic network [Manica et al., 2019], which can be expanded on a set of different fronts. Those would be: using structural data instead of SMILES<sup>1</sup> [Li et al., 2017, Do et al., 2019], using GCNNs on the PPI networks in a manner that allows for a more effective way to extract the information from them [Oskooei et al., 2019, Wang et al., 2019], or introducing particular scores (rewards) based in the interaction of the compound to certain targets [Yingkai Gao et al., 2018, Zhavoronkov et al., 2019] or the combination of the compound with other drugs [Zitnik et al., 2018]. All these possible changes to the critic model would be applied to different abstraction levels, that opens the door to integrating the representations learnt at those different levels in a single model [Ying et al., 2018, Ma and Zhang, 2019, Huang et al., 2019]. Furthermore, this integration could be then leveraged on the drug generation part of the framework.

The proposed ideas will be done in the context of designing anticancer compounds. The work will be done in collaboration with the Computational Systems Biology group at IBM Research (Zurich), currently part of the iPC consortium<sup>2</sup>. As part of such, an end goal of this project is for its results to help in the consortium efforts on pediatric cancer. For instance in contributing to the ongoing research in neuroblastoma, the most common type of cancer diagnosed on the first year of life [Maris, 2010].

## Data & Baselines

The data from this project will be obtained from multiple sources including, but not limited to, the Genomics of Drug Sensitivity in Cancer (GDSC) database [Yang et al., 2013], STRING and STICH, [Szklarczyk et al., 2019, Szklarczyk et al., 2016], DrugBank [Wishart, 2006], ChEMBL [Gaulton et al., 2017], PubChem [Kim et al., 2019] and ZINC 15 [Sterling and Irwin, 2015]. For the development of the models PyTorch [Paszke et al., 2019] will be used as the main framework, most likely alongside DeepChem<sup>3</sup>.

The novel predictive model will be evaluated against empirically measured properties of drugs in the mentioned data sources. Furthermore, the model’s performance will be compared to that of other models in the literature. For example, by comparing IC50 prediction values for cell-drug pairs (unseen during training) with the empirically measured values from the data sources, as done in [Oskooei et al., 2019, Joo et al., 2019,

---

<sup>1</sup><http://opensmiles.org/>

<sup>2</sup><https://ipc-project.eu/>

<sup>3</sup><https://deepchem.io/>

88 Oskooei et al., 2018]. Another prospective set of benchmarks to be used are those proposed by MoleculeNet  
89 [Wu et al., 2018].

90 Previous work [Theis et al., 2016] has discussed how different metrics measure different conceptions of  
91 performance for the evaluation of generative models. In order to deal with different considerations, such  
92 as diversity, novelty, molecular activity, or stability, metrics like the Fréchet ChemNet Distance (FCD)  
93 [Preuer et al., 2018] have been proposed. In this project one of the metrics for the generative model will come  
94 from the predictive model, which will be used to evaluate the effectiveness of the generated compounds.  
95 Simultaneously, another metric for the generative model will be the similarity of the generated compounds to  
96 already existing drugs. An approach that has already been used in the literature [Born et al., 2019]. Moreover, a  
97 wider benchmarking framework for generative models, GucaMol, was proposed recently [Brown et al., 2019],  
98 incorporating elements like the mentioned FCD score, so it will be explored as a benchmark for this project.

99 Lastly, a natural final step for the entire evaluation of the system would be the actual in-vitro synthesis of the  
100 generated compounds, as done in [Zhavoronkov et al., 2019]. However, the complexity of carrying out that  
101 evaluation will likely make it far too ambitious for what the scope of this project is.

## 102 References

- 103 [Boland and Yurgelun, 2017] Boland, C. R. and Yurgelun, M. B. (2017). Mutational cascades in cancer.
- 104 [Born et al., 2019] Born, J., Manica, M., Oskooei, A., Cadow, J., and Martínez, M. R. (2019). PaccMann<sup>RL</sup>:  
105 Designing anticancer drugs from transcriptomic data via reinforcement learning.
- 106 [Brown et al., 2019] Brown, N., Fiscato, M., Segler, M. H., and Vaucher, A. C. (2019). GuacaMol: Bench-  
107 marking Models for de Novo Molecular Design. *Journal of Chemical Information and Modeling*,  
108 59(3):1096–1108.
- 109 [Dargan et al., 2019] Dargan, S., Kumar, M., Ayyagari, M. R., and Kumar, G. (2019). A Survey of Deep  
110 Learning and Its Applications: A New Paradigm to Machine Learning. *Archives of Computational Methods*  
111 *in Engineering*.
- 112 [Do et al., 2019] Do, K., Tran, T., and Venkatesh, S. (2019). Graph transformation policy network for  
113 chemical reaction prediction. In *Proceedings of the ACM SIGKDD International Conference on Knowledge*  
114 *Discovery and Data Mining*, pages 750–760.
- 115 [Enriquez-Navas et al., 2015] Enriquez-Navas, P. M., Wojtkowiak, J. W., and Gatenby, R. A. (2015). Appli-  
116 cation of evolutionary principles to cancer therapy.
- 117 [Fukushima, 1980] Fukushima, K. (1980). Neocognitron: A self-organizing neural network model for a  
118 mechanism of pattern recognition unaffected by shift in position. *Biological Cybernetics*, 36(4):193–202.
- 119 [Gaulton et al., 2017] Gaulton, A., Hersey, A., Nowotka, M. L., Patricia Bento, A., Chambers, J., Mendez,  
120 D., Mutowo, P., Atkinson, F., Bellis, L. J., Cibrian-Uhalte, E., Davies, M., Dedman, N., Karlsson, A.,  
121 Magarinos, M. P., Overington, J. P., Papadatos, G., Smit, I., and Leach, A. R. (2017). The ChEMBL  
122 database in 2017. *Nucleic Acids Research*, 45(D1):D945–D954.
- 123 [Guo et al., 2016] Guo, Y., Liu, Y., Oerlemans, A., Lao, S., Wu, S., and Lew, M. S. (2016). Deep learning for  
124 visual understanding: A review. *Neurocomputing*, 187:27–48.
- 125 [Huang et al., 2019] Huang, J., Li, Z., Li, N., Liu, S., and Li, G. (2019). AttPool: Towards Hierarchical  
126 Feature Representation in Graph Convolutional Networks via Attention Mechanism. *The IEEE International*  
127 *Conference on Computer Vision (ICCV)*, pages 6480–6489.
- 128 [Hung and Chen, 2014] Hung, C. L. and Chen, C. C. (2014). Computational approaches for drug discovery.
- 129 [Joo et al., 2019] Joo, M., Park, A., Kim, K., Son, W.-J., Lee, H. S., Lim, G., Lee, J., Lee, D. H., An, J., Kim,  
130 J. H., Ahn, T., and Nam, S. (2019). A Deep Learning Model for Cell Growth Inhibition IC50 Prediction  
131 and Its Application for Gastric Cancer Patients. *International Journal of Molecular Sciences*, 20(24):6276.
- 132 [Kim et al., 2019] Kim, S., Chen, J., Cheng, T., Gindulyte, A., He, J., He, S., Li, Q., Shoemaker, B. A.,  
133 Thiessen, P. A., Yu, B., Zaslavsky, L., Zhang, J., and Bolton, E. E. (2019). PubChem 2019 update: Improved  
134 access to chemical data. *Nucleic Acids Research*, 47(D1):D1102–D1109.
- 135 [Kuhn et al., 2016] Kuhn, M., Yates, P., and Hyde, C. (2016). Statistical Methods for Drug Discovery. pages  
136 53–81.
- 137 [LeCun, 1989] LeCun, Y. (1989). Generalization and network design strategies. Technical report.

138 [Li et al., 2017] Li, J., Cai, D., and He, X. (2017). Learning Graph-Level Representation for Drug Discovery.  
139 Technical report.

140 [Li et al., 2018a] Li, Y., Vinyals, O., Dyer, C., Pascanu, R., and Battaglia, P. (2018a). Learning Deep  
141 Generative Models of Graphs.

142 [Li et al., 2018b] Li, Y., Zhang, L., and Liu, Z. (2018b). Multi-objective de novo drug design with conditional  
143 graph generative model. *Journal of Cheminformatics*, 10(1).

144 [Ma and Zhang, 2019] Ma, T. and Zhang, A. (2019). Incorporating Biological Knowledge with Factor Graph  
145 Neural Network for Interpretable Deep Learning.

146 [Manica et al., 2019] Manica, M., Oskooei, A., Born, J., Subramanian, V., Sáez-Rodríguez, J., and Rodríguez  
147 Martínez, M. (2019). Toward Explainable Anticancer Compound Sensitivity Prediction via Multimodal  
148 Attention-Based Convolutional Encoders. Technical report.

149 [Maris, 2010] Maris, J. M. (2010). Recent advances in neuroblastoma. *New England Journal of Medicine*,  
150 362(23):2202.

151 [Oskooei et al., 2018] Oskooei, A., Born, J., Manica, M., Subramanian, V., Sáez-Rodríguez, J., and Martínez,  
152 M. R. (2018). PaccMann: Prediction of anticancer compound sensitivity with multi-modal attention-based  
153 neural networks.

154 [Oskooei et al., 2019] Oskooei, A., Manica, M., Mathis, R., and Martínez, M. R. (2019). Network-based  
155 Biased Tree Ensembles (NetBiTE) for Drug Sensitivity Prediction and Drug Sensitivity Biomarker Identifi-  
156 cation in Cancer. *Scientific Reports*, 9(1).

157 [Paszke et al., 2019] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin,  
158 Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A.,  
159 Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., and Chintala, S. (2019). PyTorch: An Imperative Style,  
160 High-Performance Deep Learning Library.

161 [Preuer et al., 2018] Preuer, K., Renz, P., Unterthiner, T., Hochreiter, S., and Klambauer, G. (2018). Fréchet  
162 ChemNet Distance: A Metric for Generative Models for Molecules in Drug Discovery. *Journal of Chemical*  
163 *Information and Modeling*, 58(9):1736–1741.

164 [Reymond et al., 2012] Reymond, J. L., Ruddigkeit, L., Blum, L., and van Deursen, R. (2012). The enumera-  
165 tion of chemical space. *Wiley Interdisciplinary Reviews: Computational Molecular Science*, 2(5):717–733.

166 [Scannell et al., 2012] Scannell, J. W., Blanckley, A., Boldon, H., and Warrington, B. (2012). Diagnosing the  
167 decline in pharmaceutical R&D efficiency. Technical Report 3.

168 [Schneider, 2019] Schneider, G. (2019). Mind and machine in drug design. *Nature Machine Intelligence*,  
169 1(3):128–130.

170 [Simonovsky and Komodakis, 2018] Simonovsky, M. and Komodakis, N. (2018). GraphVAE: Towards  
171 generation of small graphs using variational autoencoders. In *Lecture Notes in Computer Science (including*  
172 *subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, volume 11139  
173 LNCS, pages 412–422.

174 [Sterling and Irwin, 2015] Sterling, T. and Irwin, J. J. (2015). ZINC 15 - Ligand Discovery for Everyone.  
175 *Journal of Chemical Information and Modeling*, 55(11):2324–2337.

176 [Sun et al., 2019] Sun, M., Zhao, S., Gilvary, C., Elemento, O., Zhou, J., and Wang, F. (2019). Graph  
177 convolutional networks for computational drug development and discovery. *Briefings in Bioinformatics*,  
178 2019(0):1–17.

179 [Szkarczyk et al., 2019] Szkarczyk, D., Gable, A. L., Lyon, D., Junge, A., Wyder, S., Huerta-Cepas, J.,  
180 Simonovic, M., Doncheva, N. T., Morris, J. H., Bork, P., Jensen, L. J., and Von Mering, C. (2019). STRING  
181 v11: Protein-protein association networks with increased coverage, supporting functional discovery in  
182 genome-wide experimental datasets. *Nucleic Acids Research*, 47(D1):D607–D613.

183 [Szkarczyk et al., 2016] Szkarczyk, D., Santos, A., Von Mering, C., Jensen, L. J., Bork, P., and Kuhn, M.  
184 (2016). STITCH 5: Augmenting protein-chemical interaction networks with tissue and affinity data. *Nucleic*  
185 *Acids Research*, 44(D1):D380–D384.

186 [Theis et al., 2016] Theis, L., Van Den Oord, A., and Bethge, M. (2016). A note on the evaluation of  
187 generative models. In *4th International Conference on Learning Representations, ICLR 2016 - Conference*  
188 *Track Proceedings*.

189 [Ulyanov D., Vedaldi A., 2018] Ulyanov D., Vedaldi A., L. V. (2018). Deep Image Prior. Technical report.

190 [Wang et al., 2019] Wang, M., Yu, L., Zheng, D., Gan, Q., Gai, Y., Ye, Z., Li, M., Zhou, J., Huang, Q., Ma,  
191 C., Huang, Z., Guo, Q., Zhang, H., Lin, H., Zhao, J., Li, J., Smola, A., and Zhang, Z. (2019). Deep Graph  
192 Library: Towards Efficient and Scalable Deep Learning on Graphs. Technical report.

193 [Wishart, 2006] Wishart, D. S. (2006). DrugBank: a comprehensive resource for in silico drug discovery and  
194 exploration. *Nucleic Acids Research*, 34(90001):D668–D672.

195 [Wu et al., 2019] Wu, Z., Pan, S., Chen, F., Long, G., Zhang, C., and Yu, P. S. (2019). A Comprehensive  
196 Survey on Graph Neural Networks. Technical report.

197 [Wu et al., 2018] Wu, Z., Ramsundar, B., Feinberg, E. N., Gomes, J., Geniesse, C., Pappu, A. S., Leswing,  
198 K., and Pande, V. (2018). MoleculeNet: A benchmark for molecular machine learning. *Chemical Science*,  
199 9(2):513–530.

200 [Yang et al., 2013] Yang, W., Soares, J., Greninger, P., Edelman, E. J., Lightfoot, H., Forbes, S., Bindal, N.,  
201 Beare, D., Smith, J. A., Thompson, I. R., Ramaswamy, S., Futreal, P. A., Haber, D. A., Stratton, M. R.,  
202 Benes, C., McDermott, U., and Garnett, M. J. (2013). Genomics of Drug Sensitivity in Cancer (GDSC): A  
203 resource for therapeutic biomarker discovery in cancer cells. *Nucleic Acids Research*, 41(D1).

204 [Ying et al., 2018] Ying, R., Morris, C., Hamilton, W. L., You, J., Ren, X., and Leskovec, J. (2018). Hier-  
205 archical graph representation learning with differentiable pooling. In *Advances in Neural Information*  
206 *Processing Systems*, volume 2018-Decem, pages 4800–4810.

207 [Yingkai Gao et al., 2018] Yingkai Gao, K., Fokoue, A., Luo, H., Iyengar, A., Dey, S., and Zhang, P. (2018).  
208 Interpretable drug target prediction using deep neural representation. In *IJCAI International Joint Confer-*  
209 *ence on Artificial Intelligence*, volume 2018-July, pages 3371–3377.

210 [Young et al., 2018] Young, T., Hazarika, D., Poria, S., and Cambria, E. (2018). Recent trends in deep learning  
211 based natural language processing.

212 [Zhavoronkov et al., 2019] Zhavoronkov, A., Ivanenkov, Y. A., Aliper, A., Veselov, M. S., Aladinskiy, V. A.,  
213 Aladinskaya, A. V., Terentiev, V. A., Polykovskiy, D. A., Kuznetsov, M. D., Asadulaev, A., Volkov, Y.,  
214 Zholus, A., Shayakhmetov, R. R., Zhebrak, A., Minaeva, L. I., Zagribelnyy, B. A., Lee, L. H., Soll, R.,  
215 Madge, D., Xing, L., Guo, T., and Aspuru-Guzik, A. (2019). Deep learning enables rapid identification of  
216 potent DDR1 kinase inhibitors. *Nature Biotechnology*, 37(9):1038–1040.

217 [Zitnik et al., 2018] Zitnik, M., Agrawal, M., and Leskovec, J. (2018). Modeling polypharmacy side effects  
218 with graph convolutional networks. In *Bioinformatics*, volume 34, pages i457–i466.