
Thesis proposal

An alpha version of the draft

Nil Adell Mill
Winter 2020
Institute of Neuroinformatics

1 Introduction/Background

2 Drug discovery—the process by which a potential new medicine is identified—is a complex process that
3 encompasses the intersection of several fields (such as biology, statistics, chemistry or pharmacology). The
4 entire process is a long and costly endeavour, with a typical time-frame of 10 to 20 years till market release and
5 an estimated cost between 1 and 2 billion USD. With just a small quantity of the initially identified compounds
6 actually becoming an approved medicine. Many of these dropouts happening at the early stages of the entire
7 pipeline.

8 It exists, then, a need for better mechanisms for detecting better candidates. One of the most promising
9 directions is to improve the *in-silico* methods—computational simulations are relatively cheap and quick
10 run that makes them an interesting solution. *In-silico* simulations then cover two main aspects: modelling
11 the dynamics of the human body—such that any effect relevant to the drug or the disease will be captured
12 by it—and methods to generate good candidates that are effective at exploring the vast space of possible
13 compounds.

14 Among the different computational approaches that have been used in the process of drug discovery deep
15 learning (DL) has shown signs to be a potential game changer [Dargan et al., 2019]. DL has been able to
16 capitalize on the exponential growth of data and the higher availability of computational resources. For example,
17 DL has had a remarkable success on computer vision (CV) and natural language processing (NLP), and has
18 become the go-to solution for any problem in these two fields. It is, at the same time, penetrating into other
19 fields, drug-discovery being one of them [Chen et al., 2018].

20 When we deal with this biological and molecular data, it exists a challenge on how to deal with the intrinsic
21 structure of the data. If we look at the case of deep learning for CV, where we deal with images, a key element
22 of any architecture for its success was the use of convolutional layers—one will mostly observe convolutional
23 neural networks (CNNs) when analyzing the state of the art in CV—which introduce a structural prior based
24 on the structure of the data. A similar case can be made for NLP. For that reason, there exists a strong signal
25 to look for models that can leverage the structural equivalent when in molecule or protein data, i.e. leverage
26 graph structures [Wu et al., 2019]. Sign [Sign? need to rewrite that] of that is the recent advancements in that
27 direction [Sun et al., 2019].

28 Another of the big challenges is to unify all the aspects of drug-discovery and be able to incorporate all the
29 relevant biological information when designing possible candidate molecules. An initial success story on
30 that line is a recently paper [Zhavoronkov et al., 2019] where the authors describe a deep learning method by
31 which they are able to discover inhibitors of discoidin domain receptor 1 (DDR1)—a kinase implicated in
32 fibrosis—in just 21 days.

33 Those promising results, albeit encouraging, are just the tip of the iceberg. There is still a long way till a model
34 can satisfactorily capture the biological complexity of any arbitrary target and produce promising candidates.
35 On top of that, there is an added dimension, as such model should account for the variability from patient to
36 patient and be able to generate a molecule that accommodates for all the genotypic and phenotypic variants, or
37 generate different candidates for each of the genetic populations of interest. [need a ref here]

38 [I am not completely sure about this paragraph but I leave it here so I don't forget for now] Even more, in the
39 case of diseases like cancer, a heterogeneous population may appear within a single patient. So the same
40 variant effects arise inside a dynamic ecosystem, where a drug that just targets a subpopulation may lead to an

41 evolutionary pressure complicating further the treatment outlook [reference paper of evolutionary perspective
42 to cancer].

43 There is then a great need to develop models that can be conditioned based on a large set of biological
44 [conditions?] and meaningfully account for this variations when generating a compound or/and evaluating a
45 compounds effect when administered.

46 In fact it is of interest to develop multi-scale models that capture system complexity at the different levels.
47 For instance, a model that is able to learn protein-compound interactions—commonly known as the docking
48 problem—while at the same time use this information to predict effects of the introduction of the compound
49 on the larger protein-protein interaction (PPI) network.

50 **Aim & Methods**

51 [Should I separate em in two different sections?]

52 The aim of this thesis will be two fold. One the one side, analyze how the explicit use of graph convolutional
53 neural networks (GCNNs) may open new oportunities when dealing with biological and checmical data. On
54 the other side, explore how modelling the biology at different levels (e.g. molecular structure v.s. molecular
55 interacton network [okay here I need to develop furhter about PPI, maybe mention NetBite (as Jannis referenced
56 in the mail)]) may help with our understanding [of the biology? of compounds interaction?] and help generate
57 better models. Furthermore, evaluate how these may be integrated toguether.

58 This precise work will be focused around exploring all these concepts in the context of drug design for cancer
59 [...] the work will be done in colaboration with the Computational Systems Biology group at IBM Research
60 (Zurich). [...] The group is currently focused on individualised paediatric cure (iPC), so an end goal of this
61 project is for the end results of it to help in that effor, for instance in contibuting to the ongoing research in
62 neuroblastoma.

63 As mentioned previously, the idea of using GCNNs is not a new one in the literature [Sun et al., 2019].
64 My project will build upon those ideas presented in the literature, expand them and test their feasibility by
65 implementing them into a wider framework for drug design [Born et al., 2019]. In that context two main
66 areas of application appear. One of them would be to re-desing the drug conditional generator, for instance
67 by reframing the vairational autoencoders, used for molecule generation, to architectures that operate over
68 graphs [Simonovsky and Komodakis, 2018, Li et al., 2018a, Li et al., 2018b]. The second area would be to
69 find better ways to asses the activity of these molecules, and in a wider context, assess their relevance as drug
70 candidates. In the concrete case of the mentioned framework it is done by using a critic network proposed
71 in [Manica et al., 2019]. This could be expanded on a set of different fronts: usign structural data instead
72 of SMILES [Li et al., 2017, Do et al., 2019], by using GCNNs to cover a much wider network of genes
73 [Oskooei et al., 2019, Wang et al., 2019], or by introducing particular scores (rewards) based in the interaction
74 of the compound to certain targets [Yingkai Gao et al., 2018, Zhavoronkov et al., 2019] or the combination of
75 the compund with other drugs [Zitnik et al., 2018] —a common practice in patients with cancer.

76 All these possible changes on the critic model would apply at different abstraction levels. That opens
77 the door to seek for ways to integrate the representations learnt at those different stages [Ying et al., 2018,
78 Ma and Zhang, 2019, Huang et al., 2019]. On top of that information extracted from here could be then
79 leveraged on the drug generation part of the framework.

80 **References**

- 81 [Born et al., 2019] Born, J., Manica, M., Oskooei, A., Cadow, J., and Martínez, M. R. (2019). PaccMann^{RL}:
82 Designing anticancer drugs from transcriptomic data via reinforcement learning.
- 83 [Chen et al., 2018] Chen, H., Engkvist, O., Wang, Y., Olivecrona, M., and Blaschke, T. (2018). The rise of
84 deep learning in drug discovery.
- 85 [Dargan et al., 2019] Dargan, S., Kumar, M., Ayyagari, M. R., and Kumar, G. (2019). A Survey of Deep
86 Learning and Its Applications: A New Paradigm to Machine Learning. *Archives of Computational Methods
87 in Engineering*.
- 88 [Do et al., 2019] Do, K., Tran, T., and Venkatesh, S. (2019). Graph transformation policy network for
89 chemical reaction prediction. In *Proceedings of the ACM SIGKDD International Conference on Knowledge
90 Discovery and Data Mining*, pages 750–760.

91 [Huang et al., 2019] Huang, J., Li, Z., Li, N., Liu, S., and Li, G. (2019). AttPool: Towards Hierarchical
 92 Feature Representation in Graph Convolutional Networks via Attention Mechanism. *The IEEE International*
 93 *Conference on Computer Vision (ICCV)*, pages 6480–6489.

94 [Li et al., 2017] Li, J., Cai, D., and He, X. (2017). Learning Graph-Level Representation for Drug Discovery.
 95 Technical report.

96 [Li et al., 2018a] Li, Y., Vinyals, O., Dyer, C., Pascanu, R., and Battaglia, P. (2018a). Learning Deep
 97 Generative Models of Graphs.

98 [Li et al., 2018b] Li, Y., Zhang, L., and Liu, Z. (2018b). Multi-objective de novo drug design with conditional
 99 graph generative model. *Journal of Cheminformatics*, 10(1).

100 [Ma and Zhang, 2019] Ma, T. and Zhang, A. (2019). Incorporating Biological Knowledge with Factor Graph
 101 Neural Network for Interpretable Deep Learning.

102 [Manica et al., 2019] Manica, M., Oskooei, A., Born, J., Subramanian, V., Saéz-Rodríguez, J., and Rodríguez
 103 Martínez, M. (2019). Toward Explainable Anticancer Compound Sensitivity Prediction via Multimodal
 104 Attention-Based Convolutional Encoders. Technical report.

105 [Oskooei et al., 2019] Oskooei, A., Manica, M., Mathis, R., and Martínez, M. R. (2019). Network-based
 106 Biased Tree Ensembles (NetBiTE) for Drug Sensitivity Prediction and Drug Sensitivity Biomarker Identifi-
 107 cation in Cancer. *Scientific Reports*, 9(1).

108 [Simonovsky and Komodakis, 2018] Simonovsky, M. and Komodakis, N. (2018). GraphVAE: Towards
 109 generation of small graphs using variational autoencoders. In *Lecture Notes in Computer Science (including*
 110 *subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, volume 11139
 111 LNCS, pages 412–422.

112 [Sun et al., 2019] Sun, M., Zhao, S., Gilvary, C., Elemento, O., Zhou, J., and Wang, F. (2019). Graph
 113 convolutional networks for computational drug development and discovery. *Briefings in Bioinformatics*,
 114 2019(0):1–17.

115 [Wang et al., 2019] Wang, M., Yu, L., Zheng, D., Gan, Q., Gai, Y., Ye, Z., Li, M., Zhou, J., Huang, Q., Ma,
 116 C., Huang, Z., Guo, Q., Zhang, H., Lin, H., Zhao, J., Li, J., Smola, A., and Zhang, Z. (2019). Deep Graph
 117 Library: Towards Efficient and Scalable Deep Learning on Graphs. Technical report.

118 [Wu et al., 2019] Wu, Z., Pan, S., Chen, F., Long, G., Zhang, C., and Yu, P. S. (2019). A Comprehensive
 119 Survey on Graph Neural Networks. Technical report.

120 [Ying et al., 2018] Ying, R., Morris, C., Hamilton, W. L., You, J., Ren, X., and Leskovec, J. (2018). Hier-
 121 archical graph representation learning with differentiable pooling. In *Advances in Neural Information*
 122 *Processing Systems*, volume 2018-Decem, pages 4800–4810.

123 [Yingkai Gao et al., 2018] Yingkai Gao, K., Fokoue, A., Luo, H., Iyengar, A., Dey, S., and Zhang, P. (2018).
 124 Interpretable drug target prediction using deep neural representation. In *IJCAI International Joint Confer-*
 125 *ence on Artificial Intelligence*, volume 2018-July, pages 3371–3377.

126 [Zhavoronkov et al., 2019] Zhavoronkov, A., Ivanenkov, Y. A., Aliper, A., Veselov, M. S., Aladinskiy, V. A.,
 127 Aladinskaya, A. V., Terentiev, V. A., Polykovskiy, D. A., Kuznetsov, M. D., Asadulaev, A., Volkov, Y.,
 128 Zholus, A., Shayakhmetov, R. R., Zhebrak, A., Minaeva, L. I., Zagribelnyy, B. A., Lee, L. H., Soll, R.,
 129 Madge, D., Xing, L., Guo, T., and Aspuru-Guzik, A. (2019). Deep learning enables rapid identification of
 130 potent DDR1 kinase inhibitors. *Nature Biotechnology*, 37(9):1038–1040.

131 [Zitnik et al., 2018] Zitnik, M., Agrawal, M., and Leskovec, J. (2018). Modeling polypharmacy side effects
 132 with graph convolutional networks. In *Bioinformatics*, volume 34, pages i457–i466.