



## Ramakrishna Mission Vivekananda Educational and Research Institute

Belur Math, Howrah, West Bengal  
Department of Computer Science  
Midterm Examination  
MSc DSAI

Course: CS110 (Data Structures and Algorithms)

Instructor: Sri Niladri Banerjee

Student Roll:

Student Name:

Date: 22 Sep 2025

Time: 2 hrs

Max Marks: 60

### Instructions:

- Answers should be clear, concise, and complete to earn the full allotted marks. All steps in the problem-solving process should be clearly stated.
- Pseudocode should be close to C/C++/Python.

### Section A

[10 questions  $\times$  2 marks = 20 marks]

1. What are the key differences between a compiled language and an interpreted language? Provide an example for each and discuss their advantages and disadvantages.
2. Define a bit and a byte. If a computer uses 8-bit bytes, how many unique unsigned integer values can a single byte store? Using a diagram, illustrate how the value 7 would be stored in a byte of memory. Assume `int` consumes 2 bytes.
3. Write down the characteristics of an algorithm.
4. Arrange the functions in ascending order of their time complexity:  $2^n$ ,  $n!$ ,  $n^{\log n}$
5. What is Big  $\Theta$  notation? Provide a diagram and an example.
6. Explain the Addition property of Big O notation and provide a proof.
7. Find the time complexity of the following loop:  

```
for (i = n; i >= 5; i =  $\sqrt{i}$ )  
    x = x + 1;
```
8. Find the time complexity of the following loop:  

```
while n > 1 do  
    for i = 1 to n do  
        x = x + 1;  
    end for  
    n = floor(n / 2);  
end while
```
9. We have an array `int A[-10..10][-20..20]`. Width of `int` = 2 bytes. Base Address = 1000. Find the address of `A[5][6]` in both Row Major Order (RMO) and Column Major Order (CMO).
10. Write the `pop` functionality of a singly linked list. Assume you pop from the tail. You have both head and tail pointers.

1. Solve the recurrence relation:

$$T(n) = \begin{cases} 1, & \text{if } n = 0, \\ T\left(\frac{n}{2}\right) + T\left(\frac{2n}{5}\right) + 7n, & \text{if } n > 0. \end{cases}$$

2. Consider an array  $A = \{3, 8, 2, 5, 7, 6, 12\}$  of length 7.

- A subarray is a sequence of consecutive elements in the original array.
- A subarray of size  $w$  contains exactly  $w$  consecutive elements.

Let  $w = 4$ . Valid subarrays:  $\{3, 8, 2, 5\}$ ,  $\{8, 2, 5, 7\}$ ,  $\{2, 5, 7, 6\}$ ,  $\{5, 7, 6, 12\}$ . Their sums are

$$3 + 8 + 2 + 5 = 18, \quad 8 + 2 + 5 + 7 = 22, \quad 2 + 5 + 7 + 6 = 20, \quad 5 + 7 + 6 + 12 = 30.$$

The maximum sum is 30. Write an optimal algorithm (time complexity  $< n^2$ ) to find the maximum sum of any subarray of size  $w$ .

3. Design an algorithm to find the middle node of a singly linked list without using its length. Examples:

10 (*head*)  $\rightarrow$  20  $\rightarrow$  30  $\rightarrow$  40  $\rightarrow$  50 (*tail*)  $\rightarrow$  None (middle node = 30)

10 (*head*)  $\rightarrow$  20  $\rightarrow$  30  $\rightarrow$  40  $\rightarrow$  50  $\rightarrow$  60 (*tail*)  $\rightarrow$  None (middle node = 40)

4. Write an algorithm to reverse a singly linked list.

*Original* : 10 (*head*)  $\rightarrow$  20  $\rightarrow$  30  $\rightarrow$  40  $\rightarrow$  50 (*tail*)  $\rightarrow$  None

*Reversed* : None  $\leftarrow$  10 (*tail*)  $\leftarrow$  20  $\leftarrow$  30  $\leftarrow$  40  $\leftarrow$  50 (*head*)

5. Write a recursive algorithm to compute  $\sin(x)$  using the series. Show the recursion tree starting with count = 3.

$$\sin(x) = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \cdots$$

Assume  $x$  in radians; terminate recursion by term count.

## Section C

[2 questions  $\times$  10 marks = 20 marks]

1. Illustrate with diagram the Tower of Hanoi problem for  $n = 1, 2, 3$  disks, showing the sequence of moves. Write a recursive algorithm to illustrate the Tower of Hanoi problem. Determine its time complexity and why it becomes impractical for large  $n$ .

2. Let `int A[15]={0,1,2,...,14}` and `key = 5`.

- Write both iterative and recursive binary search algorithms; show each step in a table.
- Compute average times for successful and unsuccessful search.