

ServiceNow Script-Controlled ACL Project

Module 3 – READ ACL with Script Control

Lab duration: 3 hours | Development/Training Instance

Objective

Allow administrators full read access and allow bb1 users to pass the role check for the protected table. The record condition is Branch = EEE.

ACL Creation

Navigate to **System Security** → **Access Control (ACL)**. Elevate to **security_admin** if required, then click **New**.

Type: **record**

Operation: **read**

Name: **u_institution_details**

Active: true

Advanced: **true**

Add **bb1** in Requires role. Add the data condition **Branch is EEE**.

Script

Important: In ServiceNow, an ACL's role requirement, condition and script are evaluated as part of the ACL decision. The script below grants administrators and users with bb1; the Branch = EEE condition should be configured on the ACL as specified above.


```
(function () {<br/>
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;if (gs.hasRole('admin')) { return true; }<br/>
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;if (gs.hasRole('bb1')) { return true; }<br/>
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;return false;<br/>
})();
```

Verification

Impersonate EEE User and open **u_institution_details.list**. Verify that the intended EEE records are available and non-EEE records are restricted according to the ACL condition. Then impersonate an account without bb1 and verify that access is denied. Finally test an administrator and verify full access.