



— SAFETY DATA SHEET

NN-RockBond Cement Capsule

Safety Data Sheet — per GHS / India CMSR 2020

SDS No.	Revision	Issue Date	Format
NNPL/SDS/PROD-05	1.0	27 June 2026	GHS Rev.9 / 16-section

1 IDENTIFICATION

Field	Detail
Product name	NN-RockBond Cement Capsule
Product type	Pre-packed cementitious grout capsule for roof bolting
Recommended use	Grout material for roof bolting / strata control in underground mines and tunnels
Composition basis	High-alumina / special cement, graded sand and additives in a polythene pouch
Supplier	NilayNarayan Polychem LLP
Address	Plot No. D-167 (P), 4-5, Kandra Industrial Area, Govindpur, Jharkhand – 826010, India
Emergency / contact	+91 82925 84106 • nilaynarayanpolychem@gmail.com

2 HAZARD IDENTIFICATION

GHS classification: Skin irritation Cat. 2; Serious eye damage Cat. 1; STOT SE Cat. 3 (respiratory irritation from dust).
Cement-based; becomes strongly alkaline when wet.

Signal word: Danger

Hazard statements: Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Wet cement may cause skin burns (alkaline).

Precautionary statements: Avoid breathing dust. Wear eye protection, gloves and protective clothing. Wash thoroughly after handling. IF IN EYES: rinse cautiously with water for several minutes and seek medical attention.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Conc. %
Cement (high-alumina / Portland-type clinker)	65997-15-1 / 65997-16-2	Major
Crystalline silica (quartz sand)	14808-60-7	Variable
Functional additives	—	Minor
Polythene pouch (packaging)	9002-88-4	Casing

Note: respirable crystalline silica content depends on the sand grade; handle to minimise dust.

4 FIRST-AID MEASURES

Route	Measure
Inhalation	Move to fresh air. If dust causes respiratory irritation or persistent cough, seek medical advice.



Route	Measure
Skin contact	Brush off dry material; wash with soap and water. For wet cement contact, wash promptly — alkaline material may cause burns. Seek advice if irritation or burns develop.
Eye contact	Rinse immediately and continuously with clean water for at least 15 minutes, holding eyelids open; remove lenses if present. Seek medical attention — risk of serious damage.
Ingestion	Do NOT induce vomiting. Rinse mouth, give water to drink and seek medical attention.

5 FIRE-FIGHTING MEASURES

Field	Detail
Flammability	Non-combustible, inorganic cementitious grout. The polythene pouch will burn.
Suitable media	Use media appropriate to the surrounding fire (water spray, foam, CO ₂ , dry chemical).
Specific hazards	Burning of the polythene casing may release smoke and CO/CO ₂ .

6 ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid dust generation. Wear eye protection, gloves and a dust mask.

Clean-up: Collect spilled capsules / dry material; avoid dry sweeping that raises dust (use vacuum or damp methods). Keep out of drains and watercourses — wetted cement is strongly alkaline.

7 HANDLING & STORAGE

Field	Detail
Safe handling	Minimise dust. Avoid skin and eye contact, especially with wet/soaked capsules. Wash before eating or drinking.
Storage	Cool, dry, covered; protect from moisture and water. Keep packaging sealed until use.
Incompatibilities	Acids; moisture (premature setting). Wet cement attacks aluminium and reactive metals.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control	Detail
Engineering	Adequate ventilation; dust extraction where capsules are cut or handled in quantity.
Respiratory	Dust mask / respirator (FFP2 or better) where airborne dust may occur.
Hands / skin	Waterproof gloves; cover exposed skin — important when handling soaked capsules.
Eyes	Tightly fitting safety goggles.
Exposure limits	Observe national limits for cement dust and respirable crystalline silica.

9 PHYSICAL & CHEMICAL PROPERTIES



Property	Value
Appearance	Cylindrical pre-packed capsule; grey cementitious powder/grout inside a polythene pouch
Odour	Odourless / earthy
pH (in water)	Strongly alkaline (~11–13) when mixed with water
Solubility in water	Reacts / hydrates with water (sets)
Setting time	Final set max 15 min including soaking (per DGMS)
Flammability	Non-combustible grout (polythene casing is combustible)

10 STABILITY & REACTIVITY

Field	Detail
Stability	Stable when kept dry in sealed packaging.
Conditions to avoid	Moisture and water (cause premature hydration / setting).
Incompatible materials	Acids; aluminium and other reactive metals (when wet).
Hazardous reactions	Hydration is exothermic; wet mixture is strongly alkaline.

11 TOXICOLOGICAL INFORMATION

Cement dust and wet cement are irritating to skin, eyes and the respiratory tract; wet cement is alkaline and prolonged contact may cause burns or dermatitis. Repeated inhalation of respirable crystalline silica over long periods is associated with a risk of silicosis; control dust exposure accordingly.

12 ECOLOGICAL INFORMATION

Not expected to bioaccumulate. Wetted/uncured material is strongly alkaline and can raise the pH of water — prevent entry of slurry into drains and watercourses. Cured grout is an inert solid.

13 DISPOSAL CONSIDERATIONS

Allow waste material to set and dispose of the inert solid as construction / inert waste in accordance with applicable State Pollution Control Board and local regulations. Dispose of packaging per local rules.

14 TRANSPORT INFORMATION

Mode	Classification
Road / Rail / Sea / Air	Not classified as dangerous goods for transport.
UN number	None / Not applicable
Proper shipping name	Not restricted (keep dry)

15 REGULATORY INFORMATION

Manufactured and tested in accordance with DGMS Circular (Approval) No. 05 of 2013 and the relevant provisions of the Coal Mines Regulations, 1957 (Reg. 181(3)) for use of cement capsules as grouting medium in below-ground coal mines. Classified / labelled per GHS as adopted in India.



16 OTHER INFORMATION

Prepared by: NN Polychem. Revision 1.0, 27 June 2026.

Disclaimer: The information in this SDS is given in good faith and is based on data believed to be reliable. NilayNarayan Polychem LLP makes no warranty, express or implied, as to its accuracy or completeness. Users must satisfy themselves as to the suitability and safe handling of the product for their own conditions and must comply with all applicable laws, the DGMS circular and mine-safety regulations.