KMS Proxy Integration Guide

The KMS proxy features both a **Standard OpenAI-Compatible API Layer** (for direct IDEs, SDKs, and tools) and a **Unified Wrapped Proxy Layer** (for custom service integrations).

---

1. Direct API Access (OpenAI-Compatible IDEs, SDKs & CLIs)

You can use KMS Scoped Client Keys (`ck_live_...`) directly in any OpenAI-compatible application (Cursor, VS Code Continue/Cline, Aider, OpenWebUI, official OpenAI SDKs, LangChain).

> *"[!IMPORTANT]*
> ***Permission Requirement**: Direct API access must be enabled for the Scoped Virtual Key in the KMS Admin Console (**Allow Direct API Access** toggle). It is disabled by default for security."*

- **Base URL / Endpoint:** `http://<your-kms-domain>:3201/v1`
- **Chat Completions Endpoint:** `POST http://<your-kms-domain>:3201/v1/chat/completions`
- **Models Endpoint:** `GET http://<your-kms-domain>:3201/v1/models`
- **Authorization Header:** `Authorization: Bearer <ck_live_your_scoped_client_key>`

Request Body Format (Standard OpenAI)

```
{
  "model": "openai/gpt-4o",
  "messages": [
    {
      "role": "system",
      "content": "You are a helpful coding assistant."
    },
    {
      "role": "user",
      "content": "Explain photosynthesis in one sentence."
    }
  ],
  "temperature": 0.7,
  "max_tokens": 150
}
```

IDE Configuration Example (e.g., Cursor, Continue, Cline, OpenWebUI)

- **API Provider:** `OpenAI`
- **Base URL:** `http://<your-kms-domain>:3201/v1`
- **API Key:** `ck_live_xxxxxxxxxxx`

---

2. Unified Wrapped Proxy Endpoint (`/v1/proxy`)

For custom backend service integrations that wrap request payloads under a `body` object:

- **Proxy Endpoint:** `POST http://<your-kms-domain>:3201/v1/proxy`
- **Authorization Header:** `Authorization: Bearer <ck_live_your_scoped_client_key>`

Request Format (Text & Vision)

```
{
  "model": "gemini-1.5-flash",
  "body": {
    "messages": [
      {
        "role": "user",
        "content": "Explain quantum computing briefly."
      }
    ],
    "temperature": 0.7
  }
}
```

Multimodal (Inline Image/Document)

```
{
  "model": "gpt-4o",
  "body": {
    "messages": [
      {
        "role": "user",
        "content": [
          { "type": "text", "text": "What is shown in this image?" },
          {
            "type": "image_url",
            "image_url": {
              "url": "..."
            }
          }
        ]
      }
    ]
  }
}
```

---

3. OpenRouter Model Catalog Quick Onboarding

KMS includes built-in integration with the **OpenRouter Models Catalog**:

- **Quick Import**: When adding a model pricing entry in the Admin Console, use the ⚡ **Quick Import from OpenRouter** search box to automatically populate canonical model name, provider (`openrouter`), modality (`text` or `image`), and calculated rate limits.
- **Catalog Browser**: Click ⚡ **OpenRouter Catalog** in the Model Pricing tab to browse 300+ live LLMs and image models with 1-click import.

---

4. Image Generation Endpoint

To generate images using dedicated image models (e.g. `openai/gpt-image-1`, `bytedance-seed/seedream-4.5`):

- **Endpoint:** `POST http://<your-kms-domain>:3201/v1/images/generations`
- **Authorization Header:** `Authorization: Bearer <ck_live_your_scoped_client_key>`

Request Body Format

```
{
  "model": "openai/gpt-image-1",
  "prompt": "A serene mountain lake at sunrise",
  "n": 1,
  "resolution": "1K",
  "aspectRatio": "16:9",
  "outputFormat": "png",
  "quality": "high"
}
```

Response Format