



THE MEGA CHEAT SHEET

CSS3 is the latest evolution of the Cascading Style Sheets language and aims at extending CSS2.1. It brings a lot of long-awaited novelties, like rounded corners, shadows, gradients, transitions or animations, as well as new layouts like multi-columns, flexible box or grid layouts. Experimental parts are vendor-prefixed and should either be avoided in production environments, or used with extreme caution as both their syntax and semantics can change in the future.

BACKGROUNDS

background

background-image

background-position

background-size

background-repeat

background-attachment

background-origin

background-clip

background-color

background-origin

border-box | padding-box | content-box

background-position

top left | top center | top right | center left |
center center | center right | bottom left |
bottom center | bottom right

x-% y-%

x-pos y-pos

background-attachment

scroll | fixed

background-break

bounding-box | each-box | continuous

background-clip

length

%

border-box | padding-box | content-box |
no-clip

background-repeat

repeat | repeat-x | repeat-y | no-repeat

background-color

color

transparent

background-color

color

transparent

background-image

url

none

background-size

length

%

auto | cover | contain

BORDER

border

border-width
border-style
border-color

border-bottom

border-bottom-width
border-style
border-color

border-left

border-left-width
border-style
border-color

border-left-style

border-style

border-right-color

border-color

border-right-width

thin | medium | thick | length

border-top-width

thin | medium | thick | length

border-width

thin | medium | thick | length

border-style

none | hidden | dotted |
dashed | solid | double |
groove | ridge | inset | outset

border-break

border-width
border-style
color
close

border-bottom-color

border-color

border-bottom-style

border-style

border-left-color

border-color

border-left-width

thin | medium | thick length

border-right-style

border-style

border-top

border-top-width
border-style
border-color

border-top-color

border-color

border-top-style

border-style

box-shadow

inset || [length, length,
length, length || <color>]
none

background-color

color
transparent

border-collapse

collapse | separate

border-color

color

border-image

image
[number / %
border-width
stretch | repeat | round]
none

border-right

border-right-width
border-style
border-color

border-radius

border-radius
border-top-right-radius
border-bottom-right-radius
border-bottom-left-radius
border-top-left-radius

border-top-right-radius

length

border-bottom-right-radius

length

border-bottom-left-radius

length

BOX MODEL

float

left | right | none

height

auto

length

%

max-height

none

length

%

max-width

none

length

%

min-height

none

length

%

min-width

none | inherit

length

%

width

auto

%

length

margin

margin-top

margin-right

margin-bottom

margin-left

margin-bottom

auto

length

%

margin-left

auto

height

%

margin-right

auto

height

%

margin-top

auto

length

%

padding

padding-top

padding-right

padding-bottom

padding-left

padding-bottom

length

%

padding-left

length

%

padding-right

length

%

padding-top

length

%

display

none | inline | block | inline-block |
list-item | run-in | compact | table |
inline-table | table-row-group |
table-header-group |
table-footer-group | table-row |
table-column-group | table-column |
table-cell | table-caption | ruby |
ruby-base | ruby-text |
ruby-base-group | ruby-text-group

marquee-direction

forward | reverse

marquee-loop

infinite

integer

marquee-play-count

infinite

integer

marquee-speed

slow | normal | fast

marquee-style

scroll | slide | alternate

overflow

visible | hidden | scroll |

auto | no-display | no-content

overflow-x

overflow-y

overflow-style

auto | marquee-line | marquee-block

overflow-x

visible | hidden | scroll |

auto | no-display | no-content

overflow-y

visible | hidden | scroll |

auto | no-display | no-content

rotation

angle

rotation-point

position (paired value off-set)

visibility

visible | hidden | collapse

clear

left | right | both | none

FONT

font

font-style

font-variant

font-weight

font-size/line-height

font-family

caption | icon | menu | message-box |
small-caption | status-bar

font-size-adjust

none | inherit

number

font-family

normal | wider | narrower |
ultra-condensed | extra-condensed |
condensed | semi-condensed |
semi-expanded | ultra-expanded |
inherit

font-style

normal | italic | oblique | inherit

font-variant

normal | small-caps | inherit

font-size

xx-small | x-small | small | medium |
large | x-large | xx-large | smaller |
larger |

inherit

length

%

font-weight

normal | bold | bolder | lighter |
100 | 200 | 300 | 400 | 500 | 600 |
700 | 800 | 900 | inherit

TEXT

direction

ltr | rtl | inherit

hanging-punctuation

none | [start | end | end-edge]

letter spacing

normal

length

%

text-outline

none

color

length

unicode-bidi

normal | embed | bidi-override

white-space

normal | pre | nowrap | pre-wrap | pre-line

white-space-collapse

preserve | collapse | pre-serve-breaks |
discard

punctuation-trim

none | [start | end | adjacent]

text-align

start | end | left | right | center | justify

text-align-last

start | end | left | right | center | justify

text-decoration

none | underline | overline |
line-through | blink

text-shadow

none

color

length

word-break

normal | keep-all | loose | break-strict |
break-all

word-wrap

normal

length

%

text-emphasis

none | [[accent | dot | circle | disc | [
before | after]?]

text-indent

length

%

text-justify

auto | inter-word | inter-ideograph |
inter-cluster | distribute | kashida |
tibetan

text-transform

none | capitalize | uppercase |
lowercase

text-wrap

normal | unresrricted | none |
suppress

word-spacing

normal

length

%

COLUMN

column-count

auto
number

column-fill

auto | balance

column-gap

normal
length

column-rule

column-rule-width
column-rule-style
column-rule-color

column-rule-style

border-style

columns

column-width
column-count

column-rule-width

thin | medium | thick
length

column-span

1 | all

column-width

auto
length

COLORS

color

inherit
color

opacity

inherit
number

grid-columns

none | inherit
[length percentage relative length]

grid-rows

none | inherit
[length percentage relative length]

TEMPLATE LAYOUT

box-align

start | end | center | base

box-direction

normal | reverse

box-flex

normal

box-flex-group

integer

box-lines

single | multiple

box-orient

horizontal | verticle | inline-axis |
block-axis

box-pack

start | end | center | justify

box-sizing

content-box | padding-box |
border-box | margin-box

tab-side

top | bottom | left | right

TABLE

border-collapse

collapse | separate

empty-cells

show | hide

border-spacing

length length

table-layout

auto | fixed

caption-side

top | bottom | left | right

cue

cue-before

cue-after

cue-before

url [silent | x-soft | soft | medium | loud | x-loud | none | inherit]

number

%

mark

mark-before

mark-after

mark-before

string

mark-after

string

voice-pitch-range

x-low | low | medium | high | x-high | inherit

number

voice-stress

strong | moderate | none | reduced | inherit

voice-volume

silent | x-soft | soft | medium | loud | x-loud | inherit

number

%

cue-after

url [silent | x-soft | soft | medium | loud | x-loud | none | inherit]

number

%

pause

pause-before

pause-after

pause-before

none | x-weak | weak | medium | strong | x-strong | inherit

time

phonemes

string

voice-duration

time

voice-family

inherit | [<specific-voice, age, generic-voice, number>]

voice-rate

x-slow | slow | medium | fast | x-fast | inherit

%

voice-pitch

x-low | low | medium | high | x-high | inherit

number

%

caption-side

top | bottom | left | right

rest

rest-before

rest-after

rest-before

none | x-weak | weak | medium | strong | x-strong | inherit

time

rest-after

none | x-weak | weak | medium | strong | x-strong | inherit

time

speak

none | normal | spell-out | digits | literal-punctuation | no-punctuation | inherit-number

cue

cue-before

cue-after

cue-beforeurl [silent | x-soft | soft | medium | loud |
x-loud | none | inherit]

number

%

mark

mark-before

mark-after

mark-before

string

mark-after

string

voice-pitch-range

x-low | low | medium | high | x-high | inherit

number

voice-stress

strong | moderate | none | reduced | inherit

voice-volumesilent | x-soft | soft | medium | loud | x-loud |
inherit

number

%

cue-afterurl [silent | x-soft | soft | medium | loud |
x-loud | none | inherit]

number

%

pause

pause-before

pause-after

pause-beforenone | x-weak | weak | medium | strong |
x-strong | inherit

time

phonemes

string

voice-duration

time

voice-familyinherit [<specific-voice, age, generic-voice,
number>]**voice-rate**

x-slow | slow | medium | fast | x-fast | inherit

%

voice-pitch

x-low | low | medium | high | x-high | inherit

number

%

caption-side

top | bottom | left | right

rest

rest-before

rest-after

rest-beforenone | x-weak | weak | medium |
strong | x-strong | inherit

time

rest-afternone | x-weak | weak | medium |
strong | x-strong | inherit

time

speaknone | normal | spell-out | digits |
literal-punctuation | no-punctuation |
inherit-number

LIST & MARKERS

list-style

list-style-type

list-style-position

list-style-image

list-style-image

none

url

list-style-type

none | asterisks | box | check | circle | diamond | disc | hyphen | square | decimal | decimal-leading-zero | lower-roman | upper-roman | lower-alpha | upper-alpha | lower-greek | lower-latin | upper-latin | hebrew | armenian | georgian | cjk-ideographic | hiragana | katakana | hiragana-iroha | katakana-iroha | footnotes

marker-offset

auto

length

ANIMATIONS

animations

animation-name

animation-duration

animation-timing-function

animation-delay

animation-iteration-count

animation-direction

animation-timing-function

ease | linear | ease-in | ease-out | ease-in-out | cubic-Bezier (number, number, number, number)

animation-delay

time

animation-delay

time

animation-name

none | IDENT

animation-direction

normal | alternate

animation-iteration-count

inherit

number

animation-play-state

running | paused

TRANSITIONS

transitions

transitions-property

transitions-duration

transitions-timing-function

transitions-delay

transitions-delay

time

transitions-duration

time

transitions-property

none | all

transition-timing-function

ease | linear | ease-in | ease-out | ease-in-out | cubic-Bezier (number, number, number, number)

appearance

normal | inherit | [icon | window | desktop | work-space | document | tooltip | dialog | button | push-button | hyperlink | radio-button | checkbox | menu-item | tab | menu | menubar | pull-down-menu | pop-up-menu | list-menu | radio-group | checkbox-group | outline-tree | range | field | combo-box | signature | password]

cursor

auto | crosshair | default | pointer | move | e-resize | ne-resize | nw-resize | n-resize | se-resize | sw-resize | s-resize | w-resize | text | wait | help

url

icon

auto | inherit

url

nav-index

auto | inherit

number

nav-up

auto | inherit
<id> [current | root | <target-name>]

nav-right

auto | inherit
<id> [current | root | <target-name>]

nav-down

auto | inherit
<id> [current | root | <target-name>]

nav-left

auto | inherit
<id> [current | root | <target-name>]

resize

none | both | horizontal | vertical | inherit

PSEUDO-CLASS

:active	an activated element
:focus	an element while the element has focus
:visited	a visited link
:hover	an element when you mouse over it
:link	an unvisited link
:disabled	an element while the element is disabled
:enabled	an element while the element is enabled
:checked	an element (form element control) that is checked
:selection	an element that is currently selected or highlighted by the user
:lang	allows the author to specify a language to use in a specified element
:nth-child(n)	an element that is the n-th sibling
:nth-last-child(n)	an element that is the n-th sibling counting from the last sibling
:first-child	an element that is the first sibling
:last-child	an element that is the last sibling
:only-child	an element that is the only child
:nth-of-type(n)	an element that is the n-th sibling of its type
:nth-last-of-type(n)	an element that is the n-th sibling of its type counting from the last sibling
:last-of-type	an element that is the last sibling of its type
:first-of-type	an element that is the first sibling of its type
:only-of-type	an element that is the only of its type
:empty	an element that has no children
:root	root element within the document
:not(x)	an element not represented by the argument 'x'
:target	a target element as specified by a target in a URI

PSEUDO-ELEMENT

::first-letter	Adds special style to the first letter of a text
::first-line	Adds special style to the first line of a text
::before	Inserts some content before an element
::after	Inserts some content after an element

ABSOLUTE MEASUREMENT

%	percentage
cm	centimeter
in	inch
mm	millimeter
pc	pica (1p = 12 points)
pt	point (1pt = 1/72 inch)

RELATIVE MEASUREMENT

ch	width of the "0" glyph found in the font for the font size used to render
em	1em = current font size of current element
ex	x-height of the element's font
gd	the grid defined by 'layout-grid'
px	pixel of the viewing device
rem	the font size of the root element
vh	the viewport's height
vw	the viewport's width
vm	viewport's height or width, whichever is smaller of the two

ANGLES

deg	degrees
grad	grads
rad	radians
turn	turns

TIME

ms	milli-seconds
s	seconds

FREQUENCY

Hz	hertz
kHz	kilo-hertz

COLORS

color name	red, blue, green, dark green
rgb(x,y,z)	red = rgb(255,0,0)
rgb(x%,y%,z%)	red = rgb(100%,0,0)
rgba(x,y,z,alpha)	red = rgba(255,0,0)
#rrggbb	red = #ff0000 (or shorthand = #f00) hsl(hue, saturation, lightness)
red=hsl	(0, 100%, 50%)
flavor	An accent color (typically chosen by the user) to customize the user interface of the user agent itself.
currentColor	computed value of the 'currentColor' keyword is the computed value of the 'color' property

SELECTOR TYPES


Name	Info	Example
Universal	Any element	<code>* { font: 10px Arial; }</code>
Type	Any element of that type	<code>h1 { text-decoration: underline; }</code>
Grouping	Multiple elements of different types	<code>h1, h2, h3 { font-family: Verdana; }</code>
Class	Multiple elements of different types when you don't want to affect all instances of that type	<code>.sampleclass { text-decoration: underline; }</code>
Id	A single element type when you don't want to affect all instances of that type	<code>#sampled { text-decoration: underline; }</code>
Descendant	An element that is below (in the document tree) another element - no matter how many levels below	<code>#gallery h1 { text-decoration: underline; }</code>
Child	An element that is directly below (in the document tree) another element	<code>#title > p { font-weight: bold; }</code>
Adjacent Sibling	All elements that share the same parent and elements are in the same immediate sequence	<code>h1 + p { font-style: italic; }</code>
General Sibling	All elements that share the same parent and elements are in the same sequence (not necessarily immediate)	<code>h1 ~ p { font-style: italic; }</code>
Attribute	An element with that matches the attribute listed	<code>E[selected]</code> - att whatever the value <code>E[att="val"]</code> - att with a specific value <code>E[rel~="next"]</code> - att with a value is a whitespace separated list <code>*[lang="en"]</code> - att value either being exactly "val" or beginning with "val" immediately followed by "-" <code>E[att^="val"]</code> - att value that begins with the prefix "val" <code>E[att\$="val"]</code> - att vale that begins with the suffix "val" <code>E[att*="val"]</code> - att value contains at least one instance of the substring "val"



**THE MEGA
CHEAT SHEET**

INFOGRAPHIC BY

make a
websitehub.com



OUTLINE

outline

outline-color
outline-style
outline-width

outline-offset

inherit
length

outline-style

none | dotted | dashed |
solid | double | groove |
ridge | inset | outset

outline-width

thin | medium | thick
length

3D / 2D TRANSFORM

backface-visibility

visible | hidden

perspective

none
number

perspective-origin

[[[percentage |
<length> | left | center |
right] [<percentage> |
<length> | top | center |
bottom]?] <length>] |
[[[left | center | right] ||
[top | center | bottom]]
<length>]

transform

none | matrix | matrix3d |
translate3d | translateX |
translateY | translateZ |
scale | scale3d | scaleX |
scaleY | scaleZ | rotate |
rotate3d | rotateX |
rotateY | rotateZ | skewX |
skewY | skew |
perspective

transform-origin

[[[<percentage> |
<length> | left | center |
right] [<percentage> |
<length> | top | center |
bottom]?] <length>] |
[[[left | center | right] ||
[top | center | bottom]]
<length>]

transform-style

flat | preserve-3d

GENERATED CONTENT

bookmark-label

content
attr
string

bookmark-level

none
integer

bookmark-target

self
url
attr

border-length

self
url
attr

content

normal | none | inhibit
url

counter-reset

none
identifier number

crop

auto
shape

display

normal | none | list-item

float-offset

length length

hyphenate-after

auto
integer

counter-increment

none
identifier number

hyphenate-lines

no-limit
integer

hyphenate-resource

none
url

hyphens

none | manual | auto

image-resolution

normal | auto
dpi

hyphenate-before

auto
integer

hyphenate-character

auto
string

marks

[crop || cross] | none

move-to

normal | here
identifier

page-policy

start | first | last

quotes

none
string string string string

string-set

identifier
content-list

text-replace

none
[<string> <string>]+

LINE BOX

alignment-adjust

auto | baseline | before-edge | text-before-edge | middle | central | after-edge | text-after-edge | ideographic | alphabetic | hanging | mathematical

length

%

alignment-baseline

baseline | iscript | before-edge | text-before-edge | after-edge | text-after-edge | central | middle | ideographic | alphabetic | hanging | mathematical

baseline-shift

baseline | sub | super

length

%

dominant-baseline

auto | use-script | no-change | reset-size | alphabetic | hanging | ideographic | mathematical | central | middle | text-after-edge | text-before-edge

drop-initial-after-align

alignment-baseline

drop-initial-after-align

central | middle | after-edge | text-after-edge | ideographic | alphabetic | mathematical

%

drop-initial-before-align

caps-height

alignment-baseline

drop-initial-before-adjust

before-edge | text-before-edge | central | middle | hanging | mathematical

length

%

drop-initial-value

initial

integer

drop-initial-size

auto

integer

%

line

inline-box-align

initial | last

integer

line-height

normal

number

length

%

line-stacking

line-stacking-strategy

line-stacking-ruby

line-stacking-shift

line-stacking-strategy

inline-line-height | block-line-height | max-height | grid-height

line-stacking-ruby

exclude-ruby | include-ruby

line-stacking-shift

consider-shifts | disregard-shifts

line-stacking

line-stacking-strategy

line-stacking-ruby

line-stacking-shift

text-height

auto | font-size | text-size | max-size

vertical-align

Baseline | sub | super | top | text-top | middle | bottom | text-bottom

length

%

HYPERLINK

target

target-name

target-new

target-position

target-name

current | root | parent | new | modal

string

target-new

window | tab | none

target-position

above | behind | front | back

POSITIONING

bottom

auto
%
length

right

auto
%
length

clip

shape
auto

top

auto
%
length

left

auto
%
length

z-index

auto
number

position

static | relative | absolute | fixed

RUBY

ruby-align

auto | start | left | center |
end | right | distribute-letter |
distribute-space | line-edge

ruby-overhang

auto | start | end | none

ruby-position

before | after | right | inline

ruby-span

attr(x) | none

PAGED MEDIA

fit

fill | hidden | meet | slice

fit-position

[top | center | bottom] ||
[left | center | right]
length
%

orphans

integer

image-orientation

auto
angle

page

auto
identifier

page-break-after

auto | always | avoid | left | right

page-break-before

auto | always | avoid | left | right

page-break-inside

auto | avoid

size

auto | landscape | portrait
length

windows

integer