

Cloud Application Development

Lab: CLI Nova

Name: - Nilesh Verma

SAP Id.: - 500087239

Batch: - B4 Non-Hons CC&VT

Roll No.: - R2142201812

```
[root@localhost nova(keystone_admin)]# openstack flavor list
```

ID	Name	RAM	Disk	Ephemeral	VCPU's	Is Public
1	m1.tiny	512	1	0	1	True
2	m1.small	2048	20	0	1	True
3	m1.medium	4096	40	0	2	True
4	m1.large	8192	80	0	4	True
5	m1.xlarge	16384	160	0	8	True

```
[root@localhost nova(keystone_admin)]#
```

```
--project <project>      multiple properties)
                          Allow <project> to access private flavor (name or ID)
                          (Must be used with --private option)
--description <description>
                          Description for the flavor. (Supported by API versions
                          '2.55' - '2.latest')
--project-domain <project-domain>
                          Domain the project belongs to (name or ID). This can
                          be used in case collisions between project names
                          exist.

output formatters:
  output formatter options
    -f {json,shell,table,value,yaml}, --format {json,shell,table,value,yaml}
        the output format, defaults to table
    -c COLUMN, --column COLUMN
        specify the column(s) to include, can be repeated

table formatter:
  --max-width <integer>
        Maximum display width, <1 to disable. You can also use
        the CLIFF_MAX_TERM_WIDTH environment variable, but the
        parameter takes precedence.
  --fit-width
        Fit the table to the display width. Implied if --max-
        width greater than 0. Set the environment variable
        CLIFF_FIT_WIDTH=1 to always enable
  --print-empty
        Print empty table if there is no data to show.

json formatter:
  --noindent
        whether to disable indenting the JSON

shell formatter:
  a format a UNIX shell can parse (variable="value")
  --prefix PREFIX
        add a prefix to all variable names
[root@localhost nova(keystone_admin)]#
```

```

[root@localhost nova(keystone_admin)]# openstack flavor create --id 10 --ram 256 --disk 2 --public
tiner
+-----+-----+
| Field | Value |
+-----+-----+
| OS-FLV-DISABLED:disabled | False |
| OS-FLV-EXT-DATA:ephemeral | 0 |
| disk | 2 |
| id | 10 |
| name | tiner |
| os-flavor-access:is_public | True |
| properties | |
| ram | 256 |
| rxtx_factor | 1.0 |
| swap | |
| vcpus | 1 |
+-----+-----+

[root@localhost nova(keystone_admin)]# openstack flavor list
+-----+-----+-----+-----+-----+-----+-----+
| ID | Name | RAM | Disk | Ephemeral | VCPUS | Is Public |
+-----+-----+-----+-----+-----+-----+-----+
| 1 | m1.tiny | 512 | 1 | 0 | 1 | True |
| 10 | tiner | 256 | 2 | 0 | 1 | True |
| 2 | m1.small | 2048 | 20 | 0 | 1 | True |
| 3 | m1.medium | 4096 | 40 | 0 | 2 | True |
| 4 | m1.large | 8192 | 80 | 0 | 4 | True |
| 5 | m1.xlarge | 16384 | 160 | 0 | 8 | True |
+-----+-----+-----+-----+-----+-----+-----+

[root@localhost nova(keystone_admin)]#

```

```

use case of connecting a new server to a given port.
For more advanced use cases, refer to the '--nic'
parameter.
--hint <key=value> Hints for the scheduler (optional extension)
--config-drive <config-drive-volume>:True
Use specified volume as the config drive, or 'True' to
use an ephemeral drive
--min <count> Minimum number of servers to launch (default=1)
--max <count> Maximum number of servers to launch (default=1)
--wait Wait for build to complete

output formatters:
output formatter options
-f {json,shell,table,value,yaml}, --format {json,shell,table,value,yaml}
the output format, defaults to table
-c COLUMN, --column COLUMN
specify the column(s) to include, can be repeated

table formatter:
--max-width <integer>
Maximum display width, <1 to disable. You can also use
the CLIFF_MAX_TERM_WIDTH environment variable, but the
parameter takes precedence.
--fit-width
Fit the table to the display width. Implied if --max-
width greater than 0. Set the environment variable
CLIFF_FIT_WIDTH=1 to always enable
--print-empty
Print empty table if there is no data to show.

json formatter:
--noindent whether to disable indenting the JSON

shell formatter:
a format a UNIX shell can parse (variable="value")
--prefix PREFIX add a prefix to all variable names
[root@localhost nova(keystone_admin)]# _

```

```
[root@localhost nova(keystone_admin)]# openstack keypair create mykeypair >>mykeypair.key
[root@localhost nova(keystone_admin)]#
```

```
[root@localhost nova(keystone_admin)]# openstack image list
+-----+-----+-----+
| ID | Name | Status |
+-----+-----+-----+
| 415e11f1-3819-4986-a42e-d2d402c60e7f | cirros | active |
+-----+-----+-----+
[root@localhost nova(keystone_admin)]#
```

```
[root@localhost nova(keystone_admin)]# openstack image list
+-----+-----+-----+
| ID | Name | Status |
+-----+-----+-----+
| 415e11f1-3819-4986-a42e-d2d402c60e7f | cirros | active |
+-----+-----+-----+
```

```
[root@localhost nova(keystone_admin)]# openstack network list
+-----+-----+-----+
| ID | Name | Subnets |
+-----+-----+-----+
| 2dd49ba0-9fe7-4013-b6ce-56afd4918096 | public | dc785206-71c2-4709-a14b-b5f771eebf2a |
| 31ae4034-c620-4f9b-a7af-3733a5afb0bd | intnet | 4f326dcc-f0fa-4afa-bf06-b4e93d7222db |
| 6fabble4-f136-4f3d-bac8-827812db943c | anantnet | 18e5742f-1781-4a24-a692-fdbf72509817 |
+-----+-----+-----+
[root@localhost nova(keystone_admin)]#
```

```
[root@localhost nova(keystone_admin)]# openstack server create --image cirros --key-name mykeypair
--flavor 10 --nic net-id=31ae4034-c620-4f9b-a7af-3733a5afb0bd instance01
+-----+-----+
| Field | Value |
+-----+-----+
| OS-DCF:diskConfig | MANUAL |
| OS-EXT-AZ:availability_zone | |
| OS-EXT-SRV-ATTR:host | None |
| OS-EXT-SRV-ATTR:hypervisor_hostname | None |
| OS-EXT-SRV-ATTR:instance_name | |
| OS-EXT-STS:power_state | NOSTATE |
| OS-EXT-STS:task_state | scheduling |
| OS-EXT-STS:vm_state | building |
| OS-SRV-USG:launched_at | None |
| OS-SRV-USG:terminated_at | None |
| accessIPv4 | |
| accessIPv6 | |
| addresses | |
| adminPass | cMB2tfMTh4xE |
| config_drive | |
| created | 2023-04-22T20:19:24Z |
| flavor | tiner (10) |
| hostId | |
| id | 1d587030-d1a7-47d0-bc3f-931dab7cc73b |
| image | cirros (415e11f1-3819-4986-a42e-d2d402c60e7f) |
| key_name | mykeypair |
| name | instance01 |
| progress | 0 |
| project_id | cd18aa9de06a4e0e88635a0f6fe9d987 |
| properties | |
| security_groups | name='default' |
| status | BUILD |
| updated | 2023-04-22T20:19:24Z |
| user_id | 9ca7b68be5f84c89ba0d7f01b55bee03 |
| volumes_attached | |
+-----+-----+
[root@localhost nova(keystone_admin)]#
```

```
root@localhost nova(keystone_admin)]# openstack server show instance01
```

Field	Value
OS-DCF:diskConfig	MANUAL
OS-EXT-AZ:availability_zone	nova
OS-EXT-SRV-ATTR:host	localhost.localdomain
OS-EXT-SRV-ATTR:hypervisor_hostname	localhost.localdomain
OS-EXT-SRV-ATTR:instance_name	instance-00000007
OS-EXT-STS:power_state	Running
OS-EXT-STS:task_state	None
OS-EXT-STS:vm_state	active
OS-SRV-USG:launched_at	2023-04-22T20:20:00.000000
OS-SRV-USG:terminated_at	None
accessIPv4	
accessIPv6	
addresses	intnet=10.5.5.15
config_drive	
created	2023-04-22T20:19:24Z
flavor	tinier (10)
hostId	c55060a06fd0b7e6cdfc55b5f8c3691f8864350c36c50a014a7ebc5
id	1d507030-d1a7-47d0-bc3f-931dab7cc73b
image	cirros (415e11f1-3819-4986-a42e-d2d402c60e7f)
key_name	mykeypair
name	instance01
progress	0
project_id	cd18aa9dc06a4e0e88635a0f6fe9d987
properties	
security_groups	name='default'
status	ACTIVE
updated	2023-04-22T20:20:11Z
user_id	9ca7b60be5f04c89ba0d7f01b55bee03
volumes_attached	

```
root@localhost nova(keystone_admin)]# _
```

```
root@localhost nova(keystone_admin)]# cat /etc/nova/nova.conf | grep filter
```

```
# not filtered. An empty string means that all levels are filtered (string
[filter_scheduler]
# Deprecated group:name - DEFAULT:scheduler_available_filters
#available_filters=nova.scheduler.filters.all_filters
available_filters=nova.scheduler.filters.all_filters
# Deprecated group:name - DEFAULT:scheduler_default_filters
#enabled_filters=AvailabilityZoneFilter,ComputeFilter,ComputeCapabilitiesFilter,ImagePropertiesFilter,ServerGroupAntiAffinityFilter,ServerGroupAffinityFilter
enabled_filters=RetryFilter,AvailabilityZoneFilter,ComputeFilter,ComputeCapabilitiesFilter,ImagePropertiesFilter,ServerGroupAntiAffinityFilter,ServerGroupAffinityFilter
# The default architecture to be used when using the image properties filter.
# exception, so it is recommended to also use the MetricFilter to filter out
# Enable filter traces that contain error/exception to a separated place. For
#filter_error_trace=false
# 'setup.cfg'. If nothing is specified in this option, the 'filter_scheduler' is
#driver=filter_scheduler
driver=filter_scheduler
# number of CPUs available if using the "filter_scheduler" scheduler driver,
# metadata key of 'filter_tenant_id' set to the project of an incoming
# number to the key, such as 'filter_tenant_id:123'. For more information, refer
#enable_isolated_aggregate_filtering=false
#sr_matching_filter=default-sr:true
root@localhost nova(keystone_admin)]# _
```

```

| protected          | False
|
| schema             | /v2/schemas/image
|
| size               | None
|
| status             | queued
|
| tags               |
|
| updated_at         | 2023-04-22T20:22:37Z
|
| virtual_size       | None
|
| visibility         | private
|
+-----+
+-----+
root@localhost nova(keystone_admin)l#

```

```
[root@localhost nova(keystone_admin)]# openstack image list
```

ID	Name	Status
415e11f1-3819-4986-a42e-d2d402c60e7f	cirros	active
8ec2bfff5-1354-4c92-a302-0129737e74f2	snapi	active

```
[root@localhost nova(keystone_admin)]#
```



```
[root@localhost nova(keystone_admin)]# openstack aggregate create --property SSD=true agg2
```

Field	Value
availability_zone	None
created_at	2023-04-22T20:24:04.000000
deleted	False
deleted_at	None
hosts	
id	1
name	agg2
properties	SSD='true'
updated_at	2023-04-22T20:24:05.923879

```
[root@localhost nova(keystone_admin)]# _
```

```
[root@localhost nova(keystone_admin)]# openstack console url show --novnc instance01
```

Field	Value
type	novnc
url	http://10.10.20.90:6000/vnc_auto.html?path=%3Ftoken%3Db526d299-55cf-474b-80ee-316e0ec573c

```
[root@localhost nova(keystone_admin)]#
```

```
[root@localhost nova(keystone_admin)]# openstack console log show instance01
[root@localhost nova(keystone_admin)]# openstack console log show instance01
[root@localhost nova(keystone_admin)]#
```

```
| server group create |
| server group delete |
| server group list |
| server group show |
| server image create |
| server list |
| server lock |
| server migrate |
| server pause |
| server reboot |
| server rebuild |
| server remove fixed ip |
| server remove floating ip |
| server remove network |
| server remove port |
| server remove security group |
| server remove volume |
| server rescue |
| server resize |
| server resize confirm |
| server resize revert |
| server restore |
| server resume |
| server set |
| server shelve |
| server show |
| server ssh |
| server start |
| server stop |
| server suspend |
| server unlock |
| server unpause |
| server unrescue |
| server unset |
| server unshelve |
| usage list |
[root@localhost nova(keystone_admin)]#
```