

Spring Boot Project Structure

Consider the below project structure

```
marvellous/  
├── src/  
│   ├── main/  
│   │   ├── java/  
│   │   │   └── com/marvellous/  
│   │   │       ├── MarvellousApplication.java  
│   │   │       ├── controller/  
│   │   │       ├── service/  
│   │   │       ├── repository/  
│   │   │       ├── model/  
│   │   │       └── dto/  
│   │   └── resources/  
│   │       ├── application.properties  
│   │       ├── static/  
│   │       ├── templates/  
│   │       └── banner.txt  
│   └── test/  
│       └── java/  
│           └── com/marvellous/  
│               └── MarvellousApplicationTests.java  
├── target/  
│   ├── marvellous-0.0.1-SNAPSHOT.jar  
│   ├── classes/  
│   ├── generated-sources/  
│   ├── test-classes/  
│   └── ...  
├── .mvn/  
├── mvnw  
├── mvnw.cmd  
├── pom.xml  
└── README.md
```

Detailed Explanation of Each Folder and File

1. src/main/java/com/marvellous/

This is your main Java source code. Follows reverse domain naming.

MarvellousApplication.java

@SpringBootApplication

public class MarvellousApplication

```
{  
    public static void main(String[] args)  
    {  
        SpringApplication.run(MarvellousApplication.class, args);  
    }  
}
```

controller/

- Contains REST API endpoint logic using @RestController.

service/

- Business logic using @Service.

repository/

- JPA interfaces (UserRepository, etc.) using @Repository.

model/

- POJOs with @Entity for DB table mapping.

dto/ (optional)

- For Data Transfer Objects (pure request/response structures).

2. src/main/resources/

Stores resources needed at runtime.

application.properties

- Main configuration file (e.g., DB connection, port).

static/

- Public assets like CSS, JS, images.

templates/

- For HTML templates using Thymeleaf or other engines.

banner.txt (optional)

- ASCII art displayed on app startup.

3. src/test/java/com/marvellous/

Unit and integration test classes using JUnit/Mockito.

MarvellousApplicationTests.java

- Sample test case with @SpringBootTest.

4. pom.xml

Maven configuration file – dependencies, plugins, etc.

```
<artifactId>marvellous</artifactId>

<dependencies>
  <!-- Example -->
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-web</artifactId>
  </dependency>
</dependencies>
```

5. target/ – Generated Folder After mvn package

The target/ directory is automatically created when you run:

mvn clean package

Contents of target/:

File/Folder	Purpose
marvellous-0.0.1-SNAPSHOT.jar	Final executable JAR with embedded Tomcat and compiled code
classes/	Compiled .class files of your source Java code
generated-sources/	Auto-generated code by plugins (like MapStruct)
test-classes/	Compiled test classes
maven-status/	Metadata about compilation status
surefire-reports/	Test results generated during <code>mvn test</code>

This folder is used during deployment or to run the app:

```
java -jar target/marvellous-0.0.1-SNAPSHOT.jar
```

6. Other Files

File/Folders	Description
.mvn/, mvnw, mvnw.cmd	Maven wrapper, allows running Maven without local install
README.md	Documentation or project instructions
.gitignore	Ignore files in Git (like /target, .class, .idea)

Summary

Component	Keyword / Annotation	Purpose
Main Class	@SpringBootApplication	Entry point
Controller	@RestController	Handles HTTP Requests
Service	@Service	Business Logic
Repository	@Repository, JpaRepository	Data Access Layer
Model	@Entity	Maps to DB Table
Configuration	application.properties	Project Settings
Final Output	target/marvellous-0.0.1-SNAPSHOT.jar	Executable File