



DAILY EFFECTIVENESS

WEEKLY EQUIPMENT & COMPLIANCE RECORD

EMPLOYEE		LOCATION / VEHICLE		MONTH / YEAR	
WEEK FROM		TO		SUPERVISOR	

EQUIPMENT / CHECK	REQUIRED ENTRY	MON	TUE	WED	THU	FRI	SAT	SUN
20B BATH	Batch # + centrifuge reading							
MAGNETIZING COIL	Coil SN + calibration due date							
GAUSS METER	Meter SN + calibration due date							
CASTROL STRIPS	Condition / verification result							
DUAL LIGHT METER	Meter SN + calibration due date							
UV LIGHT	Daily intensity reading							
WHITE LIGHT	Daily ambient-light reading							
LPI MATERIAL	Batch # + expiration / due date							
TEST BLOCK	Block ID + verification result							
AC YOKE	Yoke SN + verification status							
10-LB TEST WEIGHT	Weight SN + due date + pass/fail							
EMPLOYEE INITIALS	Initial only after all required checks							

EXCEPTIONS / CORRECTIVE ACTION	SUPERVISOR WEEKLY REVIEW
Record failed checks, out-of-tolerance readings, expired calibration, removed-from-service equipment, and the action taken.	
	Signature: _____ Date: _____

EQUIPMENT IDENTIFICATION & COMPLIANCE GUIDE

TRAINING RULE

Know the equipment name, locate its serial or batch number, verify calibration or expiration status, take the required reading, and document the result before the equipment is used. Acceptance limits must match the current DS-1 requirement and/or Zion SOP.

EQUIPMENT NAME	WHAT IT DOES	WHAT TO RECORD	DAILY COMPLIANCE CHECK
20B Bath / Centrifuge Tube	Confirms magnetic-particle bath concentration.	Batch number and centrifuge reading.	Compare with current procedure; correct or replace bath if unacceptable.
Magnetizing Coil	Applies the magnetic field during MPI.	Coil serial number and calibration due date.	Tag out if identification is missing or calibration is expired.
Gauss Meter	Measures residual or applied magnetic field.	Meter serial number and calibration due date.	Confirm calibration is current before taking measurements.
Castrol Strips	Verifies field direction and adequate magnetization.	Condition and verification result.	Use clean, serviceable strips and follow the applicable technique.
Dual Light Meter	Measures UV-A and visible white light.	Meter serial number and calibration due date.	Confirm current calibration and correct sensor selection.
UV Light	Provides UV-A illumination for fluorescent inspection.	Daily intensity reading at the required distance.	Allow warm-up and compare reading with the current procedure.
White Light	Checks ambient visible light at the inspection surface.	Daily white-light reading.	Measure at the inspection area and compare with the current procedure.
LPI Material	Penetrant-system consumable used for liquid penetrant inspection.	Product / batch number and expiration or due date.	Do not use unidentified, contaminated, mixed, or expired material.
Test Block	Confirms system performance / sensitivity.	Block ID and verification result.	Clean, use, and evaluate per the applicable procedure.
AC Yoke	Creates a localized magnetic field for MPI.	Yoke serial number and verification status.	Inspect condition and complete the required lifting-force check.
10-lb Test Weight	Verifies AC yoke lifting force.	Weight serial number, due date, and pass/fail.	Remove from service if damaged, unidentified, or out of date.

STOP WORK & NOTIFY A SUPERVISOR

Do not use equipment when calibration is expired; identification is missing; the unit is damaged; a daily reading is outside the applicable limit; or a verification check fails.

EMPLOYEE ACKNOWLEDGMENT

I can identify the listed equipment and know where to find the current acceptance criteria. Employee: _____ Trainer: _____
Date: _____