

Package ‘FnR’

April 25, 2024

Title Inbreeding and Numerator Relationship Coefficients

Version 1.0.0

Description Compute inbreeding coefficients using the method of Meuwissen and Luo (1992) <[doi:10.1186/1297-9686-24-4-305](https://doi.org/10.1186/1297-9686-24-4-305)>, and numerator relationship coefficients between individuals using the method of Van Vleck (2007) <<https://pubmed.ncbi.nlm.nih.gov/18050089/>>.

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Suggests knitr, rmarkdown

VignetteBuilder knitr

URL <https://github.com/nilforooshan/FnR>

BugReports <https://github.com/nilforooshan/FnR/issues>

NeedsCompilation no

Author Mohammad Ali Nilforooshan [aut, cre]
(<<https://orcid.org/0000-0003-0339-5442>>)

Maintainer Mohammad Ali Nilforooshan <m.a.nilforooshan@gmail.com>

R topics documented:

calcR	1
resume_inbreed	2
Index	4

calcR	<i>Compute numerator relationship coefficients between two distinct groups of individuals</i>
-------	---

Description

Compute numerator relationship coefficients between two distinct groups of individuals

Usage

```
calcR(ped, set1, set2, type = "notdam-notsire")
```

Arguments

ped : A data frame with integer columns corresponding to ID, SIRE, and DAM. IDs should be sequential, starting from 1. Missing parents (SIRE and DAM) are denoted as 0.

set1 : A set of individual IDs.

set2 : A set of individual IDs, distinct from set1.

type : "notdam-notsire" (default), "sire-sire", or "dam-dam" relationships
 "notdam-notsire" requires set1 and set2 individuals not to be members of ped\$DAM and ped\$SIRE, respectively.
 "sire-sire" requires set1 and set2 individuals to be members of ped\$SIRE.
 "dam-dam" requires set1 and set2 individuals to be members of ped\$DAM.

Value

: Numerator relationship coefficients between set1 and set2 individuals in the form of a matrix (a partition of the numerator relationship matrix **A**).

Examples

```
# A sample pedigree data frame:
ped <- data.frame(
  ID = 1:12,
  SIRE = c(0, 0, 0, 2, 2, 0, 4, 6, 0, 6, 10, 10),
  DAM = c(0, 0, 0, 1, 1, 0, 3, 5, 7, 8, 9, 0)
)

# Example 1: Calculate relationship coefficients between two groups of animals,
# one's members not among dams, and the members of the other not among sires.
calcR(ped, set1 = c(12, 6), set2 = c(11, 8), type = "notdam-notsire")
# Since `"notdam-notsire"` is the default type, `type = "notdam-notsire"` might be omitted.

# Example 2: Calculate relationship coefficients between dam 7 and dams 8 and 9.
calcR(ped, set1 = 7, set2 = 8:9, type = "dam-dam")

# Example 3: Calculate relationship coefficients between sires 2 & 6 and sires 4 & 10.
calcR(ped, set1 = c(2, 6), set2 = c(4, 10), type = "sire-sire")
```

resume_inbreed

Calculate inbreeding coefficients from scratch or resume for new individuals in the pedigree

Description

Calculate inbreeding coefficients from scratch or resume for new individuals in the pedigree

Usage

```
resume_inbreed(ped, f = c(), d = c(), export_d = FALSE)
```

Arguments

ped : A data frame with integer columns corresponding to ID, SIRE, and DAM. IDs should be sequential, starting from 1. Missing parents (SIRE and DAM) are denoted as 0.

f : (Optional) If available, the vector of inbreeding coefficients from the previous calculation of inbreeding coefficients with less number of animals in the pedigree.

d : (Optional) If available, the vector of the diagonal elements of the diagonal matrix **D** in $\mathbf{A} = \mathbf{TDT}'$ from the previous calculation of inbreeding coefficients with less number of animals in the pedigree, where **A** is the numerator relationship matrix.

export_d : FALSE (default) or TRUE. If TRUE, vector d is returned for future use.

Value

: Vector of inbreeding coefficients if `export_d == FALSE`, or a list containing the vector of inbreeding coefficients and the vector of d coefficients if `export_d == TRUE`.

Examples

```
# A sample pedigree data frame:
ped <- data.frame(
  ID = 1:12,
  SIRE = c(0, 0, 0, 2, 2, 0, 4, 6, 0, 6, 10, 10),
  DAM = c(0, 0, 0, 1, 1, 0, 3, 5, 7, 8, 9, 0)
)

oldped <- ped[1:9, ]
(oldrun <- resume_inbreed(oldped, export_d = TRUE))
resume_inbreed(ped)
resume_inbreed(ped, f = oldrun$f)
resume_inbreed(ped, f = oldrun$f, d = oldrun$d)
```

Index

calcR, [1](#)

resume_inbreed, [2](#)